

Please do not upload this copyright pdf document to any other website. Breach of copyright may result in a criminal conviction.

This pdf document was generated by me Colin Hinson from a Crown copyright document held at R.A.F. Henlow Signals Museum. It is presented here (for free) under the Open Government Licence (O.G.L.) and this pdf version of the document is my copyright (along with the Crown Copyright) in much the same way as a photograph would be.

The document should have been downloaded from my website <https://blunham.com/Radar>, or any mirror site named on that site. If you downloaded it from elsewhere, please let me know (particularly if you were charged for it). You can contact me via my Genuki email page: <https://www.genuki.org.uk/big/eng/YKS/various?recipient=colin>

You may not copy the file for onward transmission of the data nor attempt to make monetary gain by the use of these files. If you want someone else to have a copy of the file, point them at the website. (<https://blunham.com/Radar>). Please do not point them at the file itself as it may move or the site may be updated.

It should be noted that most of the pages are identifiable as having been processed by me.

I put a lot of time into producing these files which is why you are met with this page when you open the file.

In order to generate this file, I need to scan the pages, split the double pages and remove any edge marks such as punch holes, clean up the pages, set the relevant pages to be all the same size and alignment. I then run Omnipage (OCR) to generate the searchable text and then generate the pdf file.

Hopefully after all that, I end up with a presentable file. If you find missing pages, pages in the wrong order, anything else wrong with the file or simply want to make a comment, please drop me a line (see above).

It is my hope that you find the file of use to you personally – I know that I would have liked to have found some of these files years ago – they would have saved me a lot of time !

Colin Hinson

In the village of Blunham, Bedfordshire.

AIR PUBLICATION 1086
BOOK 4 (i)

SECTION 10C

**RADIO CHOKES
AND
CONDENSERS**

(i)

CAPACITORS, FIXED AND VARIABLE
PREFACE

1. All capacitors, fixed and variable, are shown in rising order of capacity within these groups. Other services' reference numbers, where known, are also included.

2. Classification of the whole range of capacitors has not been completed. This edition covers fixed capacitors in the revised form. Variable capacitors and other headings are shown still with the emphasis on type numbers.

3. Abbreviations:—(a) In "mounting" column: SUSP. = suspension; UPRT. = upright; INVT. = inverted; CLMP. = clamp; UP/SD. = upright or side.
(b) In "dimensions" column, M. = millimetres.

4. Details of the grouping of fixed capacitors are as follows:—

Type	Case or other details	Pages
CERAMIC DIELECTRIC	Solid, including cup, disc and bead ...	1-4
" "	Transmitting type, flanged pot and disc	4
" "	Tubular	4-8
" "	Other types	9
ELECTROLYTIC DIELECTRIC (DRY)	Cylindrical insulated	10
	Cylindrical metal (aluminium tube, etc.)...	10-13
	Cylindrical moulded (pre-moulded plastic tube, usually bakelite)	13
	Rectangular metal	14-15
	Rectangular moulded	15-16
	Tubular	16
	Other types	16
ELECTROLYTIC DIELECTRIC (WET)	All types	17
ELECTROLYTIC DIELECTRIC	Other types, not classifiable under above headings	17
MICA DIELECTRIC ...	Moulded in types, capacity less than 0.001 mfd. (including stacked foil, and metallized, but not protected mica)...	18-22
	Moulded in types, capacity 0.001 mfd. and upwards (including stacked foil, and metallized, but not protected mica) ...	22-26
	Protected types, capacity less than 0.001 mfd.	27-32
	Protected types, capacity 0.001 mfd. and upwards	32-34
	Rectangular metal	34-37
	Rectangular moulded (pre-moulded plastic cases, usually bakelite)	37-39
	Other types, including open clamp ...	39-40
PAPER DIELECTRIC	Cylindrical insulated covering bakelized paper or fibre, paxolin and similar materials	41-44
	Cylindrical metal (metal tube is integral part of the construction)	44-46
	Cylindrical plastic (pre-moulded bakelite or other plastic case)	46-48
	Rectangular capacity less than 1 mfd....	49-52
	Rectangular capacity 1 mfd. and upwards	53-63
	Rectangular steel or other case (static power capacitors)	63
	Other types of highly specialised nature	64

VOCABULARY OF ROYAL AIR FORCE EQUIPMENT—RADIO FIXED CAPACITORS

SECTION 100

(18th September, 1950)

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance \pm %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
CERAMIC DIELECTRIC:—													
Solid:—													
5595	Type 3058	0.5	20	500	—	—	—	—	—	—	C	each	1
3042	Type 1453	1	20	500	1,500	11	11	SUSP.	—	—	C	"	1
11491	Type 542	1.5	15	500	1,500	11	11	SUSP.	—	—	C	"	1
4753	Type 2485	2	20	—	—	—	—	—	—	—	C	"	1
3671	Type 1857	2	20	—	—	—	—	—	—	—	C	"	1
5661	Type 3086	2	20	500	1,500	11	11	SUSP.	—	ZC.3259	C	"	1
11074	Type 511	2	25	500	—	—	—	—	—	—	C	"	1
4632	Type 2423	3	10	500	1,500	9	11	SUSP.	—	ZA.12240	C	"	1
5960	Type 3269	3	10	500	1,500	9	11	SUSP.	—	—	C	"	1
17004	Type —	4	0.5 mmfd.	500	1,500	7	14	SUSP.	W.3756 W.4397	—	C	"	1
729	Type 815	4	0.5 mmfd.	500	1,500	7	14	SUSP.	—	—	C	"	1
14809	Type 4981	4	20	500	—	—	—	—	—	—	C	"	1
5810	Type 3197	4	20	500	1,500	4.5	5	SUSP.	—	ZA.14849	C	"	1
11621	Type 3545	4.5	0.5 mmfd.	500	—	—	—	—	—	—	C	"	1
3861	Type 1950	5	0.5 mmfd.	500	—	—	—	—	—	—	C	"	1
2108	Type 982	5	5	500	1,500	11	11	SUSP.	—	—	C	"	1
12147	Type 3796	5	10	500	1,500	11	13	SUSP.	—	—	C	"	1
2027	Type 937	5	10	500	—	—	—	—	—	—	C	"	1
4755	Type 2487	5	10	500	—	—	—	—	—	—	C	"	1
4768	Type 2500	5	20	500	1,500	13	13	SUSP.	—	ZC.10675	C	"	1
3611	Type 1818	6	0.5 mmfd.	500	1,500	11	13	SUSP.	—	—	C	"	1
12188	Type 3821	6	5	500	1,500	9	11	SUSP.	—	—	C	"	1
12061	Type 3737	6	1 mmfd.	500	1,500	9	11	SUSP.	—	—	C	"	1
13275	Type 4292	7	10	500	1,500	13	13	SUSP.	—	—	C	"	1
11579	Type 3543	7	1 mmfd.	500	1,500	9	11	SUSP.	—	ZC.15641	C	"	1
4240	Type 2185	7.5	5	500	1,500	13	13	SUSP.	—	—	C	"	1
11657	Type 3555	7.5	2 mmfd.	500	1,500	9	11	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
GERAMIC DIELECTRIC—cont.													
Solid—cont.													
3860	Type 1949	8	5	500	1,500	11	11	SUSP.	—	—	C	each	1
12556	Type 4006	8	10	500	—	—	—	—	—	—	C	—	1
13817	Type 4532	8	1 mmfd.	1,500	3,000	9	13.5	SUSP.	—	—	C	—	1
13629	Type 4462	9	10	500	—	—	—	—	—	—	C	—	1
3435	Type 1686	10	5	500	—	—	—	—	—	—	C	—	1
5818	Type 3205	10	5	500	—	—	—	—	—	—	C	—	1
3303	Type 1609	10	5	500	—	—	—	—	—	—	C	—	1
16	Type 572	10	10	500	—	—	—	—	—	—	C	—	1
5683	Type 3108	10	20	500	—	—	—	—	—	—	C	—	1
12062	Type 3738	10	20	500	—	—	—	—	—	—	C	—	1
11569	Type 3538	11.5	0.5 mmfd.	500	1,500	9	11	SUSP.	—	ZA.17169	C	—	1
978	Type 910	15	10	500	—	—	—	—	—	—	C	—	1
4646	Type 2431	15	10	500	1,500	11	13	SUSP.	—	ZC.3263	C	—	1
13708	Type 4492	15	20	—	—	—	—	—	—	—	C	—	1
13138	Type 4230	15	20	500	1,500	11	13	SUSP.	—	ZC.15640	C	—	1
728	Type 814	16	0.2 mmfd.	500	1,500	11	11	SUSP.	—	—	C	—	1
11860	Type 3644	18.5	1	500	1,500	9	11	SUSP.	—	ZC.18569	C	—	1
2707	Type 1300	20	2	500	1,500	9	11	SUSP.	—	ZC.18439	C	—	1
10948	Type 429	20	5	—	—	—	—	—	—	—	C	—	1
3200	Type 1555	20	10	500	1,500	11	13	SUSP.	W.2823	ZC.8985	C	—	1
12047	Type 3733	20	20	500	1,500	11	13	SUSP.	—	ZA.2002	C	—	1
10975	Type 430	25	2	500	1,500	11	13	SUSP.	—	ZC.11075	C	—	1
5168	Type 2760	25	5	500	1,500	11	11	SUSP.	—	ZA.12995	C	—	1
2403	Type 1153	25	10	500	1,500	11	13	SUSP.	W.3955	ZC.12008	C	—	1
4175	Type 2131	25	15	500	—	—	—	—	—	—	C	—	1
5649	Type 3074	25	20	500	1,500	11	13	SUSP.	—	ZC.15639	C	—	1
14154	Type 4663	27	10	500	1,500	9	11	SUSP.	—	—	C	—	1
10395	Type 405	30	2	500	1,500	11	13	SUSP.	—	ZA.0932	C	—	1
3434	Type 1685	30	5	500	1,500	11	11	SUSP.	—	—	C	—	1
2920	Type 1397	30	10	500	1,500	11	13	SUSP.	W.3937	ZA.1567	C	—	1

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	CERAMIC DIELECTRIC—cont.												
	Solid—cont.												
15786	Type —	32	5	500	1,500	9	11	SUSP.	—	ZC.1709	C	each	1
5142	Type 2734	32	10	500	1,500	11	13	SUSP.	—	—	C	"	1
11064	Type 3335	35	2	500	—	—	—	—	—	—	C	"	1
12113	Type 3781	35	5	500	1,500	11	11	SUSP.	50107	—	C	"	1
5221	Type 2813	35	10	500	1,500	11	13	SUSP.	—	ZA.19008	C	"	1
3853	Type 1942	40	0.5 mmfd.	500	1,500	11	13	SUSP.	—	—	C	"	1
11182	Type 3385	40	2	500	—	—	—	—	—	—	C	"	1
14211	Type 4688	40	5	500	1,500	9	11	SUSP.	—	—	C	"	1
2808	Type 1311	40	10	500	1,500	11	13	SUSP.	W.4143	ZA.21379	C	"	1
11417	Type 3484	45	2	500	1,500	—	—	—	—	—	C	"	1
14141	Type 4652	47	20	500	1,500	9	11	SUSP.	—	—	C	"	1
3081	Type 1487	50	5	—	—	—	—	—	—	—	C	"	1
3854	Type 1943	50	1	500	1,500	9	11	SUSP.	—	ZA.14667	C	"	1
14476	Type 4803	50	1	500	1,500	11.5	11	SUSP.	—	—	C	"	1
10568	Type 410	50	2	500	1,500	13	13	SUSP.	—	ZA.10188	C	"	1
308	Type 656	50	5	500	1,500	11	13	SUSP.	—	ZA.12996	C	"	1
3043	Type 1454	50	10	500	1,500	13	13	SUSP.	W.2321	ZA.17627	C	"	1
3870	Type 1959	50	10	500	—	—	—	—	—	—	C	"	1
3025	Type 1437	50	15	500	—	—	—	—	—	—	C	"	1
4762	Type 2494	50	20	500	1,500	11	11	SUSP.	—	ZC.12009	C	"	1
3560	Type 1775	60	2	500	1,500	11	11	SUSP.	W.7928	—	C	"	1
2877	Type 1369	60	5	500	—	—	—	—	—	—	C	"	1
3949	Type 2018	70	5	500	—	—	—	—	—	—	C	"	1
13261	Type 4281	75	5	500	1,500	13	13	SUSP.	—	—	C	"	1
14675	Type 4908	75	20	500	—	—	—	—	—	—	C	"	1
13	Type 565	80	5	500	1,500	11	11	SUSP.	—	ZA.14802	C	"	1
10569	Type 425	100	2	500	—	—	—	—	—	—	C	"	1
3436	Type 1687	100	5	500	1,500	11	11	SUSP.	W.2572	ZA.19921	C	"	1
5956	Type 3265	100	10	500	1,500	13	11	SUSP.	—	ZC.8983	C	"	1
16203	Type 5441	100	20	750	—	—	—	—	—	—	C	"	1
4760	Type 2492	100	20	500	1,600	13	13	SUSP.	—	—	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	CERAMIC DIELECTRIC—cont.												
	Solid—cont.												
14205	Type 4686	200	2	500	1,500	11.5	11	SUSP.	—	—	C	each	1
13048	Type 4197	250	10	500	1,500	12	11	SUSP.	—	—	C	"	1
	Transmitting Type, Flanged Pot and Disc:—												
17882	Type 6208	11	10	3KV	—	—	—	—	—	—	C	"	1
11853	Type 3638	20	5	4,000	7,500	80	33	UPRT.	—	—	C	"	1
2668	Type 1278	20	20	7,500	15KV	30	30	NONE	—	—	C	"	1
17883	Type 6209	40	10	3KV	—	—	—	—	—	—	C	"	1
12742	Type 4073	42	5	—	15,000	30	30	—	—	—	C	"	1
5767	Type 3154	50	20	7,500	15,000	105	38	NONE	—	—	C	"	1
17884	Type 6210	100	10	3,000	—	—	—	—	—	—	C	"	1
14528	Type 4836	100	20	7,500	15KV	63	30	UPRT.	—	—	C	"	1
17625	Type 6136	250	20	—	—	—	—	—	—	—	C	"	1
4506	Type 2332	500	5	1,000	5,000	77	33	NONE	—	—	C	"	1
15095	Type 5108	500	10	15KV	20KV	98	38	NONE	—	—	C	"	1
17881	Type 6207	500	20	—	—	—	—	—	—	—	C	"	1
15094	Type 5107	750	10	15KV	—	—	—	—	—	—	C	"	1
		mfd.											
2366	Type 1148	0.001	10	9,600	20KV	105	57	NONE	—	—	C	"	1
12187	Type 3728	0.001	10	10KV	20KV	98	78	NONE	—	—	C	"	1
12393	Type 3917	0.001	20	5,000	10KV	108	38	UPRT.	—	—	C	"	1
14574	Type 4860	0.001	20	7,500	15KV	105	45	NONE	—	—	C	"	1
14529	Type 4837	0.001	20	7,500	15KV	115	45	NONE	—	—	C	"	1
4791	Type 2523	0.0016	5	10KV	20KV	108	38	UPRT.	—	—	C	"	1
	Tubular:—	mmfd.											
16147	Type 5405	0.0015	20	300	—	32	9	SUSP.	—	—	C	"	1
16094	Type 5368	0.0047	20	300	—	32	9	SUSP.	—	—	C	"	1
5320	Type 2871	1	0.5 mmfd.	500	1,500	15.5	6.5	SUSP.	W.5070A	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
CERAMIC DIELECTRIC—cont.													
Tubular—cont.													
14647	Type 4896	2	¼ mmfd.	500	—	—	—	—	—	—	C	each	1
5962	Type 3271	2	25	500	1,500	16	6	SUSP.	—	—	C	"	1
5321	Type 2872	2	50	500	1,500	11	5	SUSP.	—	—	C	"	1
14719	Type 4939	2-2	20	500	—	—	—	—	—	—	C	"	1
12895	Type 4120	2-5	10	500	1,500	11	5	SUSP.	—	—	C	"	1
12894	Type 4119	3	0.25 mmfd.	500	1,500	11	5	SUSP.	—	—	C	"	1
5322	Type 2873	3	1 mmfd.	500	1,500	11	5	SUSP.	—	ZA.11426	C	"	1
14464	Type 4796	3-3	0.5 pf.	500	1,500	15	3	SUSP.	—	—	C	"	1
14757	Type 4955	3-9	10	500	—	—	—	—	—	—	C	"	1
14585	Type 4864	3-9	10	500	—	—	—	—	—	—	C	"	1
3572	Type 1786	5	1	500	—	—	—	—	—	—	C	"	1
15	Type 571	5	5	500	1,500	16	6	SUSP.	—	—	C	"	1
2979	Type 1431	5	10	500	—	—	—	—	—	—	C	"	1
3219	Type 1573	5	10	500	1,500	16	6	SUSP.	—	ZA.11421	C	"	1
4622	Type 2413	5	10	500	1,500	15	3	SUSP.	—	ZC.0177	C	"	1
5323	Type 2874	5	5 mmfd.	500	—	—	—	—	—	—	C	"	1
15101	Type 5114	5-6	0.5 pf.	500	1,500	16	6	SUSP.	—	—	C	"	1
4252	Type 2197	6-2	0.5	500	—	—	—	—	—	—	C	"	1
5318	Type 2869	7	10	500	1,500	16	6	SUSP.	—	—	C	"	1
4018	Type 2070	7	1 mmfd.	500	1,500	11	5	SUSP.	—	—	C	"	1
5317	Type 2868	8	0.5 mmfd.	500	—	—	—	SUSP.	—	—	C	"	1
4254	Type 2199	8	0.5 mmfd.	500	1,500	16	6	SUSP.	—	—	C	"	1
13051	Type 4199	8+8	20	500	1,000	5	38	UPRT.	—	—	C	"	1
12234	Type 3833	10	1	500	1,500	16	6	SUSP.	—	—	C	"	1
2073	Type 963	10	2½	500	1,500	16	6	SUSP.	—	—	C	"	1
3260	Type 1574	10	3	500	1,500	17	5-5	SUSP.	—	—	C	"	1
5565	Type 3028	10	5	500	1,500	16	6	SUSP.	—	—	C	"	1
3265	Type 1579	10	5	500	1,500	30	8	SUSP.	—	ZC.2251	C	"	1
3036	Type 1447	10	.5 mmfd.	500	1,500	12	5	SUSP.	—	—	C	"	1
5301	Type 2853	10	10	500	1,500	15	6	SUSP.	—	—	C	"	1
4409	Type 2275	10	10	500	1,500	17	5-5	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	CERAMIC DIELECTRIC—cont.												
	Tubular—cont.												
11939	Type 3681	12	0.5 mmfd.	500	—	—	—	—	—	—	C	each	1
3337	Type 1643	15	5	500	1,500	40	12	SUSP.	—	—	C	”	1
713	Type 809	15	10	500	1,500	22	6	SUSP.	—	ZC.0180	C	”	1
4251	Type 2196	16.4	0.5 mmfd.	500	1,500	16	6	SUSP.	—	—	C	”	1
862	Type 863	17	2	500	1,500	15	6	SUSP.	—	—	C	”	1
12233	Type 3832	20	1	500	1,500	11	4	SUSP.	—	—	C	”	1
3574	Type 1788	20	2	500	1,500	17	5	SUSP.	—	—	C	”	1
4486	Type 2312	20	0.5 mmfd.	500	1,500	16	4	SUSP.	—	—	C	”	1
4623	Type 2414	20	0.5 mmfd.	500	—	—	—	—	—	—	C	”	1
5951	Type 3261	20	5	500	1,500	22	6	SUSP.	—	—	C	”	1
14648	Type 4897	20	10	500	—	—	—	—	—	—	C	”	1
3927	Type 1996	20	10	500	1,500	11	4	SUSP.	—	—	C	”	1
3451	Type 1702	20	10	500	1,500	30	8	SUSP.	—	—	C	”	1
5319	Type 2870	20	15	500	1,500	16	6	SUSP.	—	—	C	”	1
4794	Type 2525	20	25	500	1,500	17	5	SUSP.	—	—	C	”	1
15105	Type 5118	22	10	500	1,500	16	6	SUSP.	—	—	C	”	1
16729	Type 5897	22	10	—	—	—	—	—	—	—	C	”	1
12410	Type 3930	23	5	500	—	—	—	—	—	—	C	”	1
4253	Type 2198	24.4	0.5 mmfd.	500	1,500	16	6	SUSP.	—	—	C	”	1
3266	Type 1580	25	2½	500	1,500	60	14	SUSP.	—	—	C	”	1
954	Type 888	25	5	500	—	—	—	—	—	—	C	”	1
3675	Type 6181	25	10	500	1,500	16	4	SUSP.	—	—	C	”	1
672	Type 789	25	10	500	1,500	25	9	SUSP.	—	—	C	”	1
5993	Type 3302	25	20	500	—	—	—	—	—	—	C	”	1
15106	Type 5119	27	10	500	1,500	16	6	SUSP.	—	—	C	”	1
4795	Type 2526	30	5	500	—	—	—	SUSP.	—	—	C	”	1
2075	Type 965	30	5	500	1,500	16	6	SUSP.	—	—	C	”	1
3566	Type 1781	30	2 mmfd.	500	1,500	29	7	SUSP.	—	—	C	”	1
874	Type 868	30	10	500	1,500	29	7	SUSP.	—	—	C	”	1
12409	Type 3929	33	5	500	—	—	—	—	—	—	C	”	1
861	Type 862	35	2	500	1,500	30	7.5	SUSP.	—	—	C	”	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
CERAMIC DIELECTRIC—cont.													
Tubular—cont.													
853	Type 858	40	2	500	1,500	29	7	SUSP.	—	—	C	each	1
17591	Type 6115	40	5	500	—	—	—	—	—	—	C	"	1
3089	Type 1495	40	10	500	1,500	15	3	SUSP.	—	—	C	"	1
858	Type 860	45	2	500	1,500	45	9	SUSP.	—	—	C	"	1
15043	Type 5085	47	10	500	—	—	—	—	—	—	C	"	1
857	Type 859	48	2	500	1,500	16	6	SUSP.	—	ZC.3447	C	"	1
2079	Type 969	50	1	500	1,500	16	6	SUSP.	—	ZA.1654	C	"	1
4630	Type 2421	50	2	500	1,500	16	4	SUSP.	—	ZC.2701	C	"	1
14880	Type 5007	50	2	500	1,500	16	7	SUSP.	—	—	C	"	1
2874	Type 1366	50	2½	500	1,500	16	6	SUSP.	—	—	C	"	1
3573	Type 1787	50	5	500	1,500	29	7	SUSP.	—	—	C	"	1
2718	Type 1321	50	5	500	1,500	16	6	SUSP.	—	—	C	"	1
673	Type 790	50	10	500	—	—	—	—	—	—	C	"	1
2561	Type 1208	60	2	500	1,500	45	9	SUSP.	—	—	C	"	1
859	Type 861	70	2	500	1,500	35	9	SUSP.	—	—	C	"	1
2434	Type 1180	75	5	500	1,500	30	8	SUSP.	—	—	C	"	1
3045	Type 1455	75	10	500	1,500	15	6	SUSP.	—	—	C	"	1
3263	Type 1577	80	10	500	1,500	16	6	SUSP.	—	—	C	"	1
13803	Type 4519	80	10	—	—	50	9	—	—	—	C	"	1
3397	Type 1661	80	15	500	1,500	30	8	SUSP.	—	—	C	"	1
3035	Type 1446	90	2	500	1,500	16	4	SUSP.	—	—	C	"	1
3614	Type 1820	100	1	500	—	—	—	—	—	—	C	"	1
12232	Type 3831	100	1	500	1,500	17	5	SUSP.	—	—	C	"	1
14686	Type 4919	100	2	500	—	—	—	—	—	—	C	"	1
5761	Type 3148	100	5	500	1,500	16	4	SUSP.	—	—	C	"	1
4951	Type 2641	100	5	500	1,500	16	6	SUSP.	—	ZA.1417	C	"	1
3586	Type 1800	100	5	500	1,500	38	6	SUSP.	—	—	C	"	1
5663	Type 3088	100	10	500	1,500	39	6	SUSP.	52122	—	C	"	1
18110	Type 6304	100	10	500	—	—	—	—	—	—	C	"	1
714	Type 810	100	10	500	1,500	16	6	SUSP.	—	ZC.19310	C	"	1
14515	Type 4828	100	15	500	1,500	22	6	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (mm.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	CERAMIC DIELECTRIC—cont.												
	Tubular—cont.												
667	Type 788	110	10	500	1,500	16	6	SUSP.	W.2819	—	C	each	1
16628	Type 5816	115	5	500	—	—	—	—	—	—	C	—	1
14689	Type 4920	130	3	500	—	—	—	—	—	—	C	—	1
5872	Type 3220	150	0.5 mmfd.	500	1,500	21	7	SUSP.	—	—	C	—	1
15964	Type 5308	150	10	500	1,500	28	5	SUSP.	—	—	C	—	1
732	Type 818	160	5	500	1,500	38	6	SUSP.	—	—	C	—	1
3606	Type 1814	200	1	500	1,500	40	12	SUSP.	—	—	C	—	1
5036	Type 2706	200	5	500	1,500	27	6	SUSP.	—	—	C	—	1
4920	Type 2610	200	5	500	1,500	21	6	SUSP.	—	ZA.21657	C	—	1
869	Type 865	200	10	500	1,500	40	12	SUSP.	—	ZC.8634	C	—	1
13332	Type 4337	200	10	500	—	—	—	—	—	—	C	—	1
18111	Type 6305	220	10	500	—	—	—	—	—	—	C	—	1
16146	Type 5404	220	20	300	900	16	6	SUSP.	—	—	C	—	1
3216	Type 1570	300	10	500	1,500	27	6.5	SUSP.	—	—	C	—	1
712	Type 808	350	10	500	1,500	30	7.5	SUSP.	—	—	C	—	1
4347	Type 2252	400	2½	500	—	—	—	—	—	—	C	—	1
2213	Type 1051	450	2	500	1,500	27	8	SUSP.	—	—	C	—	1
18112	Type 6306	470	10	500	—	—	—	—	—	—	C	—	1
3603	Type 1811	500	1	500	—	—	—	—	—	—	C	—	1
2401	Type 1151	500	5	500	1,500	27	8	SUSP.	W.2571	—	C	—	1
3214	Type 1568	500	10	500	1,500	42	8	SUSP.	51378	—	C	—	1
3034	Type 1445	600	2	500	1,500	45	9	SUSP.	—	—	C	—	1
13914	Type 4571	650	5	500	1,500	45	9	SUSP.	—	—	C	—	1
18113	Type 6307680 mfd.	10	500	—	—	—	—	—	—	C	—	1
3992	Type 2048	0.001	5	500	—	—	—	—	—	—	C	—	1
18114	Type 6308	0.001	10	500	—	—	—	—	—	—	C	—	1
14734	Type 4940	0.001	10	500	—	—	—	—	—	—	C	—	1
17705	Type 6176	0.001	20	500	8 KV at 85° C.	—	—	—	—	—	C	—	1
2209	Type 1048	0.0012	1	500	1,500	53	9	SUSP.	—	—	C	—	1
5020	Type 2690	4	5	—	—	—	—	—	—	—	C	—	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No	NOMENCLATURE	Capacity	Tolerance ± %	Voltage	DETAIL	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7	8	9
	CERAMIC DIELECTRIC —cont.							
	Other Types:—							
11746	Type 3577	1 mmfd.	20	500	Silvered Ceramic, pearl	C	each	1
17866	Type 6200	5.5 mmfd. + 5 mmfd.	—	3K	Ceramic Trimmer, $\frac{1}{2}$ in. max. dia. \times $\frac{3}{8}$ in. long	C	"	1
3666	Type 1852	22 mmfd.	10	—	Ceramic. Called for on RF Unit T10 only ...	C	"	1
3084	Type 1490	25-3 mmfd.	—	—	Variable Ceramic Trimmer	A	"	1
3668	Type 1854	47 mmfd.	10	—	Ceramic. Called for on RF Unit T10 only ...	C	"	1
17867	Type 6201	75 mmfd.	5	6K DC wkg.	Ceramic Trimmer, $\frac{1}{2}$ in. max. dia. \times $\frac{1}{8}$ in. long...	C	"	1
12356	Type 3898	15-3.5 mmfd.	—	500	Ceramic Trimmer Rotor Ceramic Grade I ...	C	"	1
11743	Type 3574	3.5 mmfd. to 13.5 mmfd.	—	—	Ceramic Trimmer Central adjusting screw ...	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage Working	OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13
ELECTROLYTIC DIELECTRIC:—												
Dry:—												
Cylindrical:—												
Insulated												
382	Type 687	2	- 0+ 50	200	2	$\frac{9}{16}$	SUSP.	—	ZA.2197	C	each	1
2426	Type 1169	2	- 0+ 50	250	2	$\frac{11}{16}$	SUSP.	—	ZC.2164	C	"	1
4614	Type 2405	2	-10+ 50	300	2	$\frac{11}{16}$	SUSP.	W.2564	ZC.8440	C	"	1
4950	Type 2640	4	- 0+ 50	350	$2\frac{1}{2}$	$\frac{3}{4}$	SUSP.	—	—	C	"	1
11098	Type 3352	4	- 0+100	100	2	$\frac{11}{16}$	SUSP.	—	—	C	"	1
11896	Type 3651	8	- 0+ 50	350	$2\frac{1}{2}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
3544	Type 1759	8	-15+100	150	$2\frac{1}{2}$	$\frac{11}{16}$	SUSP.	—	ZA.1946	C	"	1
3474	Type 1717	12	- 0+100	200	$2\frac{1}{2}$	1	SUSP.	—	ZA.14389	C	"	1
4095	Type 2097	20	- 0+ 50	50	$2\frac{1}{2}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
5349	Type 2897	25	- 0+ 50	50	$2\frac{1}{2}$	$\frac{3}{4}$	SUSP.	—	ZC.11482	C	"	1
4980	Type 2670	25	-10+100	25	$3\frac{1}{4}$	$\frac{3}{4}$	SUSP.	—	—	C	"	1
2965	Type 1420	50	- 0+ 50	12	2	$\frac{11}{16}$	SUSP.	—	P.8B0033	C	"	1
2148	Type 994	50	-10+100	12	$2\frac{3}{4}$	$\frac{7}{8}$	SUSP.	—	—	C	"	1
2653	Type 1269	50	-20+ 50	25	$2\frac{1}{2}$	$\frac{3}{4}$	SUSP.	W.6951	ZA.11236	C	"	1
4703	Type 2474	100	- 0+100	20	$2\frac{3}{4}$	1	SUSP.	—	ZA.11236	C	"	1
610	Type 775	160	- 0+ 50	15	$2\frac{5}{8}$	$\frac{15}{16}$	SUSP.	—	—	C	"	1
844	Type 857	250	-20+ 50	12	$2\frac{1}{4}$	1	SUSP.	—	—	C	"	1
Metal:—												
10911	Type 501	2	10	25	$2\frac{3}{4}$	$\frac{3}{4}$	STUD	—	—	C	"	1
13288	Type 4301	2	-20+ 50	350	$3\frac{1}{8}$	$\frac{3}{4}$	STUD	—	—	C	"	1
4779	Type 2511	4	- 0+ 50	200	$2\frac{3}{4}$	$\frac{3}{4}$	STUD	—	—	C	"	1
16557	Type 5750	4	-20+ 50	375	$3\frac{3}{8}$	1	CLMP	—	—	C	"	1
4780	Type 2512	4	10	500	$3\frac{7}{8}$	1	STUD	—	—	C	"	1
13281	Type 4295	4	-20+ 50	350	$3\frac{5}{8}$	1	STUD	—	—	C	"	1
12657	Type 4036	4	-20+ 50	350	$2\frac{3}{4}$	1	STUD	—	—	C	"	1
11482	Type 3503	4	-20+ 50	450	$3\frac{7}{16}$	1	STUD	—	—	C	"	1
13211	Type 4260	4	-20+ 50	500	$3\frac{1}{4}$	$1\frac{3}{8}$	CLMP	—	—	C	"	1
17774	Type 6186	8	- 0+ 50	550	$2\frac{3}{4}$	$1\frac{1}{2}$	—	—	—	C	"	1
4781	Type 2513	8	-10+ 50	500	$5\frac{1}{2}$	1	STUD	W.5567	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage Working	OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13
	ELECTROLYTIC DIELECTRIC—cont.											
	Dry—cont.											
	Cylindrical—cont.											
	Metal—cont.											
11856	Type 3641	8	20	500	5½	1½	STUD	—	—	C	each	1
13194	Type 4252	8	20	500	3¼	1⅝	CLMP.	—	—	C	"	1
3639	Type 1830	8	-20 + 50	120	3	3⅜	STUD	—	—	C	"	1
4231	Type 2176	8	-20 + 50	150	3⅜	3¼	STUD	—	—	C	"	1
13287	Type 4300	8	-20 + 50	250	3⅝	1	STUD	—	—	C	"	1
4656	Type 2441	8	-20 + 50	350	2⅝	1	STUD	—	ZC.18810	C	"	1
3138	Type 1534	8	-20 + 50	350	3⅞	1	STUD	—	—	C	"	1
13289	Type 4302	8	-20 + 50	350	3¼	1⅝	CLMP.	—	—	C	"	1
14893	Type 5011	8	-20 + 50	125	3¼	1⅝	CLMP.	50757	—	C	"	1
10408	Type 4622	8	-20 + 50	275	2½	1	SUSP.	—	—	C	"	1
14070	Type 4629	8	-20 + 50	500	2½	1	CLMP.	—	—	C	"	1
3485	Type 1719	8	-20 + 50	750	5½	1⅝	CLMP.	—	ZA.14429	C	"	1
3787	Type 1917	16	- 0 + 50	500	5½	1½	STUD	—	—	C	"	1
13086	Type 4220	16	-10 + 50	450	4⅝	1⅝	CLMP.	—	—	C	"	1
4631	Type 2422	16	-10 + 50	475	5⅞	1⅝	CLMP.	—	ZA.14433	C	"	1
13674	Type 4482	16	-20 + 50	350	3½	1⅝	STUD	—	—	C	"	1
5528	Type 2991	16	-20 + 50	450	3⅞	1⅝	CLMP.	—	—	C	"	1
14174	Type 4670	16	-20 + 50	500	4½	1⅝	CLMP.	—	—	C	"	1
13212	Type 4261	16	-20 + 50	500	5	1⅝	CLMP.	—	—	C	"	1
4778	Type 2510	16	-20 + 50	500	5½	1½	STUD	—	ZC.3815	C	"	1
5883	Type 3231	20	-20 + 50	50	3⅞	1	STUD	—	—	C	"	1
289	Type 653	20	-20 + 50	50	3⅞	1	STUD	—	ZA.13416	C	"	1
4022	Type 2074	24	-15 + 50	650	5⅝	1¼	CLMP.	—	—	C	"	1
12526	Type 3994	24	-20 + 50	550	2½	1⅝	—	—	—	C	"	1
12428	Type 3935	25	-20 + 50	25	2⅝	1	STUD	—	—	C	"	1
15969	Type 5311	25	-20 + 50	50	3¼	¾	CLMP.	50755	ZA.29811	C	"	1
17022	Type	25	-20 + 50	25	2¼	⅝	SUSP.	—	ZC.18560	C	"	1
11977	Type 3703	25	-20 + 50	25	3⅞	¾	STUD	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage Working	OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13
	ELECTROLYTIC DIELECTRIC—cont.											
	Dry—cont.											
	Cylindrical—cont.											
	Metal—cont.											
16559	Type 5752	25	-20+ 50	25	2 $\frac{3}{8}$	$\frac{3}{4}$	CLMP.	—	—	C	each	1
13283	Type 4296	25	-20+ 50	50	3 $\frac{3}{8}$	1	STUD	—	—	C	"	1
13962	Type 4587	25	-20+ 50	50	2 $\frac{3}{4}$	$\frac{3}{4}$	SUSP.	—	YB.04065	C	"	1
12302	Type 3855	32	- 0+ 50	450	5	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
12433	Type 3938	32	-20+ 50	350	5 $\frac{1}{16}$	1 $\frac{3}{8}$	CLMP.	W.5937	—	C	"	1
13290	Type 4303	32	-20+ 50	500	5	2	CLMP.	—	—	C	"	1
14754	Type 4953	40, 30 at 40° C.	—	200	—	—	—	—	—	C	"	1
12390	Type 3914	40	- 0+100	12	2 $\frac{1}{16}$	1	STUD	—	—	C	"	1
5946	Type 3256	40	-20+ 50	12	3 $\frac{1}{16}$	1	STUD	—	—	C	"	1
4501	Type 2327	50	-10+ INF	6	3 $\frac{3}{8}$	$\frac{3}{4}$	STUD	—	—	C	"	1
9611	Type 323	50	10	12	2 $\frac{7}{8}$	$\frac{3}{4}$	STUD	—	—	C	"	1
11927	Type 3670	50	-10+100	60	4 $\frac{1}{4}$	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
13193	Type 4251	50	20	12	3 $\frac{1}{4}$	$\frac{3}{4}$	STUD	—	—	C	"	1
4526	Type 2339	50	20	60	3 $\frac{13}{32}$	1	STUD	—	—	C	"	1
13375	Type 4360	50	-20+ 50	12	3 $\frac{1}{8}$	$\frac{3}{4}$	STUD	—	—	C	"	1
14303	Type 4716	50	-20+ 50	50	2 $\frac{3}{4}$	1	SUSP.	—	—	C	"	1
3072	Type 1482	50	-20+ 50	50	3 $\frac{13}{16}$	1	STUD	—	—	C	"	1
15837	Type 5227	50	-20+ 50	50	3 $\frac{3}{4}$	1	CLMP.	50756	—	C	"	1
16558	Type 5751	50	-20+ 50	50	3 $\frac{3}{8}$	1	CLMP.	—	—	C	"	1
13284	Type 4297	50	-20+ 50	50	3 $\frac{3}{8}$	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
15736	Type	50	-20+ 50	75	3 $\frac{3}{4}$	1 $\frac{3}{4}$	CLMP.	—	ZA.23971	C	"	1
15190	Type 5180	80	-20+ 50	100	5 $\frac{1}{8}$	1 $\frac{3}{8}$	CLMP.	W.3938	—	C	"	1
11907	Type 3657	200	—	35	—	—	—	—	—	C	"	1
13999	Type 4602	200	-20+ 50	25	3	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
13646	Type 4472	200	-20+ 50	250	—	—	—	—	—	C	"	1
11995	Type 3708	250	-20+ 50	20	3 $\frac{1}{16}$	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
11996	Type 3709	500	-20+ 50	15	4 $\frac{1}{16}$	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
11908	Type 3658	800	—	9	—	—	—	—	—	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage Working	OVERALL DIMENSIONS (ins)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
					Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13
	ELECTROLYTIC DIELECTRIC—cont.											
	Dry—cont.											
	Cylindrical—cont.											
	Metal—cont.											
11909	Type 3659	800	—	12	—	—	—	—	—	C	each	1
14041	Type 4616	8-8	-20+ 50	500	5 $\frac{7}{16}$	1 $\frac{1}{2}$	STUD	—	ZA.20663	C	"	1
17009	Type	8+8+8	-20+ 50	400	4 $\frac{1}{4}$	1 $\frac{3}{8}$	UPRT.	—	ZA.20068	C	"	1
13906	Type 4567	8+32	-20+ 50	450	4 $\frac{1}{2}$	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
5655	Type 3080	8+32	-10+ 50	500	4 $\frac{11}{16}$	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
18128	Type 6339	32+32	—	450	3 $\frac{1}{2}$	1 $\frac{3}{8}$	—	—	—	C	"	1
				at 60°C.								
4397	Type 2263	16-8	-20+ 50	350	5 $\frac{1}{2}$	1 $\frac{1}{2}$	STUD	—	—	C	"	1
13208	Type 4257	8-8-8	-20+ 50	400	4 $\frac{1}{4}$	1 $\frac{1}{4}$	5 Pin Base	—	—	C	"	1
	Moulded:—											
5538	Type 3001	4	10	200	2 $\frac{7}{32}$	1 $\frac{1}{32}$	SUSP.	—	—	C	"	1
2677	Type 1281	25	-20+ 50	25	2 $\frac{7}{32}$	1 $\frac{1}{32}$	SUSP.	—	—	C	"	1
5041	Type 2711	40	—	40	—	—	—	—	—	C	"	1
534	Type 755	50	-20+ 50	12	2 $\frac{7}{32}$	1 $\frac{1}{8}$	SUSP.	—	—	C	"	1
2710	Type 1303	50	-20+ 50	12	2 $\frac{7}{32}$	1 $\frac{1}{32}$	SUSP.	—	—	C	"	1
13191	Type 4249	160	-20+ 50	15	2 $\frac{11}{32}$	1 $\frac{1}{4}$	SUSP..	—	—	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance \pm %	Voltage Working	OVERALL DIMENSIONS (ins)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	ELECTROLYTIC DIELECTRIC—cont.												
	Dry—cont.												
	Rectangular:—												
	Metal:—												
2936	Type 1414	4	-20 + 50	750	$5\frac{9}{16}$	$2\frac{1}{4}$	$1\frac{1}{8}$	CLMP.	—	—	C	each	1
4536	Type 2349	8	—	—	$5\frac{11}{16}$	$2\frac{3}{4}$	$1\frac{1}{16}$	—	—	—	C	"	1
5434	Type 2936	8	- 0 + INF	250	$2\frac{1}{2}$	$3\frac{1}{2}$	1	UPRT.	—	ZA.1313	C	"	1
2971	Type 1426	8	-20 + 50	450	$5\frac{9}{16}$	2	$1\frac{1}{8}$	CLMP.	—	—	C	"	1
11400	Type 3469	8	-15 + 100	500	$5\frac{3}{8}$	$2\frac{3}{4}$	$2\frac{3}{16}$	INVT.	—	—	C	"	1
5335	Type 2885	10	10	50	$3\frac{1}{8}$	3	$1\frac{1}{8}$	INVT.	—	—	C	"	1
5439	Type 2941	10	-15 + 50	450	$2\frac{3}{8}$	2	$1\frac{1}{8}$	UPRT.	—	—	C	"	1
3271	Type 1585	16	-10 + 30	400	$5\frac{3}{16}$	3	$1\frac{1}{2}$	INVT.	—	—	C	"	1
12607	Type 4021	16	-20 + 50	550	$5\frac{9}{16}$	$2\frac{1}{2}$	$2\frac{1}{2}$	CLMP.	—	—	C	"	1
568	Type 768	16	-20 + 50	700	$5\frac{9}{16}$	$3\frac{3}{4}$	$2\frac{1}{16}$	CLMP.	—	—	C	"	1
11399	Type 3468	16	-10 + 25	450	$5\frac{3}{8}$	$2\frac{1}{2}$	$2\frac{1}{16}$	INVT.	—	—	C	"	1
532	Type 753	16	-20 + 50	250	$3\frac{3}{16}$	$2\frac{3}{4}$	$1\frac{1}{8}$	INVT.	—	—	C	"	1
5592	Type 3055	16	-15 + 50	700	$5\frac{9}{16}$	$2\frac{3}{4}$	$2\frac{3}{16}$	INVT.	—	—	C	"	1
2968	Type 1423	16	-20 + 50	450	$5\frac{9}{16}$	$2\frac{1}{2}$	$2\frac{1}{2}$	CLMP.	—	—	C	"	1
11264	Type 3429	16	-25 + INF	450	2	$3\frac{1}{4}$	$1\frac{1}{8}$	SIDE	—	—	C	"	1
17786	Type 6189	16 + 16	-10 + 50	350	$2\frac{3}{8}$	3	2	INVT.	—	—	C	"	1
5333	Type 2883	25	-10 + 50	25	$3\frac{1}{8}$	3	$1\frac{1}{8}$	INVT.	—	—	C	"	1
10755	Type 464	25	- 0 + 100	25	$1\frac{13}{16}$	$2\frac{1}{2}$	$1\frac{3}{4}$	FEET	—	—	C	"	1
565	Type 765	32	-20 + 50	300	$5\frac{9}{16}$	2	$1\frac{13}{16}$	CLMP.	—	—	C	"	1
3272	Type 1586	32	-10 + 30	400	$5\frac{9}{16}$	3	$1\frac{3}{8}$	INVT.	—	—	C	"	1
2029	Type 939	32	-20 + 50	400	$5\frac{9}{16}$	2	$1\frac{13}{16}$	CLMP.	—	—	C	"	1
2440	Type 1186	32	-20 + 50	500	$5\frac{9}{16}$	$2\frac{3}{4}$	2	INVT.	—	—	C	"	1
2605	Type 1231	32	-20 + 50	500	$5\frac{9}{16}$	$2\frac{1}{4}$	$1\frac{5}{8}$	CLMP.	—	—	C	"	1
559	Type 761	32	-20 + 50	600	$5\frac{9}{16}$	4	$1\frac{13}{16}$	CLMP.	—	—	C	"	1
5693	Type 3118	50	15	—	—	—	—	INVT.	—	—	C	"	1
11204	Type 3407	50	25	50	$3\frac{1}{4}$	$2\frac{3}{4}$	$\frac{3}{8}$	FEET	—	—	C	"	1
666	Type 787	60	-20 + 50	9	$1\frac{11}{16}$	$2\frac{3}{4}$	$2\frac{7}{8}$	SIDE	—	—	C	"	1
716	Type 812	60	-20 + 50	12	$1\frac{11}{16}$	$2\frac{3}{4}$	$2\frac{7}{8}$	INVT.	—	—	C	"	1
531	Type 752	60	-20 + 50	200	$5\frac{7}{16}$	$2\frac{1}{4}$	$1\frac{1}{8}$	CLMP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Working Voltage	OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Height	Width	Depth						
1	2	3	4	5	6	7	8	9	19	11	12	13	14
	ELECTROLYTIC DIELECTRIC—cont.												
	Dry—cont.												
	Rectangular—cont.												
	Metal—cont.												
2928	Type 1405	60	-20+ 50	600	5 $\frac{9}{16}$	5 $\frac{7}{16}$	2 $\frac{3}{4}$	CLMP.	—	—	C	"	1
5568	Type 3031	80	15	10	1 $\frac{1}{16}$	2 $\frac{13}{16}$	1 $\frac{1}{16}$	INVT.	—	—	C	"	1
2606	Type 1232	160	- 2+ 50	13	5 $\frac{9}{16}$	2 $\frac{1}{4}$	2 $\frac{3}{8}$	CLMP.	—	—	C	"	1
2438	Type 1184	160	-20+ 50	13	2 $\frac{15}{16}$	2 $\frac{1}{4}$	1	INVT.	—	—	C	"	1
652	Type 783	200	-20+ 50	35	5 $\frac{5}{16}$	2 $\frac{5}{8}$	1 $\frac{1}{4}$	INVT.	—	—	C	"	1
11203	Type 3406	250	-20+ 50	12	5 $\frac{3}{16}$	3	2	UPRT.	—	—	C	"	1
14430	Type 4768	250	-20+ 50	100	5 $\frac{3}{4}$	4	3	UPRT.	—	—	C	"	1
5644	Type 3069	500	- 0+ 50	50	5 $\frac{3}{4}$	3	2	UPRT.	—	—	C	"	1
653	Type 784	800	-20+ 50	9	5 $\frac{5}{16}$	2 $\frac{5}{8}$	1 $\frac{1}{8}$	INVT.	—	—	C	"	1
654	Type 785	800	-20+ 50	12	5 $\frac{5}{16}$	2 $\frac{5}{8}$	1 $\frac{1}{2}$	INVT.	—	—	C	"	1
8959	Type 234	2,000	-10+ 50	12	5 $\frac{3}{4}$	3	2	UPRT.	—	ZC.10652	C	"	1
13080	Type 4216	2,000	-20+ 50	25	5 $\frac{3}{4}$	3	3	UPRT.	—	ZA.13418	C	"	1
11003	Type 3312	8-8	-10+ 30	450	5	2 $\frac{1}{8}$	1 $\frac{3}{8}$	INVT.	—	—	C	"	1
11265	Type 3430	8+8	-25+ INF	450	2	3 $\frac{1}{4}$	1 $\frac{1}{8}$	SIDE	—	—	C	"	1
4933	Type 2623	8+8+8	-20+ 50	550	4 $\frac{1}{4}$	3 $\frac{3}{8}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
11979	Type 3704	8+16	8-10+30 16-15+50	450 350	4	3	2	UPRT.	—	ZA.21759	C	"	1
5825	Type 3212	8+16	-10+ 40	450	5 $\frac{1}{2}$	3 $\frac{3}{16}$	1 $\frac{7}{16}$	INVT.	—	—	C	"	1
5598	Type 3061	8+16	-20+ 50	550	5 $\frac{1}{2}$	3	2	INVT.	—	WY/10C/ 5598	C	"	1
4351	Type 2256	16+16+16	-20+ 50	450	5 $\frac{3}{16}$	3	2	INVT.	—	—	C	"	1
8638	Type 207	2000+2000	-20+ 50	12	5 $\frac{3}{4}$	3	3	UPRT.	—	ZA.46345	C	"	1
	Moulded:—												
4876	Type 2568	15	-20+ 50	100	2 $\frac{3}{4}$	2 $\frac{3}{4}$	1 $\frac{1}{16}$	UPRT.	—	—	C	"	1
3864	Type 1953	30	-20+ 50	100	2 $\frac{3}{4}$	2 $\frac{3}{4}$	1 $\frac{1}{16}$	UPRT.	—	—	C	"	1
3188	Type 1543	30	-20+ 50	200	2 $\frac{7}{8}$	2 $\frac{11}{16}$	1 $\frac{1}{8}$	UPRT.	9773	—	C	"	1
10802	Type 478	80	-20+ 50	100	3 $\frac{1}{8}$	2 $\frac{3}{4}$	2 $\frac{1}{16}$	UPRT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	Voltage Working	OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	ELECTROLYTIC DIELECTRIC—cont.												
	Dry—cont.												
	Rectangular—cont.												
	Moulded—cont.												
2255	Type 1070	100	— 0 + 50	50	2 $\frac{3}{4}$	2 $\frac{13}{16}$	1 $\frac{1}{8}$	UPRT.	—	—	C	each	1
2729	Type 1332	250	— 20 + 50	12	2 $\frac{7}{8}$	2 $\frac{13}{16}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
5801	Type 3188	250	— 20 + 50	25	3	2 $\frac{3}{4}$	2 $\frac{5}{16}$	UPRT.	—	—	C	"	1
17525	Type 6072	500	—	12	2 $\frac{1}{2}$	2 $\frac{5}{16}$	2 $\frac{3}{8}$	—	—	—	C	"	1
	Tubular:—												
5697	Type 3122	4	— 10 + 15	200	—	—	—	—	—	—	C	"	1
733	Type 819	25	— 0 + 50	25	—	—	—	—	—	—	C	"	1
14654	Type 4898	50	— 20 + 50	12	—	—	—	—	—	—	C	"	1
2265	Type 1080	60	—	—	5 $\frac{1}{8}$	1 $\frac{3}{4}$	—	—	—	—	C	"	1
						dia.							
3784	Type 1914	100	—	—	—	—	—	—	—	—	C	"	1
	Other Types:—												
17585	Type 6109	1	—	350	—	—	—	—	—	—	C	"	1
13279	Type 4294	8	— 20 + 50	440	5 $\frac{3}{8}$	4 $\frac{1}{4}$	3 $\frac{3}{4}$	UPRT.	—	—	C	"	1
14964	Type 5051	8	— 20 + 50	150	2 $\frac{1}{4}$	2 $\frac{3}{4}$	—	—	—	—	C	"	1
						dia.							
3122	Type 1517	8+8	10	450	3 $\frac{1}{2}$	2 in. wide	1 $\frac{3}{8}$	CLMP.	—	—	C	"	1
16989	Type 6052	8+16	— 20 + 50	350	—	—	—	—	—	—	C	"	1
16876	Type 5993	10	—	25V at 71°C.	—	—	—	—	—	—	C	"	1
14655	Type 4899	12	—	50	—	—	—	—	—	—	C	"	1
16875	Type 5992	20	—	12V at 71°C	—	—	—	—	—	—	C	"	1
4695	Type 2466	25	—	75	—	—	—	—	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance \pm %	Voltage Working	OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
					Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13
ELECTROLYTIC DIELECTRIC—cont.												
Wet:—												
All Types:—												
4352	Type 2257	8	-20+50	440	5 $\frac{5}{8}$	1 $\frac{3}{8}$	STUD	—	ZA.17568	C	each	1
443	Type 711	8	-20+50	500	5 $\frac{5}{8}$	1 $\frac{3}{8}$	STUD	—	ZA.1428	C	"	1
2612	Type 1236	16	- 0+50	440	5 $\frac{5}{8}$	1 $\frac{3}{8}$	STUD	—	—	C	"	1
3071	Type 1481	32	- 0+50	320	5 $\frac{5}{8}$	1 $\frac{3}{8}$	STUD	—	—	C	"	1
4097	Type 2099	32	-20+50	320	5 $\frac{5}{8}$	1 $\frac{3}{8}$	STUD	—	ZA.11348	C	"	1
741	Type 827	32	-20+50	320	5 $\frac{5}{8}$	1 $\frac{3}{8}$	STUD	—	—	C	"	1
4401	Type 2267	32	15	320	5 $\frac{5}{8}$	1 $\frac{3}{8}$	STUD	—	—	C	"	1

ELECTROLYTIC DIELECTRIC—cont.

Other types not classifiable under above headings:—

Ref. No.	NOMENCLATURE	Detail	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6
2794	Type 1336	16-8 μ f. 500 VDC	C	each	1
12852	Type 4099	25 μ f. Tolerance, \pm 50 per cent., 25 Watts Tubular	C	"	1
11063	Type 3334	100 μ f. Tolerance, \pm 50 per cent., 50 VDC. Bakelite case, 4 B.A. Terminals	C	"	1
16259	Type 5487	2000 mfd. VDC 25 V working, 4 $\frac{1}{2}$ in. \times 3 in. \times 3 in.	C	"	1
16793	Type 5950	50 mfd. \pm 100 12V at 71°C. Miniature Rev. 1 $\frac{1}{2}$ in. \times $\frac{3}{4}$ in., reversible type	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC:—													
	Moulded:—													
	Less than .001 mfd.:—													
14710	Type 4935	0.1	15	750	2,200	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{15}{16}$	SUSP.	—	ZA.1776	C	each	1
4556	Type 2366	3.5	1 pf.	350	1,000	—	—	—	—	—	—	C	"	1
4688	Type 2459	20	10	350	1,000	$\frac{3}{32}$	$\frac{15}{16}$	$\frac{1}{2}$	SUSP.	—	—	C	"	1
4699	Type 2470	25	15	350	1,000	$\frac{3}{32}$	$\frac{15}{16}$	$\frac{1}{2}$	SUSP.	—	—	C	"	1
3998	Type 2054	25	15	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	ZA.21380	C	"	1
4785	Type 2517	25	15	750	—	—	—	—	—	—	—	C	"	1
9184	Type 285	30	5	350	1,000	$\frac{3}{16}$	$2\frac{3}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
9642	Type 327	30	10	—	—	—	—	—	—	—	—	C	"	1
8800	Type 228	30	10	350	1,000	$\frac{3}{16}$	$2\frac{1}{2}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
16959	Type 6040	30	20	750	—	—	—	—	—	—	—	C	"	1
3938	Type 2007	40	2	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
3383	Type 1648	40	-20 +40	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
682	Type 794	45	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
14285	Type 4711	50	2	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
7903	Type 122	50	5	350	1,000	$\frac{3}{16}$	$1\frac{7}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
8659	Type 212	50	5	750	2,200	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
13534	Type 4426	50	10	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
2039	Type 944	50	10	750	2,200	$\frac{3}{32}$	$2\frac{1}{2}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
4416	Type 2282	50	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
4687	Type 2458	50	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	W.5608	ZA.21382	C	"	1
8386	Type 176	50	15	350	1,000	$\frac{3}{16}$	$2\frac{3}{8}$	$\frac{11}{16}$	SUSP.	W.2117	—	C	"	1
3273	Type 1587	50	15	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
5546	Type 3009	50	20	350	1,000	$\frac{3}{32}$	$\frac{15}{16}$	$\frac{1}{2}$	SUSP.	—	—	C	"	1
14995	Type 5068	50	+100	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
17584	Type 6108	68	2	350	—	—	—	—	—	—	—	C	"	1
5176	Type 2768	75	5	350	—	—	—	—	—	—	—	C	"	1
16695	Type 5870	75	5	350	—	—	—	—	—	—	—	C	"	1
3437	Type 1688	75	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
2554	Type 1206	80	5	1,500	4,500	$\frac{3}{8}$	$2\frac{7}{8}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
2416	Type 1165	80	10	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (INS)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DELECTRIC—cont. Moulded—cont. Less than .001 mfd.—cont.													
15876	Type 5265	93	2	350	1,000	$\frac{5}{32}$	$\frac{15}{16}$	$\frac{1}{2}$	SUSP.	—	—	C	each	1
4782	Type 2514	100	5	250	—	—	—	—	—	—	—	C	"	1
3693	Type 1868	100	—	750	2,200	$\frac{9}{32}$	$2\frac{7}{8}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
4100	Type 2102	100	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	ZA.22526	C	"	1
13185	Type 4244	100	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
11034	Type 437	100	5	350	1,000	$\frac{3}{16}$	$2\frac{3}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
38	Type 584	100	5	500	1,500	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
2155	Type 995	100	10	350	—	—	—	—	—	—	—	C	"	1
4249	Type 2194	100	10	350	1,000	$\frac{7}{32}$	$2\frac{9}{32}$	$\frac{11}{16}$	SUSP.	—	ZC.0589	C	"	1
3389	Type 1654	100	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	ZA.12992	C	"	1
5529	Type 2992	100	10	500	1,500	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
4255	Type 2200	100	10	750	2,200	$\frac{9}{32}$	$2\frac{1}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
12333	Type 3876	100	10	750	2,200	$\frac{7}{32}$	$\frac{29}{32}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
12334	Type 3877	100	15	750	—	—	—	—	—	—	—	C	"	1
5034	Type 2704	100	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
4995	Type 2685	100	15	350	1,000	$\frac{5}{32}$	$\frac{15}{16}$	$\frac{1}{2}$	SUSP.	—	—	C	"	1
96	Type 611	100	15	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{1}{2}$	SUSP.	—	ZC.9988	C	"	1
7902	Type 121	100	15	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
7814	Type 112	100	15	350	1,000	$\frac{3}{16}$	$1\frac{7}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
4698	Type 2469	100	15	350	1,000	$\frac{9}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
5315	Type 2866	100	15	500	1,500	$\frac{9}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
3414	Type 1675	100	15	1,000	2,200	$\frac{9}{32}$	$2\frac{1}{4}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
12347	Type 3890	100	15	2,000	5,000	$\frac{3}{16}$	$2\frac{1}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
87	Type 602	100	15	2,500	5,000	$\frac{3}{8}$	$2\frac{1}{4}$	$\frac{11}{16}$	SUSP.	W.2815	—	C	"	1
12312	Type 3858	100	—0+100	350	1,000	$\frac{3}{16}$	$2\frac{1}{2}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
17566	Type 6094	120	2	350	—	—	—	—	—	—	—	C	"	1
12440	Type 3943	150	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
3380	Type 1646	170	—15+0	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
2939	Type 1417	200	2	350	1,000	$\frac{5}{32}$	$\frac{15}{16}$	$\frac{1}{2}$	SUSP.	—	ZA.2133	C	"	1
15877	Type 5266	200	5	350	1,000	$\frac{9}{32}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	Less than .001 mfd.—cont.													
12973	Type 4153	200	5	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	each	1
5548	Type 3011	200	5	350	1,000	$\frac{5}{32}$	$\frac{13}{16}$	$\frac{1}{2}$	SUSP.	—	ZA.25438	C	"	1
13586	Type 4446	200	10	350	1,000	$\frac{5}{32}$	$\frac{13}{16}$	$\frac{1}{2}$	SUSP.	—	ZC.3267	C	"	1
3516	Type 1742	200	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	ZA.22099	C	"	1
7386	Type 69	200	10	350	1,000	$\frac{3}{16}$	$1\frac{7}{8}$	$1\frac{11}{16}$	SUSP.	—	—	C	"	1
8388	Type 178	200	15	350	—	—	—	—	SUSP.	—	—	C	"	1
4268	Type 2212	200	15	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
19	Type 575	200	15	350	1,000	$\frac{5}{32}$	$\frac{13}{16}$	$\frac{1}{2}$	SUSP.	W.1883	ZC.13046	C	"	1
4706	Type 2477	200	15	350	1,000	$\frac{5}{16}$	$1\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	ZA.21065	C	"	1
8660	Type 213	200	15	750	2,200	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{33}{32}$	SUSP.	W.2698	—	C	"	1
10392	Type 402	200	15	750	2,200	$\frac{1}{4}$	$2\frac{7}{8}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
11169	Type 3383	200	15	2,000	—	—	—	—	—	—	—	C	"	1
4765	Type 2497	200	20	350	—	—	—	—	—	—	—	C	"	1
2926	Type 1403	230	10	350	—	—	—	—	—	—	—	C	"	1
3678	Type 1863	250	2	350	—	—	—	—	—	—	—	C	"	1
13635	Type 4467	250	5	750	2,200	$\frac{3}{32}$	$1\frac{1}{8}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
12439	Type 3942	250	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	ZA.11678	C	"	1
4885	Type 2577	250	15	350	1,000	$\frac{3}{16}$	$2\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	—	C	"	1
4868	Type 2560	250	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	ZA.10972	C	"	1
4349	Type 2254	290	5	350	—	—	—	—	—	—	—	C	"	1
13323	Type 4332	300	—	—	—	—	—	—	—	—	—	C	"	1
14782	Type 4971	300	2	500	—	—	—	—	—	—	—	C	"	1
15880	Type 5269	300	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	—	C	"	1
3679	Type 1864	300	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	ZA.1387	C	"	1
9178	Type 279	300	5	350	1,000	$\frac{3}{16}$	$2\frac{3}{8}$	$1\frac{11}{16}$	SUSP.	—	—	C	"	1
2339	Type 1128	300	5	350	1,000	$\frac{7}{32}$	$1\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
271	Type 642	300	5	750	2,200	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
2390	Type 1205	300	10	350	—	—	—	—	—	—	—	C	"	1
5871	Type 3219	300	10	500	1,500	$\frac{3}{16}$	$1\frac{1}{8}$	$1\frac{11}{16}$	SUSP.	—	—	C	"	1
13678	Type 4486	300	10	750	2,200	$\frac{3}{16}$	$2\frac{3}{8}$	$1\frac{11}{16}$	SUSP.	—	—	C	"	1

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	Less than .001 mfd.—cont.													
745	Type 831	300	15	350	1,000	$\frac{5}{16}$	$\frac{15}{16}$	$\frac{1}{8}$	SUSP.	—	ZC.18445	C	each	1
2076	Type 966	300	15	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	ZA.1452	C	"	1
3196	Type 1551	300	15	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{1}{8}$	SUSP.	—	ZC.8613	C	"	1
8483	Type 173	300	15	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{1}{8}$	SUSP.	W.2550	ZA.12661	C	"	1
5947	Type 3257	300	15	500	1,500	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{1}{8}$	SUSP.	—	—	C	"	1
8673	Type 222	300	15	750	2,200	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{1}{8}$	SUSP.	—	—	C	"	1
2803	Type 1345	300	15	1,000	3,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{1}{8}$	SUSP.	—	—	C	"	1
14673	Type 4906	300	15	2,000	—	—	—	—	—	—	—	C	"	1
3388	Type 1653	300	-15+10	350	1,000	$\frac{7}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
3101	Type 1501	300	-15+INF	350	1,000	$\frac{5}{16}$	$\frac{11}{16}$	$\frac{1}{8}$	SUSP.	—	—	C	"	1
14114	Type 4642	350	10	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{1}{8}$	SUSP.	—	—	C	"	1
17887	Type 6211	400	2	350	—	—	—	—	—	—	—	C	"	1
4546	Type 2356	400	5	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	—	ZA.2631	C	"	1
3602	Type 1810	400	5	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
104	Type 617	400	5	750	2,200	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
14485	Type 4807	400	15	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
2726	Type 1329	400	15	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
5441	Type 2943	400	15	500	1,500	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
3935	Type 2004	500	2	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
11695	Type 549	500	2	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	ZC.2708	C	"	1
11490	Type 541	500	5	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
3587	Type 1801	500	5	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	W.5214	—	C	"	1
5774	Type 3161	500	5	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	ZA.1476	C	"	1
4976	Type 2666	500	5	750	2,200	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
14118	Type 4645	500	5	750	2,200	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
16960	Type 6041	500	5	750	—	—	—	—	—	—	—	C	"	1
5656	Type 3081	500	10	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	W.4958	ZA.17058	C	"	1
12324	Type 3870	500	10	350	1,000	$\frac{3}{16}$	$\frac{11}{16}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
4530	Type 2343	500	15	350	—	—	—	—	—	—	—	C	"	1
8009	Type 132	500	15	350	1,000	$\frac{3}{16}$	$\frac{23}{32}$	$\frac{11}{16}$	SUSP.	—	ZA.1392	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	Less than .001 mfd.—cont.													
3191	Type 1536	500	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	W.2802	ZC.3192	C	each	1
13172	Type 4237	500	15	500	1,500	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
958	Type 890	500	15	750	2,200	$\frac{3}{32}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	ZC.0537	C	"	1
12351	Type 3894	500	15	2,500	5,000	$\frac{3}{16}$	$2\frac{1}{4}$	$1\frac{11}{32}$	SUSP.	W.3963	—	C	"	1
4767	Type 2499	500	25	350	—	—	—	—	—	—	—	C	"	1
3338	Type 1644	500	-15+0	350	1,000	$\frac{7}{32}$	$\frac{11}{16}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
15882	Type 5271	600	2	350	1,000	$\frac{3}{16}$	$2\frac{3}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
8669	Type 214	600	5	750	2,200	$\frac{3}{32}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	W.5580	ZC.12062	C	"	1
3415	Type 1676	600	10	2,000	5,000	$\frac{3}{32}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
4776	Type 2508	600	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	ZA.21333	C	"	1
14966	Type 5053	600	15	750	—	—	—	—	—	—	—	C	"	1
11068	Type 3339	630	2	250	—	—	—	—	—	—	—	C	"	1
11286	Type 3450	700	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	ZA.13700	C	"	1
11868	Type 3647	750	10	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
4625	Type 2416	800	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	ZA.17283	C	"	1
14386	Type 4735	800	10	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
2421	Type 1174	985	5	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
3068	Type 1478	920	15	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
	.001 mfd. and upwards:—													
3568	Type 1783001	2	350	—	—	—	—	—	—	—	C	"	1
9179	Type 280001	5	350	1,000	$\frac{3}{16}$	$2\frac{3}{8}$	$\frac{11}{16}$	SUSP.	W.3802	ZA.1471	C	"	1
17901	Type 6220001	5	350	—	—	—	—	—	—	—	C	"	1
5549	Type 3012001	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	ZA.1944	C	"	1
7388	Type 71001	5	350	1,000	$\frac{3}{16}$	$1\frac{7}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
10167	Type 384001	5	750	2,200	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
214	Type 622001	10	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	ZA.12989	C	"	1
11065	Type 3336001	10	350	1,000	$\frac{7}{32}$	$1\frac{1}{8}$	$\frac{17}{16}$	SUSP.	—	—	C	"	1
9133	Type 260001	10	500	1,500	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
12391	Type 3915001	10	750	2,200	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
12405	Type 3925001	10	750	2,200	$\frac{3}{16}$	$2\frac{3}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	.001 mfd. and upwards—cont.													
13634	Type 4466001	10	2,000	5,000	$\frac{5}{16}$	2½	1½	SUSP.	—	ZA.10828	C	each	1
5253	Type 2845001	15	350	—	—	—	—	—	—	—	C	"	1
13276	Type 4293001	15	350	—	—	—	—	—	—	—	C	"	1
496	Type 734001	15	350	—	—	—	—	—	—	—	C	"	1
651	Type 782001	15	350	1,000	$\frac{3}{16}$	1½	1½	SUSP.	W.4959	—	C	"	1
7901	Type 120001	15	350	1,000	$\frac{3}{16}$	2½	1½	SUSP.	—	—	C	"	1
3589	Type 1803001	15	350	1,000	$\frac{1}{4}$	1½	1½	SUSP.	—	ZC.2707	C	"	1
13204	Type 4255001	15	2,000	5,000	$\frac{5}{16}$	2½	1½	SUSP.	—	—	C	"	1
2388	Type 1203001	15	2,000	5,000	$\frac{5}{16}$	2½	1½	SUSP.	W.3958	—	C	"	1
12046	Type 3732001	20	350	1,000	$\frac{1}{4}$	$\frac{3}{4}$	$\frac{3}{4}$	SUSP.	—	ZA.24758	C	"	1
13810	Type 4526001	20	350	700	$\frac{1}{4}$	$\frac{3}{4}$	$\frac{3}{4}$	SUSP.	—	—	C	"	1
3100	Type 1500001	-25 + INF	350	—	—	—	—	—	—	—	C	"	1
11067	Type 33380011	2	250	750	$\frac{5}{16}$	1½	—	SUSP.	—	—	C	"	1
							dia.							
3115	Type 15140013	2	350	—	—	—	—	—	—	—	C	"	1
14385	Type 47340013	10	350	1,000	$\frac{3}{16}$	1½	$\frac{3}{16}$	SUSP.	—	—	C	"	1
17026	Type0013	10	350	—	—	—	—	—	—	—	C	"	1
3093	Type 14990014	2	350	1,000	$\frac{3}{16}$	1½	$\frac{3}{16}$	SUSP.	—	—	C	"	1
12043	Type 37300014	10	200	—	—	—	—	—	—	—	C	"	1
15856	Type 52460016	5	350	1,000	$\frac{11}{16}$	1½	$\frac{3}{16}$	SUSP.	—	—	C	"	1
4624	Type 24150016	2	350	—	—	—	—	—	—	—	C	"	1
15857	Type 524700167	2	350	1,000	$\frac{11}{16}$	1½	$\frac{3}{16}$	SUSP.	—	—	C	"	1
15858	Type 5248002	2	350	1,000	$\frac{11}{16}$	1½	$\frac{3}{16}$	SUSP.	—	—	C	"	1
873	Type 867002	2	350	1,000	$\frac{1}{4}$	1½	$\frac{3}{16}$	SUSP.	—	—	C	"	1
4970	Type 2660002	5	350	1,000	$\frac{1}{4}$	1½	$\frac{11}{16}$	SUSP.	—	ZA.17735	C	"	1
17889	Type 6213002	10	350	—	—	—	—	—	—	—	C	"	1
5425	Type 2927002	10	350	1,000	$\frac{1}{4}$	$\frac{1}{4}$	$\frac{3}{16}$	SUSP.	—	—	C	"	1
11199	Type 3402002	10	750	2,200	$\frac{1}{4}$	2½	$\frac{3}{16}$	SUSP.	—	—	C	"	1
5948	Type 3258002	15	350	—	—	—	—	—	—	—	C	"	1
14001	Type 4604002	15	350	700	$\frac{3}{16}$	1½	$\frac{1}{4}$	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	.001 mfd. and upwards—cont.													
24	Type 580002	15	350	—	—	—	—	—	—	—	C	each	1
12318	Type 3864002	15	350	1,000	$\frac{3}{32}$	$2\frac{3}{8}$	$\frac{15}{16}$	SUSP.	—	ZA.20472	C	"	1
5530	Type 2993002	15	500	—	—	—	—	—	—	—	C	"	1
7847	Type 114002	15	350	1,000	$\frac{3}{16}$	$1\frac{7}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
11732	Type 3569002	15	350	—	—	—	—	—	—	—	C	"	1
8656	Type 209002	15	750	2,200	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	ZC.12064	C	"	1
4887	Type 2579002	15	2,000	5,000	$\frac{1}{16}$	$2\frac{1}{2}$	$1\frac{11}{32}$	SUSP.	—	—	C	"	1
12371	Type 3903002	15	2,000	5,000	$\frac{3}{8}$	$2\frac{7}{8}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
13589	Type 4448002	20	350	—	—	—	—	—	—	—	C	"	1
13809	Type 4525002	20	350	1,000	$\frac{3}{16}$	$1\frac{5}{8}$	$\frac{1}{4}$	SUSP.	—	—	C	"	1
14384	Type 47330021	5	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
14388	Type 473700225	2	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
4891	Type 25830025	2	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	ZA.11668	C	"	1
11867	Type 36460025	5	350	1,000	$\frac{3}{16}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
13420	Type 43750025	10	750	2,200	$\frac{3}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
336	Type 6630025	15	2,000	6,000	$\frac{3}{8}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
5952	Type 32620028	2	500	1,000	$\frac{3}{16}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
11694	Type 548003	2	350	1,000	$\frac{3}{16}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
245	Type 636003	5	750	2,200	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
12320	Type 3866003	10	750	—	—	—	—	—	—	—	C	"	1
5687	Type 3112003	10	350	1,000	$\frac{11}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	51206	ZA.1449	C	"	1
4788	Type 2520003	15	350	1,000	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	W.5529	ZA.10973	C	"	1
2342	Type 1131003	15	350	—	—	—	—	—	—	—	C	"	1
4267	Type 2211003	15	500	1,500	$\frac{3}{16}$	$1\frac{1}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
3696	Type 1871003	15	750	2,200	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
2798	Type 1340003	15	2,000	5,000	—	—	—	—	—	—	C	"	1
16657	Type 5841003	20	750	1,500	$1\frac{1}{2}$	$\frac{29}{32}$	$\frac{1}{4}$	SUSP.	—	—	C	"	1
4889	Type 25810032	2	350	1,000	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
14381	Type 473000325	2	350	700	$\frac{3}{32}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
3106	Type 15060034/0.2	—	750	2,200	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	.001 mfd. and upwards—cont.													
14383	Type 47320035	2	350	1,000		1 1/2		SUSP.	—	—	C	each	1
5953	Type 32630035	15	350	1,000		1 1/2		SUSP.	—	—	C	"	1
4626	Type 24170036	2	500	—	—	—	—	—	—	—	C	"	1
5455	Type 2287004	5	350	1,000		2 1/4		SUSP.	—	ZA.25176	C	"	1
4490	Type 2316004	2	350	—	—	—	—	—	—	—	C	"	1
8670	Type 215004	5	750	2,200		2 1/4		SUSP.	—	—	C	"	1
2055	Type 956004	10	350	1,000		2 3/4		SUSP.	—	—	C	"	1
3210	Type 1564004	10	500	1,500		2 3/4		SUSP.	—	—	C	"	1
8493	Type 185004	10	750	2,200		2 3/4		SUSP.	—	—	C	"	1
3105	Type 1505004	= 15 + 100	1,000	—	—	—	—	—	—	—	C	"	1
15859	Type 524900455	2	350	1,000		1 1/2		SUSP.	—	—	C	"	1
4943	Type 26330046	15	350	1,000		2 1/4		SUSP.	—	—	C	"	1
10047	Type 365005	—	1,500	—	—	—	—	—	—	—	C	"	1
11697	Type 551005	2	350	1,000		1 1/2		SUSP.	—	—	C	"	1
10164	Type 385005	5	500	1,500		2 1/4		SUSP.	—	ZA.23175	C	"	1
10519	Type 381005	5	750	—	—	—	—	—	—	—	C	"	1
3788	Type 1918005	10	350	1,000		1 1/2		SUSP.	—	ZA.21127	C	"	1
15741	Type005	15	1,000	2,000		2 1/4		—	—	—	C	"	1
499	Type 737005	15	350	1,000		1 1/2		SUSP.	W.973	—	C	"	1
5352	Type 2900005	15	350	1,000		2 3/4		SUSP.	—	YB.01674	C	"	1
12230	Type 3830005	15	350	1,000		2 3/4		SUSP.	—	—	C	"	1
5564	Type 3027005	15	500	1,500		1 1/2		SUSP.	—	ZC.2692	C	"	1
964	Type 896005	15	500	1,500		2 1/4		SUSP.	—	—	C	"	1
5884	Type 3232005	15	750	2,200		2 3/4		SUSP.	—	—	C	"	1
15902	Type 5281005	20	350	1,000		2 3/4		SUSP.	—	—	C	"	1
14251	Type 4703005	20	750	1,500		1 1/2		SUSP.	—	—	C	"	1
2423	Type 1176005	- 15 + 0	350	1,000		1 1/2		SUSP.	—	—	C	"	1
5531	Type 29940052	2	500	—	—	—	—	—	—	—	C	"	1
4199	Type 2155006	5	350	1,000		2 1/4		SUSP.	W.6339	—	C	"	1
14737	Type 4943006	10	350	—	—	—	—	—	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Moulded—cont.													
	.001 mfd. and upwards—cont.													
3270	Type 1584006	15	750	2,200	$\frac{3}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	W.6421	—	C	each	1
5889	Type 3237006	15	750	2,200	$\frac{3}{8}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	ZC.15572	C	"	1
2690	Type 1294006	15	1,200	2,500	$\frac{1}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
14387	Type 47360061	2	350	700	$\frac{1}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
15860	Type 525000617	2	350	1,000	$\frac{1}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
14382	Type 473100625	2	350	700	$\frac{3}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
5688	Type 3113007	2	350	—	—	—	—	—	—	—	C	"	1
17888	Type 6212008	2	350	—	—	—	—	—	—	—	C	"	1
4103	Type 2104008	2	350	1,000	—	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
14380	Type 472901	2	350	700	$\frac{3}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
13183	Type 424201	5	350	1,000	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
10562	Type 42401	5	750	2,200	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
11950	Type 368701	10	350	—	—	—	—	—	—	—	C	"	1
3448	Type 169901	10	750	2,200	$\frac{3}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	ZA.13421	C	"	1
3439	Type 169001	10	750	2,200	$\frac{3}{8}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
8496	Type 18801	15	350	1,000	$\frac{3}{8}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	ZC.19973	C	"	1
16915	Type 602701	15	350	1,000	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
10393	Type 40301	15	750	2,250	$\frac{1}{4}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
8658	Type 21101	15	1,000	2,000	$\frac{1}{8}$	$2\frac{1}{2}$	$1\frac{11}{32}$	SUSP.	W.2813	ZA.17052	C	"	1
10511	Type 37801	15	1,000	3,000	$\frac{3}{8}$	$2\frac{7}{8}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
11210	Type 341301	15	1,500	4,500	$\frac{3}{8}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
7906	Type 12501	—0+15	350	1,000	$\frac{3}{8}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
13472	Type 44050119	2	350	1,000	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{15}{16}$	SUSP.	—	—	C	"	1
5689	Type 3114013	2	350	1,000	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
12326	Type 387202	15	350	1,000	$\frac{3}{8}$	$2\frac{3}{4}$	$\frac{29}{32}$	SUSP.	W.5032	—	C	"	1
2207	Type 104602	15	1,000	3,000	$\frac{1}{8}$	$2\frac{1}{2}$	$1\frac{11}{32}$	SUSP.	—	—	C	"	1
2656	Type 12721	2	350	1,000	$\frac{3}{8}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
15866	Type 52551	5	350	1,000	$\frac{3}{8}$	$1\frac{1}{2}$	$\frac{11}{16}$	SUSP.	—	—	C	"	1
15997	Type 532225	15	750	2,250	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{29}{32}$	SUSP.	—	—	C	"	1
17028	Type300	15	750	—	—	—	—	—	—	—	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected:—													
	Less than .001 mfd.:—													
12450	Type 3948	3	15	350	1,000	5M	15M	10M	SUSP.	—	—	C	each	1
2123	Type 1005	5	15	750	2,250	$\frac{3}{16}$	$\frac{7}{8}$	$\frac{1}{2}$	SUSP.	—	—	C	"	1
12070	Type 3743	5	20	350	1,000	5M	15M	10M	SUSP.	—	—	C	"	1
12071	Type 3744	7.5	1	350	2,250	—	—	—	—	—	—	C	"	1
2908	Type 1396	10	10	350	—	—	—	—	—	—	—	C	"	1
4476	Type 2303	10	10	750	2,250	5M	15M	10M	SUSP.	—	—	C	"	1
784	Type 835	10	15	750	2,250	6M	29M	12M	SUSP.	—	—	C	"	1
11938	Type 3680	12	1 mmfd.	350	—	—	—	—	—	—	—	C	"	1
12155	Type 3802	15	1 mmfd.	350	1,000	5M	15M	10M	SUSP.	—	—	C	"	1
2278	Type 1085	15	1 mmfd.	750	2,250	5M	30M	10M	SUSP.	—	—	C	"	1
14801	Type 4976	15	5	350	—	—	—	—	—	—	—	C	"	1
11558	Type 3527	15	10	350	1,000	5M	15M	10M	SUSP.	—	ZC.16933	C	"	1
785	Type 836	15	10	750	2,250	5M	30M	10M	SUSP.	—	—	C	"	1
2121	Type 1003	17	1 mmfd.	750	2,200	6M	30M	12M	SUSP.	—	—	C	"	1
12073	Type 3746	20	5	350	1,000	5M	15M	10M	SUSP.	—	—	C	"	1
3912	Type 1981	20	10	350	—	—	—	—	—	—	—	C	"	1
11408	Type 3476	20	10	350	1,000	5M	15M	10M	SUSP.	—	—	C	"	1
786	Type 837	20	10	750	2,200	6M	30M	12M	SUSP.	—	—	C	"	1
14365	Type 4723	22	10	350	—	—	—	—	—	—	—	C	"	1
10570	Type 426	25	4	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
12074	Type 3747	25	5	350	1,000	5M	15M	10M	SUSP.	—	—	C	"	1
12075	Type 3748	25	10	350	1,000	5M	15M	10M	SUSP.	—	—	C	"	1
4479	Type 2305	25	10	750	—	—	—	—	—	—	—	C	"	1
14003	Type 4606	27	10	350	—	—	—	—	—	—	—	C	"	1
4922	Type 2612	30	1 mmfd.	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
11560	Type 3529	30	5	350	1,000	5M	15M	10M	SUSP.	—	—	C	"	1
11487	Type 538	30	5	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
13908	Type 4568	30	10	350	700	6M	30M	30M	SUSP.	—	—	C	"	1
5585	Type 3048	30	10	350	1,000	6M	20M	10M	SUSP.	W.6239	—	C	"	1
4274	Type 2218	30	10	750	2,200	6M	30M	12M	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	Less than .001 mfd.—cont.													
5989	Type 3298	35	1	350	1,000	5M	15M	10M	SUSP.	—	ZC.14597	C	each	1
5056	Type 2726	35	2	350	1,000	5M	15M	10M	SUSP.	—	—	C	..	1
3922	Type 1991	38	3	—	—	—	—	—	—	—	—	C	..	1
2146	Type 992	40	2	350	1,000	6M	50.5M	10.5M	SUSP.	—	—	C	..	1
4939	Type 2629	40	5	350	1,000	$\frac{3}{16}$	$2\frac{3}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	..	1
11206	Type 3409	40	5	350	1,000	6M	20M	10M	SUSP.	—	—	C	..	1
10552	Type 421	50	2	350	—	—	—	—	—	—	—	C	..	1
11056	Type 3327	50	2	350	—	—	—	—	—	—	—	C	..	1
11485	Type 536	50	5	350	—	—	—	—	—	—	—	C	..	1
11294	Type 3456	50	5	350	1,000	5M	15M	10M	SUSP.	—	—	C	..	1
12778	Type 4081	50	5	2,500	7,000	$\frac{1}{4}$	$1\frac{1}{8}$	$\frac{11}{16}$	SUSP.	—	—	C	..	1
2078	Type 968	50	15	350	—	—	—	—	—	—	—	C	..	1
788	Type 839	50	15	750	2,200	6M	30M	12M	SUSP.	—	—	C	..	1
5586	Type 3049	60	10	350	1,000	6M	33M	17M	SUSP.	—	—	C	..	1
16939	Type 6031	65	2	350	—	—	—	—	—	—	—	C	..	1
2649	Type 1265	65	10	350	1,000	6M	20M	10M	SUSP.	—	—	C	..	1
2147	Type 993	70	2	350	1,000	6M	20M	10M	SUSP.	—	—	C	..	1
11484	Type 535	70	5	350	1,000	6M	20M	10M	SUSP.	—	—	C	..	1
4187	Type 2143	75	2	350	—	—	—	—	—	—	—	C	..	1
17611	Type 6131	75	2	350	—	—	—	—	—	—	—	C	..	1
5990	Type 3299	75	2	350	1,000	5M	15M	10M	SUSP.	—	—	C	..	1
16083	Type 5357	75	2	750	2,200	6M	19M	14M	SUSP.	—	—	C	..	1
15029	Type 5077	75	5	750	—	—	—	—	—	—	—	C	..	1
4959	Type 2649	75	10	350	—	—	—	—	—	—	—	C	..	1
2009	Type 921	80	2	350	—	—	—	—	—	—	—	C	..	1
14043	Type 4617	90	5	350	700	6M	20M	10M	SUSP.	—	—	C	..	1
2012	Type 924	93	2	350	1,000	6M	25M	15M	SUSP.	—	—	C	..	1
14403	Type 4752	100	1	750	1,500	6M	20M	10M	SUSP.	—	—	C	..	1
13351	Type 4348	100	1	750	2,200	6M	20M	10M	SUSP.	—	—	C	..	1
5983	Type 3292	100	2	350	1,000	5M	15M	10M	SUSP.	—	—	C	..	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	Less than .001 mfd.—cont.													
16084	Type 5358	100	5	750	2,200	6M	19M	14M	SUSP.	—	—	C	each	1
12971	Type 4151	100	5	750	—	—	—	—	—	—	—	C	"	1
14366	Type 4724	100	10	350	1,000	6M	18M	15M	SUSP.	—	—	C	"	1
4271	Type 2215	100	10	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
15216	Type 5198	100	10	500	—	20M	10M	4M	SUSP.	—	—	C	"	1
5788	Type 3175	100	10	750	2,200	6M	20M	10M	SUSP.	—	—	C	"	1
2428	Type 1171	100	15	350	—	—	—	—	—	—	—	C	"	1
789	Type 840	100	15	750	2,250	5M	30M	12M	SUSP.	—	—	C	"	1
11944	Type 3684	115	2	350	1,000	6M	25M	15M	SUSP.	—	—	C	"	1
12069	Type 3742	120	5	750	2,200	6M	25M	15M	SUSP.	—	—	C	"	1
5903	Type 3251	125	5	350	1,000	6M	32M	16M	SUSP.	—	—	C	"	1
14803	Type 4978	130	2	350	—	—	—	—	—	—	—	C	"	1
14802	Type 4977	150	2	350	—	—	—	—	—	—	—	C	"	1
3080	Type 1486	150	2	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
4798	Type 2529	150	2	350	1,000	6M	25M	15M	SUSP.	—	—	C	"	1
3643	Type 1834	150	5	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
12079	Type 3752	150	5	350	1,000	6M	25M	15M	SUSP.	—	—	C	"	1
4961	Type 2651	150	10	350	1,000	$\frac{3}{2}$ "	$\frac{3}{4}$ "	$\frac{3}{8}$ "	SUSP.	—	ZA.1187	C	"	1
12080	Type 3753	150	10	350	1,000	6M	24M	16M	SUSP.	—	—	C	"	1
790	Type 841	150	10	750	2,200	6M	30M	12M	SUSP.	—	—	C	"	1
10228	Type 417	160	2	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
4923	Type 2613	160	5	350	1,000	6M	25M	15M	SUSP.	—	—	C	"	1
11916	Type 3663	175	5	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
5583	Type 3046	180	2	350	1,000	6M	32M	16M	SUSP.	—	—	C	"	1
14404	Type 4753	200	1	750	1,500	6M	20M	10M	SUSP.	—	—	C	"	1
13352	Type 4349	200	1	750	2,250	6M	20M	10M	SUSP.	—	—	C	"	1
3533	Type 1753	200	2	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
4184	Type 2140	200	2	350	750	6M	25M	15M	SUSP.	—	—	C	"	1
11658	Type 3556	200	5	350	—	—	—	—	—	—	—	C	"	1
2010	Type 922	200	5	350	—	—	—	—	—	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance \pm %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	Less than .001 mfd.—cont.													
4326	Type 2231	200	5	350	1,000	6M	20M	10M	SUSP.	—	—	C	each	1
5669	Type 3094	200	10	350	—	—	—	—	—	—	—	C	..	1
4763	Type 2495	200	20	350	1,000	0-6M	20M	9-9M	SUSP.	—	ZC.12010	C	..	1
12157	Type 3804	225	5	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
4872	Type 2564	230	2	350	1,000	6M	24M	16M	SUSP.	—	—	C	..	1
4238	Type 2183	230	5	350	1,000	6M	28M	16M	SUSP.	—	—	C	..	1
14422	Type 4764	230	5	350	1,000	6M	18M	15M	SUSP.	—	—	C	..	1
2008	Type 920	240	1	350	1,000	5M	33M	20M	SUSP.	—	—	C	..	1
3925	Type 1994	245	15	350	—	—	—	—	—	—	—	C	..	1
5970	Type 3279	250	2	350	—	—	—	—	—	—	—	C	..	1
11562	Type 3531	250	2	350	1,000	6M	30M	12M	SUSP.	—	—	C	..	1
5484	Type 2985	250	5	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
14421	Type 4763	250	5	350	700	6M	18M	15M	SUSP.	—	—	C	..	1
17557	Type 6090	250	5	750	—	—	—	—	—	—	—	C	..	1
4960	Type 2650	250	10	350	1,000	2M	18M	15M	SUSP.	—	—	C	..	1
3956	Type 2025	250	10	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
3594	Type 1804	275	5	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
5030	Type 2700	300	2	350	1,000	2M	18M	15M	SUSP.	—	—	C	..	1
4797	Type 2528	300	2	350	1,000	6M	25M	15M	SUSP.	—	—	C	..	1
2017	Type 929	300	2	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
3064	Type 1474	300	5	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
13501	Type 4417	300	5	350	1,000	6M	20M	10M	SUSP.	—	—	C	..	1
11563	Type 3532	300	5	350	1,000	6M	30M	12M	SUSP.	—	—	C	..	1
3955	Type 2024	300	10	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
5802	Type 3189	300	10	750	2,200	6M	32M	16M	SUSP.	—	—	C	..	1
791	Type 842	300	15	750	2,200	6M	30M	12M	SUSP.	—	—	C	..	1
14703	Type 4929	330	50	350	—	—	—	—	—	—	—	C	..	1
4201	Type 2157	350	2	350	1,000	6M	25M	15M	SUSP.	—	—	C	..	1
5477	Type 2978	350	2	350	1,000	6M	32M	16M	SUSP.	—	—	C	..	1
11269	Type 3434	350	10	350	1,000	6M	28M	16M	SUSP.	—	—	C	..	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	Less than .001 mfd.—cont.													
12081	Type 3754	350	10	350	—	—	—	—	—	—	—		each	1
3545	Type 1760	382	3	350	1,000	0.6M	28.2M	20.8M	SUSP.	—	—	C	"	1
14405	Type 4754	400	1	750	1,500	6M	28M	15M	SUSP.	—	—	C	"	1
13353	Type 4350	400	1	750	2,200	6M	2M	16M	SUSP.	—	—	C	"	1
4185	Type 2141	400	2	350	1,000	6M	28M	16M	SUSP.	—	—	C	"	1
5456	Type 2957	400	2	350	1,000	6M	30M	12M	SUSP.	—	—	C	"	1
5792	Type 3179	400	2	350	1,000	6M	32M	16M	SUSP.	—	—	C	"	1
11263	Type 3428	400	5	350	1,000	6M	32M	16M	SUSP.	—	—	C	"	1
3549	Type 1764	414	3	350	1,000	0.025	1.11	0.82	SUSP.	—	ZA.11988	C	"	1
14978	Type 5059	470	10	350	—	—	—	—	—	—	—	C	"	1
11797	Type 3609	475	2	350	1,000	6M	30M	12M	SUSP.	—	—	C	"	1
11512	Type 543	500	1	350	—	—	—	—	—	—	—	C	"	1
13354	Type 4351	500	1	750	2,200	6M	24M	16M	SUSP.	—	—	C	"	1
4197	Type 2153	500	2	350	1,000	6M	28M	16M	SUSP.	—	—	C	"	1
5144	Type 2736	500	2	350	1,000	6M	32M	16M	SUSP.	W.8851	—	C	"	1
11564	Type 3533	500	2	350	1,000	6M	30M	12M	SUSP.	—	—	C	"	1
5230	Type 2822	500	5	350	1,000	3.2M	26.9M	—	SUSP.	—	—	C	"	1
							dia.							
4237	Type 2182	500	5	350	1,000	6M	25M	15M	SUSP.	—	—	C	"	1
5483	Type 2984	500	5	350	1,000	6M	30M	12M	SUSP.	—	—	C	"	1
12153	Type 3801	500	10	350	1,000	6M	30M	12M	SUSP.	—	—	C	"	1
5670	Type 3095	500	10	350	1,000	—	—	—	—	—	—	C	"	1
11099	Type 3353	500	10	750	2,200	6M	32M	16M	SUSP.	—	—	C	"	1
94	Type 609	500	15	350	—	—	—	—	—	—	—	C	"	1
5971	Type 3280	600	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
5475	Type 2976	600	5	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
5047	Type 2717	612	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
4198	Type 2154	650	2	350	—	—	—	—	—	—	—	C	"	1
4424	Type 2290	700	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
14804	Type 4979	700	2	350	—	—	—	—	—	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance \pm %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	Less than .001 mfd.—cont.													
674	Type 791	700	20	350	1,000	0.6M	28.2M	20.8	SUSP.	—	—	C	each	1
5901	Type 3249	750	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
12083	Type 3756	750	5	350	1,000	—	—	—	—	—	—	C	"	1
12084	Type 3757	750	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
969	Type 901	800	2	350	—	—	—	—	—	—	—	C	"	1
14805	Type 4980	800	2	350	—	—	—	—	—	—	—	C	"	1
3530	Type 1750	800	10	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
12943	Type 4135	850	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
3046	Type 1456	850	10	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
	.001 mfd. and upwards:—													
3954	Type 2023001	1	350	1,000	0.6M	28.2M	20.8M	SUSP.	—	—	C	"	1
13355	Type 4352001	1	750	2,200	6M	33M	20M	SUSP.	—	—	C	"	1
12799	Type 4084001	2	350	1,000	6M	20M	10M	SUSP.	—	—	C	"	1
3198	Type 1553001	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
12086	Type 3759001	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
14993	Type 5066001	10	750	2,200	6M	28M	20M	SUSP.	—	—	C	"	1
4613	Type 2404001	10	350	1,000	6M	33M	20M	SUSP.	—	—	C	"	1
12087	Type 3760001	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
793	Type 844001	15	750	—	—	—	—	—	—	—	C	"	1
14047	Type 4621001	20	3,000	6,000	6M	30M	30M	SUSP.	—	—	C	"	1
10229	Type 41200105	2	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
12089	Type 37620012	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
12159	Type 38060012	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
3983	Type 20390013	2	350	1,000	5M	33M	20M	SUSP.	—	—	C	"	1
5782	Type 31690015	5	350	1,000	6M	32M	16M	SUSP.	—	—	C	"	1
11500	Type 35100015	10	350	1,000	6M	32M	16M	SUSP.	—	—	C	"	1
12092	Type 37650015	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
17602	Type 61260015	10	1,250	—	—	—	—	—	—	—	C	"	1
14391	Type 47400017	15	350	700	6M	20M	10M	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	.001 mfd. and upwards—cont.													
13356	Type 4353002	1	750	2,200	6M	33M	17M	SUSP.	—	—	C	each	1
14408	Type 4757002	1	750	1,500	6M	28M	20M	SUSP.	—	—	C	"	1
2011	Type 923002	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
3957	Type 2026002	5	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
12093	Type 3766002	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
11270	Type 3435002	10	350	—	—	—	—	—	—	—	C	"	1
12094	Type 3767002	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
12128	Type 3786002	10	750	2,200	5M	30M	30M	SUSP.	—	—	C	"	1
3443	Type 1694002	15	750	2,200	6M	33M	17M	SUSP.	—	—	C	"	1
12554	Type 400400225	10	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
5798	Type 31850023	2	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
5046	Type 271600236	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
5710	Type 31350025	5	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
12095	Type 37680025	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
14815	Type 49820025	10	350	—	—	—	—	—	—	—	C	"	1
12096	Type 37690025	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
14571	Type 48570025	10	750	2,200	$\frac{1}{4}$	$1\frac{1}{2}$	$\frac{1}{8}$	SUSP.	—	—	C	"	1
5979	Type 3288003	2	350	1,000	6M	20M	20M	SUSP.	—	—	C	"	1
12400	Type 3920003	2	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
3642	Type 1833003	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
5786	Type 3173003	10	750	2,200	6M	33M	17M	SUSP.	—	—	C	"	1
14082	Type 463500318	2	350	700	6M	30M	17M	SUSP.	—	—	C	"	1
4209	Type 21650035	2	350	1,000	6M	45M	21M	SUSP.	—	—	C	"	1
14799	Type 497400375	5	350	—	—	—	—	—	—	—	C	"	1
13357	Type 4354004	1	750	2,200	6M	33M	17M	SUSP.	—	—	C	"	1
14099	Type 4640004	5	350	700	6M	45M	20M	SUSP.	—	—	C	"	1
11193	Type 3396004	5	350	1,000	5M	30M	30M	SUSP.	—	—	C	"	1
11801	Type 3611004	5	350	1,000	6M	33M	17M	SUSP.	—	—	C	"	1
14409	Type 4758004	10	750	—	—	—	—	—	—	—	C	"	1
11942	Type 3683004	15	350	1,000	6M	33M	20M	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Protected—cont.													
	.001 mfd. and upwards—cont.													
17603	Type 61270045	10	1,250	—	—	—	—	—	—	—	C	each	1
14980	Type 50610047	10	350	—	—	—	—	—	—	—	C	..	1
2294	Type 1097005	2	350	1,000	6M	45M	21M	SUSP.	—	—	C	..	1
5478	Type 2979005	2	350	1,000	6M	33M	33M	SUSP.	—	—	C	..	1
15734	Type005	5	350	1,000	$\frac{1}{16}$	$1\frac{3}{16}$	$\frac{1}{16}$	SUSP.	—	Z.A.15409	C	..	1
11192	Type 3395005	5	350	1,000	6M	33M	17M	SUSP.	—	—	C	..	1
17012	Type005	5	750	—	—	—	—	—	—	—	C	..	1
4611	Type 2402005	10	350	1,000	6M	33M	17M	SUSP.	—	—	C	..	1
12162	Type 3809005	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	..	1
17730	Type 6177006	5	750	—	—	—	—	—	—	—	C	..	1
794	Type 845006	15	750	2,250	6M	33M	20M	SUSP.	—	—	C	..	1
12102	Type 37750075	2	350	1,000	6M	45M	21M	SUSP.	—	—	C	..	1
12104	Type 37770075	10	350	1,000	6M	45M	21M	SUSP.	—	—	C	..	1
12401	Type 3921008	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	..	1
17604	Type 6128009	10	1,250	—	—	—	—	—	—	—	C	..	1
11935	Type 367701	1	350	—	—	—	—	—	—	—	C	..	1
12105	Type 377801	2	350	1,000	—	—	—	—	—	—	C	..	1
5479	Type 298001	2	350	1,000	5M	30M	30M	SUSP.	—	—	C	..	1
12106	Type 377901	5	350	1,000	6M	45M	21M	SUSP.	—	—	C	..	1
15745	Type01	5	750	2,200	6M	75M	20M	SUSP.	W.6931	—	C	..	1
12107	Type 378001	10	350	—	—	—	—	—	—	—	C	..	1
14458	Type 479005	—	—	—	—	—	—	—	—	—	C	..	1
	Rectangular:—													
	Metal:—													
17909	Type 6228	328	5	250	—	—	—	—	—	—	—	C	..	1
17904	Type 6223	407	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17908	Type 227	500	5	250	—	—	—	—	—	—	—	C	..	1
10015	Type 352	500	10	2,400	7,200	6	7½	4½	UPRT.	—	—	C	..	1

SECTION 10C—cont.

RADIOFIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Rectangular—cont.													
	Metal—cont.													
17958	Type 6277	514	5	250	—	1.750	2.062	1	—	—	—	C	each	1
17903	Type 6222	651	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17953	Type 6272	661	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17957	Type 6276	823	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17948	Type 6267	872	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17952	Type 6271	1,058	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17947	Type 6266	1,395	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17939	Type 6258	1,655	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17942	Type 6261	1,888	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17934	Type 6253	2,419	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17938	Type 6257	2,649	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17929	Type 6248	3,741	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17933	Type 6252	3,870	5	250	—	1.750	2.062	1	—	—	—	C	"	1
7204	Type 56	5,000	5	500	1,000	1 $\frac{3}{8}$	3	1 $\frac{5}{8}$	UPRT.	—	—	C	"	1
17928	Type 6247	5,990	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17912	Type 6231	6,250	5	250	—	—	—	—	—	—	—	C	"	1
17924	Type 6243	6,250	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17907	Type 6226	7,180	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17961	Type 6280	8,340	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17956	Type 6275	9,800	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17923	Type 6242	9,965	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17910	Type 6229	10,000	5	250	—	—	—	—	—	—	—	C	"	1
7174	Type 57	10,000	5	500	1,000	1 $\frac{3}{8}$	3	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
17911	Type 6230	10,183	5	250	—	—	—	—	—	—	—	C	"	1
17905	Type 6224	11,490	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17919	Type 6238	11,520	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17951	Type 6270	11,690	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17906	Type 6225	11,725	5	250	—	1.750	2.062	1	—	—	—	C	"	1
17943	Type 6262	11,800	5	250	—	1.750	2.062	1	—	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Nava Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Rectangular—cont.													
	Metal—cont.													
17959	Type 6278	13,350	5	250	—	1.750	2.062	1	—	—	—	C	each	1
17946	Type 6265	14,170	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17954	Type 6273	15,868	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17955	Type 6274	16,065	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17962	Type 6281	17,540	5	250	—	1.750	2.062	1	—	—	—	C	..	1
4113	Type 2112	18,000	$\frac{1}{2}$	250	500	3	$2\frac{3}{8}$	$1\frac{1}{32}$	UPRT.	—	—	C	..	1
17918	Type 6237	18,430	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17949	Type 6268	18,700	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17950	Type 6269	19,179	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17937	Type 6256	22,230	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17944	Type 6263	22,680	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17945	Type 6264	23,320	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17914	Type 6233	24,910	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17940	Type 6259	28,050	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17941	Type 6260	28,932	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17932	Type 6251	29,150	5	250	—	1.750	2.062	1	—	—	—	C	..	1
3991	Type 2047	34,770	$\frac{1}{2}$	250	500	3	$2\frac{3}{8}$	$1\frac{1}{32}$	UPRT.	—	—	C	..	1
17935	Type 6254	35,580	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17960	Type 6279	36,410	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17936	Type 6255	36,878	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17927	Type 6246	39,800	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17913	Type 6232	39,870	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17930	Type 6249	46,640	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17931	Type 6250	48,622	5	250	—	1.750	2.062	1	—	—	—	C	..	1
4112	Type 2111	50,000	$\frac{1}{2}$	250	500	3	$2\frac{3}{8}$	$1\frac{1}{32}$	UPRT.	—	—	C	..	1
17922	Type 6241	57,600	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17925	Type 6244	63,700	5	250	—	1.750	2.026	1	—	—	—	C	..	1
17926	Type 6245	66,905	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17917	Type 6236	90,200	5	250	—	1.750	2.062	1	—	—	—	C	..	1
17920	Type 6239	92,150	5	250	—	1.750	2.062	1	—	—	—	C	..	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Rectangular—cont.													
	Metal—cont.													
17921	Type 6240	97,880 mfd.	5	250	—	1-750	2-062	1	—	—	—	C	each	1
17915	Type 6234	0-14430	5	250	—	1-750	2-062	1	—	—	—	C	"	1
17916	Type 6235	0-15613	5	250	—	1-750	2-062	1	—	—	—	C	"	1
18082	Type 6300	0-163414	$\frac{1}{2}$	250	—	—	—	—	—	—	—	C	"	1
3990	Type 2046	0-17043	$\frac{1}{2}$	250	500	3	2 $\frac{3}{8}$	$\frac{1}{4}$	UPRT.	—	—	C	"	1
	Moulded:—													
15119	Type 5122	50	5	1,500	3,000	3 $\frac{1}{32}$	2 $\frac{1}{4}$	$\frac{33}{32}$	UP/SD.	—	—	C	"	1
8498	Type 190	75	6	$\frac{1}{2}$ a at 100 Kc/s		$\frac{13}{16}$	2 $\frac{7}{16}$	$\frac{37}{32}$	UPRT.	—	—	C	"	1
564	Type 764	80	5 mmfd.	6,000	12 KV	3 $\frac{3}{32}$	3 $\frac{1}{8}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
3354	Type 6	100	5	2,500	5,000	$\frac{5}{8}$	2 $\frac{7}{16}$	$\frac{27}{32}$	UPRT.	—	—	C	"	1
11826	Type 3628	100	10	2,500	5,000	$\frac{5}{8}$	3 $\frac{1}{2}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
11823	Type 3625	150	5	2,500	5,000	$\frac{5}{8}$	3 $\frac{1}{2}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
3341	Type 9	200	10	500	1,000	$\frac{5}{8}$	2 $\frac{7}{16}$	$\frac{27}{32}$	UPRT.	—	—	C	"	1
2310	Type 63	200	10	Inf. Meg.	1,000	$\frac{5}{8}$	2 $\frac{7}{16}$	$\frac{37}{32}$	UPRT.	—	—	C	"	1
16912	Type 6024	250	5	5,000	—	4	2 $\frac{3}{8}$	—	STUD	—	—	C	"	1
8507	Type 198	260	7	1a at 100 Kc/s		$\frac{13}{16}$	2 $\frac{7}{16}$	$\frac{37}{32}$	UPRT.	—	—	C	"	1
8497	Type 189	300	6	$\frac{1}{4}$ at 100 Kc/s		$\frac{13}{16}$	2 $\frac{7}{16}$	$\frac{37}{32}$	UPRT.	—	—	C	"	1
2933	Type 1410	300	10	500	1,000	1 $\frac{5}{8}$	2 $\frac{3}{8}$	$\frac{13}{16}$	UPRT.	—	—	C	"	1
15981	Type 5317	300	10	10 KV	20 KV	5 $\frac{1}{4}$	2 $\frac{1}{4}$	—	STUD	—	ZC.1536	C	"	1
14512	Type 4827	500	5	2,000	4,000	5 $\frac{1}{4}$	2 $\frac{1}{4}$	—	STUD	—	—	C	"	1
9294	Type 271	500	5	2,500	5,000	$\frac{5}{8}$	2 $\frac{7}{16}$	$\frac{37}{32}$	UPRT.	—	—	C	"	1
9377	Type 302	500	15	1a at 3-15 Mc/s		3 $\frac{1}{8}$	2 $\frac{1}{4}$	$\frac{3}{4}$	UP/SD.	—	—	C	"	1
16913	Type 6025	800	5	5,000	—	4	2 $\frac{3}{8}$	—	STUD	—	—	C	"	1
15889	Type 5275	850	5	500	1,000	4 $\frac{1}{2}$	3 $\frac{1}{8}$	—	UPRT.	—	—	C	"	1
14509	Type 4824	1,000	5	2,800	3,600	7 $\frac{1}{8}$	7 $\frac{1}{8}$	3 $\frac{1}{4}$	UPRT.	—	—	C	"	1
8048	Type 143	1,000	5	2,500	5,000	$\frac{7}{16}$	1 $\frac{1}{8}$	1 $\frac{15}{16}$	UPRT.	—	—	C	"	1
5223	Type 2815	1,000	10	1,500	3,000	3 $\frac{1}{8}$	2 $\frac{3}{4}$	$\frac{3}{4}$	UP/SD.	—	ZA.1705	C	"	1
7763	Type 108	1,000	10	10a at 250 Kc/s		$\frac{33}{32}$	3 $\frac{1}{4}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Rectangular—cont.													
	Moulded—cont.													
5193	Type 2785 ...	1,250	10	2,500	5,000	3 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{13}{16}$	UPRT.	—	—	C	each	1
16914	Type 6026 ...	1,600	5	5,000	—	4	2 $\frac{3}{8}$	—	STUD	—	—	C	"	1
8499	Type 191 ...	2,000	5	2,500	5,000	5 $\frac{1}{8}$	3 $\frac{1}{2}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
9297	Type 274 ...	2,000	5	2,500	5,000	1 $\frac{13}{16}$	2 $\frac{7}{16}$	1 $\frac{17}{32}$	UPRT.	—	—	C	"	1
7764	Type 109 ...	2,000	5	5,000	10 KV	1	3 $\frac{11}{16}$	1 $\frac{55}{64}$	UPRT.	—	—	C	"	1
8164	Type 152 ...	2,600	2	2,000	4,000	3 $\frac{7}{8}$	4 $\frac{1}{4}$	2 $\frac{3}{8}$	UPRT.	—	—	C	"	1
	mfd.													
14510	Type 4825001	5	1,400	2,800	5 $\frac{1}{4}$	2 $\frac{1}{4}$	—	STUD	—	—	C	"	1
2043	Type 948004	10	850	1,700	3 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{3}{16}$	UP/SD.	—	—	C	"	1
3845	Type 19340045	5	3,500	7,000	3 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{1}{16}$	UP/SD.	—	—	C	"	1
3798	Type 1928005	10	—	5,000	3 $\frac{7}{8}$	4 $\frac{1}{8}$	2 $\frac{3}{8}$	UP/SD.	—	—	C	"	1
2626	Type 1250005	20	2,500	5,000	3 $\frac{1}{4}$	2 $\frac{1}{2}$	1 $\frac{1}{8}$	UP/SD.	—	—	C	"	1
2314	Type 330089	10	Inf. Meg.	1,000	3 $\frac{1}{8}$	2 $\frac{7}{16}$	1 $\frac{17}{32}$	UPRT.	—	—	C	"	1
7039	Type 5301	5	2,500	5,000	3 $\frac{1}{8}$	2 $\frac{7}{16}$	1 $\frac{17}{32}$	UPRT.	—	—	C	"	1
8044	Type 13901	5	2,500	5,000	3 $\frac{1}{8}$	3 $\frac{1}{2}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
4034	Type 208601	10	500	1,000	3 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{1}{4}$	UP/SD.	—	—	C	"	1
17879	Type 620501	10	500	—	2 $\frac{3}{8}$	1 $\frac{1}{8}$	1 $\frac{1}{8}$	—	—	—	C	"	1
2934	Type 141101	10	500	1,000	1 $\frac{1}{8}$	2 $\frac{11}{16}$	1 $\frac{1}{8}$	UP/SD.	—	—	C	"	1
4042	Type 209401	10	1,500	3,000	3 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{3}{16}$	UP/SD.	—	—	C	"	1
4036	Type 208801	10	2,500	5,000	3 $\frac{1}{4}$	2 $\frac{1}{4}$	2 $\frac{3}{8}$	UP/SD.	—	—	C	"	1
8163	Type 15101	10	5,000	10 KV	1 $\frac{1}{16}$	3 $\frac{1}{4}$	2	UPRT.	—	—	C	"	1
4345	Type 2250 ...	0.25	10	1,000	2,000	2 $\frac{3}{8}$	2 $\frac{3}{4}$	1 $\frac{11}{16}$	UPRT.	—	—	C	"	1
11011	Type 33200295	1	300	600	2 $\frac{3}{4}$	2 $\frac{11}{16}$	1 $\frac{1}{8}$	UP/SD.	—	—	C	"	1
11761	Type 358905	5	350	1,200	3 $\frac{3}{32}$	2 $\frac{1}{4}$	1 $\frac{11}{32}$	UP/SD.	—	—	C	"	1
3193	Type 154805	10	500	1,000	3 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{3}{16}$	UP/SD.	—	—	C	"	1
10221	Type 41405	10	1,000	2,000	2 $\frac{15}{16}$	2 $\frac{1}{4}$	1 $\frac{11}{16}$	UPRT.	—	—	C	"	1
11012	Type 3321006	1	300	600	2 $\frac{3}{4}$	2 $\frac{11}{16}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
9833	Type 3411	10	250	500	3 $\frac{1}{4}$	2 $\frac{3}{4}$	1 $\frac{11}{16}$	UPRT.	—	—	C	"	1
5137	Type 27291	10	500	1,000	2 $\frac{3}{4}$	2 $\frac{13}{16}$	1 $\frac{1}{8}$	UP/SD.	—	—	C	"	1
11010	Type 3319185	1	300	600	2 $\frac{1}{4}$	2	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Rectangular—cont.													
	Moulded—cont.													
8567	Type 2052	10	250	500	3	2 $\frac{1}{8}$	1 $\frac{1}{8}$	UPRT.	—	—	C	each	1
10010	Type 34725	10	250	500	2 $\frac{1}{4}$	2 $\frac{1}{8}$	1 $\frac{1}{8}$	UP/SD.	—	—	C	"	1
	Other Types:—	mmfd.												
17779	Type 6188 ...	2-8	—	—	—	—	—	—	—	—	—	C	"	1
8488	Type 180 ...	10	—	—	—	—	—	—	—	—	—	C	"	1
4215	Type 2171 ...	15	20	350	—	—	—	—	—	—	—	C	"	1
14683	Type 4916 ...	25	± 1 μ mf.	350	—	—	—	—	—	—	—	C	"	1
11973	Type 3699 ...	35	5	350	—	—	—	—	—	—	—	C	"	1
11197	Type 3400 ...	35	5	350	1,000	—	—	—	—	—	—	C	"	1
3905	Type 1974 ...	35-5	—	—	—	—	—	—	—	—	—	C	"	1
14682	Type 4915 ...	50	+ 1 μ mf.	350	—	—	—	—	—	—	—	C	"	1
3183	Type 1538 ...	70	—	—	—	—	—	—	—	—	—	C	"	1
14681	Type 4914 ...	75	± 1 μ mf.	350	—	—	—	—	—	—	—	C	"	1
14680	Type 4913 ...	100	± 1 μ mf.	350	—	—	—	—	—	—	—	C	"	1
13339	Type 4343 ...	100	—	1,000	—	—	—	—	—	—	—	C	"	1
2006	Type 918 ...	100	5	350	—	—	—	—	—	—	—	C	"	1
8500	Type 192 ...	100	5	2,500	5,000	—	—	—	—	—	—	C	"	1
15743	Type ...	160	5	28 KV	35 KV	5 $\frac{1}{8}$	1 $\frac{1}{8}$	—	UPRT.	W.5767	—	C	"	1
4191	Type 2147 ...	230	20	500	1,500	5 $\frac{1}{8}$	2 $\frac{3}{8}$	—	STUD	—	—	C	"	1
2013	Type 925 ...	255	2	350	—	3 $\frac{3}{8}$	1 $\frac{1}{8}$	1 $\frac{1}{2}$	SUSP.	—	ZC.11445	C	"	1
2693	Type 12 ...	300	5	1,500	3,000	—	—	—	—	—	—	C	"	1
14684	Type 4917 ...	430	1	350	—	3 $\frac{1}{4}$	2	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
14704	Type 4930 ...	470	5	350	—	—	—	—	—	—	—	C	"	1
4938	Type 2628 ...	500	2	350	—	—	—	—	—	—	—	C	"	1
3796	Type 1926 ...	500	5	25 KV	50 KV	—	—	—	—	—	—	C	"	1
2179	Type 1026 ...	500	10	5,000	10 KV	8 $\frac{1}{4}$	3 $\frac{3}{8}$	—	STUD	—	—	C	"	1
4433	Type 2299 ...	500	20	500	1,500	4 $\frac{1}{4}$	2 $\frac{3}{8}$	—	STUD	—	ZC.2175	C	"	1
2014	Type 926 ...	537	2	350	—	3 $\frac{3}{8}$	1 $\frac{1}{8}$	1 $\frac{1}{2}$	SUSP.	—	ZC.11915	C	"	1
14800	Type 4975 ...	850	2	350	—	—	—	—	—	—	—	C	"	1
4342	Type 2247 ...	900	5	350	—	—	—	—	—	—	—	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mmfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins. or mm.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	MICA DIELECTRIC—cont.													
	Rectangular—cont.													
	Other Types—cont.	mfd.												
14679	Type 4912001	1	350	—	—	—	—	—	—	—	C	each	1
3326	Type 1632001	4	250	—	—	—	—	—	—	—	C	"	1
2244	Type 1062001	10	15 KV	30 KV	8 $\frac{5}{8}$	3 $\frac{3}{4}$	—	STUD	—	—	C	"	1
2386	Type 1201001	10	25 KV	51 KV	6 $\frac{11}{16}$	3 $\frac{3}{4}$	—	UPRT.	—	ZC.1707	C	"	1
2243	Type 1061001	10	28 KV	56 KV	14 $\frac{1}{4}$	5 $\frac{5}{8}$	—	CLMP.	—	—	C	"	1
4190	Type 2146001	20	500	1,500	7 $\frac{7}{32}$	1 $\frac{1}{8}$	$\frac{5}{8}$	SUSP.	—	ZC.11916	C	"	1
14685	Type 41980013	1	350	—	—	—	—	—	—	—	C	"	1
2181	Type 10280015	10	25 KV	50 KV	5 $\frac{11}{16}$	3 $\frac{3}{4}$	—	UPRT.	—	ZC.1535	C	"	1
14511	Type 4826002	5	600	1,200	5 $\frac{1}{4}$	2 $\frac{3}{4}$	—	STUD	—	—	C	"	1
13068	Type 42120035	2	350	—	—	—	—	—	—	—	C	"	1
14516	Type 48290035	5	3,500	7,000	5 $\frac{1}{4}$	2 $\frac{3}{4}$	—	STUD	—	—	C	"	1
2182	Type 1029004	10	2,000	4,000	1 $\frac{1}{4}$	2 $\frac{11}{16}$	—	UPRT.	—	—	C	"	1
14185	Type 46730047	10	350	—	—	—	—	—	—	—	C	"	1
16911	Type 6023005	5	—	—	—	—	—	—	—	—	C	"	1
3386	Type 1651005	10	5,000	10 KV	4 $\frac{9}{16}$	2 $\frac{3}{4}$	—	STUD	—	—	C	"	1
5532	Type 2995006	5	250	500	2 $\frac{1}{16}$	1	—	STUD	—	—	C	"	1
2246	Type 106401	10	5,000	10 KV	4 $\frac{7}{16}$	2 $\frac{3}{4}$	—	STUD	—	—	C	"	1
2245	Type 106301	20	15 KV	30 KV	14	5 $\frac{5}{8}$	—	CLMP.	—	—	C	"	1
17019	Type01	20	750	2,200	3 $\frac{5}{32}$	1 $\frac{1}{8}$	$\frac{3}{4}$	SUSP.	—	ZC.11328	C	"	1
15887	Type 527304	5	750	1,500	1 $\frac{7}{8}$	$\frac{1}{8}$	—	UPRT.	—	—	C	"	1
15888	Type 527404	5	750	1,500	1 $\frac{7}{8}$	$\frac{1}{8}$	—	—	—	—	C	"	1

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC:—												
	Cylindrical:—												
	Insulated:—												
2102	Type 981001	20	1,500	—	—	—	—	—	—	—	each	1
13238	Type 42730015	10	450	900	1 3/4	15/16	SUSP.	—	—	C	"	1
11134	Type 3370002	10	1,000	2,000	1 1/2	1/8	SUSP.	—	—	C	"	1
4774	Type 25060022	20	400	800	1 1/2	1/8	SUSP.	—	—	C	"	1
2173	Type 1020003	10	3,500	10,500	3 1/2	1/8	SUSP.	—	ZC.0511	C	"	1
11139	Type 3375003	20	1,000	2,000	1 1/2	1/8	SUSP.	—	—	C	"	1
11956	Type 36930035	10	450	1,000	1 1/8	1/8	SUSP.	—	—	C	"	1
11140	Type 3376004	20	1,000	2,000	1 1/2	1/8	SUSP.	—	ZA.21760	C	"	1
4566	Type 2376005	2	450	1,500	1 3/4	15/16	SUSP.	—	—	C	"	1
4610	Type 2401005	10	30,000	50,000	23 1/4	27/16	CLMP.	—	—	C	"	1
5807	Type 3194005	15	600	1,500	1 3/4	15/16	SUSP.	—	—	C	"	1
11136	Type 3372005	20	375	750	1 1/2	1/8	SUSP.	—	—	C	"	1
16644	Type 5828005	25	350	—	—	—	SUSP.	—	—	C	"	1
5536	Type 2999006	20	750	—	—	—	—	—	—	C	"	1
11141	Type 3377006	20	1,000	2,000	1 1/2	1/8	SUSP.	—	—	C	"	1
13497	Type 441401	10	250	700	1 9/16	1/16	SUSP.	—	—	C	"	1
5868	Type 321601	10	500	1,000	1 5/8	1/8	SUSP.	—	—	C	"	1
2590	Type 122801	10	3,000	6,000	2 1/2	7/8	SUSP.	—	—	C	"	1
13312	Type 432501	15	—	—	—	—	—	—	—	C	"	1
12944	Type 413601	15	600	1,200	1 3/4	9/16	SUSP.	—	—	C	"	1
2715	Type 131801	20	250	700	1 9/16	1/16	SUSP.	—	ZA.21212	C	"	1
17021	Type01	20	500	1,000	3 1/4	1/8	SUSP.	—	ZC.19218	C	"	1
2716	Type 131901	20	800	2,000	1 3/4	1/8	SUSP.	—	—	C	"	1
11960	Type 369701	20	1,000	2,000	1 1/8	1/8	SUSP.	—	—	C	"	1
12772	Type 407501	20	1,500	3,000	1 3/4	1/8	SUSP.	—	—	C	"	1
16296	Type 549901	20	3,000	—	2 1/2	1/8	—	—	—	C	"	1
16708	Type 588001	25	350	—	—	—	—	—	—	C	"	1
15204	Type 519201	25	350	—	1 9/16	5/16	—	—	—	C	"	1
2812	Type 131501	25	750	2,000	1 3/4	1/8	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Insulated—cont.												
15939	Type 529801	25	1,000	3,000	1½	½	SUSP.	—	ZA.20915	C	each	1
17027	Type015	10	1,000	—	—	—	—	—	—	C	—	1
15937	Type 529602	5	750	—	—	—	—	—	—	C	—	1
13664	Type 447902	+20—10	1,500	3,000	1½	7/16	SUSP.	—	—	C	—	1
17005	Type02	15	450	1,500	1½	7/16	SUSP.	W.2560	—	C	—	1
5976	Type 328502	20	450	1,500	1¼	3/32	SUSP.	—	—	C	—	1
15203	Type 519102	20	600	—	—	—	—	—	—	C	—	1
11961	Type 369802	20	2,000	4,000	1¾	25/32	SUSP.	—	—	C	—	1
5149	Type 2741025	15	1,000	2,000	1¾	25/32	SUSP.	—	—	C	—	1
2791	Type 133303	20	800	2,000	2	25/32	SUSP.	—	—	C	—	1
12960	Type 4145035	20	600	1,200	1¾	25/32	SUSP.	—	—	C	—	1
12430	Type 393704	15	1,000	2,000	1¼	25/32	SUSP.	—	—	C	—	1
12144	Type 379304	15	1,500	3,000	2⅛	15/16	SUSP.	—	—	C	—	1
11953	Type 369005	5	450	—	—	—	—	—	—	C	—	1
2630	Type 125405	15	450	—	—	—	—	—	—	C	—	1
2271	Type 108105	15	750	2,000	2¼	¾	SUSP.	—	—	C	—	1
2680	Type 128405	15	600	—	—	—	—	—	—	C	—	1
4998	Type 268805	15	1,000	2,000	2½	7/8	SUSP.	—	—	C	—	1
16690	Type 586505	20	500	1,500	1½	25/32	SUSP.	—	—	C	—	1
11959	Type 369605	20	1,000	2,000	1¾	15/32	SUSP.	—	—	C	—	1
16647	Type 583105	25	100	—	—	—	—	—	—	C	—	1
16649	Type 583305	25	200	—	—	—	—	—	—	C	—	1
15950	Type 530005	25	250	375	5/8	5/16	SUSP.	—	ZA.30403	C	—	1
744	Type 830075	15	350	1,000	2¼	21/32	SUSP.	—	—	C	—	1
12860	Type 410309	20	3,000	6,000	3½	1¼	CLMP.	—	—	C	—	1
14660	Type 49031	—	150	—	—	—	—	—	—	C	—	1
14196	Type 46791	5	350	—	1 7/16	7/16	—	—	—	C	—	1
2717	Type 13201	5	350	700	1¼	7/16	SUSP.	—	—	C	—	1
5356	Type 29041	5	450	1,000	1¾	5/16	SUSP.	—	—	C	—	1
12773	Type 40761	10	2,000	4,000	2½	1 3/32	SUSP.	—	—	C	—	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Insulated—cont.												
2252	Type 10671	15	250	700	1 3/4	7/16	SUSP.	W.6709	—	C	each	1
17006	Type1	15	250	1,000	1 3/4	7/16	SUSP.	W.3612	—	C	"	1
5673	Type 30981	15	2,000	4,000	2 1/2	1 3/32	SUSP.	W.4037	—	C	"	1
15722	Type1	20	350	1,000	1 11/16	5/8	SUSP.	—	ZA.1641	C	"	1
15936	Type 52951	20	350	1,000	1 1/2	1 1/2	SUSP.	—	—	C	"	1
4823	Type 25541	20	1,500	3,000	2 1/2	1 3/32	SUSP.	—	—	C	"	1
16648	Type 58321	25	120	—	—	—	—	—	—	C	"	1
16214	Type 54481	25	200	—	—	—	—	—	—	C	"	1
15245	Type 52101	25	250	700	1 1/2	15/32	SUSP.	—	—	C	"	1
11955	Type 369215	5	450	1,000	1 5/8	11/16	SUSP.	—	—	C	"	1
12398	Type 391915	10	350	700	1 5/8	5/8	SUSP.	—	—	C	"	1
5641	Type 30662	15	450	1,000	1 3/4	1	SUSP.	—	—	C	"	1
5973	Type 328223	5	450	1,000	1 3/4	26/32	SUSP.	—	—	C	"	1
5974	Type 328323	20	450	1,000	1 3/4	26/32	SUSP.	W.8069	ZC.11448	C	"	1
5362	Type 291025	10	250	—	2 3/8	26/32	—	—	—	C	"	1
12988	Type 416825	10	1,000	2,000	2 1/2	1 3/32	SUSP.	—	—	C	"	1
2253	Type 106825	15	350	1,000	2 1/4	3/4	SUSP.	—	—	C	"	1
5162	Type 275425	15	450	1,000	1 3/4	11/16	SUSP.	—	—	C	"	1
11788	Type 360625	15	750	1,500	2 1/4	3/4	SUSP.	—	—	C	"	1
12023	Type 372025	15	1,000	—	—	—	—	—	—	C	"	1
4803	Type 253425	20	450	1,000	1 5/8	11/16	SUSP.	—	—	C	"	1
13005	Type 417425	20	700	1,400	2 9/16	15/16	SUSP.	—	—	C	"	1
5657	Type 30824	15	450	1,000	2 3/16	15/16	SUSP.	—	—	C	"	1
2711	Type 13045	15	450	900	1 3/4	1	SUSP.	—	—	C	"	1
4909	Type 26015	15	450	1,500	1 3/4	15/16	SUSP.	—	ZA.24291	C	"	1
5795	Type 31825	20	450	1,000	2 1/2	27/32	SUSP.	W.8073	ZC.11924	C	"	1
12379	Type 39065	20	450	1,000	2 1/8	15/16	SUSP.	—	—	C	"	1
11131	Type 33675	20	500	—	2 1/4	1	—	—	—	C	"	1
16714	Type 58855	25	150	—	—	—	—	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Insulated—cont.												
11954	Type 3691	1	5	450	1,000	2 $\frac{3}{8}$	1 $\frac{1}{16}$	SUSP.	—	—	C	each	1
4544	Type 2354	1	15	400	800	2 $\frac{1}{2}$	1 $\frac{1}{4}$	CLMP.	—	—	C	"	1
5763	Type 3150	1	20	350	—	—	—	—	—	—	C	"	1
4871	Type 2563	1	20	450	1,000	2 $\frac{1}{8}$	1 $\frac{5}{32}$	SUSP.	W.8072	ZC.11186	C	"	1
15126	Type 5127	1	25	150	250	1 $\frac{1}{8}$	1 $\frac{1}{8}$	SUSP.	—	—	C	"	1
608	Type 773	2	20	250	500	2 $\frac{9}{16}$	1 $\frac{1}{4}$	CLMP.	—	—	C	"	1
12883	Type 4112	2	20	250	500	2 $\frac{1}{2}$	1 $\frac{3}{8}$	SUSP.	—	—	C	"	1
15125	Type 5126	2	25	150	250	1 $\frac{3}{8}$	1 $\frac{1}{8}$	SUSP.	—	—	C	"	1
15244	Type 5209	2	25	250	375	2 $\frac{1}{8}$	1 $\frac{1}{8}$	SUSP.	—	—	C	"	1
	Metal:—												
12809	Type 4087001	—5+10	375	1,000	3 $\frac{1}{4}$	1 $\frac{3}{16}$	STUD	—	—	C	"	1
16642	Type 5826001	25	350	—	—	—	—	—	—	C	"	1
16643	Type 5827002	25	350	—	—	—	—	—	—	C	"	1
15953	Type 5301005	10	1,000	3,000	1 $\frac{5}{8}$	1 $\frac{1}{4}$	SUSP.	—	—	C	"	1
16904	Type 6016005	20	—	—	1 $\frac{3}{8}$	1 $\frac{1}{4}$	—	—	—	C	"	1
16118	Type 5377005	25	350	1,000	1	1 $\frac{1}{4}$	SUSP.	—	—	C	"	1
16707	Type 5789005	25	350	—	—	—	—	—	—	C	"	1
14346	Type 472101	10	350	700	1 $\frac{13}{32}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
4024	Type 207601	15	350	1,000	2 $\frac{5}{16}$	1 $\frac{3}{4}$	STUD	W.9244	—	C	"	1
11753	Type 358301	15	350	1,000	3 $\frac{3}{8}$	1 $\frac{3}{4}$	STUD	—	—	C	"	1
3276	Type 159001	15	750	2,250	1 $\frac{5}{8}$	1 $\frac{1}{2}$	SUSP.	—	—	C	"	1
5645	Type 307001	20	2,500	—	—	—	—	—	—	C	"	1
11747	Type 357801	20	2,500	5,000	3 $\frac{5}{8}$	1	UPRT.	—	—	C	"	1
2625	Type 124901	20	2,500	5,000	3 $\frac{17}{32}$	1	STUD	W.3715	—	C	"	1
16085	Type 535901	25	350	1,000	1	1 $\frac{1}{4}$	SUSP.	—	—	C	"	1
16129	Type 538701	25	500	1,000	1	1 $\frac{11}{32}$	SUSP.	—	—	C	"	1
17010	Type02	10	350	1,000	2 $\frac{1}{4}$	1 $\frac{3}{4}$	STUD	—	ZA.20955	C	"	1
13209	Type 425802	10	350	1,000	2 $\frac{1}{2}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
2157	Type 99702	15	8,000	16,000	6 $\frac{3}{4}$	1 $\frac{3}{4}$	CLMP.	W.7913	ZA.3356	C	"	1
13578	Type 444402	20	350	1,000	1 $\frac{3}{8}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Metal—cont.												
15201	Type 519002	25	350	700	1	$\frac{11}{32}$	SUSP.	—	—	C	each	1
3026	Type 143802	-10+25	450	1,500	$2\frac{5}{32}$	$\frac{3}{4}$	STUD	—	—	C	"	1
16837	Type 597104	10	350	1,000	$1\frac{1}{8}$	$\frac{3}{4}$	SUSP.	—	—	C	"	1
11388	Type 346004	-15+25	4,000	8,000	5	$1\frac{1}{2}$	CLMP.	—	—	C	"	1
14371	Type 472505	10	350	700	$2\frac{1}{2}$	$\frac{1}{2}$	UPRT.	—	—	C	"	1
14372	Type 472605	10	350	700	$2\frac{13}{16}$	$\frac{1}{2}$	UPRT.	—	—	C	"	1
11754	Type 358405	15	350	1,000	$3\frac{3}{8}$	$\frac{1}{2}$	UPRT.	—	—	C	"	1
17893	Type 621405	20	2,000	—	$2\frac{3}{8}$	1	—	—	—	C	"	1
13188	Type 42461	10	350	1,000	$1\frac{1}{2}$	$\frac{3}{4}$	UPRT.	—	—	C	"	1
3291	Type 16021	10	250	—	—	—	—	—	—	C	"	1
2567	Type 12141	10	450	1,500	$2\frac{3}{16}$	$\frac{3}{4}$	STUD	—	—	C	"	1
2651	Type 12671	10	375	—	—	—	—	—	—	C	"	1
17008	Type1	15	350	750	$1\frac{3}{8}$	$\frac{1}{2}$	STUD	—	ZA.11422	C	"	1
4021	Type 20731	15	350	1,000	$1\frac{33}{32}$	$\frac{1}{2}$	STUD	—	—	C	"	1
4023	Type 20751	15	350	1,000	$1\frac{13}{16}$	$\frac{1}{2}$	STUD	—	—	C	"	1
967	Type 8991	15	350	1,000	2	$\frac{1}{2}$	STUD	W.2983	—	C	"	1
13203	Type 42541	15	350	1,500	$1\frac{3}{4}$	$\frac{1}{2}$	SUSP.	—	—	C	"	1
2280	Type 10861	15	1,500	—	$2\frac{1}{2}$	$1\frac{1}{8}$	—	—	—	C	"	1
12694	Type 40541	20	350	1,000	$1\frac{13}{16}$	$\frac{1}{2}$	STUD	—	—	C	"	1
12693	Type 40531	20	350	1,000	$1\frac{33}{32}$	$\frac{1}{2}$	STUD	—	—	C	"	1
12332	Type 38751	20	1,500	3,000	$3\frac{1}{2}$	1	STUD	—	—	C	"	1
13998	Type 46011	20	2,500	5,000	4	1	CLMP.	—	—	C	"	1
16122	Type 53801	25	350	1,000	$1\frac{1}{2}$	$\frac{7}{16}$	SUSP.	—	—	C	"	1
12810	Type 40881	-5+10	375	1,000	$2\frac{1}{4}$	$\frac{1}{2}$	STUD	—	—	C	"	1
2565	Type 12121	-10+Inf.	2,500	5,000	$5\frac{15}{16}$	$1\frac{13}{32}$	CLMP.	—	—	C	"	1
11756	Type 358625	15	350	700	4	$\frac{1}{2}$	STUD	—	—	C	"	1
12132	Type 378825	15	375	750	$2\frac{3}{4}$	$\frac{1}{2}$	SUSP.	W.5168	—	C	"	1
12633	Type 402825	20	500	1,500	$3\frac{1}{8}$	$\frac{1}{2}$	STUD	—	—	C	"	1
11752	Type 358236	10	350	700	$3\frac{1}{2}$	$\frac{1}{2}$	STUD	—	—	C	"	1
3290	Type 16015	10	250	500	$2\frac{33}{32}$	1	STUD	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Nava Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Metal—cont.												
13190	Type 42485	10	350	700	2 $\frac{1}{2}$	$\frac{3}{4}$	STUD	—	—	C	each	1
17007	Type5	15	350	700	2 $\frac{1}{2}$	$\frac{3}{4}$	STUD	—	ZA.20956	C	"	1
2654	Type 12705	-5+10	375	750	3 $\frac{1}{4}$	$\frac{13}{16}$	STUD	—	—	C	"	1
13298	Type 43115	20	500	—	—	—	—	—	—	C	"	1
8671	Type 216	1.0	10	250	650	5 $\frac{11}{16}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
4777	Type 2509	1.0	10	350	—	—	—	—	—	—	C	"	1
14390	Type 4739	1.0	10	350	700	2 $\frac{11}{16}$	1	STUD	—	—	C	"	1
13189	Type 4247	1.0	10	350	750	2 $\frac{11}{16}$	1	SUSP.	—	—	C	"	1
2890	Type 1382	1.0	10	450	1,000	3 $\frac{7}{8}$	1 $\frac{1}{2}$	STUD	—	—	C	"	1
8657	Type 210	1.0	15	650	1,500	5 $\frac{11}{16}$	1 $\frac{5}{8}$	UPRT.	—	—	C	"	1
11132	Type 3368	1.0	20	350	700	2 $\frac{1}{4}$	1	SUSP.	—	—	C	"	1
15086	Type 5105	1.0	20	350	1,000	2 $\frac{3}{8}$	1	SUSP.	—	—	C	"	1
11748	Type 3579	1.25	-20+Inf.	350	700	4 $\frac{3}{4}$	1	STUD	—	—	C	"	1
17894	Type 6215	2.0	2	2,000	—	2 $\frac{3}{8}$	1 $\frac{3}{8}$	—	—	—	C	"	1
13300	Type 4313	2.0	20	400	—	—	—	—	—	—	C	"	1
16779	Type 5947	2.6	-0+10	230	—	10 $\frac{3}{8}$	3 $\frac{1}{2}$	U-shaped Strap	—	—	C	"	1
2083	Type 97305+.05	15	350	500	3 $\frac{3}{4}$	$\frac{3}{4}$	STUD	—	—	C	"	1
11838	Type 36311+.1	15	350	700	3 $\frac{3}{4}$	$\frac{3}{4}$	STUD	—	—	C	"	1
3399	Type 16621+.1	15	250	500	3 $\frac{3}{4}$	$\frac{3}{4}$	STUD	—	—	C	"	1
4020	Type 20721+.1 +.1	15	750	2,250	2	$\frac{11}{16}$	STUD	—	—	C	"	1
	Plastic:—												
2871	Type 13630003	20	350	—	—	—	—	—	—	C	"	1
884	Type 8700005	20	350	700	2 $\frac{1}{2}$	$\frac{15}{16}$	STUD	—	—	C	"	1
13018	Type 41870005	20	350	700	1 $\frac{5}{8}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
2679	Type 12830005	20	600	1,200	1 $\frac{5}{8}$	$\frac{33}{32}$	SUSP.	—	—	C	"	1
2891	Type 1383001	20	3,000	6,000	3 $\frac{1}{16}$	1 $\frac{3}{32}$	STUD	—	—	C	"	1
2681	Type 1285002	20	500	1,000	1 $\frac{1}{2}$	$\frac{31}{32}$	SUSP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Plastic—cont.												
2678	Type 1282003	20	600	1,200	1 5/8	2 3/8	SUSP.	—	—	C	each	1
5707	Type 3132005	15	3,000	6,000	2 7/16	1 3/8	SUSP.	—	—	C	"	1
2683	Type 1287005	20	200	400	1 5/8	2 3/8	SUSP.	—	—	C	"	1
2963	Type 1418007	20	750	1,500	1 5/8	2 3/8	SUSP.	—	—	C	"	1
2429	Type 117201	10	1,500	3,000	2 7/16	1 3/8	SUSP.	—	ZC.1666	C	"	1
2722	Type 132501	15	600	1,200	1 5/8	2 3/8	STUD	—	—	C	"	1
2020	Type 93101	15	600	1,200	1 5/8	2 3/8	SUSP.	—	—	C	"	1
535	Type 75601	15	1,000	2,000	2 1/2	1 1/8	STUD	—	—	C	"	1
2686	Type 129001	15	2,000	4,000	2 3/8	1 1/8	STUD	—	—	C	"	1
707	Type 80501	15	3,000	6,000	3 1/8	1 3/8	STUD	—	ZC.0172	C	"	1
17583	Type 610701	25	750	—	1 1/8	—	—	—	—	C	"	1
2341	Type 113002	10	350	—	—	—	—	—	—	C	"	1
11545	Type 351702	15	2,000	4,000	2 15/16	1 3/8	STUD	—	—	C	"	1
2439	Type 118503	15	500	1,000	2	1 1/8	SUSP.	—	—	C	"	1
12498	Type 397603	20	2,500	6,000	3 1/8	1	STUD	—	—	C	"	1
3963	Type 203204	5	750	1,500	2	1 5/16	SUSP.	—	—	C	"	1
13975	Type 459405	10	15,000	30,000	1 3/4	1 1/8	SUSP.	—	—	C	"	1
2724	Type 1327075	10	350	700	2	1 1/8	SUSP.	—	—	C	"	1
12140	Type 379109	15	3,000	6,000	3 11/16	1 1/8	STUD	—	—	C	"	1
14396	Type 47451	5	250	500	1 3/4	1 1/8	SUSP.	—	—	C	"	1
3902	Type 19711	10	350	700	2	1 1/8	SUSP.	—	ZA.1744	C	"	1
4589	Type 23991	10	500	1,000	2	1 1/8	SUSP.	—	ZC.3059	C	"	1
2881	Type 13731	15	300	600	2 1/2	1 1/8	STUD	—	—	C	"	1
2048	Type 9531	15	350	700	2	1 1/8	SUSP.	—	—	C	"	1
12505	Type 39831	20	2,500	6,000	3 3/4	1 7/8	STUD	—	—	C	"	1
17792	Type 61901	30	350	—	3 9/16	1 1/8	—	—	—	C	"	1
4638	Type 24292	10	350	—	—	—	—	—	—	C	"	1
2132	Type 98825	15	350	700	2 5/8	1 3/8	STUD	—	—	C	"	1
13010	Type 417925	20	350	700	3 1/8	1 3/8	STUD	—	—	C	"	1
2578	Type 12235	10	200	400	2 1/8	1 1/8	STUD	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (INS)		Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Length	Diameter						
1	2	3	4	5	6	7	8	9	10	11	12	13	14
	PAPER DIELECTRIC—cont.												
	Cylindrical—cont.												
	Plastic—cont.												
4634	Type 24255	10	350	—	—	—	—	—	—	C	each	1
3862	Type 19515	10	350	700	$2\frac{7}{16}$	$1\frac{9}{32}$	SUSP.	—	—	C	..	1
4636	Type 24275	15	350	—	—	—	—	—	—	C	..	1
13013	Type 41825	20	350	700	$3\frac{1}{16}$	$1\frac{9}{32}$	STUD	—	—	C	..	1
12508	Type 39865	20	400	1,000	$2\frac{1}{2}$	1	SUSP.	—	—	C	..	1
12509	Type 39875	20	400	1,000	$3\frac{1}{8}$	1	STUD	—	—	C	..	1
13008	Type 41775	20	350	700	$2\frac{7}{16}$	1	SUSP.	—	—	C	..	1
17793	Type 61915	30	150	—	$\frac{11}{16}$	$\frac{9}{16}$	—	—	—	C	..	1
2346	Type 113575	10	600	1,200	$3\frac{3}{16}$	$1\frac{1}{2}$	SUSP.	—	—	C	..	1
12510	Type 3988	1.0	20	400	1,000	$3\frac{1}{8}$	$1\frac{7}{32}$	SUSP.	—	—	C	..	1
12511	Type 3989	1.0	20	400	1,000	$3\frac{1}{4}$	$1\frac{7}{32}$	STUD	—	—	C	..	1

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE ...	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (INS)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
PAPER DIELECTRIC—cont.														
Rectangular:—														
Less than 1 mfd:—														
5210	Type 280201	15	350	1,000	2 $\frac{5}{8}$	1 $\frac{1}{4}$	2 $\frac{1}{4}$	UPRT.	—	—	C	each	1
4969	Type 265902	10	250	—	—	—	—	—	—	—	C	"	1
686	Type 79802	10	6,000	15 KV	6 $\frac{1}{4}$	5 $\frac{1}{8}$	3	CLMP.	—	—	C	"	1
17505	Type 606502	20	12,000	—	6 $\frac{1}{4}$	1 $\frac{5}{8}$	1 $\frac{5}{8}$	—	—	—	C	"	1
14463	Type 479502	20	8,000	15 KV	8 $\frac{1}{4}$	2 $\frac{1}{8}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
12383	Type 3909025	+ Inf. — 15	2,500	5,000	3 $\frac{1}{8}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
3989	Type 2045025	10	600	1,500	2 $\frac{5}{8}$	2 $\frac{1}{4}$	2 $\frac{1}{4}$	UPRT.	—	—	C	"	1
13917	Type 457305	10	2,000	4,000	5 $\frac{1}{2}$	2 $\frac{3}{8}$	2	UPRT.	—	—	C	"	1
2101	Type 98005	10	4,000	8,000	3 $\frac{5}{8}$	2 $\frac{7}{8}$	1 $\frac{7}{16}$	SIDE	—	—	C	"	1
5471	Type 297205	10	7,000	17.5KV	8 $\frac{1}{4}$	6 $\frac{1}{2}$	3	CLMP.	—	—	C	"	1
5950	Type 326005	15	2,000	4,000	3 $\frac{3}{16}$	3	1 $\frac{11}{16}$	INVT.	—	—	C	"	1
4528	Type 234105	20	2,000	5,000	2 $\frac{3}{4}$	3 $\frac{3}{4}$	1	SIDE	—	—	C	"	1
11013	Type 332207	5	250	500	2 $\frac{11}{16}$	2 $\frac{1}{16}$	1 $\frac{11}{16}$	UPRT.	—	—	C	"	1
3211	Type 156506	15	250	500	2 $\frac{11}{16}$	2 $\frac{3}{4}$	1 $\frac{11}{16}$	UPRT.	—	—	C	"	1
11292	Type 4361	10	250	500	1 $\frac{1}{16}$	1 $\frac{3}{4}$	5 $\frac{5}{8}$	CLMP.	—	—	C	"	1
468	Type 7171	10	250	500	1 $\frac{3}{4}$	2 $\frac{1}{2}$	2 $\frac{9}{16}$	UPRT.	—	—	C	"	1
4534	Type 23471	10	300	600	1 $\frac{1}{2}$	2 $\frac{1}{16}$	2 $\frac{1}{16}$	INVT.	—	—	C	"	1
10649	Type 4471	10	400	800	2 $\frac{5}{8}$	2 $\frac{3}{4}$	2 $\frac{1}{4}$	UPRT.	—	—	C	"	1
11005	Type 33141	10	500	1,000	2 $\frac{1}{16}$	2 $\frac{25}{64}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
333	Type 6621	10	500	1,000	2 $\frac{13}{64}$	2 $\frac{3}{8}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
4786	Type 25181	10	500	1,000	3 $\frac{1}{16}$	2 $\frac{7}{16}$	2 $\frac{15}{16}$	UPRT.	—	—	C	"	1
533	Type 7541	10	550	1,100	1 $\frac{7}{16}$	2 $\frac{3}{4}$	2 $\frac{3}{4}$	INVT.	—	—	C	"	1
10826	Type 4851	10	750	2,000	3 $\frac{1}{16}$	3	3 $\frac{3}{4}$	UPRT.	—	—	C	"	1
2175	Type 10221	10	1,000	2,000	2 $\frac{3}{8}$	2 $\frac{3}{8}$	1 $\frac{9}{16}$	UPRT.	—	ZC.0504	C	"	1
706	Type 8041	10	1,000	2,000	2 $\frac{15}{16}$	2 $\frac{3}{4}$	2 $\frac{3}{4}$	INVT.	—	—	C	"	1
5145	Type 27371	10	1,500	4,000	3 $\frac{1}{16}$	3 $\frac{1}{8}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
11975	Type 37011	10	2,000	—	4 $\frac{3}{4}$	2 $\frac{1}{2}$	1 $\frac{3}{8}$	—	—	—	C	"	1
2177	Type 10241	10	2,000	4,000	2 $\frac{3}{4}$	2 $\frac{3}{8}$	2 $\frac{7}{16}$	UPRT.	—	ZC.0505	C	"	1
697	Type 8011	10	2,000	4,000	3 $\frac{15}{16}$	2 $\frac{3}{4}$	1	INVT.	—	—	C	"	1
3499	Type 17251	10	2,000	5,000	4 $\frac{1}{16}$	4 $\frac{1}{4}$	1 $\frac{3}{4}$	UPRT.	—	ZC.1542	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	Less than 1 mfd.—cont.													
938	Type 8831	10	3,000	6,000	6 $\frac{7}{8}$	2 $\frac{1}{2}$	2	CLMP.	—	—	C	each	1
939	Type 8841	10	4,000	8,000	6 $\frac{7}{8}$	2 $\frac{1}{2}$	2	CLMP.	—	—	C	"	1
4213	Type 21691	10	5,000	10 KV	7 $\frac{1}{2}$	3 $\frac{1}{2}$	3 $\frac{1}{4}$	CLMP.	—	—	C	"	1
5185	Type 27771	+10—20	750	2,000	3 $\frac{1}{8}$	3	3 $\frac{1}{4}$	UPRT.	—	—	C	"	1
10833	Type 5081	15	400	1,000	2 $\frac{3}{8}$	2 $\frac{3}{4}$	2 $\frac{3}{4}$	UPRT.	—	—	C	"	1
11899	Type 36531	15	1,000	2,000	2 $\frac{3}{8}$	2 $\frac{7}{16}$	2 $\frac{3}{4}$	UPRT.	—	—	C	"	1
2248	Type 10661	15	1,000	2,000	3	2 $\frac{3}{4}$	3 $\frac{1}{4}$	UPRT.	—	—	C	"	1
5949	Type 32591	15	2,000	—	—	—	—	—	—	—	C	"	1
11290	Type 34541	15	5,000	12 KV	8 $\frac{1}{2}$	4 $\frac{1}{2}$	2 $\frac{3}{8}$	INVT.	—	—	C	"	1
12761	Type 40651	15	7,500	15 KV	6 $\frac{1}{2}$	5 $\frac{1}{2}$	3 $\frac{1}{2}$	STRP.	—	—	C	"	1
13316	Type 43261	20	1,200	2,500	2 $\frac{7}{8}$	2 $\frac{5}{8}$	1 $\frac{7}{8}$	INVT.	—	—	C	"	1
14543	Type 48381	20	1,500	3,000	3 $\frac{1}{8}$	2 $\frac{1}{4}$	1 $\frac{5}{8}$	UPRT.	—	—	C	"	1
13905	Type 45661	20	2,000	4,000	3	3 $\frac{1}{8}$	1	UPRT.	—	—	C	"	1
14462	Type 47941	20	3,000	6,000	4	4 $\frac{1}{2}$	2 $\frac{5}{8}$	UPRT.	—	—	C	"	1
16968	Type 60451	20	3,000	—	—	—	—	—	—	—	C	"	1
13262	Type 42821	20	3,000	6,000	4 $\frac{1}{8}$	4 $\frac{1}{2}$	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
13855	Type 45451	20	4,000	8,000	4	3	3 $\frac{1}{2}$	UPRT.	—	—	C	"	1
2192	Type 10361	25	4,000	8,000	8 $\frac{5}{8}$	4 $\frac{1}{2}$	2 $\frac{5}{8}$	UPRT.	—	ZC.10476	C	"	1
5764	Type 31511	+Inf.—15	3,000	6,000	3 $\frac{7}{8}$	2 $\frac{3}{4}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
5762	Type 31491	+Inf.—15	4,000	8,000	3 $\frac{7}{8}$	3 $\frac{3}{4}$	2	UPRT.	—	—	C	"	1
10297	Type 3892	10	350	700	1 $\frac{7}{8}$	2	1 $\frac{3}{4}$	CLMP.	—	—	C	"	1
2620	Type 12442	10	600	1,250	1 $\frac{3}{8}$	2 $\frac{1}{2}$	1	UPRT.	—	—	C	"	1
2290	Type 109325	10	250	500	3 $\frac{5}{8}$	2 $\frac{1}{2}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
11394	Type 52425	10	350	700	1 $\frac{7}{8}$	2	1 $\frac{3}{4}$	CLMP.	—	—	C	"	1
5891	Type 323925	10	500	1,000	3	2 $\frac{3}{8}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
2436	Type 118225	10	750	2,000	2 $\frac{15}{16}$	2 $\frac{1}{4}$	2 $\frac{3}{4}$	INVT.	—	—	C	"	1
3509	Type 173525	10	750	2,000	3 $\frac{1}{8}$	3	3 $\frac{1}{4}$	UPRT.	—	ZA.22001	C	"	1
2040	Type 94525	10	1,000	3,000	3 $\frac{1}{8}$	3	1	UPRT.	—	—	C	"	1
5711	Type 313625	10	1,500	3,000	3 $\frac{1}{8}$	3	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
11205	Type 340825	10	2,000	5,000	4	4 $\frac{1}{4}$	2 $\frac{3}{8}$	UPRT.	—	—	C	"	1

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	Less than 1 mfd.—cont.													
11214	Type 341725	10	3,000	6,000	4 $\frac{1}{16}$	3 $\frac{1}{2}$	2 $\frac{1}{2}$	UPRT.	—	—	C	each	1
2351	Type 114025	10	4,000	8,000	6 $\frac{1}{16}$	3	3	UPRT.	—	—	C	"	1
2174	Type 102125	10	4,000	8,000	6 $\frac{11}{16}$	3 $\frac{3}{4}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
3490	Type 172325	10	4,000	8,000	8 $\frac{1}{2}$	4 $\frac{3}{4}$	3	UPRT.	—	ZC.1540	C	"	1
4884	Type 257625	10	5,000	10 KV	8 $\frac{5}{8}$	4 $\frac{3}{4}$	3 $\frac{1}{2}$	UPRT.	—	—	C	"	1
16187	Type 543525	10	7,500	15 KV	6	9 $\frac{1}{4}$	11 $\frac{1}{4}$	NONE	—	—	C	"	1
4533	Type 234625	15	300	600	3 $\frac{1}{4}$	2 $\frac{13}{16}$	—	INVT.	—	—	C	"	1
5537	Type 300025	15	550	—	—	—	—	—	—	—	C	"	1
11900	Type 365425	15	2,000	5,000	3 $\frac{1}{2}$	3	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
14329	Type 471925	15	9,000	18 KV	8 $\frac{5}{8}$	7 $\frac{1}{8}$	3 $\frac{3}{4}$	UPRT.	—	—	C	"	1
12619	Type 402625	20	750	1,500	3 $\frac{3}{8}$	2 $\frac{3}{4}$	—	UPRT.	—	—	C	"	1
13272	Type 428925	20	1,000	3,000	3 $\frac{3}{16}$	3	1	UPRT.	—	—	C	"	1
16969	Type 604625	20	2,000	—	—	—	—	—	—	—	C	"	1
13576	Type 444225	20	2,000	5,000	4 $\frac{1}{16}$	4 $\frac{3}{4}$	2 $\frac{1}{4}$	UPRT.	—	—	C	"	1
13990	Type 459825	20	4 KV	10 KV	8 $\frac{5}{8}$	4 $\frac{3}{4}$	3 $\frac{1}{8}$	UPRT.	—	—	C	"	1
14433	Type 477125	20	10 KV	20 KV	7 $\frac{3}{4}$	7 $\frac{1}{2}$	5	UPRT.	—	—	C	"	1
15709	Type25	+20-10	2,750	10 KV	8 $\frac{1}{2}$	4 $\frac{3}{4}$	3	UPRT.	—	—	C	"	1
15737	Type25	+20-10	2,750	10 KV	8 $\frac{1}{2}$	4 $\frac{3}{4}$	3	UPRT.	—	ZC.23735	C	"	1
5217	Type 280925	+Inf.-15	450	1,000	2 $\frac{7}{8}$	2 $\frac{1}{2}$	1	UPRT.	—	—	C	"	1
5440	Type 294225	+Inf.-15	1,500	3,000	2 $\frac{7}{8}$	2 $\frac{1}{2}$	1	UPRT.	—	—	C	"	1
5216	Type 280825	+Inf.-15	2,000	4,000	5 $\frac{1}{4}$	3	2	UPRT.	—	—	C	"	1
11859	Type 364325	+Inf.-0	4,000	8,000	5 $\frac{11}{16}$	4 $\frac{1}{2}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
7593	Type 855	10	150	300	2 $\frac{9}{16}$	1 $\frac{7}{8}$	—	CLMP.	—	—	C	"	1
2447	Type 11885	10	250	500	3	2 $\frac{1}{2}$	—	UPRT.	—	ZA.20307	C	"	1
17899	Type 62185	10	250	—	3 $\frac{1}{2}$	2 $\frac{1}{4}$	—	—	—	—	C	"	1
10342	Type 3925	10	250	500	1 $\frac{3}{16}$	2 $\frac{7}{16}$	1	UPRT.	—	—	C	"	1
2176	Type 10235	10	350	700	2 $\frac{3}{4}$	2 $\frac{1}{2}$	—	UPRT.	—	ZC.0506	C	"	1
4532	Type 23455	10	350	700	3 $\frac{1}{4}$	2 $\frac{13}{16}$	—	INVT.	—	—	C	"	1
3127	Type 15235	10	400	800	3 $\frac{1}{8}$	2 $\frac{3}{4}$	—	UPRT.	—	ZC.1543	C	"	1
10801	Type 4775	10	400	1,000	3 $\frac{1}{8}$	2 $\frac{1}{4}$	—	UPRT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont. Rectangular—cont. Less than 1 mfd.—cont.													
15738	Type5	10	450	1,300	2 $\frac{11}{16}$	2 $\frac{1}{4}$	$\frac{9}{16}$	UPRT.	—	YB.03298	C	each	1
16963	Type 60435	10	500	—	—	—	—	—	—	—	C	..	1
561	Type 7635	10	550	1,100	2 $\frac{11}{16}$	2 $\frac{3}{4}$	$\frac{3}{4}$	INVT.	—	—	C	..	1
2688	Type 12925	10	1,000	2,000	3 $\frac{11}{16}$	2 $\frac{3}{4}$	$\frac{3}{4}$	INVT.	—	—	C	..	1
5191	Type 27835	10	1,500	—	—	—	—	—	—	—	C	..	1
4214	Type 21705	10	1,500	4,000	5 $\frac{7}{8}$	3 $\frac{1}{8}$	1	UPRT.	—	—	C	..	1
9012	Type 2575	10	2,000	4,000	9 $\frac{1}{2}$	4 $\frac{3}{4}$	$\frac{7}{8}$	UPRT.	—	—	C	..	1
4683	Type 24545	10	2,000	5,000	6 $\frac{5}{16}$	4 $\frac{1}{4}$	1 $\frac{3}{4}$	UPRT.	—	—	C	..	1
4805	Type 25365	10	2,500	6,000	6 $\frac{5}{16}$	3	2 $\frac{1}{4}$	UPRT.	—	—	C	..	1
4570	Type 23805	15	400	800	3 $\frac{1}{8}$	2 $\frac{3}{4}$	$\frac{3}{4}$	INVT.	—	—	C	..	1
9675	Type 5335	15	1,500	3,000	3 $\frac{27}{32}$	3 $\frac{23}{32}$	3 $\frac{3}{8}$	UPRT.	—	—	C	..	1
13979	Type 45955	20	200	400	3 $\frac{11}{16}$	3 $\frac{3}{32}$	$\frac{3}{8}$	UPRT.	—	—	C	..	1
11543	Type 35155	20	250	700	3	2 $\frac{1}{2}$	$\frac{3}{4}$	UPRT.	—	—	C	..	1
13095	Type 42245	20	600	1,200	3 $\frac{1}{2}$	2 $\frac{3}{4}$	$\frac{3}{4}$	UPRT.	—	—	C	..	1
13762	Type 45065	20	750	1,500	3 $\frac{1}{8}$	2 $\frac{3}{8}$	$\frac{3}{4}$	INVT.	—	—	C	..	1
12635	Type 40305	20	800	2,000	3	2 $\frac{5}{8}$	1 $\frac{1}{8}$	UPRT.	50814	—	C	..	1
14545	Type 48405	20	1,000	2,500	3 $\frac{1}{16}$	3 $\frac{1}{2}$	1 $\frac{1}{4}$	UPRT.	—	—	C	..	1
14624	Type 48865	20	1,200	—	2 $\frac{5}{8}$	1 $\frac{3}{4}$	2 $\frac{3}{8}$	—	—	—	C	..	1
12524	Type 39925	20	2,000	4,000	5 $\frac{5}{8}$	4 $\frac{1}{2}$	1 $\frac{3}{16}$	UPRT.	—	—	C	..	1
17503	Type 60635	20	5,000	—	—	—	—	—	—	—	C	..	1
17504	Type 60645	20	5,000	—	6 $\frac{1}{2}$	5 $\frac{1}{8}$	4 $\frac{3}{8}$	—	—	—	C	..	1
13633	Type 44655	20	7,000	14 KV	8 $\frac{5}{8}$	7 $\frac{1}{8}$	3 $\frac{1}{2}$	UPRT.	—	—	C	..	1
17778	Type 6187	2.5 + 2.5	20	2 KV + 2 KV	—	3 $\frac{1}{2}$	4 $\frac{1}{8}$	1 $\frac{7}{8}$	SIDE	—	—	C	..	1
9181	Type 2825	+20-10	250	500	1 $\frac{17}{16}$	2 $\frac{7}{16}$	1	UPRT.	—	—	C	..	1
2635	Type 12575	+25-10	450	900	3 $\frac{1}{8}$	3 $\frac{1}{16}$	1	UPRT.	—	—	C	..	1
5215	Type 28075	+Inf.-15	450	900	2 $\frac{7}{8}$	1 $\frac{3}{4}$	1	UPRT.	—	—	C	..	1
5415	Type 292175	10	750	—	—	—	—	—	—	—	C	..	1
5245	Type 283775	15	400	800	5 $\frac{7}{16}$	3 $\frac{1}{4}$	1	UPRT.	—	—	C	..	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards:—													
1805	Type 45	1	10	150	300	1 $\frac{3}{8}$ 2 $\frac{1}{8}$	4 $\frac{1}{8}$ 2 $\frac{1}{8}$	2 $\frac{1}{8}$	UPRT.	—	—	C	each	1
5597	Type 3060	1	10	250	500	2 $\frac{1}{8}$	2 $\frac{1}{8}$	1	INVT.	—	—	C	"	1
13972	Type 4591	1	10	250	500	3 $\frac{1}{4}$	2	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
4531	Type 2344	1	10	350	700	3 $\frac{1}{4}$	2 $\frac{1}{8}$	1 $\frac{1}{8}$	INVT.	—	—	C	"	1
16881	Type 5996	1	10	350	1,000	3 $\frac{1}{8}$	3	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
4905	Type 2597	1	10	400	800	3 $\frac{1}{8}$	2 $\frac{3}{8}$	1 $\frac{1}{8}$	UPRT.	—	ZA.1754	C	"	1
5158	Type 2750	1	10	350	700	3	2 $\frac{3}{8}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
2189	Type 1033	1	10	400	1,000	3 $\frac{1}{8}$	2 $\frac{3}{8}$	1 $\frac{1}{8}$	INVT.	—	ZC.10391	C	"	1
2448	Type 1189	1	10	400	1,000	3 $\frac{1}{8}$	2 $\frac{3}{8}$	1 $\frac{1}{8}$	UPRT.	—	ZC.3275	C	"	1
14181	Type 4672	1	10	450	—	4 $\frac{3}{8}$	2 $\frac{1}{2}$	1	—	—	—	C	"	1
2969	Type 1424	1	10	450	1,000	5 $\frac{1}{8}$	2	1 $\frac{1}{8}$	UPRT.	—	ZC.0165	C	"	1
2119	Type 985	1	10	450	1,000	2 $\frac{3}{4}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	UPRT.	—	YB.1922	C	"	1
10937	Type 431	1	10	450	1,000	2 $\frac{3}{4}$	2 $\frac{3}{4}$	1	UPRT.	—	—	C	"	1
14746	Type 4949	1	10	500	—	—	—	—	—	—	—	C	"	1
5639	Type 3064	1	10	500	1,000	3 $\frac{1}{8}$	2 $\frac{3}{8}$	1	UPRT.	—	ZA.1494	C	"	1
655	Type 786	1	10	500	1,000	2 $\frac{1}{8}$	2 $\frac{3}{8}$	1 $\frac{3}{8}$	INVT.	—	—	C	"	1
2687	Type 1291	1	10	600	1,200	3 $\frac{1}{8}$	2 $\frac{3}{8}$	1 $\frac{3}{8}$	INVT.	—	—	C	"	1
2922	Type 1399	1	10	750	2,000	3 $\frac{1}{8}$	3	1 $\frac{3}{8}$	UPRT.	—	—	C	"	1
5480	Type 2981	1	10	1,000	3,000	5 $\frac{7}{8}$	3 $\frac{1}{8}$	1 $\frac{3}{8}$	INVT.	—	—	C	"	1
10048	Type 366	1	10	1,500	—	—	—	—	—	—	—	C	"	1
5524	Type 2987	1	10	1,500	3,000	6 $\frac{1}{8}$	2 $\frac{1}{4}$	2 $\frac{1}{4}$	SIDE	—	—	C	"	1
9011	Type 256	1	10	2,000	4,000	9 $\frac{1}{4}$	4 $\frac{3}{8}$	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
4044	Type 2096	1	10	2,000	5,000	6 $\frac{5}{8}$	4 $\frac{1}{4}$	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
3900	Type 1969	1	10	2,500	6,000	6 $\frac{5}{8}$	3 $\frac{1}{2}$	3	UPRT.	—	—	C	"	1
2336	Type 1126	1	10	3,500	—	6	5	6	—	—	—	C	"	1
3049	Type 1459	1	10	5,000	10 KV	6	8	4	CLMP.	—	ZC.0151	C	"	1
4572	Type 2382	1	15	250	500	3	2 $\frac{1}{4}$	2 $\frac{1}{4}$	UPRT.	W.7436	ZA.17540	C	"	1
14194	Type 4678	1	15	250	—	1 $\frac{3}{4}$	2 $\frac{1}{4}$	2 $\frac{1}{4}$	—	—	—	C	"	1
5244	Type 2836	1	15	400	800	5 $\frac{7}{8}$	3 $\frac{1}{4}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
2813	Type 1316	1	15	450	1,000	2 $\frac{3}{4}$	2 $\frac{1}{2}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
5591	Type 3054	1	15	700	1,400	4 $\frac{3}{8}$	2 $\frac{13}{16}$	$\frac{11}{16}$	INVT.	—	—	C	each	1
2810	Type 1313	1	15	800	1,600	6 $\frac{1}{4}$	3	1	UPRT.	—	—	C	"	1
4997	Type 2687	1	15	1,000	—	—	—	—	—	—	—	C	"	1
801	Type 852	1	15	1,000	2,000	4 $\frac{1}{8}$	2 $\frac{15}{16}$	1 $\frac{39}{32}$	UPRT.	—	—	C	"	1
469	Type 718	1	15	1,000	2,000	3 $\frac{1}{2}$	3 $\frac{1}{2}$	1 $\frac{3}{16}$	UPRT.	—	—	C	"	1
5796	Type 3183	1	15	1,000	3,000	2 $\frac{3}{4}$	2 $\frac{3}{4}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
5692	Type 3117	1	15	1,500	—	—	—	—	—	—	—	C	"	1
17029	Type	1	15	2,000	—	—	—	—	—	—	—	C	"	1
14568	Type 4854	1	15	5,000	10 KV	6	10	4 $\frac{1}{2}$	UPRT.	—	—	C	"	1
12574	Type 4018	1	20	250	—	—	—	—	—	—	—	C	"	1
11189	Type 3392	1	20	250	500	2 $\frac{15}{16}$	2 $\frac{9}{16}$	$\frac{3}{4}$	INVT.	—	—	C	"	1
12634	Type 4029	1	20	600	—	—	—	—	—	—	—	C	"	1
13736	Type 4503	1	20	400	1,000	3	2 $\frac{5}{8}$	1 $\frac{1}{8}$	INVT.	—	—	C	"	1
13047	Type 4196	1	20	600	1,200	3	2 $\frac{5}{8}$	1 $\frac{1}{8}$	INVT.	—	—	C	"	1
12775	Type 4078	1	20	600	1,200	3 $\frac{1}{8}$	2 $\frac{3}{4}$	1	UPRT.	—	—	C	"	1
12567	Type 4012	1	20	600	1,500	3 $\frac{1}{8}$	2 $\frac{3}{4}$	1	INVT.	—	—	C	"	1
4865	Type 2557	1	20	750	1,500	3 $\frac{1}{16}$	3	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
14461	Type 4793	1	20	1,500	3,000	5 $\frac{7}{16}$	3 $\frac{1}{8}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
13274	Type 4291	1	20	1,500	3,000	5 $\frac{7}{16}$	3 $\frac{1}{8}$	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
5337	Type 2887	1	+ Inf.—15	500	1,000	3 $\frac{1}{4}$	2 $\frac{3}{4}$	1	UPRT.	—	—	C	"	1
5183	Type 2775	1	+10—20	750	2,000	3 $\frac{1}{16}$	3	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
2400	Type 1150	1.4	10	250	500	3 $\frac{3}{8}$	1 $\frac{5}{8}$	$\frac{1}{2}$	CLMP.	—	—	C	"	1
10920	Type 428	1.5	10	4,000	10 KV	9 $\frac{1}{4}$	4 $\frac{3}{4}$	1 $\frac{3}{4}$	CLMP.	—	—	C	"	1
13983	Type 4596	1.6	+20—10	1,200	2,400	5 $\frac{5}{8}$	2 $\frac{13}{16}$	1 $\frac{7}{16}$	INVT.	—	—	C	"	1
4617	Type 2408	1.7	+40—15	250	500	2 $\frac{1}{2}$	4 $\frac{1}{4}$	2 $\frac{1}{8}$	SIDE	—	—	C	"	1
14622	Type 4884	1+1	—	250	—	2	1.75	.75	—	—	—	C	"	1
5328	Type 2878	1+1	+25—10	500	—	2 $\frac{3}{8}$	1 $\frac{3}{4}$	1 $\frac{3}{4}$	—	—	—	C	"	1
7391	Type 74	2	10	150	300	2 $\frac{1}{2}$	2	1	CLMP.	—	—	C	"	1
8275	Type 164	2	10	150	300	3 $\frac{1}{16}$	2 $\frac{3}{4}$	1	UPRT.	—	—	C	"	1
2170	Type 1017	2	10	200	400	2 $\frac{3}{4}$	2 $\frac{11}{16}$	1 $\frac{1}{8}$	UPRT.	—	ZC.0593	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
5893	Type 3241	2	10	250	—	—	—	—	—	—	—	C	each	1
2220	Type 1031	2	10	250	500	$2\frac{19}{32}$	$2\frac{1}{8}$	$\frac{3}{4}$	UPRT.	—	—	C	"	1
10343	Type 393	2	10	250	500	$2\frac{1}{8}$	$2\frac{1}{8}$	1	UPRT.	—	—	C	"	1
50	Type 590	2	10	250	500	$2\frac{1}{8}$	$2\frac{1}{8}$	1	UPRT.	—	—	C	"	1
4341	Type 2246	2	10	250	500	$2\frac{3}{4}$	$2\frac{3}{4}$	1	UPRT.	—	—	C	"	1
380	Type 685	2	10	250	500	$2\frac{3}{4}$	$2\frac{3}{4}$	$\frac{7}{8}$	UPRT.	—	—	C	"	1
9382	Type 307	2	10	250	500	3	$2\frac{1}{8}$	1	UPRT.	—	—	C	"	1
288	Type 652	2	10	250	500	$3\frac{5}{32}$	$2\frac{1}{8}$	1	UPRT.	—	—	C	"	1
5892	Type 3240	2	10	250	500	$3\frac{11}{16}$	1	1	INVT.	—	—	C	"	1
3277	Type 1591	2	10	250	500	$3\frac{13}{16}$	$1\frac{5}{8}$	1	UPRT.	—	—	C	"	1
11722	Type 557	2	10	250	500	$2\frac{27}{64}$	$4\frac{3}{8}$	1	CLMP.	—	—	C	"	1
10509	Type 376	2	10	300	600	$2\frac{5}{8}$	3	$1\frac{1}{8}$	UPRT.	—	—	C	"	1
12681	Type 4044	2	10	350	700	$3\frac{15}{16}$	$2\frac{3}{4}$	1	UPRT.	—	—	C	"	1
4904	Type 2596	2	10	350	700	$3\frac{1}{16}$	3	$1\frac{1}{8}$	UPRT.	—	—	C	"	1
560	Type 762	2	10	350	700	$3\frac{13}{16}$	$2\frac{3}{4}$	1	INVT.	—	—	C	"	1
5042	Type 2712	2	10	350	700	$4\frac{7}{16}$	$2\frac{13}{16}$	$1\frac{11}{16}$	INVT.	—	—	C	"	1
4977	Type 2667	2	10	350	800	$2\frac{5}{8}$	$2\frac{3}{4}$	$1\frac{1}{4}$	UPRT.	—	—	C	"	1
10803	Type 479	2	10	400	—	—	—	—	—	—	—	C	"	1
10821	Type 480	2	10	400	—	—	—	—	—	—	—	C	"	1
2193	Type 1037	2	10	400	800	3	3	$1\frac{1}{8}$	SIDE	—	ZC.10521	C	"	1
12003	Type 3715	2	10	400	800	$3\frac{1}{2}$	2	$1\frac{1}{8}$	SIDE	—	—	C	"	1
4029	Type 2081	2	10	400	800	$3\frac{1}{8}$	3	$1\frac{1}{8}$	INVT.	—	ZC.2654	C	"	1
11958	Type 3695	2	10	400	800	$3\frac{1}{8}$	3	$1\frac{1}{8}$	UPRT.	—	—	C	"	1
2970	Type 1425	2	10	450	900	—	—	—	—	—	ZC.01070	C	"	1
2190	Type 1034	2	10	400	1,000	$3\frac{1}{4}$	3	$1\frac{1}{8}$	—	—	ZC.10350	C	"	1
3863	Type 1952	2	10	500	1,000	$3\frac{1}{2}$	2	$1\frac{3}{4}$	CLMP.	—	—	C	"	1
10822	Type 481	2	10	500	1,000	$3\frac{1}{2}$	3	2	UPRT.	—	ZC.1532	C	"	1
10546	Type 419	2	10	750	2,000	$5\frac{7}{16}$	3	$1\frac{1}{4}$	UPRT.	—	ZC.0533	C	"	1
3459	Type 1708	2	10	1,000	2,000	$3\frac{1}{4}$	3	$2\frac{1}{8}$	UPRT.	—	—	C	"	1
3069	Type 1479	2	10	1,000	3,000	$5\frac{7}{16}$	4	$1\frac{1}{4}$	UPRT.	—	ZC.1529	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
3512	Type 1738	2	10	2,000	5,000	6 $\frac{5}{16}$	3 $\frac{1}{2}$	6	UPRT.	—	—	C	each	1
3050	Type 1460	2	10	2,500	5,000	6	4	4	CLMP.	—	—	C	..	1
3462	Type 1709	2	10	4,000	8,000	6 $\frac{1}{4}$	7	4 $\frac{3}{8}$	UPRT.	—	—	C	..	1
3610	Type 1817	2	10	6,000	12 KV	8 $\frac{3}{8}$	4 $\frac{1}{8}$	2 $\frac{3}{4}$	UPRT.	—	—	C	..	1
13913	Type 4570	2	10	12 KV	24 KV	16	25 $\frac{3}{4}$	15 $\frac{1}{8}$	UPRT.	—	—	C	..	1
2239	Type 1057	2	15	100	300	2 $\frac{15}{16}$	2 $\frac{1}{2}$	1 $\frac{3}{4}$	UPRT.	—	—	C	..	1
11268	Type 3433	2	15	250	500	3	2 $\frac{1}{8}$	1	UPRT.	W.2797	—	C	..	1
2792	Type 1334	2	15	250	500	2 $\frac{1}{4}$	2 $\frac{1}{2}$	1	UPRT.	—	—	C	..	1
11493	Type 3504	2	15	250	500	2 $\frac{11}{16}$	2 $\frac{1}{2}$	1 $\frac{3}{4}$	INVT.	—	—	C	..	1
4568	Type 2378	2	15	250	500	3	2 $\frac{1}{8}$	1	INVT.	—	—	C	..	1
5533	Type 2996	2	15	250	500	3 $\frac{1}{4}$	2 $\frac{11}{16}$	1 $\frac{11}{16}$	INVT.	—	—	C	..	1
2257	Type 1072	2	15	350	700	2 $\frac{3}{4}$	2 $\frac{1}{8}$	1	UPRT.	—	—	C	..	1
4510	Type 2336	2	15	400	800	3 $\frac{5}{8}$	2	1 $\frac{1}{8}$	SIDE	—	—	C	..	1
10885	Type 498	2	15	400	1,000	3 $\frac{1}{4}$	3	1 $\frac{1}{8}$	UPRT.	W.2792	ZC/PY. 67154	C	..	1
11494	Type 3505	2	15	400	1,000	2 $\frac{31}{32}$	3	1 $\frac{1}{8}$	INVT.	—	—	C	..	1
15788	Type ZC/15409	2	15	500	1,000	2 $\frac{3}{8}$	2	2	CLMP.	—	ZC.15409	C	..	1
467	Type 716	2	15	500	1,000	3 $\frac{3}{8}$	3	2	UPRT.	—	—	C	..	1
5566	Type 3029	2	15	500	1,000	5 $\frac{3}{8}$	2 $\frac{11}{16}$	1 $\frac{11}{16}$	INVT.	—	—	C	..	1
2322	Type 1112	2	15	800	1,600	5 $\frac{1}{4}$	3 $\frac{1}{4}$	1 $\frac{1}{2}$	UPRT.	—	—	C	..	1
5338	Type 2888	2	15	1,000	2,000	5 $\frac{7}{16}$	3	1 $\frac{1}{4}$	UPRT.	W.5610	—	C	..	1
15004	Type 5071	2	15	3,000	8,000	6 $\frac{7}{16}$	7	4 $\frac{1}{2}$	UPRT.	W.6455	—	C	..	1
13761	Type 4505	2	20	250	500	3	2 $\frac{5}{8}$	1 $\frac{1}{8}$	INVT.	—	—	C	..	1
13960	Type 4585	2	20	250	—	—	—	—	—	—	—	C	..	1
11544	Type 3516	2	20	250	700	3	2 $\frac{1}{2}$	1	UPRT.	—	ZA.21626	C	..	1
12659	Type 4038	2	20	350	700	3 $\frac{1}{4}$	2 $\frac{3}{4}$	1	INVT.	—	—	C	..	1
16697	Type 5872	2	20	400	—	—	—	—	—	—	—	C	..	1
14690	Type 4921	2	20	400	—	—	—	—	—	—	—	C	..	1
5799	Type 3186	2	20	400	800	3 $\frac{1}{8}$	3	1 $\frac{1}{8}$	UPRT.	—	—	C	..	1
16297	Type 5500	2	20	400	1,200	3	2	1 $\frac{1}{8}$	NONE	—	—	C	..	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
13307	Type 4320	2	20	450	900	2 $\frac{15}{16}$	2 $\frac{3}{4}$	3 $\frac{3}{8}$	UPRT.	—	—	C	each	1
12573	Type 4017	2	20	600	1,500	3 $\frac{1}{16}$	3 $\frac{1}{8}$	2 $\frac{1}{8}$	UPRT.	—	—	C	"	1
4824	Type 2555	2	20	750	2,000	5 $\frac{3}{16}$	3	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
13267	Type 4287	2	20	1,000	—	—	—	—	—	—	—	C	"	1
14438	Type 4776	2	20	2,000	4,000	5 $\frac{7}{16}$	3 $\frac{1}{2}$	2 $\frac{1}{8}$	UPRT.	—	ZA.25846	C	"	1
2818	Type 1360	2	—	200	—	—	—	—	—	—	—	C	"	1
11471	Type 3496	2	—	250	—	2-578	1-915	.942	—	—	—	C	"	1
11618	Type 546	2	—	250	—	3 $\frac{3}{16}$	2	3 $\frac{3}{4}$	—	—	—	C	"	1
9180	Type 281	2	+20-10	250	500	3 $\frac{1}{8}$	1 $\frac{1}{2}$	1	SIDE	—	—	C	"	1
5218	Type 2810	2	+Inf.-15	400	1,000	3 $\frac{1}{8}$	3	1 $\frac{1}{8}$	INVT.	—	—	C	"	1
5219	Type 2811	2	+Inf.-15	450	900	3 $\frac{1}{8}$	2 $\frac{3}{4}$	1 $\frac{1}{8}$	INVT.	—	—	C	"	1
5759	Type 3146	2	+Inf.-15	1,000	2,000	2 $\frac{7}{8}$	2 $\frac{3}{4}$	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
11576	Type 3540	2-25	15	2,000	4,000	5 $\frac{11}{16}$	5 $\frac{3}{4}$	2 $\frac{3}{4}$	UPRT.	—	—	C	"	1
12007	Type 3716	3	10	380	760	4 $\frac{7}{8}$	5 $\frac{3}{4}$	2 $\frac{7}{8}$	SIDE	—	—	C	"	1
11215	Type 3418	3-25	10	2,000	4,000	6 $\frac{11}{16}$	4 $\frac{1}{2}$	5 $\frac{3}{4}$	UPRT.	—	—	C	"	1
14202	Type 4683	4	5	600	1,200	2 $\frac{1}{4}$	2	2	UPRT.	—	—	C	"	1
8378	Type 168	4	10	150	300	2 $\frac{1}{4}$	3	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
4555	Type 2365	4	10	250	—	—	—	—	—	—	—	C	"	1
251	Type 641	4	10	250	500	2 $\frac{3}{4}$	3 $\frac{1}{2}$	1 $\frac{1}{8}$	—	—	ZA.11373	C	"	1
979	Type 911	4	10	250	500	5 $\frac{5}{32}$	2 $\frac{1}{2}$	1 $\frac{1}{2}$	INVT.	—	—	C	"	1
11498	Type 3509	4	10	350	700	2 $\frac{15}{32}$	2	1 $\frac{5}{8}$	UPRT.	—	—	C	"	1
12680	Type 4043	4	10	350	700	3 $\frac{1}{8}$	4 $\frac{1}{2}$	1	UPRT.	—	—	C	"	1
9805	Type 338	4	10	400	1,000	3 $\frac{1}{8}$	3	2 $\frac{1}{4}$	UPRT.	—	—	C	"	1
3930	Type 1999	4	10	450	900	4 $\frac{3}{16}$	2 $\frac{3}{4}$	2	INVT.	—	—	C	"	1
3048	Type 1458	4	10	450	900	5 $\frac{1}{16}$	2 $\frac{1}{4}$	1 $\frac{5}{8}$	CLMP.	—	—	C	"	1
567	Type 767	4	10	450	900	5 $\frac{9}{16}$	2 $\frac{1}{2}$	1 $\frac{3}{4}$	CLMP.	—	—	C	"	1
13319	Type 4328	4	10	500	1,000	5 $\frac{1}{8}$	3	2	CLMP.	—	—	C	"	1
5297	Type 2850	4	10	500	1,000	5 $\frac{1}{8}$	3	2	INVT.	—	ZA.2565	C	"	1
2030	Type 940	4	10	600	1,200	5 $\frac{1}{8}$	2	2 $\frac{1}{16}$	CLMP.	—	—	C	"	1
2437	Type 1183	4	10	600	1,200	5 $\frac{9}{16}$	2 $\frac{3}{4}$	2	INVT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom of Qty.	Carton Unit Qty
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
569	Type 769	4	10	700	1,400	5 $\frac{9}{16}$	2 $\frac{3}{4}$	2 $\frac{1}{16}$	CLMP.	—	—	C	each	1
3638	Type 1829	4	10	700	1,600	5 $\frac{3}{16}$	2 $\frac{7}{8}$	2 $\frac{1}{4}$	UPRT.	—	—	C	"	1
3491	Type 1724	4	10	750	1,500	5 $\frac{3}{16}$	3 $\frac{1}{4}$	2	UPRT.	—	—	C	"	1
9608	Type 320	4	10	750	2,000	5 $\frac{1}{2}$	3	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
2162	Type 1009	4	10	750	2,000	5 $\frac{7}{16}$	5	1 $\frac{3}{8}$	UPRT.	—	ZC.0540	C	"	1
2937	Type 1415	4	10	800	1,500	6 $\frac{5}{8}$	3	2 $\frac{1}{16}$	CLMP.	—	—	C	"	1
566	Type 766	4	10	800	1,600	5 $\frac{9}{16}$	4	1 $\frac{13}{16}$	CLMP.	—	—	C	"	1
13675	Type 4483	4	10	1,000	—	—	—	—	INVT.	—	—	C	"	1
13910	Type 4569	4	10	1,000	2,000	5 $\frac{1}{2}$	3	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
2222	Type 1039	4	10	1,000	3,000	5 $\frac{7}{16}$	5 $\frac{3}{4}$	2 $\frac{1}{2}$	UPRT.	—	ZC.10602	C	"	1
2191	Type 1035	4	10	1,000	3,000	5 $\frac{7}{16}$	4	2 $\frac{1}{2}$	INVT.	—	ZC.10480	C	"	1
11004	Type 3313	4	10	1,500	3,000	5 $\frac{1}{2}$	4 $\frac{1}{2}$	3	CLMP.	—	—	C	"	1
2382	Type 1197	4	10	1,500	4,000	5 $\frac{7}{16}$	5 $\frac{1}{4}$	2 $\frac{5}{8}$	UPRT.	—	—	C	"	1
11216	Type 3419	4	10	2,000	4,000	6	5 $\frac{1}{4}$	2 $\frac{3}{4}$	UPRT.	—	—	C	"	1
10828	Type 509	4	10	2,000	5,000	6 $\frac{5}{16}$	5 $\frac{1}{2}$	6	UPRT.	—	—	C	"	1
9385	Type 310	4	10	4,000	8,000	8 $\frac{1}{4}$	9 $\frac{1}{2}$	9 $\frac{1}{8}$	UPRT.	—	—	C	"	1
2240	Type 1058	4	15	100	200	2 $\frac{7}{8}$	2 $\frac{1}{8}$	1	UPRT.	—	—	C	"	1
10825	Type 484	4	15	250	500	3	2 $\frac{1}{2}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
5567	Type 3030	4	15	250	500	3 $\frac{1}{8}$	2 $\frac{13}{16}$	1 $\frac{7}{16}$	INVT.	—	—	C	"	1
2809	Type 1312	4	15	250	500	2 $\frac{3}{8}$	2 $\frac{1}{2}$	1 $\frac{1}{8}$	UPRT.	—	—	C	"	1
3641	Type 1832	4	15	250	500	5 $\frac{3}{32}$	2 $\frac{1}{2}$	1 $\frac{3}{4}$	INVT.	—	—	C	"	1
3608	Type 1815	4	15	400	800	5 $\frac{1}{4}$	2 $\frac{3}{4}$	1 $\frac{3}{8}$	UPRT.	—	ZA.24245	C	"	1
5147	Type 2739	4	15	400	1,000	3 $\frac{1}{8}$	3	2 $\frac{1}{4}$	UPRT.	4060	—	C	"	1
3121	Type 1516	4	15	450	900	2 $\frac{15}{16}$	3	2 $\frac{1}{4}$	INVT.	—	—	C	"	1
5890	Type 3238	4	15	500	1,000	5 $\frac{1}{8}$	2	1 $\frac{5}{8}$	CLMP.	—	—	C	"	1
4535	Type 2348	4	15	800	1,600	5 $\frac{5}{8}$	2 $\frac{13}{16}$	2 $\frac{3}{16}$	INVT.	—	—	C	"	1
13502	Type 4418	4	15	1,000	2,000	5 $\frac{7}{8}$	4 $\frac{1}{2}$	1 $\frac{3}{4}$	UPRT.	W.638	ZA.11472	C	"	1
12946	Type 4138	4	20	250	700	3	2 $\frac{3}{4}$	1 $\frac{3}{4}$	UPRT.	—	—	C	"	1
13063	Type 4207	4	20	350	700	2 $\frac{15}{16}$	2 $\frac{1}{4}$	2 $\frac{1}{4}$	UPRT.	—	—	C	"	1
12776	Type 4079	4	20	400	1,000	3 $\frac{1}{8}$	3	2 $\frac{1}{4}$	UPRT.	—	ZA.8616	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (Ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
13264	Type 4284	4	20	400	1,000	3 $\frac{1}{2}$	3	2 $\frac{1}{2}$	INVT.	—	—	C	each	1
13192	Type 4250	4	20	400	1,000	4 $\frac{1}{2}$	1 $\frac{3}{4}$	1 $\frac{3}{4}$	INVT.	—	—	C	"	1
4527	Type 2340	4	20	450	—	—	—	—	—	—	—	C	"	1
12572	Type 4016	4	20	600	—	—	—	—	—	—	—	C	"	1
13734	Type 4501	4	20	600	1,200	4 $\frac{5}{8}$	1 $\frac{3}{4}$	1 $\frac{7}{8}$	INVT.	—	—	C	"	1
13179	Type 4241	4	20	800	2,000	5	2 $\frac{1}{8}$	3	UPRT.	—	—	C	"	1
13093	Type 4222	4	20	1,000	2,000	5 $\frac{7}{16}$	5	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
13273	Type 4290	4	20	1,000	3,000	5 $\frac{7}{16}$	4	2 $\frac{5}{8}$	UPRT.	—	—	C	"	1
13676	Type 4484	4	20	1,000	3,000	5 $\frac{1}{2}$	5	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
13864	Type 4551	4	20	1,500	3,000	5 $\frac{3}{8}$	4	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
14249	Type 4701	4	20	1,500	3,000	5 $\frac{7}{16}$	5 $\frac{3}{4}$	2 $\frac{5}{8}$	NONE	—	—	C	"	1
12847	Type 4095	4	20	1,500	4,000	5 $\frac{7}{16}$	5 $\frac{1}{2}$	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
13915	Type 4572	4	20	2,000	4,000	6 $\frac{1}{4}$	5 $\frac{1}{2}$	6 $\frac{1}{8}$	UPRT.	—	—	C	"	1
5758	Type 3145	4	+0—15	450	900	2 $\frac{7}{8}$	2 $\frac{7}{8}$	2 $\frac{1}{4}$	UPRT.	—	ZA.22619	C	"	1
10829	Type 510	4	—	3,000	—	—	—	—	—	—	—	C	"	1
17508	Type 6066	5	15	500	—	4 $\frac{3}{4}$	2	1 $\frac{1}{2}$	—	—	—	C	"	1
11415	Type 3482	5	10	500	1,000	5 $\frac{7}{8}$	4 $\frac{1}{2}$	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
10766	Type 475	6	10	250	—	—	—	—	—	—	—	C	"	1
10887	Type 500	6	10	400	—	—	—	—	—	—	—	C	"	1
2090	Type 977	6	10	600	1,500	4 $\frac{5}{8}$	3	3	UPRT.	—	—	C	"	1
4028	Type 2080	6	10	750	2,000	5 $\frac{7}{16}$	5	1 $\frac{7}{8}$	UPRT.	—	ZA.17051	C	"	1
4027	Type 2079	6	10	1,500	4,000	5 $\frac{15}{16}$	5 $\frac{3}{4}$	3 $\frac{7}{8}$	UPRT.	—	—	C	"	1
13873	Type 4553	6	20	350	700	3 $\frac{1}{16}$	3	2 $\frac{3}{8}$	UPRT.	—	—	C	"	1
14739	Type 4945	6	20	1,500	—	4 $\frac{3}{4}$	3 $\frac{3}{4}$	3	—	—	—	C	"	1
4900	Type 2592	8	10	250	700	5 $\frac{1}{8}$	2 $\frac{1}{2}$	2 $\frac{5}{8}$	UPRT.	—	ZA.1481	C	"	1
5769	Type 3156	8	10	250	—	3·25	1·625	3·187	—	—	—	C	"	1
2161	Type 1008	8	10	350	700	2 $\frac{13}{16}$	4	2	UPRT.	—	—	C	"	1
2326	Type 1116	8	10	400	800	5 $\frac{1}{4}$	3	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
9806	Type 339	8	10	400	1,000	5 $\frac{3}{8}$	2 $\frac{1}{2}$	3	UPRT.	—	ZA.1539	C	"	1
5559	Type 3022	8	10	450	900	5	2 $\frac{5}{8}$	3 $\frac{3}{4}$	UPRT.	—	—	C	"	1

SECTION 100—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
15712	Type	8	10	565	1,500	5 $\frac{13}{16}$	3 $\frac{7}{8}$	2	CLMP.	—	YB.03482	C	each	1
5665	Type 3090	8	10	600	1,500	5 $\frac{1}{8}$	3	4	UPRT.	—	—	C	"	1
8639	Type 208	8	10	700	2,000	2 $\frac{13}{16}$	5 $\frac{1}{2}$	4 $\frac{1}{2}$	UPRT.	—	—	C	"	1
3513	Type 1739	8	10	750	2,000	5 $\frac{7}{16}$	5	2 $\frac{3}{8}$	UPRT.	—	ZA.1480	C	"	1
2614	Type 1238	8	10	750	2,000	5 $\frac{7}{16}$	5	2 $\frac{3}{8}$	UPRT.	—	—	C	"	1
2331	Type 1121	8	10	100	1,600	5 $\frac{7}{16}$	5	3	UPRT.	—	—	C	"	1
12608	Type 4022	8	10	1,000	2,000	5 $\frac{1}{16}$	4 $\frac{1}{2}$	2	UPRT.	—	—	C	"	1
3698	Type 1873	8	10	1,000	3,000	5 $\frac{13}{16}$	6	3	UPRT.	—	ZA.21028	C	"	1
11934	Type 3676	8	10	2,000	5,000	6 $\frac{7}{16}$	7 $\frac{1}{2}$	8 $\frac{1}{2}$	UPRT.	—	ZA.1479	C	"	1
		(2+2+2+2)												
11078	Type 505	8	15	25	—	—	—	—	—	—	—	C	"	1
13973	Type 4592	8	15	1,000	2,000	5 $\frac{3}{8}$	4 $\frac{1}{2}$	3 $\frac{1}{4}$	INVT.	—	—	C	"	1
13271	Type 4288	8	20	600	—	—	—	—	—	—	—	C	"	1
14923	Type 5035	8	15	1,200	—	—	—	—	—	—	—	C	"	1
14712	Type 4936	8	20	1,000	—	—	—	—	—	—	—	C	"	1
4895	Type 2587	10	5	2,500	5,000	7	3	1 $\frac{1}{2}$	UPRT.	—	—	C	"	1
10051	Type 369	10	10	250	700	5 $\frac{3}{16}$	2 $\frac{1}{2}$	3 $\frac{1}{4}$	UPRT.	—	ZA.13415	C	"	1
3416	Type 1677	10	10	400	800	5 $\frac{1}{8}$	3	2 $\frac{1}{4}$	UPRT.	—	—	C	"	1
9807	Type 340	10	10	400	800	5 $\frac{3}{8}$	3 $\frac{1}{4}$	3	UPRT.	—	ZA.22930	C	"	1
2224	Type 1041	10	10	400	1,000	5 $\frac{3}{8}$	3 $\frac{1}{4}$	3	UPRT.	—	ZC.10603	C	"	1
2165	Type 1012	10	10	1,000	2,000	5 $\frac{3}{8}$	5	4 $\frac{1}{2}$	UPRT.	—	ZC.0510	C	"	1
2194	Type 1038	10	10	400	1,000	5 $\frac{1}{4}$	3 $\frac{1}{4}$	3	INVT.	—	ZC.7276	C	"	1
10827	Type 486	10	10	600	1,500	5 $\frac{1}{4}$	3	5	UPRT.	—	—	C	"	1
10832	Type 490	10	10	750	2,000	5 $\frac{7}{16}$	5	2 $\frac{3}{4}$	UPRT.	—	ZC.0534	C	"	1
2622	Type 1246	10	10	1,000	3,000	5 $\frac{13}{16}$	7 $\frac{1}{4}$	6 $\frac{1}{4}$	UPRT.	—	ZC.1527	C	"	1
2323	Type 1113	10	15	800	2,000	6 $\frac{1}{4}$	5	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
277	Type 647	10	15	250	500	2 $\frac{11}{16}$	1 $\frac{3}{4}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
276	Type 646	10	15	250	500	2 $\frac{1}{16}$	3 $\frac{1}{4}$	3	UPRT.	—	—	C	"	1
12848	Type 4096	10	20	400	1,000	5 $\frac{3}{8}$	3 $\frac{1}{4}$	3	UPRT.	—	—	C	"	1
14144	Type 4654	10	20	600	1,200	5 $\frac{3}{16}$	3	5 $\frac{1}{4}$	UPRT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont. Rectangular—cont. 1 mfd. and upwards—cont.													
13974	Type 4593	10	20	1,000	2,000	4 $\frac{1}{2}$	4 $\frac{1}{8}$	4	INVT.	—	—	C	each	1
13992	Type 4600	10	20	1,500	3,000	5 $\frac{1}{2}$	4 $\frac{7}{8}$	6 $\frac{3}{4}$	UPRT.	—	—	C	"	1
14431	Type 4769	20	+5-15	1,000	2,500	6 $\frac{1}{2}$	8 $\frac{1}{8}$	5 $\frac{1}{4}$	—	—	—	C	"	1
5805	Type 3192	(10+10) 100	10	150	300	6 $\frac{5}{8}$	4 $\frac{7}{8}$	6	UPRT.	—	—	C	"	1
3953	Type 202201+.01 .01+.01	10	500	1,000	$\frac{3}{4}$	2 $\frac{1}{2}$	1	SIDE	W.7059	—	C	"	1
883	Type 86901+.01 + .01	15	600	1,200	3 $\frac{1}{4}$	1 $\frac{1}{16}$	1 $\frac{1}{2}$	INVT.	—	—	C	"	1
2712	Type 130505+.05	10	7,000 + 5,000	14 KV 10 KV	9	4	2	CLMP.	—	—	C	"	1
696	Type 80005+.1	10	5,000 + 3,000	10 KV 6 KV	7 $\frac{1}{4}$	4	3	CLMP.	—	—	C	"	1
17011	Type1+.1	10	600	1,250	1 $\frac{1}{8}$	2 $\frac{1}{2}$	1	UPRT.	—	ZA.11349	C	"	1
695	Type 7991+.1	10	2,000	4,000	4 $\frac{1}{2}$	2	1 $\frac{7}{8}$	CLMP.	—	—	C	"	1
941	Type 8861+.1	10	8,000	16 KV	8 $\frac{1}{4}$	5	5	CLMP.	—	—	C	"	1
2634	Type 125625 +1.8 +1.0 +1.0	10 10 20 20	124 70 500 500	—	3 $\frac{5}{16}$	4 $\frac{1}{8}$	2 $\frac{1}{4}$	SIDE	—	—	C	"	1
2046	Type 95125+.25	10	4,000	8,000	6 $\frac{1}{4}$	5	2	CLMP.	—	—	C	"	1
12697	Type 405625+.25	15	9,000	18 KV	7 $\frac{3}{8}$	6 $\frac{1}{2}$	3 $\frac{1}{2}$	UPRT.	—	—	C	"	1
2053	Type 95525+ .5	10	1,500 250	3,000 500	2 $\frac{15}{16}$	2	2 $\frac{1}{2}$	UPRT.	—	—	C	"	1
9223	Type 2915+.5	10	150	300	2 $\frac{3}{4}$	2 $\frac{3}{4}$	1	UPRT.	—	—	C	"	1
5525	Type 29885+.5	10	500	1,000	2 $\frac{15}{16}$	1 $\frac{1}{8}$	1	CLMP.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
13050	Type 41985+.5	10	1,500	3,000	5 $\frac{3}{16}$	3 $\frac{1}{2}$	1 $\frac{1}{4}$	UPRT.	—	—	C	each	1
11281	Type 34455+.5	10	4,400	8,800	5 $\frac{1}{2}$	5 $\frac{1}{8}$	2 $\frac{1}{2}$	CLMP.	—	—	C	"	1
2389	Type 15565+.5 +1.0	10	3,500	7,000	4 $\frac{1}{8}$	5 $\frac{3}{4}$	10	UPRT.	—	—	C	"	1
4616	Type 24075+.5	+40-5	100	200	7 $\frac{5}{8}$	2 $\frac{3}{8}$	2 $\frac{3}{8}$	SIDE	—	—	C	"	1
3869	Type 1958	1+1	10	250	500	2 $\frac{15}{16}$	2 $\frac{3}{4}$	2 $\frac{3}{8}$	CLMP.	—	—	C	"	1
2564	Type 1211	1+1	10	450	1,000	3 $\frac{7}{8}$	2	1 $\frac{1}{4}$	SIDE	—	—	C	"	1
2563	Type 1210	1+1	10	450	1,100	3 $\frac{1}{2}$	2	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
2047	Type 952	1+1	10	1,000	2,000	5 $\frac{1}{16}$	2 $\frac{1}{4}$	1 $\frac{5}{8}$	CLMP.	—	—	C	"	1
11459	Type 3488	1+1	20	500	1,000	3 $\frac{11}{16}$	2	2	SIDE	—	—	C	"	1
4615	Type 2406	1+1	+40-5	100	200	2 $\frac{15}{16}$	2 $\frac{3}{8}$	1 $\frac{1}{4}$	UPRT.	—	—	C	"	1
710	Type 806	2+1	10	350	600	3 $\frac{3}{16}$	2 $\frac{1}{8}$	2	CLMP.	—	—	C	"	1
715	Type 811	2+1	10	600	1,200	3 $\frac{15}{16}$	2 $\frac{1}{8}$	2	CLMP.	—	—	C	"	1
3719	Type 1894	2+2	10	250	500	3 $\frac{5}{16}$	3 $\frac{1}{4}$	1 $\frac{1}{2}$	CLMP.	—	—	C	"	1
4618	Type 2409	2+ 4	+40-5	250 400	500 800	2 $\frac{15}{16}$	3 $\frac{1}{4}$	3	UPRT.	—	—	C	"	1
2332	Type 1122	2+ 4	10 30	800	1,600	4	5	3	UPRT.	—	—	C	"	1
11575	Type 3559	2.25+ 2.25	15	3,000	6,000	6 $\frac{5}{16}$	10 $\frac{1}{2}$	7	UPRT.	—	—	C	"	1
962	Type 894	2.5+2.5 +1.0	15	300	400	2	1 $\frac{3}{4}$	2 $\frac{7}{8}$	SIDE	—	—	C	"	1
960	Type 892	2.5+2.5 +1.0	15	200	400	2 $\frac{3}{4}$	1 $\frac{3}{4}$	2 $\frac{1}{8}$	UPRT.	—	—	C	"	1
2696	Type 1295	4+2	10	350	700	3 $\frac{1}{8}$	3	3 $\frac{1}{4}$	INVT.	—	—	C	"	1
11577	Type 3541	4+2	10	3,000	9,000	7 $\frac{3}{4}$	10 $\frac{1}{4}$	12	UPRT.	—	—	C	"	1
2381	Type 1196	4+4	10	2,000	4,000	6 $\frac{9}{16}$	10 $\frac{1}{2}$	7	UPRT.	—	—	C	"	1
2380	Type 1195	4+4	10	3,000	9,000	6 $\frac{9}{16}$	10 $\frac{1}{2}$	7	UPRT.	—	—	C	"	1
2383	Type 1198	4+4	10	4,500	11 $\frac{1}{4}$ KV	6 $\frac{11}{16}$	10 $\frac{1}{4}$	12	UPRT.	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont.													
	Rectangular—cont.													
	1 mfd. and upwards—cont.													
4263	Type 2207	8+4	15	{ 350 500	{ 700 1,000	5½	3¼	2	INVT.	—	WY.1846	C	each	1
4932	Type 2622	8+4	20	{ 500 350	{ 1,000 700	4½	4½	2⅞	UPRT.	—	—	C	"	1
	Steel or other case:—													
2795	Type 1337003	—	3,500	—	—	—	—	—	—	—	C	"	1
17049	Type ZA.208081	20	7,000	12 KV	4	2⅜	3⅝	—	—	ZA.20808	C	"	1
2329	Type 1119125	15	1,600	—	—	—	—	—	—	—	C	"	1
17747	Type 617825 + .25	20	3.5KV	—	2½	5½	6	—	—	—	C	"	1
17610	Type 61305	10	250	500	—	—	—	—	—	—	C	"	1
3588	Type 18025	10	375	—	—	—	—	—	—	—	C	"	1
2320	Type 11105	10	10 KV	—	4	2½	3	—	—	—	C	"	1
16817	Type 59645	—	7,500	—	—	—	—	—	—	—	C	"	1
2379	Type 11945	+20-5	25 KV	51 KV	15⅞	15⅞	16	UPRT.	—	—	C	"	1
13677	Type 44858	15	36 KV	72 KV	27	23	15	UPRT.	—	—	C	"	1
2317	Type 1107	1	10	3,000	—	—	—	—	—	—	—	C	"	1
17579	Type 6103	1	10	7,500	—	5½	—	—	—	—	—	C	"	1
11371	Type 523	2	—	—	—	—	—	—	—	—	—	C	"	1
5426	Type 2928	2	10	350	—	—	—	—	—	—	—	C	"	1
2321	Type 1111	2	15	18KV	36 KV	19⅞	14⅞	14⅞	UPRT.	—	—	C	"	1
16204	Type 5442	2	20	500	—	4⅜	1½ dia.	—	—	—	—	C	"	1
3111	Type 1511	2.25	+20-5	25 KV	51 KV	15½	36¼	29	UPRT.	—	ZC.1526	C	"	1
17578	Type 6102	4	10	7,500	—	—	—	—	—	—	—	C	"	1
15222	Type 5202	4	20	400	—	3½	5¼	1⅞	—	—	—	C	"	1
3209	Type 1563	5	15	250	—	—	—	—	—	—	—	C	"	1
14164	Type 4667	6	15	150	—	—	—	—	—	—	—	C	"	1
10534	Type 418	8	—	350	—	—	—	—	—	—	—	C	"	1

SECTION 10C—cont.

RADIO FIXED CAPACITORS

Ref. No.	NOMENCLATURE	Capacity mfd.	Tolerance ± %	VOLTAGE		OVERALL DIMENSIONS (ins.)			Mounting	Naval Ref.	Army Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
				Working	Test	Height	Width	Depth						
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
	PAPER DIELECTRIC—cont. Rectangular—cont. Other Types:—													
14573	Type 4859	0.15+ 0.05	20	7 K	—	—	—	—				C	each	1
17617	Type 6133045+ .045+ .045	10	3,500	—	8+2 terminal s	9 $\frac{3}{4}$	7 $\frac{3}{4}$				C	„	1
17580	Type 6104	Sub- divided .2 mfd. .05 mf. .01 mf. .005 mf.	—	4,500	—	25 $\frac{1}{4}$	—	—				C	„	1
14924	Type 5036	2	10	6,000	—	13	12 $\frac{1}{2}$	5 $\frac{1}{2}$				C	„	1
17990	Type 6285	2	10	10K	—	6	19	13 $\frac{1}{2}$				C	„	1
11289	Type 3543	2.25	20	25 K	—	15 $\frac{1}{2}$	28 $\frac{3}{4}$	36 $\frac{1}{4}$				C	„	1
									Other Details:—					
									Oil immersed					
									Oil immersed, sub-divided					
									Petroleum jelly impregnated. Welded steel case. End terminals and side handles With 2 carrying handles. Porcelain insulated $\frac{1}{8}$ in. Whit. terminals, metal case 84 lbs. On four wheels 2 in. dia. Tropicalised					

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
15810	BRUSHES	Copper carbon, $\frac{15}{16}$ in. \times $\frac{5}{8}$ in. \times $\frac{9}{16}$ in.		C	each	10
3342	CAPACITORS:— Type 100001 to .00005 mfd. Single vane, adjustable, mica dielectric, mounted on square base.	ZA. 3155/89	C	..	1
3403	Type 3	20 mfd.		C	..	1
5954	Type 4000024 to 0003 mfd. \pm 5 per cent. Variable, air dielectric, vernier adjustment dial engraved "0-210". With remote control attachment.		A	..	1
2951	Type 7	1 jar, variable, air (or oil) dielectric, with glass container, handle, pointer, engraved scale, and shorting switch.		A	..	1
3486	Type 800015 mfd. Fixed capacity, mica dielectric, clamped, with 2 clips for $1\frac{3}{4}$ in. grid leak.		C	..	1
5302	Type 43	0.5 mfd. Paper dielectric, in waxed filled metal case, with soldering tabs. 300 volts D.C. test.		C	..	1
7203	Type 540003 mfd. Variable air dielectric.		A	..	1
7249	Type 590008-.0013 μ F. With fine tuning lever and magnifying lens.		A	..	1
7469	Type 800005 mfd. Variable, air dielectric, without knob and dial.		A	..	1
7594	Type 860003 mfd. Variable, air dielectric, without handle.		A	..	1
7762	Type 1070001 mfd. Fixed, mica dielectric, with disc clamps. 5 amps. at 5,000 kc/s. test.		C	..	1
7853	Type 111125 mfd. Fixed, 28,000 volts test.		C	..	1
7895	Type 1185 mfd. Paper dielectric, in waxed filled metal case. 2,500 volts D.C. test.		C	..	1
7904	Type 12300005 mfd. Variable, air dielectric.		A	..	1
7905	Type 1240002 mfd. Variable, air dielectric, slow motion.		A	..	1
8116	Type 14700025 mfd. Fixed, mica dielectric, clamped 1,000 volts megger test.		C	..	1
8140	Type 149002 mfd. Fixed, mica dielectric, clamped.		C	..	1
8162	Type 150	80 pfd. Variable air		A	..	1
8166	Type 1540003 mfd. Mica dielectric, clamped.		C	..	1
8167	Type 155000192 mfd. Bank of 6 units with square micas and disc clamps.	C	..	1	
8168	Type 15600103 mfd. Bank of 10 units with square micas and disc clamps.	C	..	1	
8169	Type 1570002 mfd. Bank of 2 units with square micas and disc clamps.	C	..	1	
8171	Type 159000032 mfd. With square micas and disc clamps.	C	..	1	
8172	Type 160000106 mfd. With square micas and disc clamps.	C	..	1	

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
8206	Type 162 ...	·000212 mfd. 2 units with square micas and disc clamps.		C	each	1
8286	Type 166 ...	8 mfd. Paper dielectric, wax filled metal case. 400 volts D.C. test.		C	..	1
8380	Type 170 ...	·00001 mfd. Variable, air dielectric.		A	..	1
8381	Type 171 ...	·0005 mfd. Variable, air dielectric.		A	..	1
8484	Type 174 ...	·00025 mfd. Pre-set type ...		C	..	1
8387	Type 177 ...	·00001 mfd. Mica dielectric, clip in type.		C	..	1
8487	Type 179 ...	250 pfd. Circular plates ...		C	..	1
8490	Type 182 ...	·0003 mfd. Variable, air dielectric, without handle.		A	..	1
8561	Type 201 ...	·0003 mfd. With handle, Variable.		A	..	1
8566	Type 204 ...	·00025 mfd. Pre-set type. (Modification of T.174.)		C	..	1
8637	Type 206 ...	2 mfd. Metal case, 5,000 volts D.C. working.		C	..	1
8720	Type 218 ...	·00083 mfd. Maximum. Variable air dielectric. With double set of vanes.		A	..	1
8672	Type 221 ...	1 mfd. Cylindrical, paper dielectric, non-inductive. 450 volts working.		C	..	1
8804	Type 230 ...	·0005 mfd. Variable, air dielectric. Without knob and dial.		A	..	1
9145	Type 261 ...	·000415 mfd. Mica dielectric ...		C	..	1
9151	Type 263 ...	·00085 mfd. Maximum. Variable, air dielectric.		A	..	1
9152	Type 264 ...	·0001 mfd. Maximum. Variable, air dielectric.		A	..	1
2227	Spindles extension		C	..	1
9318	Type 265 ...	·000135 mfd. Mica dielectric ...		C	..	1
9300	Type 277 ...	·5 mfd. Paper dielectric in wax-filled metal case.		C	..	1
9182	Type 283 ...	Miniature, variable, with screw adjustment.		A	..	1
9197	Type 287 ...	·000048 mfd. Variable, 3 gang, air dielectric.		A	..	1
9198	Type 288 ...	12 pfd. min. to 233 pfd. max. variable air, complete with drive.		A	..	1
9186	Type 292 ...	2 mfd. Paper dielectric, in metal case.		C	..	1
9346	Type 297 ...	30–60 μ F. Variable air. With handle.		A	..	1
9907	Type 335 ...	1 mfd. 16,000 volts D.C. test. Metal case.		C	..	1
10082	Type 371 ...	·5 mfd. Metal case. 1,500 volts working.		C	..	1
10513	Type 380 ...	·00025 mfd. Variable, air. Series plate with shorting switch.		A	..	1
10317	Type 391 ...	·0005 mfd. Variable, air ...		A	..	1
10344	Type 394 ...	·0001 mfd. Variable, air ...		A	..	1
10390	Type 400 ...	250 pfd. 1,250 volts D.C. test. Variable, air.		A	..	1
10460	Type 407 ...	10 + 6 + 4 mfd. Electrolytic block in cardboard case, 30 volts.		C	..	1
10461	Type 408 ...	25 mfd. Electrolytic. Metal case.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
10476	Type 411 ...	30 pfd. ...		—	each	—
10230	Type 413 ...	3-17 pfd. Variable, air, trimming capacitor.		A	„	1
10226	Type 415 ...	·0005 mfd. Variable, air ...		A	„	1
10227	Type 416 ...	3-35 pfd. Variable, air, trimming capacitor.		A	„	1
10938	Type 432 ...	100 pfd. Variable, air, dielectric, trimmer.		A	„	1
10644	Type 442 ...	·0003 mfd. ...		C	„	1
10646	Type 444		C	„	1
10647	Type 445 ...	20 pfd. ...		C	„	1
10648	Type 446 ...	40 pfd. ...		C	„	1
10651	Type 449 ...	·1 mfd. ...		C	„	1
10655	Type 450 ...	·001 mfd....		C	„	1
10656	Type 451 ...	·01 mfd. ...		C	„	1
10743	Type 457 ...	300 pfd. ...		C	„	1
10752	Type 461		A	„	1
10753	Type 462		A	„	1
10883	Type 496 ...	·1 mfd. ...		C	„	1
11305	Type 513 ...	60 mfd. 25 volts working, electrolytic.		C	„	1
11364	Type 516 ...	50 pfd. Variable. Pre-set trimmer.		A	„	1
11455	Type 527 ...	65 pfd. Variable, air ...		A	„	1
11588	Type 544 ...	Variable, series gap ...		A	„	1
3628	Type 545 ...	Min. not more than 1·3 mfd. Max. between 4·5, and 7·6 pfd. Trimmer ceramic.		A	„	1
11693	Type 547 ...	·001 mfd. Silvered mica, moulded.		C	„	1
21	Type 577 ...	50 mfd. 2 volts D.C. Electrolytic.		C	„	1
84	Type 598 ...	2 gang air variable. 6 pfd. min. 30 pfd. swing; ceramic base.		A	„	1
83	Type 599 ...	2 gang air variable. 5·5 pfd. swing; ceramic base.		A	„	1
90	Type 605 ...	3-65 pfd. air variable ...		A	„	1
233	Type 630 ...	5 mfd. ± 2 mfd., ceramic disc		C	„	1
234	Type 631 ...	40 pfd. ...		C	„	1
247	Type 638 ...	2 mfd. Without fixing lugs ...		C	„	1
275	Type 645 ...	2·5 mfd., paper dielectric in metal case, 500 volts working, without fixing feet.		C	„	1
279	Type 649 ...	2·5 mfd., paper dielectric in metal case, 500 volts working, with fixing lugs.		C	„	1
302	Type 654 ...	20 mmF. Variable air, Ceramic		A	„	1
312	Type 658 ...	4 mfd. 750 volts D.C. test, dry electrolytic.		C	„	1
339	Type 665 ...	4 mfd. electrolytic ...		C	„	1
344	Type 667 ...	14 pfd. min. to 350 pfd. max.; length of spindle 0·74 in., with tapped hole.		A	„	1
369	Type 674 ...	Vernier capacitor (slow motion)		A	„	1
372	Type 677 ...	·1 mfd., paper capacitor ...		C	„	1
374	Type 679 ...	23½-30 pfd., variable ...		A	„	1
392	Type 689 ...	·001 pfd. ...		C	„	1
399	Type 696 ...	18 pfd., variable ...		A	„	1
477	Type 726 ...	·5 mfd., 4,000 volts working ...		C	„	1
497	Type 735 ...	·003 mfd., mica moulded ...		C	„	1
543	Type 757 ...	20 pfd., variable, air dielectric, ¾ in. spindle.		A	„	1
609	Type 774 ...	4 mfd., 150 volts D.C. working. 1½ in. dia., tubular.		C	„	1
730	Type 816 ...	Ceramic trimmer ...		A	„	—

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	GAPACITORS —cont.					
731	Type 817 ...	2-30 pfd., variable ...		A	each	1
735	Type 821 ...	1,000 μF . \pm 5 per cent., 500 volts working, ceramic, tubular, negative, temperature co-efficient, end wires.		C	"	1
746	Type 8325 mfd. \pm 15 per cent., tubular, paper, 350 volts working.		C	"	1
769	Type 833 ...	100 + 100 pfd. \pm 10 per cent., special short wave, variable air dielectric, left hand.		A	"	1
770	Type 834 ...	As Type 833, but right hand		A	"	1
843	Type 856 ...	16 mfd., electrolytic, 450 volts...		C	"	1
872	Type 866 ...	130 pfd., 2 gan... ..		A	"	1
894	Type 873 ...	100 + 100 pfd. \pm 5 per cent., split stator, variable air dielectric.		A	"	1
915	Type 878 ...	60 pfd. variable air dielectric, tag connections. Rotor tag spaced 90° from stator tag.		A	"	1
916	Type 879 ...	60 pfd., variable air dielectric, tag connections. Rotor tag spaced 90° from stator tag.		A	"	1
917	Type 8800001 mfd., variable air dielectric, tag connections. Rotor tag spaced 90° from stator tag.		A	"	1
968	Type 900 ...	75 pfd., variable air trimmer ...		A	"	1
974	Type 906 ...	7-100 pfd., ceramic trimmer, centre adjusting screw.		A	"	1
975	Type 907 ...	40-4 μF ., variable air. Ceramic base. H.F. trimmer.		A	"	1
976	Type 908 ...	5-40 pfd. Ceramic trimmer, with tag connections.		A	"	1
2018	Type 94200001 mfd. \pm 10 per cent., fixed air, double spaced.		C	"	1
2069	Type 959 ...	3-18 pfd.		A	"	1
2071	Type 961 ...	3-18 pfd.		A	"	1
2082	Type 972 ...	1.5 pfd., variable		A	"	1
2086	Type 976 ...	6 pfd. \pm 10 per cent., fixed air, double spaced.		C	"	1
2103	Type 979 ...	15 pfd. to 0.000197 mfd., 4 gang dielectric.		A	"	1
2223	Type 1040	.1 mfd., 450 volts, block metal case.		C	"	1
2282	Type 1088	.0005 mfd., variable		A	"	1
2283	Type 1089	.0001 mfd., variable air dielectric.		A	"	1
2318	Type 1108	.004 mfd. mica, in copper flanged case, 2 $\frac{3}{4}$ in. dia. \times 1 $\frac{1}{16}$ in., with 4 hole fixings.		C	"	1
2319	Type 1109	Inverted vacuum		C	"	1
2328	Type 1118	Bushing type, 36 KV. D.C. ...		C	"	1
2334	Type 1124	2 mfd., 2,000 volts D.C. + 30 per cent., 100 cycles ripple working.		C	"	1
2337	Type 1127	.001 mfd., 500 volts D.C. Mica. Porcelain case.		C	"	1
2352	Type 1141	.2 mfd., 4,000 volts D.C. working		C	"	1
2353	Type 1142	50 mfd., 50 volts D.C. working		C	"	1
2414	Type 1163	3.8-50 pfd. Variable air, $\frac{1}{4}$ in. spindle.		A	"	1
2387	Type 1202	.001 mfd. (approx.)		C	"	1
2560	Type 1207	10-65 pfd. trimmer		A	"	1
2572	Type 1217	Tuning air dielectric, 2 sections		A	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
2574	Type 1220 ...	28 pfd. max. air, variable, ceramic insulation, metal frame. Spindle $\frac{1}{4}$ in. dia. \times .546 in.		A	each	1
2575	Type 1221 ...	Variable, twin section ...		A	..	1
2579	Type 1224 ...	5 mfd., 200 volts, tubular, with terminal sleeved wires sweated to ends, without sleeves.		C	..	1
2610	Type 1234		C	..	1
2615	Type 123901 mfd. ...		C	..	1
2617	Type 1241 ...	1 μ F. ...		C	..	1
2638	Type 1260		C	..	1
2676	Type 1280 ...	2 \times 15 pfd., — 45 pfd., trimmer, ceramic.		A	..	1
2684	Type 12881 + .1 μ F., 10 per cent, 3,000 volts, D.C. Metal case, 6 in. \times 2 in. \times 7 in.		C	..	1
				C	..	1
2705	Type 1298 ...	23 pfd. max., 2 gang, air, variable, ceramic insulation, metal frame, spindle $\frac{1}{4}$ in. dia. \times .562 in. at front and rear.		A	..	1
2706	Type 1299 ...	3.5 pfd.—42 pfd. ceramic trimmer.		A	..	1
2708	Type 1301 ...	70 pfd. (max.) double trimmer		A	..	1
2806	Type 1309001 mfd. variable air dielectric		A	..	1
2714	Type 13171 mfd., 800 volts, tubular, wire end connections.		C	..	1
2725	Type 1328 ...	75 + 75 + 5 — 0 pfd., variable air dielectric.		A	..	1
2727	Type 1330 ...	100 + 100 pfd. + 5 — 0 pfd., variable air dielectric.		A	..	1
2796	Type 133801 mfd., 400 volts, tubular, wire end connection.		C	..	1
2799	Type 1341 ...	11 mfd., 450 volts working ...		C	..	1
2800	Type 1342 ...	H.T. feeder bushing ...		C	..	1
2801	Type 1343 ...	H.T. feeder bushing ...		C	..	1
2802	Type 1344 ...	300 pfd., moulded, pre-set ...		C	..	1
2816	Type 1358 ...	300 mmF. Variable ...		A	..	1
2819	Type 1361 ...	2 mfd., 450 volts working, tag connections.		C	..	1
2870	Type 1362 ...	30—3 μ F. Trimmer ...		A	..	1
2873	Type 13650001 mfd. \pm 2 per cent., 1,300 volts A.C. 60 cycles test, ceramic rod type, concentric wire ends, negative temperature coefficient.		C	..	1
2879	Type 1371 ...	170 μ F. \pm 15 per cent., moulded mica, stacked foil.		C	..	1
2882	Type 1374 ...	110 pfd., variable air dielectric, $2\frac{1}{2}$ in. dia. panel mounting, 1 hole fixing.		A	..	1
2896	Type 138800018 mfd., variable air ...		A	..	1
2898	Type 1390 ...	4.8—100 μ F. Air spaced trimmer. 13 fixed plates, 12 moving.		A	..	1
2930	Type 1407 ...	2 \times 30 pfd., variable ...		A	..	1
2931	Type 1408 ...	Variable air dielectric ...		A	..	1
2932	Type 140901 mfd. mica, 250 volts D.C. working.		C	..	1
2935	Type 1413 ...	10 pfd., max., air spaced trimmer, with locking device.		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
2966	Type 1421 ...	60–15 μ F., trimmer, ceramic...		A	each	1
2973	Type 14285 mfd. \pm 15 per cent., tubular, paper, 450 volts working.		C	"	1
3023	Type 1435 ...	25 μ F. + 100–0 per cent., 50 volts D.C. Electrolyte.		C	"	1
3028	Type 1440 ...	Variable, 3 gang, including calibrated scale.		A	"	1
3031	Type 14425 mfd., 750 volts D.C. working, metal case, tags, tropical.		C	"	1
3039	Type 145005 mfd., 200 volts D.C. working, paper, tubular, with 2 leads, 12 in. long.		C	"	1
3047	Type 145700062 mfd., trimmer ...		A	"	1
3066	Type 14760001 mfd., variable air spaced, screwdriver adjustment, locking device.		A	"	1
3070	Type 1480 ...	1 μ F., 450 volts D.C. ...		C	"	1
3085	Type 1491 ...	30–315 pfd., 2 gang, variable...		A	"	1
3092	Type 1498 ...	4–20 pfd., variable air, frequency base.		A	"	1
3125	Type 1520 ...	Special, 2 ganged, variable dielectric, 2–15 pfd., each section.		A	"	1
3129	Type 1525 ...	5–60 pfd., variable, air trimmer		A	"	1
3180	Type 15360014 mfd., variable air ...		A	"	1
3186	Type 15411 mfd. \pm 15 per cent., paper dielectric, in moulded bakelite case, 250 volts D.C. working, terminal connections.		C	"	1
3194	Type 1549 ...	50 mfd., electrolytic, 12 volts D.C. working, terminal connections.		C	"	1
3207	Type 15610002 mfd., mica dielectric, in moulded case, 500 volts D.C. working, tag connections.		C	"	1
3275	Type 1589 ...	8 μ F., 15 per cent., 250 volts D.C. Paper, metal case ...		C	"	1
3294	Type 1605 ...	25 pfd., air spaced trimmer, $\frac{1}{4}$ in. dia. extended spindle.		A	"	1
3298	Type 160700016 mfd., variable ceramic base, air dielectric.		A	"	1
3299	Type 1608 ...	3.5–25 pfd., air spaced trimmer		A	"	1
3304	Type 16100001 mfd. \pm 2 pfd., silvered mica.		C	"	1
3305	Type 16110002 mfd. \pm 2 pfd., silvered mica.		C	"	1
3308	Type 16140005 mfd. \pm 2 pfd., silvered mica.		C	"	1
3313	Type 1619001 mfd. \pm 4 pfd., silvered mica		C	"	1
3325	Type 163100014 mfd., variable ...		A	"	1
3330	Type 1636005 mfd., .3 per cent., silvered mica.		C	"	1
3332	Type 1638007 mfd. \pm .3 per cent., silvered mica.		C	"	1
3333	Type 1639008 mfd. \pm .3 per cent., silvered mica.		C	"	1
3336	Type 1642 ...	45 + 45 pfd., variable, air dielectric.		A	"	1
3394	Type 1658003 mfd. \pm 2 per cent., silvered mica.		C	"	1
3395	Type 1659 ...	3.5 to 25 pfd., air, variable, ceramic base, $\frac{1}{8}$ in. \times $1\frac{1}{2}$ in. short spindle, slotted.		A	"	1
3452	Type 1703 ...	650 pfd., 15 per cent., 750 volts D.C., silvered mica, protected.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Glass of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
3466	Type 1713 ...	25 pfd., air dielectric, variable, tropical, $1\frac{7}{32}$ in. \times $\frac{1}{16}$ in. \times $1\frac{5}{8}$ in. long.		A	each	1
3467	Type 1714 ...	25 pfd., 35 volts. ...		C	"	1
3487	Type 1720 ...	$\frac{1}{2} + \frac{1}{2}$ mfd., 1,500 volts ...		C	"	1
3500	Type 1726 ...	43 μ F. Variable air, 2 gang ...		A	"	1
3501	Type 1727000317 mfd. \pm 15 per cent., air spaced, 350 volts D.C. working. Standard spacing shaft, $\frac{1}{4}$ in. \times $1\frac{1}{8}$ in.		A	"	1
3517	Type 1743 ...	Variable air dielectric ...		A	"	1
3535	Type 1755 ...	8 + 8 mfd. + 50 per cent. — 0, 550 volts D.C. working, waxed cardboard case.		C	"	1
				C	"	1
3546	Type 17610005 mfd., 3 gang, variable, 5 in. \times $1\frac{1}{8}$ in. \times 3 in.		A	"	1
3550	Type 17650005 mfd., 3 gang, variable, $4\frac{1}{2}$ in. \times $1\frac{1}{8}$ in. \times 3 in.		A	"	1
3551	Type 1766 ...	Balanced, variable, fitted with switch attachment.		A	"	1
3552	Type 1767 ...	Block capacitor, .01 + .004 + .003 + .002 + .001 mfd. \pm 1 per cent., mica dielectric.		C	"	1
3575	Type 1789 ...	100 μ F., 2 per cent., 500 volts D.C., silvered ceramic, tubular.		C	"	1
3576	Type 17900005 mfd. \pm 5 per cent., 350 volts D.C. working, moulded mica.		C	"	1
3581	Type 17951 + .1 + .1 mfd. Black capacitor.		C	"	1
3609	Type 18160001 mfd., space tuning ...		A	"	1
3661	Type 1847 ...	8 mfd., electrolytic ...		C	"	1
3663	Type 1849 ...	8 + 8 mfd., electrolytic ...		C	"	1
3669	Type 1855 ...	10–3 pfd., variable split stator		A	"	1
3670	Type 1856 ...	2 to 8 pfd., air variable, trimmer		A	"	1
3676	Type 1862 ...	100–3 pfd., variable. Screw-driver adjustment.		A	"	1
3691	Type 1866 ...	1.73 pfd. to .9.8 pfd., trimmer...		A	"	1
3694	Type 186905 mfd. \pm 10 per cent., 1000 volts D.C. working, paper, petroleum jelly, impregnated.		C	"	1
3705	Type 1880001 mfd. ...		C	"	1
3715	Type 1890 ...	1 mfd. ...		C	"	1
3717	Type 1892 ...	25 pfd., 1,400 volts working, vacuum type.		C	"	1
3786	Type 1916 ...	8 mfd., 600 volts D.C. peak working, 700 volts surge, $4\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. dia., aluminium case, fixing nuts, and tags below chassis.		C	"	1
3790	Type 192000016 mfd., variable, 1 gang...		A	"	1
3791	Type 192100016 mfd., variable, 2 gang...		A	"	1
3841	Type 1930 ...	40 pfd. \pm 10 per cent., for 1,800 r.m.s. at 100–600 kc/s. + 100 per cent. TM, 2,000 volts D.C., 180°F.		C	"	1
3844	Type 1933002 μ F., 2 per cent volts D.C., 1,500 H.F. porcelain pot.		C	"	1
3846	Type 1935003 μ F. \pm 5 per cent., for 2,000 volts r.m.s. at 90–225 at 180°F.		C	"	1
3848	Type 1937 ...	4–0005 mfd., ganged ...		A	"	1
3850	Type 1939 ...	3 to 24 pfd., variable air, ceramic base.		A	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
3851	Type 1940	3 to 12.5 pfd., variable air, ceramic base.		A	each	1
3852	Type 1941	3 to 9 pfd., variable air, ceramic base.		A	„	1
3855	Type 1944	2 pfd. to 10 pfd., max., variable air.		A	„	1
3856	Type 1945	Each section 3.5 pfd. min. to 20 pfd. max., 3 gang variable air.		A	„	1
3858	Type 1947	Each section 3.5 pfd. min. to 21 pfd. max., 2 gang variable air.		A	„	1
3865	Type 1954	500 $\mu\mu\text{F}$., variable		A	„	1
3904	Type 1973	5-35 pfd., air spaced trimmer on bakelite base, with tags.		A	„	1
3908	Type 1977	4-21 pfd. + 5 per cent., trimmer.		A	„	1
3909	Type 1978	43-15 $\mu\mu\text{F}$., trimmer. Screw adjustment.		A	„	1
3940	Type 2009	40 $\mu\mu\text{F}$., 2 per cent., 500 volts D.C., silvered ceramic, tubular.		C	„	1
3947	Type 2016	Variable, air spaced, min. capacity less than 10 pfd., max. capacity between 105 and 120 pfd.		A	„	1
3948	Type 2017	50 pfd., air spaced trimmer, frequentite base, variable.		A	„	1
3959	Type 2028	30 pfd. max., trimmer		A	„	1
3994	Type 2050	.0001 mfd., variable		A	„	1
3995	Type 2051	50 pfd., variable		A	„	1
3996	Type 2052	35 pfd., variable		A	„	1
3999	Type 2055	Special series, gap type		A	„	1
4000	Type 2056	50-5 $\mu\mu\text{F}$., trimmer		A	„	1
4010	Type 2062	30 pfd., variable trimmer, ceramic base $\frac{3}{4}$ in. \times $\frac{5}{8}$ in.		A	„	1
4025	Type 2077	.01 \pm 10 per cent., 500 volts D.C. working. paper, moulded tags.		C	„	1
4104	Type 2105	50 mmfd., variable, air spaced		A	„	1
4106	Type 2107	.0001 mfd., aluminium vanes, square law transmitting capacitor, variable, 1,500 volts A.C. working, $4\frac{1}{4}$ in. \times $3\frac{5}{8}$ in. \times 3 in.		A	„	1
4107	Type 2108	.0001 mfd., aluminium vanes, square law transmitting capacitor, variable, 1,500 volts A.C. working, $4\frac{1}{4}$ in. \times $3\frac{5}{8}$ in. \times 3 in.		A	„	1
4109	Type 2109	35 pfd., variable, double spaced, ceramic base, brass construction.		A	„	1
4114	Type 2113	34 pfd., variable		A	„	1
4115	Type 2114	55-7 $\mu\mu\text{F}$., variable air. Split stator, log law.		A	„	1
4265	Type 2209	6.6 pfd., air spaced, 5 spaces, split stator.		A	„	1
4266	Type 2210	2-6 $\mu\mu\text{F}$., trimmer		A	„	1
4334	Type 2239	.000426 mfd., variable		A	„	1
4340	Type 2245	.1 + .1 mfd., block, rectangular metal case.		C	„	1
4415	Type 2281	50 mfd., variable, trimmer		A	„	1
4419	Type 2285	16 mfd., 300 volts D.C. working		C	„	1
4425	Type 2291	4 gang, variable		A	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
4474	Type 2301 ...	·15 μ F., 2 per cent., 375 volts D.C., paper, tubular, bakelised waxed, $2\frac{1}{4}$ in. \times $\frac{9}{16}$ in. dia.		C	each	1
4507	Type 2233 ...	Variable, split stator, precision capacitor, with integral induction loop.		A	„	1
4512	Type 2338 ...	3–10 μ F., variable air, frequency base.		A	„	1
4569	Type 2379 ...	·5 mfd. \pm 15 per cent., 400 volts D.C., paper, metal case.		C	„	1
4571	Type 2381 ...	Value ·1 + ·1 + ·1 μ F., 15 per cent., 250 volts D.C., tubular chassis mounting.		C	„	1
4705	Type 2476 ...	Trimmer, 8 pfd., 120–200 pfd. max. pre-set compression.		A	„	1
4772	Type 2504 ...	·1 μ F., 400 volts D.C., tubular		C	„	1
4792	Type 2524 ...	100 + 100 pfd., butterfly variable.		A	„	1
4807	Type 2538 ...	Tuning, air dielectric, 1·8 pfd.–4·8 pfd., spindle length ·182 in.		A	„	1
4821	Type 2552 ...	25 μ F., padding ...		C	„	1
4864	Type 2556 ...	·5 mfd. \pm 20 per cent., 1,000 volts D.C. working, paper, jelly impregnated, metal case.		C	„	1
4870	Type 2562 ...	50 pfd., variable, air spaced, with ball bearings.		A	„	1
4875	Type 2567 ...	100 pfd., 10 per cent., 500 volts D.C. working, ceramic tubular side wires.		C	„	1
4896	Type 2588 ...	10 mfd. + 5 mfd. \pm 5 per cent., 1,500 volts D.C. working, paper, oil or petroleum jelly filled, tropical.		C	„	1
4917	Type 2607 ...	3–30 pfd., trimmer, air dielectric, 75 volts working at 20°C.		A	„	1
4934	Type 2624 ...	15–45 pfd., trimmer ...		A	„	1
4947	Type 2637 ...	·00023 mfd., maximum variable		A	„	1
4965	Type 2655 ...	Reaction, variable; min. 9 pfd. \pm 1 pfd.; max. 100 pfd. \pm 5 per cent.; ceramic base.		A	„	1
4966	Type 2656 ...	Trimmer, min. 3 pfd. \pm 1 pfd.; max. 25 pfd. \pm 10 per cent.; ceramic base.		A	„	1
4968	Type 2658 ...	Tuning, 3 gang, ·00025 mfd. capacity, swing.		A	„	1
4979	Type 2669 ...	Variable, air, tuning with switch, 2 gland washers (4 LU.26, Dets. 105 and 106), and nuts (4LU.26, Det. 107).		A	„	1
5021	Type 2691 ...	27 μ F., variable air, dielectric		A	„	1
5024	Type 2694 ...	3–23·5 mmfd., variable air. Trimmer 3 rotor vanes, 3 stator vanes, single spaced.		A	„	1
5026	Type 2696 ...	500 μ F., 10 per cent., 350 volts D.C., silvered mica, protected.		C	„	1
5027	Type 2697 ...	·0016 mfd., 15 per cent., 350 volts D.C., silvered mica, protected.		C	„	1
5028	Type 2698 ...	20–100 pfd., ceramic trimmer, test voltage 500 at 50 cycles, single plate.		A	„	1
5043	Type 2713 ...	100 pfd., variable, $\frac{1}{4}$ in. dia. shaft, slotted end, $\frac{3}{16}$ in. to base of bush.		A	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom of Qty	Carton Unit Qty
1	2	3	4	5	6	7
	CAPACITORS—cont.					
5170	Type 2762 ...	25-3½ μ F., variable air. Trimmer 4 fixed, 3 moving plates		A	each	1
5220	Type 2812 ...	3-23 pfd, trimmer, ¾ in. std shaft \times ¼ in dia.		A	..	1
5228	Type 2820	Variable air		A	..	1
5237	Type 2829 .	16 mfd, 600 volts D C working, electrolytic, metal case, inverted lugs and pillar, solder connections for chassis mounting, tropical		C	..	1
5238	Type 2830 ...	32 mfd, 300 volts D C working, electrolytic, metal case, inverted lugs and pillar, solder connections for chassis mounting, tropical		C	..	1
5239	Type 2831 ..	60 mfd, 200 volts D C working, electrolytic, metal case, inverted lugs and pillar, solder connections for chassis mounting, tropical		C	..	1
5241	Type 2833 .	.001 mfd, 10 amp M U.R.F. at 50 kc/s		C	..	1
5304	Type 2855 ...	2.5 pfd (min), 5.2 pfd (max.), variable, split stator, air spaced		A	..	1
5329	Type 2879 ...	9.5 pfd max, variable, ceramic, end plates, 3 mounting pillars opposite to operating shaft, friction device at operating shaft		A	..	1
5342	Type 2892 .	Double ended spindle, ganged, 3½ to 25 pfd		A	..	1
5414	Type 2920 ..	1 mfd, 500 volts D C test, paper, metal case, 1.62 in \times .5 in \times 3.18 in high G P O No 101 TF, tropical, 160°F	Army YA 4694	—	—	—
5443	Type 2945 ...	Block, .5 + 2 + 2 + 4 mfd		C	each	1
5444	Type 2946			C	..	1
5534	Type 2997 .			C	..	1
5535	Type 2998 ..	.0018 μ F \pm 15 per cent, 350 volts D C working, moulded mica (stacked foil), wire ends		C	..	1
5539	Type 3002 ..	32 mfd, 600 volts D C working, metal case, electrolytic, inverted terminals for chassis mounting, tropical finish.		C	..	1
5543	Type 3006 ...	1-3 pfd, variable trimmer, air dielectric, spindle, 1½ in. \times ¼ in dia		A	..	1
5544	Type 3007 ..	4 gang, variable, air spaced 9-223 pfd one section, 7-157 pfd other sections		A	..	1
5556	Type 3019 .	5-35 pfd, ceramic trimmer, variable		A	..	1
5576	Type 3039 .	2 + 2 μ F, 2,000 volts D C. ...		C	..	1
5588	Type 3051	4-12 pfd, variable, air spaced, single bearing with locking device		A	..	1
5593	Type 3056 ..	20 pfd, air spaced, variable, with Hoffman ball-race, frequentite top and bottom plates.		A	..	1
5594	Type 3057 ..	40.8 pfd, air spaced, variable, split stator; spindle ¾ in. \times ¼ in. dia 10 spaces 0.15 air gap		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
5638	Type 3063 ...	32.6 pfd., split stator, air spaced, variable; 8 spaces .015 in. air gap.		A	each	1
5647	Type 30720001 mfd., variable, air spaced $\frac{1}{16}$ in. shaft.		A	..	1
5654	Type 3079 ...	100 mfd. + 50 per cent. — 10 per cent., 200 volts D.C. working, sheet metal case 3 in. × 3 in. × 4 $\frac{3}{4}$ in., 2 B.A. terminal studs.		C	..	1
5666	Type 3091 ...	20 max.—4 pfd. min. each section. Variable, 2 ganged.		A	..	1
5667	Type 3092 ...	20 max.—4 pfd. min. Variable air.		A	..	1
5706	Type 3131 ...	Glass, 4 in. max. dia. × 4 $\frac{3}{4}$ in. high, with sheds; capacitance .00035 to .000425 mfd.		A	..	1
5772	Type 3159 ...	Trimmer, 4–40 pfd.		A	..	1
5790	Type 3177 ...	25 μ F., 2 per cent., 500 volts D.C., silvered ceramic, tubular.		C	..	1
5800	Type 318705 mfd. + 10 per cent. — 20 per cent., 1,000 volts D.C. working, metal case, paper terminals.		C	..	1
5806	Type 31930001 mfd. \pm 15 per cent., ceramic cup, waxed.		C	..	1
5873	Type 322101 mfd., 600 volts D.C. working, paper, tubular, screwed ends, tropical.		C	..	1
5875	Type 3223 ...	Not greater than 4.5 pfd. min. to 7.5–8.5 pfd. max., trimmer with brackets.		A	..	1
5887	Type 3235 ...	4–59.5 pfd., air variable, D.L.9 moulded base; spindle $\frac{1}{4}$ in. dia.; tropical.		A A	1 1
5888	Type 3236 ...	8 and 8–8 mfd., 500 volts D.C. working, negative case.		C	..	1
5896	Type 3244 ...	23.5–5.5 μ F., 2 gang, air variable, ceramic base, tropical finish; 4 moving, 3 fixed vanes.		A	..	1
5897	Type 3245 ...	3.2–1.5 μ F., variable air; 2 fixed, 2 moving vanes; tropical finish.		A	..	1
5898	Type 3246 ...	3.2–1.5 μ F., variable air; 2 fixed, 2 moving vanes; tropical finish.		A	..	1
5958	Type 32671 mfd. \pm 20 per cent., 1,500 volts D.C., paper tubular, wire ends.		C	..	1
5969	Type 3278 ...	5–75 mfd., variable; spindle $\frac{3}{4}$ in. long, including bush; screwdriver slot.		A	..	1
5980	Type 3289 ...	5 pfd.—15 pfd., variable, air ...		A	..	1
5985	Type 3294 ...	23 pfd. \pm 20 per cent., 350 volts D.C. working, foil tags, waxed.		C	..	1
5987	Type 3296 ...	Spindle, $\frac{3}{8}$ in., .282 in. flat for knob, 100–5.5 μ F.		C	..	1
5991	Type 330025 mfd. \pm 20 per cent., 400 D.C. working, tubular, wire ends.		C	..	1
5997	Type 3306 ...	2 gang, 130 pfd., total, tropical finish.		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
11006	Type 3315 ...	15 pfd. approx., variable air; 4 moving, 5 fixed vanes; intermediate spacing; $\frac{3}{4}$ in. long spindle.		A	each	1
11061	Type 3332 ...	22.5 pfd. to 346 pfd. total ± 1 per cent., variable air, split stator, ceramic insulation.		A	„	1
11062	Type 3333 ...	11 pfd. to 135 pfd. ± 1 per cent., variable air, ceramic insulation.		A	„	1
11066	Type 3337 ...	8–8 mfd., 400 volts peak working, electrolytic, fixing clip.		C	„	1
11069	Type 3340 ...	100 pfd. ± 15 per cent., 250 volts D.C. working.		C	„	1
11071	Type 3341 ...	5 pfd. min., 50 pfd. max., 500 A.C. working, ceramic, variable, trimmer, single.		A	„	1
11100	Type 3354 ...	16–8 mfd., wet electrolytic, 450 volts D.C. working.		C	„	1
11188	Type 3391 ...	86–8 $\mu\mu\text{F}$., variable ...		A	„	1
11196	Type 3399 ...	1,000 mfd. + 100 per cent. – 10 per cent., 8 volts D.C., electrolytic, rectangular metal case $4\frac{7}{16}$ in. \times $1\frac{13}{16}$ in. \times $1\frac{9}{16}$ in.		C	„	1
11207	Type 3410 ...	140 $\mu\mu\text{F}$., 2 per cent., 500 volts D.C., silver, mica, protected.		C	„	1
11208	Type 3411 ...	425 pfd., 2 per cent., 350 volts D.C., silver, mica, protected.		C	„	1
11211	Type 3414 ...	3 pfd. to 10 pfd., air variable, ceramic base, spindle $\frac{1}{4}$ in. dia. \times $\frac{3}{4}$ in.		A	„	1
11219	Type 3422 ...	0–540 pfd., variable, ball bearings, solid fixed feet.		A	„	1
11261	Type 3426 ...	2 mfd. ± 25 per cent., 250 volts D.C. working, tubular, paper, dielectric; 2 leads at one end, $2\frac{1}{2}$ in. long \times $1\frac{3}{8}$ in. dia.		C	„	1
11274	Type 3438 ...	40 $\mu\mu\text{F}$., 10 per cent., 500 volts D. C. working, silvered ceramic, tubular.		C	„	1
11277	Type 3441 ...	60 mfd. ± 5 per cent., 350 volts D.C. working, silvered mica, protected type.		C	„	1
11287	Type 3451 ...	2 pfd. to 5 pfd., air dielectric; 2 moving, 3 fixed vanes; spindle .155 in. dia.		A	„	1
11288	Type 3452 ...	1.5 pfd. to 3 pfd., variable air; 2 fixed, 3 moving vanes; spindle .155 in. dia. \times $1\frac{1}{8}$ in. long.		A	„	1
11397	Type 34660025 mfd. ± 10 per cent., 350 volts D.C. working, moulded, silvered mica, wire ends.		C	„	1
11409	Type 3477 ...	100 pfd. ± 20 per cent., 500 volts D.C. working, mica, waxed.		C	„	1
11413	Type 3480 ...	10 $\mu\mu\text{F}$., variable, spindle $\frac{11}{16}$ in. long.		A	„	1
11463	Type 3492 ...	50–6 $\mu\mu\text{F}$., variable air, split stator; spindle $\frac{1}{4}$ in. dia. \times $\frac{9}{16}$ in.		A	„	1
11495	Type 3506 ...	3–20 pfd., air, variable ...		A	„	1
11540	Type 351205 mfd., 9 k. volts, oil-filled, in metal case.		C	„	1
11541	Type 3513 ..	7.5 mfd.–1.5 mfd., air variable		A	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
CAPACITORS—cont.						
11565	Type 3534 ...	500 pfd. \pm 5 per cent., 350 volts D.C. working, silvered mica, end wires.		C	each	1
11568	Type 3537 ...	13 to 541 pfd., air variable, metal frame, spindle $\frac{1}{4}$ in. dia. \times $\frac{7}{8}$ in.		A	„	1
11622	Type 3546 ...	8 + 8 mfd., 450 volts, dry electrolytic.		C	„	1
11631	Type 3548 ...	500 mfd. + 100 per cent.— 20 per cent., 15 volts D.C. working, cardboard box electrolytic.		C	„	1
11656	Type 355401 mfd. \pm 15 per cent., 3,000 volts D.C. working, moulded case.		C	„	1
11718	Type 356402 mfd. \pm 15 per cent, 4,500 volts D.C. working, 500 volts R.M.S. at 1,500 cycles, A.C. working, cylindrical, dome nut connection, $1\frac{1}{2}$ in. dia. \times $4\frac{1}{2}$ in. high.		C	„	1
11744	Type 3575 ...	1.5 pfd. to 7.5 pfd., ceramic trimmer, centre adjusting screw.		A	„	1
11771	Type 3594 ...	50 μ F. \pm 5 per cent., 350 volts		C	„	1
11780	Type 3601 ...	Variable, 200 pfd., 2,000 volts A.C. test, 20 S.W.G., spindle $\frac{1}{2}$ in. dia.; $4\frac{1}{4}$ in. \times $3\frac{3}{8}$ in. \times 4 in.		A	„	1
11796	Type 3608 ...	50 mfd., metal case, 275 volts A.C. working, with waterproof junction box; incorporates discharge resistance.		C	„	1
11804	Type 3614 ...	40 mfd., 40 volts D.C. working, metal case, electrolytic, inverted terminals for chassis mounting, tropical finish.		C	„	1
11816	Type 3621 ...	8 mfd., 500 volts working, electrolytic, $2\frac{9}{16}$ in. \times 1 in. radius.		C	„	1
11858	Type 364225 mfd. + unlimited—0, 4,000 volts D.C. working, metal case $1\frac{3}{4}$ in. \times $3\frac{1}{2}$ in. \times 6 in. high over terminals; tropical.		C	„	1
11894	Type 3649 ...	500 + 500 + 1,000 — 2 gang, variable, spindle $\frac{1}{2}$ in. long.		A	„	1
11910	Type 3660 ...	One set of rotor and four sets of stator plates, air dielectric, ball bearings; maximum capacity between rotor and any stator 100 pfd.		A	„	1
11921	Type 3668 ...	25 mfd., 50—0 per cent., 50 volts D.C., electrolytic, alum. can chassis, working lead connections, flex.		C	„	1
11922	Type 3669 ...	Electrolytic, 10 mfd., 50 volts		C	„	1
11929	Type 3671 ...	38 mfd., 10 volts A.C. working, dry electrolytic, tubular, insulated case, $1\frac{1}{8}$ in. dia. \times $2\frac{1}{8}$ in.; side wires, $2\frac{1}{8}$ in. long.		C	„	1
11933	Type 3675 ...	150 max., 5 min., air variable...		A	„	1
11992	Type 3707 ...	5 pfd. to 50 pfd., ceramic trimmer, centre screw adjustment.		A	„	1
12020	Type 3719 ...	16 + 16 mfd., 450 volts D.C., 4 terminals, dry electrolytic surge-proof, metal cased, rectangular.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
12033	CAPACITORS —cont. Type 3723 ...	500 pfd., 10 per cent., 1,000 volts D.C., air variable, mica plates 1½ in. sq., brass discs, 4 B.A. clamping screw, 2 mounting angles.		A	each	1
12040	Type 3727 ...	·1 mfd. ± 10 per cent., 10 k. volts D.C., metal-cased block, oil immersed, paper dielectric.		C	..	1
12055	Type 3736 ...	1 to 7 pfd., variable, pre-set, lockable, tubular, screw adjustment.		A	..	1
12114	Type 3782 ...	40 μμF. ± 5 per cent., 350 volts D.C., silvered mica, protected.		C	..	1
12138	Type 3790 ...	3–30 mfd., trimmer with mounting plate, 75 volts D.C. working., air dielectric.		C	..	1
12141	Type 3792 ...	100 pfd., air variable. Taken out for Trainers T.3.		A	..	1
12176	Type 3813 ...	·007 mfd. ± 5 per cent., silvered mica, protected.		C	..	1
12178	Type 3815 ...	100 pfd., air spaced trimmer. Taken out for Trainers T.23.		A	..	1
12180	Type 3817 ...	Variable, split stator, precision capacitor with integral induction loop.		A	..	1
12182	Type 3818 ...	3·8 to approx. 35 pfd., air variable, frequentite base, 1⅞ in. × 1⅜ in., screwdriver adjustment.		A	..	1
12185	Type 3819 ...	·25 + ·25 mfd., 20 per cent., 3,000 volts D.C., paper, tubular, cardboard case, 2⅜ in. dia. × 5 in. terminals.		C	..	1
12204	Type 3823 ...	Variable, air		A	..	1
12205	Type 3824 ...	Variable, air		A	..	1
12226	Type 3826 ...	115 μμF., 2 per cent., 350 volts D.C., silvered mica, protected.		C	..	1
12229	Type 3829 ...	100 pfd. ± 10 per cent., 500 volts R.M.S. test, trimmer, air dielectric, ceramic base, screwdriver slot.		A	..	1
12246	Type 3839 ...	3 sections, each 7 pfd. to 23 pfd., variable, air dielectric, midget type vanes.		A	..	1
12265	Type 3846 ...	30 pfd., variable, air		A	..	1
12267	Type 3848 ...	100 pfd. + 100 pfd., circular metal plates and mica discs.		C	..	1
12308	Type 3856 ...	20–3·5 μμF., variable, air, 3 gang		A	..	1
12354	Type 3897 ...	1 mfd. ± 15 per cent., 1,000 volts D.C. working, 1,500 volts test, 2⅜ in. × 2 in. × 1¼ in., rectangular metal; fixing feet, moulded, terminals.		C	..	1
12384	Type 3910 ...	25 mfd., 50 volts D.C., electrolytic.		C	..	1
12392	Type 3916 ...	·001 mfd. ± 5 per cent., 500 volts D.C. working, ceramic tube, protected type, 14 mm. × 60 mm. long.		C	..	1
12394	Type 3918 ...	2 gang variable, 168 μμF. max. each section (6 μμF. min. each section).		A	..	1
12436	Type 3940 ...	100 pfd., air variable		A	..	1
12449	Type 3947 ...	9–2 μμF., trimmer		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
12462	Type 395306 mfd. \pm 2 per cent., 1,000 volts test, silvered mica, metal case, screw tags.		C	each	1
12470	Type 3956 ...	40 + 16 + 8 mfd., 320 volts A.C. working, paper, oil immersed.		C	..	1
12480	Type 395801 + .01 μ F., 10 per cent., 750 W., block, tubular.		C	..	1
12582	Type 4019 ...	10 mfd. \pm 20 per cent., 250 volts D.C. working, in rectangular metal case, terminals.		C	..	1
12620	Type 4027 ...	1 μ F., 250 volts D.C. working, paper, tubular, metal case .62 in. dia. \times 1 in., self sealing, wires, tropical.		C	..	1
12649	Type 4031 ...	One set of rotor plates (2 per set) and 4 sets of stator plates (3 per set), air, dielectric, ball bearings, max. capacity between rotor and any stator 100 μ F.		A	..	1
12684	Type 4047 ...	8 μ F., 350 volts peak working, electrolytic, aluminium case, 3 $\frac{3}{8}$ in. \times 1 $\frac{3}{8}$ in. dia.		C	..	1
12690	Type 4052 ...	500 μ F., 20 per cent., 350 W., variable, mica.		A	..	1
12698	Type 405725 μ F. \pm 15 per cent., rectangular metal case, base mounting, moulded terminals, oil impregnated and immersed paper dielectric, 9 kv., D.C. working.		C	..	1
12731	Type 4066 ...	6.50 mmf., variable, spindle $\frac{1}{4}$ in. dia. \times $\frac{5}{8}$ in. free length.		A	..	1
12732	Type 4067 ...	6.50 mmf., variable, spindle $\frac{1}{4}$ in. dia. \times $\frac{5}{8}$ in. free length.		A	..	1
12780	Type 4083 ...	50 μ F. + 50 per cent.—20 per cent., 12 volts, dry electrolytic.		C	..	1
12811	Type 4089 ...	1 μ F. + 10 per cent.—5 per cent., 375 volts D.C. working, tubular, paper, one hole fixing, tags.		C	..	1
12845	Type 4094 ...	30 pfd. \pm 20 per cent., 500 volts D.C., silvered ceramic disc.		C	..	1
12863	Type 410602 μ F., 20 per cent., 5,000 W., paper, tubular.		C	..	1
12889	Type 4114 ...	Variable, 2 section, 40.8 μ F. each section.		A	..	1
12891	Type 4116 ...	7 μ F., trimmer		A	..	1
12892	Type 4117 ...	75 μ F., trimmer		A	..	1
12964	Type 4148 ...	100 μ F., mica circular ...		C	..	1
12970	Type 41500045 μ F., variable power amplifier tank, test 500 amps. 600 kc/s.		A	..	1
12992	Type 4170 ...	17 mfd. min., 510 mfd. max., 3 gang, variable, air spaced.		A	..	1
13038	Type 4191 ...	8 μ F. + 50 per cent.—20 per cent., 500 volts working; electrolytic metal tubular case 2 $\frac{3}{4}$ in. high \times 1 $\frac{3}{8}$ in. dia., tags.		C	..	1
13039	Type 4192 ...	2 mfd. + 50 per cent.—20 per cent., metal tubular case, 350 volts D.C. working, tags, electrolytic.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	CAPACITORS—cont.					
13042	Type 4193 ...	$\cdot 004 \mu\text{F.} + \cdot 004 \mu\text{F.} + \cdot 004 \mu\text{F.}$, H.F. oil filled, 8 in. long \times 6 in. wide \times 8 in. high approx.		C	each	1
13044	Type 4194 ...	1,000 $\mu\mu\text{F.}$, rectangular, $7\frac{3}{16}$ in. \times $8\frac{1}{4}$ in. \times 24 in. overall, $\frac{3}{8}$ in. spindle.		C	"	1
13060	Type 4204 ...	4 $\mu\text{F.} + 50$ per cent.—20 per cent., aluminium cased, electrolytic, 350 volts D.C. peak voltage, stud fixing. Dims $2\frac{3}{4}$ in. \times 1 in.		C	"	1
13061	Type 4205 ...	25 $\mu\text{F.} + 50$ per cent.—20 per cent., 25 volts peak D.C. working, aluminium cased electrolytic, stud fixing. Dims. $1\frac{3}{4}$ in. \times 1 in.		C	"	1
13083	Type 4218 ...	30 $\mu\mu\text{F.}$, variable air, spindle tapped 6 B.A.		A	"	1
13088	Type 4221 ...	400 $\mu\text{F.} \pm 15$ per cent., 750 volts working, stacked foil mica, tag ends.		C	"	1
13094	Type 4223 ...	8 mF. ± 20 per cent., 1,000 volts D.C. working (140°F), paper, block, metal case, upright mounting.		C	"	1
13149	Type 4231 ...	3.5 $\mu\mu\text{F.}$ —25 $\mu\mu\text{F.}$, 3 moving and 4 fixed vanes; spindle .25 in. dia. \times 2.1 in. long; variable, air.		A	"	1
13165	Type 4233 ...	2 mfd., 50 per cent.—20 per cent., 500 W., dry electrolytic, reversible, $2\frac{3}{8}$ in. \times $1\frac{3}{8}$ in. dia.		C	"	1
13306	Type 4319 ...	5–75 $\mu\mu\text{F.}$, variable; spindle $\frac{1}{4}$ in. dia. \times $\frac{3}{16}$ in. free length.		A	"	1
13308	Type 4321 ...	450 $\mu\text{F.}$, ceramic, 100 volts R.M.S. H.F. at 20°C zero temp. co-eff.		C	"	1
13324	Type 4333 ...	9.5 $\mu\mu\text{F.}$, .5 $\mu\text{F.}$ per cent., 2,000 W., ceramic special, within castor oil filled neocrine bag clamped between bracket on flat mounting, plate.		C	"	1
13325	Type 4334 ...	19 $\mu\mu\text{F.}$, — 5 $\mu\mu\text{F.}$, 3,000 W., ceramic. Special. In castor oil filled neocrine bag; clamped between bracket on flat mounting plate.		C	"	1
13326	Type 43351 mfd., 20 per cent., 100 volts D.C., paper, rect. metal case.		C	"	1
13331	Type 4336 ...	7.5 $\mu\text{F.}$, 275 W. A.C., metal case		C	"	1
13370	Type 4358 ...	3 to 20 pfd., air dielectric trimmer.		A	"	1
13374	Type 4359 ...	500 $\mu\mu\text{F.}$, variable air dielectric		A	"	1
13392	Type 4366 ...	$1\frac{1}{2}$ –4 $\mu\mu\text{F.}$, split stator, variable. Air gap .045 in., spindle $\frac{1}{4}$ in. dia. \times .78 in.		A	"	1
13433	Type 4382 ...	Variable, split stator, 9.6 + 9.6 $\mu\mu\text{F.}$, ceramic insulation, in metal frame, 3 fixed and 2 moving vanes per section, free spindle .781 in. \times $\frac{1}{4}$ in. dia.		A	"	1
13456	Type 4395001 $\mu\text{F.}$, 8 amps., 550/1,500 kc/s.		C	"	1
13493	Type 4410 ...	35 $\mu\mu\text{F.}$ max., 13 $\mu\mu\text{F.}$ min., variable air, spindle $1\frac{13}{16}$ in. \times $\frac{3}{8}$ in. dia.		A	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
13506	Type 4420 ...	100 μF ., ceramic transmitting, negative temperature co-efficient.		C	each	1
13507	Type 4421 ...	50 μF ., transmitting —VE, temp. coefficient.		C	„	1
13508	Type 4422 ...	20 μF ., transmitter ...		C	„	1
13529	Type 4424 ...	40 pfd.—8 pfd., variable air ...		A	„	1
13554	Type 4431 ...	8 μF ., — 15 per cent. + 100 per cent., 450 volts D.C. working, electrolytic, tropical; can $2\frac{1}{2}$ in. \times 2 in.; base overall $2\frac{3}{4}$ in. \times $1\frac{1}{16}$ in.		C	„	1
13570	Type 4439 ...	32 + 32 μF . + 50 per cent. — 20 per cent., 35 volts D.C.; sprayed gauge, non-tropical, on high ripple.		C	„	1
13590	Type 4449 ...	1 μF . + 50 per cent. — 20 per cent., 150 volts working, dry electrolytic in aluminium can, $\frac{3}{8}$ in. dia., $2\frac{1}{4}$ in. long, with M.A. fixing stud at one end.		C	„	1
13599	Type 4451 ...	Variable, max. 13.5 pfd., min. 3.5 pfd., trimmer, ceramic.		A	„	1
13600	Type 4452 ...	6.5–2.5 pfd., variable air, ceramic base, 2 fixed vanes, 2 moving vanes, spindle .2 in. \times .838 in.		A	„	1
13601	Type 4453 ...	75–7 pfd., variable air, 2 gang, spindle .25 in. dia. \times .465 in.		A	„	1
13602	Type 4454 ...	75–7 pfd., variable air, single gang, spindle .2 in. dia. \times .465 in. at each end.		A	„	1
13625	Type 4458 ...	— .004 μF . + .004 μF . + .004 μF . + .004 μF ., block. Oil filled. $8\frac{7}{8}$ in. high \times $7\frac{1}{2}$ in. \times 11 in. long, base $9\frac{1}{2}$ in. long, top $4\frac{1}{2}$ in.; fixing centres \times 10 in., $\frac{1}{4}$ in. Whitworth terminals 1 in. high.		C	„	1
13649	Type 4475 ...	30 μF ., 100 volts D.C., dry electrolytic.		C	„	1
13650	Type 4476 ...	25 μF . + 50 per cent. — 0 per cent., 50 volts D.C. dry electrolytic.		C	„	1
13680	Type 4487150 μF ., variable, 4 gang; capacity sweep per sec., 3 mounting brackets, cover plate.		A	„	1
13718	Type 4496 ...	4 + 10 mfd., 250 R.M.S., metal block.		C	„	1
13727	Type 4499 ...	46 μF ., mica, metal clamp, fixing centres $4\frac{3}{4}$ in.		C	„	1
13749	Type 4504 ...	30 pfd.—6 pfd., air variable, $2\frac{1}{8}$ in. between top and bottom plates, $\frac{3}{8}$ in. dia. tufnol spindle.		A	„	1
13792	Type 45151 mfd., 10,000 volts D.C., paper, metal case.		C	„	1
13847	Type 4544 ...	50 μF .—3.8 μF ., variable air, 6 fixed vanes, 7 moving; air gap .015 in., steel end plate and bar, brass shaft with steel ball bearings, silver plate finish, low loss ceramic.		A	„	1
13859	Type 4547 ...	50 μF .—6 μF ., variable air, 2 gang, fixed plate 2 in. \times 6 in., moving plate 2 in. \times 7 in., air gap .015 in.		A	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
13899	Type 4565 ...	8 μ F., 440 volts A.C., metal case		C	each	1
13929	Type 4575 ...	Air variable, 2 gang, 4–19 μ F. each section.		A	„	1
13930	Type 4576 ...	Air variable, 3 gang, 4–18 μ F. each section.		A	„	1
13931	Type 4577 ...	Air variable, 3 gang, 1st section 3.5–22.5 μ F., 2nd and 3rd sections 3.3–13.4 μ F.		A	„	1
13950	Type 4581 ...	32 mfd. + 50 per cent – 20 per cent., 320 volts, dry electrolytic.		C	„	1
13951	Type 4582 ...	8 mfd. + 50 – 20 per cent., 500 volts peak voltage, dry electrolytic in cylindrical alum. can, vertical, chassis fixing, $\frac{3}{4}$ in. hole stud positive, case negative.		C	„	1
13984	Type 4597 ...	Air variable, 3 gang, including scale calibrated to suit R.F. unit.		A	„	1
14005	Type 4608 ...	7.5, 250 volts D.C., power factor, wax.		C	„	1
14046	Type 4620 ...	25 pfd., air variable		A	„	1
14142	Type 4653 ...	Type 43, inverted vacuum, valve 43C.E.D. modified.		C	„	1
14157	Type 4664 ...	305–125 μ F., variable, split stator, $\frac{1}{4}$ in. spindle.		A	„	1
14204	Type 4685 ...	32 μ F., 500 volts D.C., electrolytic.		C	„	1
14216	Type 4689 ...	20 pfd., 6,000 volts. Special condenser plate in polystyrene moulding, with 2 additional plates added externally, 1 each side and connected together. Overall dims. 2 in. \times 1 $\frac{1}{4}$ in. \times $\frac{3}{8}$ in., excluding connecting lug.		C	„	1
14230	Type 4698 ...	50 + 50 mfd., 260 volts R.M.S.; 550 volts R.M.S. PK. Paper block.		C	„	1
14232	Type 4699 ...	320 pfd. \pm 10 per cent. Air fixed. Silvered ceramic tube complete with threaded bush and two $\frac{5}{16}$ in. B.S.F. (Fixed.)		C	„	1
14273	Type 4710 ...	750 μ F., 10 per cent., 350 volts, silvered, mica protected.		C	„	1
14301	Type 4714 ...	Variable, 2 gang. Air dielectric.		A	„	1
14389	Type 4738001–.0005 mfd., variable, mica. On ceramic case 1 $\frac{1}{2}$ in. \times 1 in.		A	„	1
14392	Type 4741 ...	890 pfd. \pm 10 per cent., 350 volts D.C., silvered mica, protected.		C	„	1
14393	Type 4742 ...	480 μ F. \pm 5 per cent., protected, silvered mica.		C	„	1
11394	Type 4743 ...	263 μ F. \pm 5 per cent., protected, silvered mica.		C	„	1
14428	Type 476602 mfd., 500 volts D.C. working, fixed mica.		C	„	1
14432	Type 4770 ...	950 μ F., 5 per cent., 10,000 D.C. working, 750 volts H.F., silvered ceramic tag., temp. coefficient. 600 parts.		C	„	1
14460	Type 4792 ...	20 pfd., 500 D.C. working, ceramic trimmer, temp. coefficient, 0–500 part. Size 34, 8 mm. \times 22.4 mm. \times 10 mm.		A	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
14481	Type 4804 ...	500 pfd., air variable ...		A	each	1
14486	Type 4808 ...	15 pfd., ceramic trimmer ...		A	"	1
14508	Type 4823 ...	500 pfd., 5 per cent., 1,800 volts R.M.S., mica, rect., moulded.		C	"	1
14548	Type 4841 ...	27·8–3·3 pfd., air variable, split stator.		A	"	1
14550	Type 4843 ...	9·6 max., 3 min., variable air, differential type.		A	"	1
14565	Type 4851 ...	470 pfd. ± 10 per cent., 350 volts D.C., silvered mica, protected.		C	"	1
13570	Type 4856 ...	20–80 pfd. Ceramic, screw adjustment, base 25 mm. × 31·5 mm.		A	"	1
14591	Type 4868 ...	6–50 μF. Air variable, single gang; spindle at each end .25 in. dia. × .465 in.		A	"	1
14602	Type 4870 ...	500 pfd. Air variable, 2 gangs		A	"	1
14623	Type 488525 mfd. ± 20 per cent. 1,200 volts D.C. Paper, metal case, invt., 2¾ in. × 1¼ in. × 1¼ in.; invt. tags.		C	"	1
14625	Type 4887 ...	1 mfd. ± 20 per cent. 1,200 volts D.C. Paper, metal case, invt., 2¾ in. × 1¼ in. × 4½ in.; invt. tags.		C	"	1
14626	Type 4888 ...	12 mfd. + 50 per cent. – 20 per cent. 50 volts D.C. Electrolytic, dry.		C	"	1
14631	Type 4893 ...	4 mfd. ± 20 per cent. 600 volts D.C. Paper, metal case, invt. mounting.		C	"	1
14646	Type 4895 ...	3–30 μF. Air spaced variable (trimmer).		A	"	1
14671	Type 4904001 μF. ± 20 per cent. 350 volts D.C. working. Moulded mica, stacked foil, wire ends.		C	"	1
14676	Type 4909 ...	16 mfd. + 50 per cent. – 20 per cent. 500 volts D.C. Electrolytic, alum. can, 4½ in. × 1¾ in. dia.; alum. bush.		C	"	1
14693	Type 4923 ...	1,600 pfd., 5 per cent. 10,000 D.C. working. Ceramic flanged pot.		C	"	1
14696	Type 492401 mfd. ± 15 per cent. 350 volts D.C. Silver mica moulded.		C	"	1
14699	Type 4927 ...	4–30 μF. Variable, plain spindle; 7 fixed and 6 moving vanes. .045 in. air gap.		A	"	1
14705	Type 4931 ...	8 mfd. + 50 per cent. – 20 per cent. 350 volts D.C. at 60°C Electrolytic. 2¼ in. × ¾ in.		C	"	1
14706	Type 4932 ...	100 pfd. ± 25 per cent. 500 volts D.C. Ceramic cup.		C	"	1
14735	Type 4941 ...	4–20 μF. Air spaced trimmer; 7 fixed, 6 moving vanes. ¼ in. spindle.		A	"	1
14740	Type 4946 ...	Value 1·16–3·05 μF. Trimmer special.		A	"	1
14741	Type 4947 ...	Value 1·87–4·17 μF. Trimmer special.		A	"	1
14742	Type 4948 ...	Value 1·31–3·35 μF. Trimmer special.		A	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS —cont.					
14779	Type 4968 ...	Value 4.5 to 30 μF . Air variable concentric trimmer with detachable mounting brackets.		A	each	1
14844	Type 498902 mfd., 10 per cent. 2,000 D.C. working. Paper, rect. metal case $2\frac{3}{8}$ in. \times 2 in. \times $1\frac{1}{4}$ in.		C	..	1
14845	Type 499025 mfd., 20 per cent. 3,000 D.C. working. Paper, rect. metal case $3\frac{1}{8}$ in. \times $3\frac{3}{8}$ in. \times $1\frac{7}{8}$ in.		C	..	1
14852	Type 499301 mfd. \pm 10 per cent. 350 volts. Silver mica, protected.		C	..	1
14869	Type 4997 ...	320 μF ., 5 per cent. 350 D.C. working. Silver mica protected.		C	..	1
14870	Type 49980025 mfd. \pm 10 per cent. 750 volts D.C. Silver mica protected.		C	..	1
14872	Type 5000 ...	1,400 μF ., 20 per cent. 5 KV. Ceramic flange pot.		C	..	1
14876	Type 5003 ...	70 pfd., 10 per cent. 1,000 D.C. working. Ceramic, tubular, 15 mm. \times 8 mm.		C	..	1
14899	Type 5014 ...	250 μF . + 15 per cent. — 20 per cent. 70 W. Electrolytic, metal rect. case. 100 volts peak working 1.		C	..	1
14903	Type 5017006 mfd. \pm 5 per cent. 350 W. Silver mica, protected.		C	..	1
14904	Type 5018008 mfd. \pm 5 per cent. 350 W. Silver mica, protected.		C	..	1
14905	Type 5019009 mfd. \pm 5 per cent. 350 W. Silver mica, protected.		C	..	1
14907	Type 5021 ...	100 pfd. \pm 15 per cent. 350 volts D.C. Silver mica, protected.		C	..	1
14935	Type 5041 ...	Air variable; split stator, 8 moving and 18 fixed vanes. Mycalex mounting $4\frac{1}{2}$ in. \times $8\frac{5}{8}$ in. \times $\frac{1}{4}$ in. Lever action, ball and socket coupling; base for 3-pin coil.		A	..	1
14936	Type 5042 ...	Air variable; split stator, 6 moving and 14 fixed vanes. Mycalex mounting $4\frac{1}{2}$ in. \times $8\frac{5}{8}$ in. \times $\frac{1}{4}$ in. Lever action, ball and socket coupling; base for 3-pin coil.		A	..	1
14937	Type 5043 ...	Air variable; split stator, 10 moving and 22 fixed vanes. Mycalex mounting $4\frac{1}{2}$ in. \times $8\frac{5}{8}$ in. \times $\frac{1}{4}$ in. Lever action, ball and socket coupling; base for 5-pin coil.		A	..	1
14938	Type 5044 ...	Capacitor plate assembly with indicator and scale.		A	..	1
14939	Type 5045 ...	46 μF ., 5 per cent. Air spaced coupling. Variable.		A	..	1
14940	Type 5046 ...	46 μF ., 5 per cent. Air spaced coupling. Variable.		A	..	1
14982	Type 5063 ...	11 pfd., 10 per cent. 3,000 volts. Mycalex, $1\frac{7}{8}$ in. \times 3 in. \times $\frac{9}{16}$ in.		C	..	1
14983	Type 5064 ...	40 pfd., 10 per cent. 3,000 volts. Mycalex, $1\frac{7}{8}$ in. \times 3 in. \times $\frac{9}{16}$ in.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
CAPACITORS—cont.						
15037	Type 5079 ...	100–7.5 pfd. Variable air; spindle $\frac{3}{4}$ in., .465 in. at each end; air gap .012 in.; single gang.		A	each	1
15104	Type 5117 ...	6–8 $\mu\mu\text{F.}$, 10 per cent. 500 W. Silvered ceramic, tubular, tropical.		C	„	1
15123	Type 5125 ...	35–6 pfd. Variable; split stator, 5 rotor, 6 stator plates per section. .058 in. spacing.		A	„	1
15134	Type 5135 ...	4 max., 2 min. Air variable; neutralising capacitor.		A	„	1
15135	Type 5136 ...	4.7 $\mu\mu\text{F.}$ Swing 30 $\mu\mu\text{F.}$ Air variable.		A	„	1
15136	Type 5137 ...	18 max. 4.5 min. Air variable		A	„	1
15137	Type 5138 ...	42 max. 4.8 min. Air variable		A	„	1
15138	Type 5139 ...	3 $\mu\mu\text{F.}$ –11 $\mu\mu\text{F.}$ Air variable ...		A	„	1
15140	Type 5140 ...	11 max. Air variable ...		A	„	1
15141	Type 5141 ...	Air variable, 3 gang ...		A	„	1
15142	Type 5142 ...	Air fixed ...		C	„	1
15144	Type 5143 ...	4 $\mu\text{F.}$ 500 volts working. Rect. metal case. Mica dielectric. Insulation resistance not less than 4,000 Meg. per $\mu\text{fd.}$		C	„	1
15223	Type 5203 ...	Value, 100. Air variable. Spindle $\frac{7}{8}$ in. with flat $\frac{27}{32}$ in. long.		A	„	1
15251	Type 5211 ...	60 pfd., 5 per cent. On adjustment mica. Coupling $5\frac{1}{4}$ in. \times $3\frac{11}{16}$ in. overall.		C	„	1
15274	Type 5213 ...	97–89 value. Air variable. Padding plug-in $3\frac{7}{8}$ in.		A	„	1
15275	Type 5214 ...	Variable. Min. 13 pfs., swing 528 pfs. Overall dims, $1\frac{3}{32}$ in. \times $2\frac{3}{4}$ in. \times $1\frac{7}{32}$ in. Spindle .906 in. from base.		A	„	1
15280	Type 5216 ...	1–7 $\mu\text{F.}$ Concentric trimmer		A	„	1
15818	Type 5219 ...	Left-hand output circuit wave change.		C	„	1
15819	Type 5220 ...	Right-hand output circuit wave change.		C	„	1
15872	Type 5261 ...	100 value + 60 per cent. – 20 per cent. 50 W. Electrolytic.		C	„	1
15890	Type 527600085 $\mu\text{F.}$ Metal clamp type, left-hand assembly. $4\frac{1}{2}$ in. \times $3\frac{1}{8}$ in.		C	„	1
15913	Type 5288 ...	6–100 $\mu\mu\text{F.}$, 650 W. Air dielectric. Trimmer.		A	„	1
15915	Type 5290 ...	554 pfd. Air variable, 4 gang		A	„	1
15924	Type 5291 ...	300 pfd. Variable, air ...		A	„	1
15925	Type 5292 ...	50 pfd. Variable, air ...		A	„	1
15938	Type 529705 mfd., 5 per cent. 500 W. Paper, tubular. $1\frac{1}{2}$ in. \times $1\frac{3}{8}$ in. dia.		C	„	1
15963	Type 5307 ...	40 $\mu\mu\text{F.}$ Ceramic trimmer ...		A	„	1
16030	Type 53310005 $\mu\mu\text{F.}$ Air variable, twin gang ...		A	„	1
16081	Type 5355 ...	47 pfd., 20 per cent. 500 volts D.C. Ceramic tube.		C	„	1
16195	Type 5436005 $\mu\mu\text{F.}$ Air variable, 2 gang		A	„	1
16199	Type 5440		C	„	1
17043	Type W.5661 ...	Fixed paper, metal case. .25 mfd., 3 K. V.D.C.		C	„	1
5686	Type 3111 ...	50 $\mu\mu\text{F.}$ Variable. Brass ball bearings.		A	„	1
16705	Type 5877 ...	7–61. Air variable ...		A	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
16721	Type 5889 ...	30–100 $\mu\mu\text{F}$. Variable ...		A	each	1
16805	Type 5954 ...	2.8–8.1. Air variable. 2 fixed and 3 moving plates, .045.		A	"	1
16839	Type 5973 ...	1 μF . Rect. metal case, $3\frac{1}{16}$ in. \times $1\frac{1}{8}$ in. \times $\frac{1}{2}$ in. $3\frac{7}{8}$ in. over taps.		C	"	1
16906	Type 6018 ...	1,800 pfd., 5 per cent. 2.5 amp. H.F. Capacitor, 260–300 kc/s.		C	"	1
16907	Type 6019 ...	1,700 pfd., 1 per cent. 1 amp H.F. Capacitor, 260–300 kc/s.		C	"	1
16908	Type 6020 ...	1,000 pfd., 5 per cent. 1 amp. H.F. Capacitor, 250–320 kc/s.		C	"	1
16932	Type 6028 ...	815 pfd., 5 per cent. 1 amp.		C	"	1
16933	Type 6029 ...	6,350 pfd., 5 per cent. 1.5 amp. H.F. transmitting.		C	"	1
16934	Type 6030 ...	2,610 pfd., 5 per cent. 1 amp. H.F. transmitting.		C	"	1
16981	Type 6049 ...	Variable, air dielectric. Modn. of 10C/11910 Capacitor, Type 3660, by shortening of spindle, different screws, etc.		A	"	1
16982	Type 6050 ...	100 pfd. Variable, air dielectric. Similar to Wingrove and Rogers C16–01 but spindle cut to .528.		A	"	1
16998	Type 6058 ...	40 $\mu\mu\text{F}$. + 5 per cent. 750 volts. Bakelite case $\frac{5}{8}$ in. \times $1\frac{1}{4}$ in. \times $3\frac{1}{2}$ in.		C	"	1
16999	Type 6059 ...	100 $\mu\mu\text{F}$., 5 per cent. 750 volts. Bakelite case $\frac{5}{8}$ in. \times $1\frac{1}{4}$ in. \times $3\frac{1}{2}$ in.		C	"	1
17000	Type 6060 ...	300 $\mu\mu\text{F}$., 5 per cent. 750 volts. Bakelite case $\frac{5}{8}$ in. \times $1\frac{1}{4}$ in. \times $3\frac{1}{2}$ in.		C	"	1
17501	Type 6061 ...	600 $\mu\mu\text{F}$., 5 per cent. 750 volts. Bakelite case $\frac{5}{8}$ in. \times $1\frac{1}{4}$ in. \times $3\frac{1}{2}$ in.		C	"	1
17514	Type 6069 ...	4.8 $\mu\mu\text{F}$. Variable, with screwdriver slot and fitted with min.–max. stop.		A	"	1
17515	Type 6070 ...	3.3–25 $\mu\mu\text{F}$. Variable, with screwdriver slot and fitted with min.–max. stop.		A	"	1
17560	Type 6093 ...	17–289.5 $\mu\mu\text{F}$. 13 fixed and 12 moving vanes, variable air spaced, left-hand square law. Spindle $2\frac{1}{4}$ in. \times $\frac{1}{16}$ in (Cyldon "Bebe" special to W.I.S.649) with nickel frame and bakelised fabric insulation and reduction to VISK Ed. A.		A	"	1
17623	Type 6134 ...	Max. 8 mmf., min. 2 mmf. Air variable. As T.1866 but with ceramic base. Tropical replacement for T.1866.		A	"	1
17674	Type 6152 ...	3 pfd., $\frac{1}{2}$ pfd. per cent. 350 volts, silvered mica, protected.		C	"	1
17679	Type 6156 ...	30 pfd. Air variable. Ceramic base, screw adjustment.		A	"	1
17680	Type 6157		C	"	1
17681	Type 6158 ...	100 max., 3 min. Air variable. G.P.O. W4/10 WL.53070.		A	"	1
17683	Type 6159 ...	300 pfd. Air variable ...		A	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITORS—cont.					
17684	Type 6160 ...	·336 μ F. \pm 1 per cent., 250 volts D.C. working. Moulded mica, sealed terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	each	1
17685	Type 6161 ...	·0652 μ F. \pm 1 per cent., 250 volts. Paper rect. case, sealed terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17686	Type 6162 ...	·013 μ F. \pm 2 per cent., 250 volts D.C. working. Paper, hermetically sealed, metal case, rect., upright chassis mounting, top terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17687	Type 6163 ...	·047 μ F. \pm 2 per cent., 250 volts D.C. working. Paper, hermetically sealed, metal case, rect., upright chassis mounting, top terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17688	Type 6164 ...	·209 μ F. \pm 5 per cent., 250 volts D.C. working. Paper, hermetically sealed, metal case, rect., upright chassis mounting, top terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17689	Type 6165 ...	·247 μ F. \pm 5 per cent., 250 volts D.C. working. Paper, hermetically sealed, metal case, rect., upright chassis mounting, top terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17690	Type 6166 ...	·462 μ F. \pm 5 per cent., 250 volts D.C. working. Paper, hermetically sealed, metal case, rect., upright chassis mounting, top terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17691	Type 6167 ...	·487 μ F. \pm 5 per cent., 250 volts D.C. working. Paper, hermetically sealed, metal case, rect., upright chassis mounting, top terminals, 2 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17692	Type 6168 ...	·949 μ F. \pm 5 per cent., 250 volts D.C. working. Paper, hermetically sealed, metal case, rect., upright chassis mounting, top terminals, 1 $\frac{1}{4}$ in. \times 2 in. \times $\frac{5}{8}$ in.		C	..	1
17760	Type 6185 ...	37 + 37 mmF. Twin gang variable; air dielectric (balanced). Mounted on special bracket.		A	..	1
17826	Type 6196 ...	10 mfd., 15 per cent., 600 volts D.C. at 71°C. Rect. metal case, 3 $\frac{1}{4}$ in. \times 2 $\frac{1}{2}$ in. \times 5 $\frac{3}{8}$ in. high, over terminals. Clamp fixing.		C	..	1
17877	Type 6203 ...	3–35 pfd. per section. Variable, split stator, 5 fixed and 4 moving vanes per section fitted with bush and mounting plate.		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
17878	CAPACITORS —cont. Type 6204 ...	Variable, split stator, 6 moving and 14 fixed vanes. Mycalex mounting $4\frac{1}{2}$ in. \times $8\frac{3}{8}$ in. \times $\frac{1}{4}$ in., lever action, ball socket coupling. 4 sockets on Mycalex panel 5 in. \times 1 in. \times $\frac{1}{4}$ in. approx.		A	each	1
17780	Type 6206 ...	100 pfd. $\frac{1}{4}$ in. spindle, variable air.		A	„	1
17900	Type 6219 ...	$\cdot 01 \mu\text{F.}$, 10 per cent., 1,000 volts D.C. working. Porcelain fixed, porcelain barrel $2\frac{3}{8}$ in. dia. \times 2 in., screwed stem $\frac{5}{16}$ in. Whit.		C	„	1
17985	Type 6282 ...	Air dielectric. Variable, 250 mmf. max., 25 mmf. min., 17 rotor blades, 16 stator blades. $\frac{1}{4}$ in. spindle, $\frac{3}{8}$ in. projection. Overall dims. 10 in. \times 6.6 in. \times 5 in. approx.		A	„	1
17986	Type 6283 ...	Air dielectric. Variable, 900 mmf max., 30 rotor blades, 29 stator blades. $\frac{1}{4}$ in. spindle, $\frac{3}{8}$ in. projection. Overall dims. 11 in. \times 5.7 in. \times 5 in. approx.		A	„	1
18103	Type 6295 ...	Variable, solid dielectric. Max. $1,500 \mu\mu\text{F.}$ — 5 per cent. + 20 per cent., 500 volts D.C. working. 10 moving, 12 fixed plates, $\frac{1}{4}$ in. dia. spindle, $1\frac{3}{8}$ in. long.		A	„	1
18104	Type 6296 ...	$\cdot 10 \mu\text{fd.}$ + $\cdot 050 \mu\text{fd.}$ + $\cdot 50 \mu\text{fd.}$ \pm 10 per cent., 500 volts D.C. test. Mica, rectangular metal case.		C	„	1
18081	Type 6299 ...	Multi unit No. 14— 1-2 $\cdot 001525 \mu\text{F.}$ \pm $\frac{1}{2}$ per cent. 1-3 $\cdot 0029 \mu\text{F.}$ \pm $\frac{1}{2}$ per cent. 1-4 $\cdot 0055 \mu\text{F.}$ \pm $\frac{1}{2}$ per cent. 1-5 $\cdot 01 \mu\text{F.}$ \pm $\frac{1}{2}$ per cent.		A	„	1
18108	Type 6303 ...	500 pfd., 20 per cent., 600 volts D.C. working. Ceramic pot.		C	„	1
18115	Type 6309 ...	200 $\mu\text{F.}$, 200 volts D.C. Electrolytic R.M.C., $9\frac{1}{8}$ in. \times $3\frac{1}{4}$ in. \times 2 in., plain, without lugs or feet.		C	„	1
18116	Type 6310 ...	1,000 $\mu\text{F.}$, 30 volts D.C. Electrolytic.		C	„	1
18098	Type 6314 ...	200 $\mu\mu\text{F.}$ } \pm 5 per cent., 250 200 $\mu\mu\text{F.}$ } volts D.C. working 200 $\mu\mu\text{F.}$ } rectangular metal case.		C	„	1
18219	Type 6323 ...	200 $\mu\mu\text{F.}$, 100 volts. Paper, metal case, 4 in. \times 4 in. \times $4\frac{1}{4}$ in. No fixing feet or lugs.		C	„	1
18206	Type 6326 ...	$\cdot 009813 \mu\text{F.}$ \pm 5 per cent., 250 volts D.C. Mica, rectangular metal case. Tag terms. Dry-stack.		C	„	1
18225	Type 6327 ...	1,000 mf. — 0 per cent. \times 50 per cent., 100 volts working. Plain foil, electrolytic, r.m.c., $4\frac{3}{8}$ in. \times 4 in. \times 4 in. Two terms, no fixing.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store		Carton Unit Qty.
				Denom. of Qty.	Qty.	
1	2	3	4	5	6	7
18125	CAPACITORS—cont. Type 6331 ...	1 $\frac{3}{8}$ in. \times 3 $\frac{1}{2}$ in. long. Clamp fixing Can negative 1st anode plain foil, others fabricated plate.		C	each	1
18228	Type 6333 ...	40 + 16 + 8 mfd., 320 R.M.S. Oil immersed. 8 $\frac{1}{2}$ in. \times 6 $\frac{3}{4}$ in. \times 6 $\frac{1}{4}$ in. high.		A	..	1
18229	Type 6334 ...	250 μ F., 100 volts D.C. working. Electrolytic. Size of can 3 in. \times 2 in. \times 3 $\frac{5}{8}$ in. 2 top terminals.		C	..	1
18235	Type 6347038 mfd. \pm $\frac{1}{2}$ per cent. Clamped mica. 250 volts D.C.		C	..	1
18236	Type 6348047 mfd. \pm $\frac{1}{2}$ per cent. Clamped mica. 250 volts D.C.		C	..	1
17013	Type ...	For use on Reperforator 10GP/123.		C	..	1
170155 mfd. Voltage — working 1,000 volts test.		C	..	1
—	For use on Reperforator 10GP/123.		C	..	1
170165 mfd., 300 volts D.C. For use Reperforator, 10GP/123.		C	..	1
5421	Ring top, 2.188 in. o/d \times 1.438 in. \times .664 in. thick. Brass, silver plate. 4 holes. .257 in. dia.		C	..	1
17649	CAPACITOR ASSEMBLIES.	Bracket mounting, including 2 capacitors, T.4587.		C	..	1
17650	CAPACITOR ASSEMBLIES.	Bracket mounting, including 2 capacitors, T.4587.		C	..	1
11572	Type 1		A	..	1
11587	Type 3		A	..	1
	CAPACITOR UNITS:—					
7037	Type 1 ...	Tapped fine tuning, .0001 μ F. min., .00032 μ F. max.		A	..	1
10545	Type 4 ...	Aluminium plate, 4 $\frac{1}{2}$ in. \times 3 in., with feet, fitted with 3 capacitors.		A	..	1
768	Type 5 ...	Used on Amplifying Units, T.5		A	..	1
863	Type 6 ...	Taken out for Receiver R.3016		A	..	1
2392	Type 10 ...	Bracket assembly ...		A	..	1
2364	Type 13 ...	Tufnol panel, 2 $\frac{1}{4}$ in. \times 1 $\frac{3}{8}$ in. \times 1 $\frac{1}{2}$ mm.		A	..	1
2365	Type 14 ...	Tufnol panel, 5 $\frac{1}{2}$ in. \times 3 $\frac{7}{8}$ in. \times 2 mm.		A	..	1
2598	Type 15 ...	Base plate with valve base ...		A	..	1
2829	Type 20 ...	11–21 pfd., split stator precision capacitor, series, gap type, mounted in silver-plated screening box.		A	..	1
2832	Type 21 ...	Assemblage of 1 capacitor T.1344, 1 capacitor T.458, and 1 inductor T.125, in metal case.		A	..	1
8473	Type 25 ...	Earth. Combined capacitor and resistor.		A	..	1
8474	Type 26	Listening through. Combined capacitor and plug and socket.		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITOR UNITS—cont.					
3173	Type 34 ...	Five 4-40 pfd. H.F. ceramic trimmer capacitors, mica dielectric, with screw adjustment, mounted on metal bracket.		A	each	1
3174	Type 35 ...	Three 4-40 pfd. H.F. ceramic trimmer capacitors, mica dielectric, with screw adjustment, mounted on metal bracket.		A	..	1
3075	Type 40 ...	25 KV., glass dielectric, with sheds and corona flange.		A	..	1
3378	Type 42 ...	Tuning capacitor, 2.3-11.3 pfd., rotor float, with shorting bar, inductor and valve caps.		A	..	1
3593	Type 44 ...	Tufnol panel, 2½ in. × 1¾ in. × 2 mm., and meter screen.		A	..	1
3822	Type 49 ...	Bakelised fabric panel fitted with various capacitors. Taken out for Tuning Unit T.71.		A	..	1
3824	Type 51 ...	4 gang capacitor, complete with slow motion logging scale.		A	..	1
4061	Type 52 ...	Tufnol panel, complete with pillars (6).		A	..	1
4062	Type 53 ...	Tufnol panel, 2¾ in. × 1½ in. × 1½ mm.		A	..	1
4470	Type 57 ...	Tag panel, insulating panel, nuts and screws.		A	..	1
4471	Type 58 ...	Tag panel, and oscillator tuning capacitor coil.		A	..	1
5629	Type 68 ...	Bushing capacitor assembly ...		A	..	1
5729	Type 72		A	..	1
5750	Type 73 ...	S.R.B.P. panel		A	..	1
11048	Type 82 ...	Bracket mounted assembly, copper, 18 S.W.G., 1¾ in. × 1½ in. base, with copper rod coil.		A	..	1
11449	Type 88 ...	Neutralizer plate, right-hand; fitted with 2 brass sleeves, and 2 brass 6 B.A. screws, ¾ in. long, countersunk heads.		A	..	1
11450	Type 89 ...	Neutralizer plate, left-hand; fitted with 2 brass sleeves, and 2 brass 6 B.A. screws, ¾ in. long, countersunk heads.		A	..	1
11505	Type 90 ...	M.S. bracket, 3½ in. × 2¼ in. × 1½ in. C/W 4 capacitors.		A	..	1
11571	Type 92 ...	S.R.B.P. panel, 1½ in. × 1¼ in., including 1 capacitor 30 μμF., and 1 capacitor 100 μμF.		A	..	1
11573	Type 93 ...	S.R.B.P. panel, 2¾ in. × 2 in., including 2 capacitors T.2338 and 1 T.819.		A	..	1
11574	Type 94 ...	S.R.B.P. panel, 2¾ in. × 1¼ in., including 2 capacitors T.3363.		A	..	1
11637	Type 95 ...	S.R.B.P. panel		A	..	1
11798	Type 98 ...	Assembly, including 1 capacitor T.3056, 3 T.3059, and 2 T.1687.		A	..	1
12225	Type 103 ...	Bakelized paper board, 2¾ in. × 2¼ in. First used on T.1366.		A	..	1
12564	Type 107 ...	Complete with trimmer, capacitors, and inductors.		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CAPACITOR UNITS—cont.					
12965	Type 118 ...	Ruby mica wafer, rect., 1½ in. × 1 in. × .003 in. app., drilled 2 holes.		A	each	1
13313	Type 126 ...	Moulded base with one 350 μμF. Silver mica capacitor, and 1 terminal Type C, wax filled.		A	..	1
13741	Type 136 ...	2-90 μμF. Variable capacitor (2 banks 180° apart in parallel). Capacitor rotor on moving spindle at Desynon motor. Oil filled. .12 volt operation. For control by remote potentiometer.		A	..	1
13928	Type 139 ...	Variable, air, 3.3-6.1 μμF. Ceramic end plates, complete with inductors, centre tapped.		A	..	1
13949	Type 141 ...	Assembly of mounting with three 8 μF. and one 16 μF. capacitor.		A	..	1
14061	Type 142 ...	S.R.B.P. tag panel (A17897) with 1 capacitor. Used on Ind. Unit T.198.		A	..	1
14340	Type 148 ...	4 gang, complete with calibration.		A	..	1
14367	Type 149 ...	Compensating capacitor assembly of adjustable plate and trimmer on bracket.		A	..	1
14743	Type 151 ...	Right-hand. First used on Power Unit T.87.		A	..	1
14744	Type 152 ...	Left-hand. First used on Power Unit T.87.		A	..	1
14847	Type 156 ...	For fitting to receiving units, Types 50 and 184.		A	..	1
14881	Type 157 ...	3.2 in. × 2.1 in. S.R.B.P., .1 in. thick, with 8 taps, complete with 2 capacitors.		A	..	1
15281	Type 158 ...	S.R.B.P. board, 2½ in. × 2½ in., with 10 tags and 2 tapped pillars and 5 capacitors.		A	..	1
16075	Type 172 ...	Tuning, 5 gang variable, ceramic, metal plates, air dielectric 2.5 μμF. to 21.5 μμF. swing maximum section. Wired with fixed resistors, capacitors and choke.		A	..	1
16151	Type 173 ...	Air dielectric metal plates, 5 gang.		A	..	1
16996	Type 175 ...	50 pfd. Variable capacitor mounted in brackets in box 1½ in. × 1½ in. × 2 in.		A	..	1
17848	Type 178 ...	Tuning, 5 gang, variable, ceramic, metal plates, air dielectric, 2.5 μμF. to 21.5 μμF. swing max. sec., wired with fixed resistors, capacitors, choke and coil (as 10C/16075 but increased turns on coil).		A	..	1
17849	Type 179 ...	Ceramic, air dielectric, metal plates, 5 gang.		A	..	1
18130	Type 182		A	..	1
18131	Type 183		A	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
5714	CAPS	For Capacitor Unit, Type 68. Copper sheet, .028 dome, $2\frac{11}{16}$ in. dia. \times $\frac{3}{8}$ in. high, 6 slots, and B.A. terminal stud on top.		C	each	1
3541	CASES, TRANSIT	Wood, $\frac{1}{4}$ in. thick. $6\frac{1}{2}$ in. \times $6\frac{1}{2}$ in. \times $7\frac{1}{2}$ in. inside. For Inductor, Type 237.		C	"	1
3650	CASES, TRANSIT ...	For Inductance, Types 165-168		C	"	1
	CHOKES					
	H.F.:—					
7490	Type 2	Air with adjustment. Rheostat in wooden case, 8 in. \times $3\frac{1}{2}$ in. \times $3\frac{1}{2}$ in.		C	"	1
8383	Type 18	Cylindrical former, 2 in. dia., with 3 winding slots.		C	"	1
8384	Type 19	Cylindrical former, $\frac{3}{8}$ in. dia. with 10 winding slots.		C	"	1
8716	Type 22	Paxolin former, pancake winding		C	"	1
8718	Type 24	Cylindrical former, wire wound, twin chokes.		C	"	1
8682	Type 28	45,000 microhenries. Slotted former, with end caps.		C	"	1
9206	Type 34	Cylindrical former, $2\frac{3}{8}$ in. \times $\frac{3}{4}$ in.		C	"	1
9514	Type 35	Cylindrical former, $1\frac{5}{8}$ in. long \times 1 in. dia., wire wound.		C	"	1
9832	Type 36		C	"	1
10117	Type 37	Former, 1.55 in. \times 40 in., with 8 grooves. Inductance: 600 m/H max., 560 m/H min.		C	"	1
10312	Type 39	H.T. choke, with dust iron core, screened.		C	"	1
10504	Type 41	Cylindrical former, $2\frac{1}{2}$ in. \times 1 in. dia., with 14 slots.		C	"	1
10505	Type 42	Cylindrical former, $2\frac{1}{2}$ in. \times 1 in. dia., with 14 slots.		C	"	1
10986	Type 43	Spider former, air spaced winding.		C	"	1
11393	Type 44	Crystal monitor, Type 2 ...		C	"	1
11341	Type 45	Attached to coil, master oscillator, range.		C	"	1
11601	Type 46	120 turns		C	"	1
11603	Type 47	110 turns		C	"	1
11605	Type 49	64 turns		C	"	1
79	Type 53	1.5 millihenries, 4 banks, on $\frac{1}{4}$ in. dia. \times $1\frac{3}{4}$ in. former.		C	"	1
80	Type 54	1.25 millihenries, 4 banks, on $\frac{1}{4}$ in. dia. \times $1\frac{3}{4}$ in. former.		C	"	1
249	Type 60	Inductor, 125 microhenries ...		C	"	1
384	Type 62		C	"	1
386	Type 64		C	"	1
447	Type 67	210,000 microhenries, 330 ohms		C	"	1
482	Type 68	210,000 microhenries, 330 ohms, with canister.		C	"	1
578	Type 70	8.8 microhenries \pm 10 per cent. Bakelite moulding.		C	"	1
583	Type 71	250 microhenries, 630 ohms, D.C		C	"	1
719	Type 74		C	"	1
849	Type 78		C	"	1
880	Type 80	Winding in 5 sections. Inductance 3.8 microhenries, at 1,000 cycles, D.C. resistance 660 ohms. Paxolin former, $2\frac{1}{4}$ in. \times $\frac{1}{2}$ in. dia. Tag connections.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
866	Type 81 ...	Heater inductance 15 microhenries, approx. at 1,000 cycles, D.C. resistance .02 ohms (approx.). Tufnol former, 3 in. × 1 in. dia.		C	each	1
902	Type 82 ...	Heater resistance .72 ohms, inductance 7–8 millihenries at 1,000 cycles.		C	..	5
2019	Type 83 ...	6.7 mH, 135 ohms D.C. resistance; moulded former, 1½ in. × ¾ in. dia.; aluminium screening can, 1 in. dia. × 1½ in. high; tags through top of screen.		C	..	1
2087	Type 88 ...	8.8 millihenries ± 10 per cent.		C	..	1
836	Type 89 ...	Heater, .2 ohm ...		C	..	1
837	Type 90 ...	Heater, .1 ohm ...		C	..	1
2185	Type 93 ...	5.6 mH, 1.3 ohms D.C. resistance, tubular wire end connections.		C	..	1
2186	Type 94 ...	6.7 mH, 135 ohms D.C. resistance, moulded former, 1½ in. × ¾ in. dia. Aluminium screening can, 1½ in. × 1 in. dia. Tags through bottom of screen.		C	..	1
2232	Type 95 ...	Large tubular ...		C	..	1
2233	Type 96 ...	Large tubular ...		C	..	1
2234	Type 97 ...	Small tubular ...		C	..	1
2235	Type 98 ...	Spools, moulded bakelite ...		C	..	1
2236	Type 99 ...	With iron core cemented in ...		C	..	1
2299	Type 100	Wound on porcelain tubular core, with terminal stud each end. Fitted with 2 nuts one end and 4 nuts the other end.		C	..	1
3804	Type 101	Wound on porcelain tubular core, with terminal stud each end. Each fitted with 2 nuts.		C	..	1
2360	Type 104	1.25 microhenries, 22 ohms ...		C	..	1
2361	Type 105		C	..	1
2268	Type 106	Air dielectric, 2 × 1,350 turns, double wound, 36 S.W.G. Fixing through centre of coil.		C	..	1
2269	Type 107	Air dielectric, 1,000 turns. Centre top fixing through centre coil.		C	..	1
2378	Type 108	Air dielectric, 2 × 600 turns. Centre top fixing through centre coil.		C	..	1
2558	Type 111	H.F. ...		C	..	1
2585	Type 114	2.5 millihenries. Variable iron dust core.		C	..	1
2593	Type 115	Coiled electro-plated copper tube		C	..	1
2594	Type 116	Coiled electro-plated copper tube		C	..	1
2701	Type 118		C	..	1
2736	Type 121	Large tubular ...		C	..	1
2737	Type 122	Large tubular ...		C	..	1
2762	Type 123	Four microhenries, 1½ in. dia. × ¾ in. Centre hole fixing.		C	..	1
2773	Type 124	520 microhenries ± 5 per cent. Overall size, ¾ in. × ½ in. dia.		C	..	1
2775	Type 125	150 milli/H, 3 banks Leeson wound on 2 dust iron cores, in screening case 1½ in. dia. × 2¾ in.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
2847	Type 126 ...	45 turns of 16 S.W.G. E. and SCC. wire. Wound on Tufnol former, $1\frac{7}{8}$ in. \times 1 in. dia.		C	each	1
2849	Type 127 ...	Heater, $\cdot 130$ ohms D.C. resistance (approx.). Tufnol former, $1\frac{1}{8}$ in. \times $\frac{1}{2}$ in. \times $\frac{1}{2}$ in.		C	"	1
2850	Type 128 ...	Heater, $\cdot 130$ ohms D.C. resistance (approx.). Tufnol former, $1\frac{1}{8}$ in. \times $\frac{1}{2}$ in. \times $\frac{1}{2}$ in.		C	"	1
2859	Type 129 ...	1.28 millihenries, 4 banks, Leeson wound, on $\frac{1}{4}$ in. former, 2 in. long.		C	"	1
2942	Type 132 ...	Less brackets (Detail 12, TG. 17730).		C	"	1
2944	Type 133 ...	Anode		C	"	1
2953	Type 136 ...	105 microhenries \pm 15 per cent.		C	"	1
2954	Type 137		C	"	1
3008	Type 138		C	"	1
3220	Type 150 ...	Filament choke		C	"	1
3221	Type 151		C	"	1
3224	Type 154 ...	Dust, iron core		C	"	1
3425	Type 161 ...	T.F. 460 kc/s adjustable iron dust core.		C	"	1
10625	Type 164		C	"	1
10626	Type 165 ...	Choke coil		C	"	1
11117	Type 175		C	"	1
10775	Type 176		C	"	1
10779	Type 179		C	"	1
3524	Type 183 ...	Wave-wound dust iron core, $\cdot 17$ amp. D.C. Multi-section 5 mH.		C	"	1
3590	Type 185 ...	2 microhenries, 21 turns of 30 D.S.C. on bakelite former, $\frac{1}{4}$ in. dia.		C	"	1
3806	Type 197 ...	Cylindrical former wound with 16 turns of 23 S.W.G. enam. copper wire.		C	"	1
3807	Type 198		C	"	1
3808	Type 199 ...	1.25 \pm 10 per cent millihenries, 22 ohms \pm 10 per cent D.C. resistance.		C	"	1
3809	Type 200 ...	15.5 microhenries \pm 15 per cent. Resistance 65–70 ohms.		C	"	1
3899	Type 202 ...	Heater choke, $\cdot 17$ ohms approx.		C	"	1
3979	Type 207 ...	Filament, choke, 1 millihenry...		C	"	1
4064	Type 208		C	"	1
4065	Type 209		C	"	1
4066	Type 210		C	"	1
4067	Type 211		C	"	1
4068	Type 212		C	"	1
4069	Type 213		C	"	1
4070	Type 214		C	"	1
4091	Type 218 ...	Inductance 7.2 mH. 26 S.W.G. wire.		C	"	1
4092	Type 219 ...	500 millihenries. Sectionalised, pile wound; 38 S.W.G. copper wire, D.C. resistance 9 ohms, loaded ebonite former.		C	"	1
4093	Type 220 ...	8.4 millihenries. Sectionalised, pile wound; 26 S.W.G. copper wire, D.C. resistance $\cdot 25$ ohms, loaded ebonite.		C	"	1
4094	Type 221 ...	Heater, $\cdot 2$ ohms		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
4132	Type 225	... H.T. smoothing choke, 1,000 volts, 2,000 turns of 33 S.W.G.		C	each	1
4147	Type 226	... H.T. smoothing choke, 300 volts, laminated iron core, 2,800 turns of S.W.G.		C	"	1
4150	Type 229	... Tuning, copper strip on paxolin former.		C	"	1
4152	Type 231	... Approx. 85 microhenries. 195 turns of 41 S.W.G. wire on bakelite former.		C	"	1
4153	Type 232	... 3 windings of 40 turns of 22 S.W.G. wire on Tufnol former.		C	"	1
4357	Type 243	... Inductance 280 μ H, 1.62 μ F, 640 turns each of 40 S.W.G. 16 sections, on former W.C.P.43.		C	"	1
4359	Type 245		C	"	1
4360	Type 246		C	"	1
4362	Type 248		C	"	1
4461	Type 251		C	"	1
4517	Type 255	... Wound on Tufnol former, $\frac{3}{8}$ in. dia., 30 turns approx. of 23 S.W.G. enam. copper wire, close wound.		C	"	1
4599	Type 263	... 26 μ H. 21 turns 18 S.W.G. choke windings, 4 layers, single silk enam. C. wire, coated with varnish. 1 in. dia. \times 1 $\frac{1}{4}$ in. app. tags.				
4851	Type 274		C	"	1
5016	Type 277	... 4 coils, each 102 turns of .0076 dia. enamel and silk covered copper wire on $\frac{1}{2}$ in. dia. paxolin tube.		C	"	1
5017	Type 278	... 2 coils, each 105 turns of .0075 in. dia. enam. and silk covered copper wire on $\frac{1}{2}$ in. dia. paxolin tube.		C	"	1
5065	Type 279		C	"	1
5066	Type 280		C	"	1
5069	Type 283	... Former, 1.25 in. \times .5 in., 3 sections, 200 turns each. 40 S.W.G.		C	"	1
5070	Type 284	... R.F. plate former, 2 $\frac{1}{8}$ in. \times .5 in. 2 sections, 135 and 120 turns 40 S.W.G.		C	"	1
5090	Type 287		C	"	1
5091	Type 288	... Inductance 1.0 mH. 4 honeycomb coils, spaced wire mounting. 10 ohms, D.C. resistance.		C	"	1
5094	Type 292	... Resonant to 200 mc/s. paxolin rod, wound enamel.		C	"	1
5114	Type 293	... Assembly of 2 paxolin rods, wound enam. wire, tags, on S.R.B.P. support, special.		C	"	1
5277	Type 301	... Ringing		C	"	1
5285	Type 305	... 24 turns of 26 S.W.G. enamelled wire, paxolin former $\frac{1}{4}$ in. dia. \times 1 $\frac{1}{8}$ in.		C	"	1
5287	Type 306	... 24 turns of 26 S.W.G. enamelled wire, paxolin former $\frac{1}{4}$ in. dia. \times 1 $\frac{1}{4}$ in., wire ends for connection mounting.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
5343	Type 307	... Loaded ebonite rod, $\frac{5}{8}$ in. \times $\frac{1}{4}$ in., wound with 14 turns S.W.G. wire.		C	each	1
3592	Type 310	... Heater choke; 1.3 microhenries, 15 turns 22 D.C.C. copper wire.		C	..	1
5402	Type 316	... Ind. 720 mH \pm 20 per cent., without core. Fitted with iron dust core. 280 turns of 38 S.W.G. SS. en. cu. wire $\frac{1}{2}$ wave wound.		C	..	1
5403	Type 317	... 40 μ H \pm 10 per cent., 1,600 turns of No. 42 D.S.C. wire; overall size $\frac{15}{16}$ in. dia. \times $\frac{11}{16}$ in. long.		C	..	1
5492	Type 320108 ohms \pm 10 per cent., 48 turns of 24 enam. and S.C.C. copper wire, slotted former $\frac{3}{4}$ in. \times $\frac{1}{2}$ in. overall.		C	..	1
5615	Type 322	... 12 slots, S.W.G. enamelled Eureka wire. All wound in same direction.		C	..	1
5616	Type 323	... 12 slots, 120 turns 39 S.W.G. enam. copper wire. All wound in same direction.		C	..	1
5619	Type 326	... 100 microhenries at 50 mA ...		C	..	1
5613	Type 329	... 5 turns of .018 in. enam. copper wire on 50 ohms $\frac{1}{2}$ watt resistance.		C	..	1
5614	Type 330	... 9 turns of .018 in. enam. copper wire on 50 ohms $\frac{1}{2}$ watt resistance.		C	..	1
5741	Type 332	... 1.3 mH, 22 turns of 30 S.W.G. equally spaced between pins on $\frac{5}{16}$ in. dia. former; bakelite varnish over windings.		C	..	1
5743	Type 334	... 20 turns of 20 S.W.G. D.S.C. wire on $\frac{5}{16}$ in. former.		C	..	1
5847	Type 335		C	..	1
5910	Type 337	... 296 turns of 38 S.W.G. enam. and S.S.C. copper wire, wound in 4 sections; inductance, 270 millihenries \pm 10 per cent.		C	..	1
5911	Type 338	... 60 turns of 36 S.W.G. S.S.C., $1\frac{1}{8}$ in. dia. \times $1\frac{1}{4}$ in. side tags insulating tube former.		C	..	1
5912	Type 339		C	..	1
5913	Type 340	... 200 + 200 turns 38 S.W.G. and S.S.C. wire. 11 ohms \pm 10 per cent., in slot on insulating former, $\frac{1}{2}$ in. dia. \times $1\frac{1}{4}$ in. overall, with 4 B.A. fixing one end; 2 side pins for connectors.		C	..	1
5914	Type 341		C	..	1
11149	Type 350	... 75 turns 30 S.W.G. en. copper wire on $\frac{1}{2}$ in. former.		C	..	1
11227	Type 356	... 30 S.W.G. en. copper on bakelite former.		C	..	1
11246	Type 362	... 21 turns No. 22 S.W.G. E/C. Ceramic former, .22 in. dia. \times 1.03 in.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
11326	Type 363 ...	Inductance 2,600 μ H. Open, air cooled, 6 wave-wound coils on silvonite former, with brackets.		C	each	1
11330	Type 367 ...	30 turns 24 S.W.G. en. cu. wire, $\frac{1}{4}$ in. dia. \times $1\frac{1}{8}$ in., end wires.		C	"	1
11331	Type 368 ...	800 mH, 20 mA, 3 windings, each 180 turns of 38 S.W.G. ESSC.		C	"	1
11298	Type 370 ...	130 mH		C	"	1
11314	Type 371 ...	Wire-wound, 14 turns 20 gauge EC. on Tufnol former, 2 in. \times $\frac{1}{4}$ in. dia.		C	"	1
11336	Type 572 ...	25 turns 30 S.W.G. enam., close wound on 2.12 in. \times $\frac{1}{4}$ in. dia. Tufnol rod.		C	"	1
11345	Type 373 ...	Winding, 23 turns of 26 S.W.G. en. cu. wire on $\frac{5}{16}$ in. former.		C	"	1
11346	Type 374 ...	19 turns of S.W.G. en. cu. wire, $\frac{1}{4}$ in. dia. \times 1 in. long.		C	"	1
11432	Type 375 ...	Spool, $1\frac{1}{8}$ in. dia. \times $1\frac{3}{8}$ in. long, 3 collars, $1\frac{1}{8}$ in. dia. \times $\frac{1}{8}$ in., spaced $\frac{1}{2}$ in. apart. Wound with 2,210 turns of 36 S.W.G. Inductance 67 mH \pm 10 per cent.		—	—	—
11433	Type 376 ...	As Type 375 but with 2,000 turns; inductance 52 mH \pm 10 per cent.		C	each	1
11435	Type 377 ...	18 turns of 38 S.W.G. en. cu. wire on $\frac{3}{16}$ in. former.		C	"	1
11447	Type 380 ...	Wave-wound, 5 sections, 400 turns each, 36 S.W.G. D.S.C. copper, on Tufnol rod, $3\frac{1}{4}$ in. \times $\frac{5}{8}$ in. dia.		C	"	1
11448	Type 381 ...	Wave-wound, 3 sections, 400 turns each, 36 S.W.G. D.S.C. copper on Tufnol rod, $2\frac{1}{16}$ in. \times $\frac{5}{8}$ in. dia.		C	"	1
11452	Type 382 ...	Suppressor choke, 24 $\frac{1}{2}$ -turns of 22 S.W.G. copper D.S.C. on loaded ebonite former $2\frac{5}{8}$ in. long; wire ends.		C	"	1
11528	Type 383 ...	Copper strip, double right-angled, $\frac{3}{32}$ in. wide; length $1\frac{3}{8}$ in.; length before winding 2.735 in.		C	"	1
11529	Type 384 ...	"U" shape copper strip, $\frac{3}{32}$ in. wide; length before bending 2.735 in.		C	"	1
11530	Type 385 ...	10 turns 1 mm. en. cu. wire, $1\frac{1}{2}$ mm. pitch; internal dia. 8 mm.		C	"	1
11592	Type 386 ...	I.F. grid, 20 turns 37 S.W.G. S.S. enamelled, $\frac{1}{2}$ wave-wound. Moulded former, $\frac{3}{8}$ in. dia. \times $\frac{5}{8}$ in., flanged, tapped 6 B.A. for fixing screws.		C	"	1
11593	Type 387 ...	I.F. diode, 180 turns 37 S.W.G. S.S. en. cu. wire, $\frac{1}{2}$ wave-wound; moulded former, $\frac{3}{8}$ in. dia. \times $\frac{5}{8}$ in., flanged, tapped 6 B.A. for fixing screws.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
11594	Type 388 ...	100 turns 40 S.W.G. S.S. en. cu. wire on moulded former, .375 in. dia. \times $1\frac{5}{16}$ in. long; 4 B.A. insert at end.		C	each	1
11617	Type 389 ...	95 turns 37 S.W.G. S.S. en. $\frac{1}{2}$ wave-wound; moulded former, $\frac{3}{8}$ in. dia. \times $\frac{5}{8}$ in., with flange at each end.		C	"	1
11612	Type 390 ...	15 turns 1 mm. en. cu. wire, $1\frac{1}{2}$ mm. pitch; internal dia. 8 mm.		C	"	1
11639	Type 393 ...	I.F. filter, moulded former (C.12098).		C	"	1
11738	Type 395 ...	Wound 170 turns per coil on former, 2.25 in. \times .75 in. dia.; frequency 10 kc/s.; inductance, 1,160 micro H.		C	"	1
11793	Type 397 ...	$1\frac{3}{8}$ in. dia. copper rod, 3 turns, $\frac{3}{8}$ in. pitch, $1\frac{5}{8}$ in. i/d, with tapping connection hole, tapped 4 B.A.		C	"	1
11794	Type 398 ...	$\frac{3}{16}$ in. dia., copper rod, 3 turns, $\frac{3}{8}$ in. pitch, $1\frac{5}{8}$ in. i/d with tapping connection hole .167 in. dia.		C	"	1
11821	Type 399 ...	70 turns 40 S.W.G. E.C. wire, $1\frac{1}{2}$ in. long \times $\frac{3}{8}$ in. dia., end wires (R.F.).		C	"	1
11822	Type 400 ...	40 S.W.G. en. Eureka wire, $\frac{1}{4}$ in. dia., bakelite former; 20 turns of 28 S.W.G. en. cu. wire.		C	"	1
11842	Type 404 ...	260 turns S.W.G. S.C.C. wave-wound, $\frac{7}{16}$ in. former.		C	"	1
11844	Type 406 ...	20 micro H., 74 turns of 16 S.W.G. wire, pile wound, $\frac{5}{16}$ in. former.		C	"	1
11849	Type 408 ...	Inductance 1 mH. 6 turns; Steatite former, $2\frac{1}{2}$ in. \times 1 in. dia.		C	"	1
11871	Type 412 ...	1 coil, 15 turns 22 S.W.G. en. wire on former, loaded ebonite, $\frac{1}{2}$ in. \times $3\frac{1}{2}$ in. long; ends tapped 6 B.A.		C	"	1
11875	Type 415 ...	D.C. 1.5 amp., multi-section, wave-wound, 100 kc/s, 1-2 mc/s., resistance 2-2 ohms.		C	"	1
11962	Type 421 ...	74 turns 30 S.W.G. en. cu. wire $1\frac{7}{16}$ in. \times $\frac{3}{8}$ in. former.		C	"	1
11963	Type 422 ...	85 micro H., 195 turns 41 S.W.G. Eureka en. wire, 3 slots, 65 turns each, on 1 in. \times $\frac{1}{4}$ in. dia. former.		C	"	1
11964	Type 423 ...	8 tappings, 7 sections, 44 turns each, 20 S.W.G. en. cu. wire, on former, 15 in. long \times $\frac{5}{16}$ in. dia.		C	"	1
11968	Type 424 ...	Tufnol former, $\frac{5}{8}$ in. \times .312 in. dia. 370 turns of 34 S.W.G. en. D.S.C. cu. wire; 1 mH \pm 5 per cent.		C	"	1
11969	Type 425 ...	85 micro H., 195 turns 41 S.W.G. en. cu., 3 slots of 65 turns each 1 in. \times $\frac{1}{4}$ in. dia. former.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
11970	Type 426 ...	34 turns 30 S.W.G. en. cu. ebonite former $1\frac{7}{16}$ in. \times $\frac{5}{16}$ in.		C	each	1
12024	Type 430 ...	Inductance 38 μ H., 82 $\frac{1}{2}$ turns 34 S.W.G. S.S.E. cu. wire, tags; Keramot rod, $\frac{1}{2}$ in. dia. \times $1\frac{3}{4}$ in. long.		C	"	1
12027	Type 433 ...	9 turns 12 S.W.G. cu. wire, air spaced, 1 in. dia. \times 2 in. long, on S.R.B.P. panel, 2 in. \times 2 in. \times $\frac{1}{8}$ in. thick.		C	"	1
12051	Type 434 ...	17 in. of 28 S.W.G. Eureka wire, wound on moulded former, $\frac{3}{16}$ in. dia. \times 1 in., spaced 1 in. dia.		C	"	1
12056	Type 435 ...	17 in. of 20 S.W.G. cu. wire on moulded former, $\frac{3}{16}$ in. dia. \times $1\frac{7}{8}$ in., spaced 1 in. dia.		C	"	1
12066	Type 436 ...	1,360 turns of 40 S.W.G. D.S.C. wire wave-wound on $\frac{1}{2}$ in. dia. bakelite former.		C	"	1
12067	Type 437 ...	130 turns 38 S.W.G. en. cu. wire wound on $\frac{3}{8}$ in. dia. former.		C	"	1
12116	Type 439 ...	4 mH \pm 5 per cent. 6 coils of 181 turns of 36 S.W.G. D.S.C. cu. wire.		C	"	1
12455	Type 465 ...	5 Leeson wound coils on ebonite former, 60 mH air core, 9 K. volt working.		C	"	1
12474	Type 467 ...	23 turns of 22 S.W.G. en. cu. wound on loaded ebonite former, threaded $\frac{3}{8}$ in. Whit., wire ends.		C	"	1
12476	Type 468 ...	4 mH \pm 5 per cent., wound on $1\frac{1}{2}$ in. o/d former, $\frac{1}{2}$ in. long.		C	"	1
12559	Type 473 ...	26 turns of 22 S.W.G. E.C. wire on moulded tube, $\frac{1}{2}$ in. dia. \times 1 in. long.		C	"	1
12560	Type 474 ...	40 turns of 30 S.W.G. E.C. wire on moulded tube, $\frac{1}{2}$ in. dia. \times 1 in. long.		C	"	1
12571	Type 475 ...	180 μ H \pm 2 per cent. Coil, 100 turns of .0076 in. dia. en. and single silk-covered copper wire, wound clockwise; $1\frac{7}{16}$ in. long \times $\frac{3}{4}$ in. dia. overall.		C	"	1
12592	Type 477 ...	12 ft. approx. of 32 S.S.C. en. cu. wire and $3\frac{1}{2}$ in. of 18 S.W.G. tinned copper wire, wound on Trolitol former.		C	"	1
12593	Type 478 ...	12 ft. approx. of 32 S.W.G. en. cu. wire S.S.C. and $3\frac{1}{2}$ in. of 18 S.W.G. tinned cu. wire, wound on Trolitol former and mounted on 2 pillars.		C	"	1
12636	Type 481 ...	57 turns No. 37 S.W.G. S.S. en. cu. wire, wave-wound, on Keramot former.		C	"	1
12755	Type 488 ...	6 sections wound on $\frac{1}{4}$ in. bakelite rod, $2\frac{3}{4}$ in. long; each section 190 turns of 38 S.W.G. en. S.C.C. 250 μ H \pm 5 per cent.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
12760	Type 493 ...	45 c.m.s. of S.W.G. en. wire wound in 42 spaced turns on $\frac{1}{4}$ in. dia. Tufnol former.		C	each	1
12916	Type 502 ...	17 turns of 22 S.W.G. E.C. wire, close wound, tags.		C	"	1
12937	Type 504 ...	22 turns of 20 S.W.G., space wound, on bakelite former, $\frac{1}{4}$ in. dia. \times $1\frac{1}{8}$ in. long.		C	"	1
13049	Type 513 ...	120 turns of 38 S.W.G. D.S.C. on fine D.C.C. wire on former of Durex tape, wax dipped; $150 \mu\text{H} \pm 3 \mu\text{H}$.		C	"	1
13079	Type 516 ...	12 ft. approx. of 32 S.W.G. S.S.C. en. cu. wire wound on Keramot former.		C	"	1
13089	Type 517 ...	26 S.W.G. en. cu. wire wound on former to cover whole area with one layer.		C	"	1
13097	Type 518 ...	28 in. 26 S.W.G. S.S.C. wound on $\frac{1}{4}$ in. Tufnol former, $2\frac{1}{2}$ mH at 100 mA.		C	"	1
13109	Type 520 ...	6 in. of 22 S.W.G. wound into $\frac{1}{8}$ in. dia. coil.		C	"	1
13151	Type 523 ...	9 ft. 6 in. of 43 S.W.G. en. copper wire on former.		C	"	1
13152	Type 524 ...	9 ft. 10 in. of 43 S.W.G. copper wire on former.		C	"	1
13157	Type 525 ...	Inductance $470 \mu\text{H} \pm 5$ per cent. 17.3 ohms D.C. resistance.		C	"	1
13158	Type 526 ...	$18\frac{3}{4}$ in. of S.W.G. en. copper wire on former, adjustable core, $3\frac{3}{4}$ in. of sleeving.		C	"	1
13159	Type 527 ...	25 in. of 30 S.W.G. en. copper wire on former, adjustable core, $3\frac{3}{4}$ in. of sleeving.		C	"	1
13160	Type 528 ...	$23\frac{1}{2}$ in. of 30 S.W.G. en. copper wire on former, adjustable core, $3\frac{3}{4}$ in. of sleeving.		C	"	1
13162	Type 529 ...	$16\frac{1}{2}$ in. of 30 S.W.G. en. copper wire on former, adjustable core, $1\frac{1}{2}$ in. of sleeving.		C	"	1
13163	Type 530 ...	$16\frac{1}{2}$ in. of 30 S.W.G. en. copper wire on former, adjustable core, 1 in. of sleeving.		C	"	1
12173	Type 531 ...	30 in. of $\frac{1}{4}$ in. dia. copper wire; 8 turns 1 in. i/d \times $3\frac{1}{2}$ in. long, complete with flexible connections and clamp.		C	"	1
13225	Type 533 ...	12 turns of 26 S.W.G. copper wire on former.		C	"	1
13226	Type 534 ...	6 turns of 26 S.W.G. copper wire on former.		C	"	1
13227	Type 535 ...	11 turns of 26 S.W.G. copper wire on former.		C	"	1
13280	Type 538 ...	Winding—5 sections, each $\frac{3}{16}$ in. wide, Leeson wound. Former, moulded bakelite, $\frac{1}{2}$ in. dia. \times $1\frac{3}{8}$ in. long, with 4 B.A. studs, tags, and nuts each end.		C	"	1
13314	Type 540 ...	11 turns 31 S.W.G. enam. copper wire on loaded ebonite former, .25 in. dia. \times .75 in., tapped 6 B.A. one end.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
13315	Type 541 ...	13 turns 30 S.W.G. en. on loaded ebonite former, .25 in. dia. × 1.22 in., one end tapped 6 B.A. hole.		C	each	1
13399	Type 552 ...	25 turns 26 S.W.G. en. cu. wire Trohtol former. (Former coil, Type 1.)		C	"	1
13422	Type 555 ...	25 turns 20 S.W.G. en. cu. wire		C	"	1
13442	Type 557 ...	10 turns 18 gauge tinned copper wire, $\frac{1}{4}$ in. i/d.		C	"	1
13474	Type 559		C	"	1
13482	Type 560 ...	12 in. of 30 S.W.G. en. copper wire on former, adjustable core, $1\frac{1}{4}$ in. of sleeving.		C	"	1
13483	Type 561 ...	20 turns 18 S.W.G. en. cu. wire on Tufnol former, $1\frac{1}{2}$ in. × $\frac{1}{2}$ in. o/d.		C	"	1
13561	Type 564 ...	25 turns 38 S.W.G. en. cu. wire. 2 windings.		C	"	1
13580	Type 565 ...	108 turns of 40 S.W.G. copper wire on $\frac{1}{4}$ in. dia. former.		C	"	1
13584	Type 566 ...	92 turns of 38 S.W.G. copper wire on $\frac{1}{4}$ in. dia. former.		C	"	1
13596	Type 568 ...	20 turns of 22 S.W.G. wire D.S.C. wire on insulating former, $1\frac{1}{2}$ in. × $\frac{1}{2}$ in. dia. 2 Eureka spills. Screwed on 8 B.A.		C	"	1
13641	Type 570 ...	Inductance 700 μ H. 700 μ H. per section.		C	"	1
13642	Type 571 ...	4 μ H. 480 turns 38 S.W.G. D.S.C. copper wire; with moulded cover.		C	"	1
13656	Type 572 ...	25 μ H \pm 10 per cent. 60 turns 40 S.W.G. double enam. copper on bakelite bobbin former, 1 in. × $\frac{3}{8}$ in.		C	"	1
13657	Type 573 ...	4.7 μ H. 33 $\frac{3}{4}$ turns 22 S.W.G. wire on bakelite bobbin former, $1\frac{5}{16}$ in. × $\frac{7}{16}$ in.		C	"	1
13659	Type 575 ...	3.95 μ H nominal. 18 turns 30 S.W.G. (tapped 4 turns) en. copper on moulded former, with core.		C	"	1
13660	Type 576 ...	3.83 μ H nominal. 18 turns + 4 turns overwound. 30 S.W.G. en. copper wire, moulded former, with dust iron core.		C	"	1
13661	Type 577 ...	1 to 1.55 μ H. 10 $\frac{1}{2}$ -turns 22 S.W.G. en. copper wire, moulded former, with dust iron core.		C	"	1
13662	Type 578 ...	47 mics. \pm 10 per cent. 34 $\frac{1}{2}$ -turns 22 S.W.G. en. copper wire on $1\frac{1}{2}$ in. × $\frac{7}{16}$ in. former.		C	"	1
13669	Type 580 ...	10 turns 30 S.W.G. enam. copper wire, tapped at 7 $\frac{1}{2}$ turns.		C	"	1
13714	Type 5851 ohms, heater. 17 turns of 32 S.W.G. enam. copper wire, space wound.		C	"	1
13721	Type 587 ...	25 μ H, 10 per cent. 60 $\frac{1}{2}$ turns 40 S.W.G. double enam. copper on former, 1 in. × $\frac{3}{8}$ in.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
13742	Type 590 ...	Wire-wound, 26 S.W.G. E.C. wire on bakelite former, 1 in. $\times \frac{1}{4}$ in.		C	each	1
13743	Type 591 ...	Wire-wound, 40 S.W.G. enam. copper wire on bakelite former, $1\frac{1}{2}$ in. $\times \frac{3}{8}$ in. dia.		C	"	1
13744	Type 592 ...	Wire-wound, 11 turns 22 S.W.G. enam. copper, $\frac{3}{8}$ in. dia.		C	"	1
13745	Type 593 ...	Wire-wound, 20 turns 22 S.W.G. enam. copper, $\frac{1}{8}$ in. i/d.		C	"	1
13746	Type 594 ...	Wire-wound, 14 turns 20 S.W.G. enam. copper, $\frac{3}{8}$ in. i/d.		C	"	1
13747	Type 595 ...	Paxolin former, $\frac{1}{2}$ in. o/d $\times \frac{3}{8}$ in. i/d $\times 1\frac{1}{4}$ in. Wound $7\frac{1}{2}$ turns 18 S.W.G. enam. copper wire.		C	"	1
13750	Type 596 ...	S.W. $1 \mu\text{H} \pm 15$ per cent., ind. 250 mA. Wire-wound, 3 sections on former, $1\frac{1}{2}$ in. $\times \frac{7}{8}$ in.		C	"	1
13774	Type 597 ...	30 mH former, $\frac{3}{8}$ in. $\times 2\frac{1}{4}$ in., including end wires. 75 turns of 38 gauge D.S.C.		C	"	1
13776	Type 598 ...	22 S.S.C. wound on $\frac{3}{4}$ in. $\times 1\frac{1}{4}$ in. former.		C	"	1
13789	Type 600 ...	$185 \mu\text{H} \pm 10$ per cent. Wound 20 S.W.G. copper on former with dust iron core.		C	"	1
13857	Type 601 ...	40 turns 24 S.W.G. T.C. ...		C	"	1
13895	Type 603 ...	30 turns 24 S.W.G. enam. copper wire. Former, $\frac{3}{8}$ in. dia. $\times 1\frac{1}{4}$ in. long, paxolin.		C	"	1
13896	Type 604 ...	400 turns 34 S.W.G. silk copper wire.		C	"	1
13911	Type 606 ...	240 mH. Approx. 450 yds. 26 S.W.G.		C	"	1
13919	Type 607 ...	2 sections, wave-wound single, 175 turns each section, continuous between windings; and 1 section, 350 turns wave-wound single .006 in. cu. wire, on S.R.B.P. former, .25 in. dia. $\times 2$ in.		C	"	1
13954	Type 608 ...	24 turns 22 S.W.G. en. wire, paxolin former, $\frac{1}{4}$ in. dia. $\times 1\frac{1}{8}$ in.; 22 S.W.G. terminal wires, fitted with bracket.		C	"	1
13966	Type 609 ...	23 turns 28 S.W.G. en. copper wire on Trolitol former.		C	"	1
14017	Type 614 ...	40/80 μH		C	"	1
14062	Type 617 ...	10C modified to 3 turns ...		C	"	1
14065	Type 618 ...	28 turns of 30 S.W.G. en. cu. wire on former, $\frac{3}{8}$ in. $\times 1\frac{1}{4}$ in. long; 40 turns 30 S.W.G. en. cu. on former, $\frac{1}{2}$ in. dia. $\times 2$ in. long.		C	"	1
14066	Type 619 ...	40 turns of 30 S.W.G. wire wound on former, $\frac{1}{2}$ in. dia. $\times 2$ in. long.		C	"	1
14077	Type 620 ...	Used on T.1440 and T.1440A ...		C	"	1
14090	Type 622 ...	Loaded ebonite, $1\frac{1}{4}$ in. $\times \frac{3}{8}$ in. o/d. 55 turns of 48 S.W.G. D.S.C. copper wire, close wound.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
14101	Type 623	... 25 turns 24 S.W.G. en. wire, wound on EK Cole former, Type 12098.		C	each	1
14102	Type 624	... 95 turns 40 S.W.G. en. copper wire wound on laminated former (Murphy V.C.21278).		C	..	1
14103	Type 625	... 35 turns 24 S.W.G. enamelled...		C	..	1
14104	Type 626	... Eddystone 1010 H.F. Choke has 4 sections of $\cdot 25 \mu\text{H}$, each of 3 interconnections are unwound and taken down to tag panel.		C	..	1
14108	Type 627	... $35 \mu\text{H} \pm 20$ per cent. ...		C	..	1
14109	Type 628	... $110 \mu\text{H} \pm 20$ per cent. ...		C	..	1
14110	Type 629	... $146 \mu\text{H} \pm 20$ per cent. ...		C	..	1
14111	Type 630	... $44 \mu\text{H} \pm 20$ per cent. ...		C	..	1
14135	Type 633	... 48 turns 24 gauge iron wire on former (Siemen's S.O.2351).		C	..	1
14156	Type 635	... 630 turns 38 S.W.G. D.W.S. wire on paxolin former, $1\frac{3}{16}$ in. $\times \frac{1}{2}$ in. dia., with base and cover, 1.576 in. o/d \times 1 ft. 9 in.		C	..	1
14159	Type 636	... $6 \mu\text{H} \pm 5$ per cent. 25 turns of 24 S.W.G. D.S.C. copper wire.		C	..	1
14221	Type 641	... $4 \mu\text{H} \pm 50$ per cent., 20 mA. Wave-wound. Insulation 350 volts.		C	..	1
14234	Type 643	... $3\cdot 3 \mu\text{H}$. 23 turns 28 S.W.G. en. cu. wire, close wound on ebonite former.		C	..	1
14235	Type 644	... 18 turns 22 S.W.G. en. cu. wire wound close on loaded ebonite former.		C	..	1
14294	Type 647	... 9 turns 26 gauge S.W.G. en. copper wire on former.		C	..	1
14319	Type 652	... Noise modulator peaking coil. 7 sections, each 13 OT 38 S.W.G. D.S.C., former of ebonite, 1.89 in. long $\times \frac{1}{2}$ in. dia.		C	..	1
14320	Type 653	... H.F. fitter coil, $1\cdot 2 \mu\text{H} \pm 5$ per cent. Each bank of 4 banks; each 345 turns 36 D.S.C. Ebonite former, $2\frac{7}{16}$ in. $\times \frac{3}{8}$ in.		C	..	1
14326	Type 654	... Modulator, $60 \mu\text{H} \pm 10$ per cent. 1 bank of 2,000 turns of 36 D.S.C. Former of bakelite tubing, $\frac{1}{2}$ in. o/d $\times \frac{1}{4}$ in. i/d $\times 11\frac{3}{8}$ in. long.		C	..	1
14330	Type 655	... 265 turns of 44 S.W.G. enam. copper wire, close wound. Inductance, $100 \mu\text{H} \pm 10$ per cent.		C	..	1
14362	Type 657	... Inductance 2 H, current 80 mA		C	..	1
14363	Type 658	... D.S.C. former, 4 in. long $\times \frac{5}{8}$ in. dia. W.T. 22 rod, 40 turns 26 S.W.G.		C	..	1
14425	Type 659	... Anode. $2 \mu\text{H}$ D.C. Resistance max., 60 ohms, 1.5 amps. D.C. $5\frac{11}{16}$ in. dia. $\times 13\frac{1}{8}$ in. high.		C	..	1
14426	Type 660	... Inductance 20 H, current 60 mA		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
14441	Type 661 ...	2 yds. 28 S.W.G. cu. S.S.C., 20 yds. 40 S.W.G. en. S.S.C., wound on former, $\frac{3}{4}$ in. long $\times \frac{1}{2}$ in. dia.		C	each	1
14487	Type 664 ...	24 turns 23 S.W.G. enam. on paxolin strip.		C	..	1
14502	Type 665		C	..	1
14505	Type 667 ...	Ind. 700 μ H \pm 5 per cent. Upper unit coil, wound in 2 parts, each to consist of 145 turns of 30 S.W.G. D.S.C. wire, wave-wound on former. Overall dia. of coil, approx. 1 in., two parts wound in same direction $\frac{3}{4}$ in. apart.		C	..	1
14513	Type 668 ...	Ind. 26,000 μ H \pm 10 per cent. Lower unit, 6 coils wound in same direction, each to consist of 310 turns of 30 S.W.G. D.S.C. enam. wire, wound on former, dia. 1.312 in. overall \times .265 in. thick, 1.79 in. over coils.		C	..	1
14541	Type 671 ...	Ind. 9.3 mH \pm 20 per cent., 1 amp. D.C., 450 turns wire. Open, air cooled, tripple bank; wound on annular porcelain former.		C	..	1
14579	Type 674 ...	36 turns 38 S.W.G. enam. copper wire, $\frac{1}{4}$ in. dia. former.		C	..	1
14580	Type 675 ...	36 turns 28 S.W.G. enam. copper wire, bakelite laminated former.		C	..	1
14634	Type 681 ...	10 mH. 750 turns 38 S.W.G. wire wound on 3 banks of 250 turns each. Former, $1\frac{1}{2}$ in. dia. \times $1\frac{3}{4}$ in. long with dust iron core.		C	..	1
14653	Type 682 ...	Ind. 1.1 henries at 120 mA, 5 volts, 50 cycles, D.C. Res., 130 ohms.		C	..	1
14714	Type 683 ...	Pile wound with 18 S.W.G. copper wire in 7 sections; 9 turns per section, equally spaced on S.R.V.T. former, with iron dust core.		C	..	1
14715	Type 684 ...	300 turns D.S.C. copper wire, wave-wound, $\frac{1}{2}$ in. wide, 1,100 mH \pm 10 per cent., D.C. resis. 2,850 ohms, on moulded former.		C	..	1
14716	Type 685 ...	36 turns close-wound 18 S.W.G. wire, "Bicolon" M covered copper wire, on loaded ebonite former.		C	..	1
14733	Type 686 ...	Filament choke. 32 turns of 20 S.W.G. silk covered wire on S. R. B. P. tubular former. $1\frac{3}{8}$ in. long \times $\frac{3}{4}$ in. o/d \times $\frac{1}{8}$ in. i/d, wire ends.		C	..	1
14766	Type 687 ...	1 mH. Wave-wound		C	..	1
14769	Type 688 ...	500 mH. 200 turns 38 D.S.C. $\frac{1}{16}$ in. former.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
14884	Type 691 ...	Ind. 4 mH. 600 turns .0076 in. wire. Size—Overall length $1\frac{9}{16}$ in. Wave-wound on $\frac{3}{4}$ in. dia. former.		C	each	1
14926	Type 693 ...	Ind. 1 mH \pm 5 per cent. 155 turns 36 S.W.G. en. copper S.C.C. on bobbin.		C	..	1
14969	Type 694 ...	Wave-wound, 4 in. \times $3\frac{1}{4}$ in. dia., with mounting insulator and terminal connectors.		C	..	1
14975	Type 696 ...	5 turns 28 S.W.G. en. cu. wire on Pye former.		C	..	1
14976	Type 697 ...	7 turns 26 S.W.G. en. cu. wire		C	..	1
15007	Type 699 ...	19 coils choke mounted on frame, with 2 mounting feet, $7\frac{1}{8}$ in. long \times $2\frac{3}{8}$ in. high \times $1\frac{3}{8}$ in. wide.		C	..	1
15028	Type 700		C	..	1
15031	Type 701 ...	Ind. $6\ \mu\text{H} \pm 5$ per cent. Number of turns, $100\frac{1}{2} \pm 1\cdot018$ in. D.S.C. copper wire. Loaded ebonite former, end wires.		C	..	1
15065	Type 702 ...	Wound on former and fitted with iron dust core, tapped at 3 turns.		C	..	1
15066	Type 703 ...	$11\frac{1}{2}$ primary and $4\frac{1}{2}$ secondary turns 26 S.W.G. en. cu. wire, wound on former and fitted with dust iron core.		C	..	1
15124	Type 706 ...	Ind. 10 mH. 3 coils, 350 turns each of 37 D.S.C. wire.		C	..	1
15165	Type 708 ...	Ind. $1\cdot6\ \mu\text{H} \pm 10$ per cent. 3 coils in series, single wave-wound, 280 turns each of 40 S.W.G.		C	..	1
15176	Type 709 ...	25 turns 22 S.W.G. enam. copper wire on S. R. B. P. former, .187 in. dia. \times 2.12 in.		C	..	1
15179	Type 710 ...	Ind. 3.46 mH. Number of turns, 5 section each, 150, 36 S.W.G. D.R.C. copper wire. Size of former, $\frac{1}{2}$ in. dia. \times $2\frac{3}{4}$ in.		C	..	1
15177	Type 711 ...	Complete assembly on moulded base. Ind. 21 microhenries at 1,000 c.p.s.		C	..	1
15178	Type 712 ...	As Type 711 but opposite hand		C	..	1
15218	Type 714 ...	4 in. of 24 S.W.G. wire, tight wound on $\frac{5}{16}$ in. former.		C	..	1
15279	Type 715 ...	17 in. of 28 S.W.G. enam. wire, spaced one dia. on former, $1\frac{1}{16}$ in. long \times $\frac{3}{16}$ in.		C	..	1
15861	Type 717 ...	66 turns of S.W.G. copper wire, single layer on $\frac{3}{8}$ in. dia. former.		C	..	1
15918	Type 718 ...	940 mics. wire wound on tubular porcelain former, 1 ft. 6 in. \times $2\frac{13}{16}$ in. dia., with copper end straps.		C	..	1
15920	Type 720 ...	Wound on S.R.P.T. former, $\frac{1}{2}$ in. o/d and $\frac{3}{8}$ in. long; Leeson wound single wave on S.R.B.P., $\frac{1}{2}$ in. o/d \times 1.375 mH.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
15972	Type 723 ...	Ind. 4,250 microhenries. W. wound on $5\frac{1}{4}$ in. porcelain former with end straps.		C	each	1
15982	Type 725 ...	$41\frac{3}{8}$ turns 22 S.W.G. en. cu. wire wound in 3 layers and 30 turns wound in 2 layers. Moulded former with 3 washers.		C	"	1
15983	Type 726 ...	69 turns 30 S.W.G. en. cu. wire wound in 3 layers on former.		C	"	1
15984	Type 727 ...	72 turns 30 S.W.G. en. cu. wire wound in one layer on former.		C	"	1
15991	Type 729 ...	24 turns 22 S.W.G. en. cu. wire. Size $\frac{11}{32}$ in. \times $\frac{1}{4}$ in. dia. on S.R.B.P. Drilled and tapped one end 6 B.A. for mounting.		C	"	1
15992	Type 730 ...	28 turns 18 S.W.G. "Bicelon" or Newmex wire. Size, 2 in. \times $\frac{3}{8}$ in. \times $\frac{1}{4}$ in., on S.R.B.P. former. One fixing hole 6 B.A. clearance.		C	"	1
15993	Type 731 ...	24 turns 26 S.W.G. en. cu. wire on S.R.B.P. former, One fixing hole 6 B.A. clearance.		C	"	1
15994	Type 732 ...	24 turns 24 S.W.G. en. cu. wire. Size, $1\frac{1}{32}$ in. \times $\frac{1}{4}$ in. dia., on S.R.B.P. former. Drilled and tapped one end 6 B.A. for mounting.		C	"	1
15995	Type 733 ...	5 coil choke, resistance 1.5 ohms per coil; mounted in frame with 2 mounting brackets. Size, $3\frac{3}{4}$ in. \times $2\frac{3}{4}$ in. high \times $\frac{3}{4}$ in.		C	"	1
16038	Type 735 ...	Ind. 200 mH. 34 S.W.G. D.S.C. wire, wave-wound on $\frac{1}{4}$ in. dia. former. Dim. of winding, $\frac{1}{8}$ in. wide \times $\frac{5}{8}$ in. dia.		C	"	1
16070	Type 739 ...	$8.5 \mu\text{H} \pm 5$ per cent. 2 sections of 500 turns, 29 turns per layer of 38 S.W.G. S.S.C. enam. cu. wire. Single wave-wound on S.R.B.P. former, 2 in. long \times $\frac{1}{4}$ in. dia. 6 B.A. threaded brass insert at end for mounting.		C	"	1
16076	Type 740 ...	Ind. $1,350 \mu\text{H} \pm 10$ per cent. 4 bank wave-wound on former $\cdot 187$ in. dia. \times 1 in. long; includes one fixing bracket.		C	"	1
16077	Type 741 ...	$330 \mu\text{H} \pm 10$ per cent. 4 bank wave-wound on former $\cdot 187$ in. \times $\cdot 937$ in.; includes one fixing bracket.		C	"	1
16078	Type 742 ...	Ind. $13 \mu\text{H} \pm 5$ per cent. Close wound on former $\cdot 187$ in. \times $\cdot 937$ in. long.		C	"	1
16079	Type 743 ...	Ind. $62 \mu\text{H} \pm 10$ per cent. Single bank wire wound on former $\cdot 187$ in. \times $\cdot 5$ in. long.		C	"	1
16110	Type 746 ...	17 sections of 180 turns of 36 S.W.G. wire on S.R.B.P. former, size $6\frac{1}{2}$ in. \times $1\frac{1}{16}$ in. dia. Fitted with 18 pins.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
16119	Type 747 ...	Ind. 275 μ H \pm 10 per cent. Single bank, wave-wound on bakelite former .187 in. dia. \times .406 in. long.		C	each	1
16162	Type 749 ...	Number of turns 67 c.m.s. \pm 1 cm. 24 S.W.G. en. cu. wire wound on S.R.B.P. former, 1.593 in. long \times .1875 in. dia.		C	..	1
16220	Type 756 ...	Ind. 2.15 μ H \pm 5 per cent. 375 turns 40 S.W.G. en. cu. wire wave-wound on hollow S.R.B.P. former, 1 $\frac{1}{2}$ in. long \times $\frac{1}{2}$ in. dia., with connecting tags.		C	..	1
16221	Type 757		C	..	1
16264	Type 761 ...	Ind. 500 micro H. S.S.C. enam. wire, wound in 3 sections on $\frac{1}{4}$ in. Tufnol rod, each section 159 turns. Tropical.		C	..	1
16265	Type 762 ...	Ind. 700 micro H. S.C.C. enam. wire, wound in 4 sections on $\frac{1}{4}$ in. dia. Tufnol rod, each section 163 turns.		C	..	1
16266	Type 763 ...	6 turns 26 S.W.G. en. cu. wire. Tapped at 2 $\frac{1}{2}$ turns on former.		C	..	1
16885	Type 775 ...	Ind. 5.6 mH. D.C. Resistance 1.3 ohms.		C	..	1
16930	Type 776 ..	Feed reactor ind. .1 H. Tapped .7 \pm 5 per cent.		C	..	1
16931	Type 777 ...	Feed reactor ind. 15 H. 1.4 amps. D.C.		C	..	1
16958	Type 779 ...	Ind. 1.5 mH. 190 turns \pm 10 per cent., 4 sections, 34 S.W.G.		C	..	1
16978	Type 780 ...	Ind. 150 mH		C	..	1
16980	Type 781 ...	Ind. 400 mH. 376 turns (4 sections, 94 turns per section) of 40 S.W.G. en. cu. wire.		C	..	1
17511	Type 782 ...	32 turns 26 S.W.G. wire close wound on former 1 in. \times $\frac{3}{16}$ in. 18 S.W.G. wire ends.		C	..	1
17517	Type 783 ...	1.5 mH \pm 10 per cent. 375 turns S.W.G. on Ekco former; colour code blue and black.		C	..	1
17518	Type 784 ...	40 μ H \pm 5 per cent. Wave-wound. 57 turns of 34 S.W.G. on Ekco former; colour code blue and blue.		C	..	1
17532	Type 790 ...	Ind. 1.45 mH		C	..	1
17561	Type 792 ...	5 mH. 820 turns of 40 S.W.G. enam. wire on P.O. bobbin W4/1.		C	..	1
17605	Type 794 ...	17 millihenries \pm 10 per cent. 1,415 turns, wave-wound, of D.S.C. copper sire.		C	..	1
17606	Type 795 ...	50 mH, 10 per cent., wound on on W4/3 distrene bobbin 1.72 in. o/d.		C	..	1
17607	Type 796 ...	50 mH \pm 10 per cent., wound on 1,800 T of 2 W4/3 bobbins 1.172 in. o/d.		C	..	1
17620	Type 798 ...	45 mH \pm 5 per cent. Tunes at 10 kc/s with 500 μ F. Wire wound on polystyrene bobbin, 4.5 microhenries, 1,500 turns 42 en.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	H.F.—cont.					
17621	Type 799 ...	Ind. 120 mH \pm 5 per cent. Tunes at 60 kc/s with 50 μ F. 2,450 turns 42 en.		C	each	1
17622	Type 800 ...	Ind. 13 mH \pm 5 per cent. Tunes at 100 kc/s with 175 μ F. 840 turns 38 en.		C	"	1
17641	Type 802 ...	Ind 5 μ H \pm 5 per cent. 10 turns of 9/47 E. and S.S. wire, W4/2A core; W4/4 bobbin, insulating pillar and platform.		C	"	1
17675	Type 805 ...	Ind. 12 mH. 10 turns ...		—	—	—
17693	Type 806 ...	5 mH		C	each	1
17731	Type 813 ...	Ind. 14 ohms \pm 5 per cent. 18 turns 40 S.W.G. Eureka wire D.S.C. coil.		C	"	1
17834	Type 829 ...	17 turns of 22 S.W.G. en. cu. wire on former. Tropical version of 10C/16069, Type 738.		C	"	1
17846	Type 830 ...	180 μ H. 36 S.W.G. D.S.C. wire on $\frac{1}{4}$ in. former; to resonate at 600 kc/s 1,400 μ F.		C	"	1
17847	Type 831 ...	65 μ H. 36 S.W.G. D.S.C. wire on $\frac{1}{4}$ in. former; to resonate 1 mc/s 1,400 μ F.		C	"	1
17868	Type 832 ...	129 turns of 38 S.W.G. D.S.C. en. cu. wire, on former. Ind. 120 μ H \pm 5 per cent. Moulded in polythene. Approx. dims. 1 $\frac{1}{16}$ in. long \times $\frac{5}{8}$ in. dia.		C	"	1
18010	Type 833 ...	13 MH \pm 5 per cent. at 1,000 cycles; 2 sections of honeycomb winding on DL 9 tube $\frac{1}{2}$ in. \times 1 in., 2 terminals on strip $\frac{1}{2}$ in. \times 1 $\frac{3}{8}$ in. long.		C	"	1
18012	Type 834 ...	5 $\frac{1}{2}$ turns 16 S.W.G. en. cu. wire, wound on 1 $\frac{1}{8}$ in. \times $\frac{3}{8}$ in. dia. former.		C	"	1
18013	Type 835 ...	46 turns 24 S.W.G. en. cu. wire, wound on 2 $\frac{1}{8}$ in. \times $\frac{3}{8}$ in. dia. former.		C	"	1
18018	Type 836 ...	Wire ends, self-supporting ...		C	"	1
18019	Type 837 ...	Wire ends, self-supporting ...		C	"	1
17886	Type 838 ...	20 turns 26 S.W.G. enam. wire on $\frac{5}{16}$ in. distrene former, $\frac{3}{4}$ in. long, with 16 S.W.G. wire ends $\frac{5}{8}$ in. long.		C	"	1
17970	Type 842 ...	500 μ H \pm 10 per cent. at 100 c/s. 384 turns (96 turns per sec.) 44 S.W.G. en. cu. wire.		C	"	1
17971	Type 843 ...	150 μ H \pm 10 per cent. at 1,000 c/s. 236 turns (59 turns per sec.) 36 S.W.G. en. cu. wire.		C	"	1
18109	Type 845 ...	1.25 mH, 22 ohms D.C. resistance. Wound in 4 banks and polythene dipped.		C	"	1
18156	Type 8548 mH \pm 10 per cent. 3 coils in C series, 185 turns of 40 S.W.G. S.S.C. en. cu. wire. Single wave-wound on former 1 $\frac{3}{16}$ in. long \times $\frac{1}{4}$ in. dia.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.:—					
15702	5 H. 150 MA		C	each	1
15701	10 H. 150 MA		C	"	1
15703	50 H. 2 MA		C	"	1
7384	Type B ...	Iron core choke, with bakelite former. Overall dims. 2 in. × 2½ in. × 1¾ in.		C	"	1
7512	Type C ...	Iron core power smoothing choke, with paxolin bobbin; air gap, .15 in. Overall dims. 8¾ in. × 8¼ in. × 6½ in.		C	"	1
7912	Type G ...	Iron core choke, with bakelite former. Overall dims. 2 in. × 1½ in. × 1¼ in.		C	"	1
8634	Type J ...	Iron core, .009 henries, 15 amps.		C	"	1
9341	Type M ...	Iron core choke, with moulded cover, 2¼ in. × 2¼ in. × 2 in. overall. 4 henries, 150 millihenries.		C	"	1
9497	Type N ...	Iron core, .08 in. gap, 3½ in. × 3½ in. × 5 in. overall approx. Fitted with mounting, Type 13, Ref. No. 10A/9882.		C	"	1
9606	Type R ...	Iron core, 30/20 henries, 0–150 mA, 6⅝ in. × 4½ in. × 3¼ in. overall.		C	"	1
9607	Type S ...	Iron core, 300 henries, metal cased, 3 in. × 3¼ in. × 3¼ in. overall.		C	"	1
9628	Type T ...	Iron core, 2¾ in. × 2⅝ in. × 1⅝ in. overall.		C	"	1
42	Type W ...	Open type, 2⅝ in. × 1¾ in. × 1¾ in. high. Black varnish impregnated, with tag panel at top.		C	"	1
72	Type 26 ...	Smoothing		C	"	1
74	Type 28 ...	Mains		C	"	1
76	Type 30 ...	Smoothing		C	"	1
77	Type 31		C	"	1
78	Type 32 ...	4,500 turns of .0148 in. dia. en. cu. wire, open type.		C	"	1
81	Type 33 ...	8,000 turns of .0048 in. en. cu. wire, 1,440 ohms approx., open type, 2¾ in. × 1¾ in. × 2¼ in., with tag panel at top.		C	"	1
448	Type 39 ...	30/7 henries, 100 mA, 215 ohms, 500 volts, D.C.		C	"	1
449	Type 40		C	"	1
520	Type 42 ...	Ind. 150 μH. C.–D.C.R. ...		C	"	1
571	Type 44 ...	45 henries with 30 mA, D.C., 20 volts A.C., 1,090 ohms D.C.		C	"	1
572	Type 45 ...	8 henries with 8 mA, D.C., and 20 volts A.C., 115 ohms D.C.		C	"	1
579	Type 46 ...	1.21–99 henries, 143–117 ohms		C	"	1
580	Type 4722 henries approx. at approx. 2.5 volts, 1,000 cycles.		C	"	1
581	Type 488 to .5 henries, 12.6 to 10.44 ohms.		C	"	1
582	Type 49 ...	1 henry approx. at approx. 1 volt, 1,000 cycles.		C	"	1
605	Type 50 ...	2.50 henries at 150 mA, 42.5 ohms D.C. resistance.		C	"	1
658	Type 5135 henries ± 20 per cent. 400 mA. D.C. Resistance 4.1 ohms. 20 per cent.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
826	Type 52 ...	4 millihenries, 50 turns, 20 S.W.G. on $\frac{3}{8}$ in. former.		C	each	1
846	Type 55 ...	8 henries ...		C	"	1
2061	Type 57 ...	$2\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. overall leads, mexpthalte dipped.		C	"	1
2092	Type 58 ...	32 henries, 370 ohms ...		C	"	1
2093	Type 59 ...	20 henries, 180 ohms ...		C	"	1
2098	Type 60 ...	Ind., 4 henries at 50 cycles at 30 mA.		C	"	1
2142	Type 63 ...	1,400 ohms ...		C	"	1
2143	Type 64 ...	200 ohms ...		C	"	1
2184	Type 65 ...	Smoothing, 10 henries. Inductance at 100 mA D.C., insulated for 1,000 volts D.C.		C	"	1
2187	Type 66 ...	Smoothing ...		C	"	1
2226	Type 67 ...	Smoothing ...		C	"	1
2273	Type 69 ...	10 henries, 200 mA A.C. + 150 mA D.C.		C	"	1
2279	Type 70 ...	100 henries, 5 mA ...		C	"	1
2289	Type 71 ...	325 henries approx. at approx. 7 volts, 1,000 cycles.		C	"	1
2296	Type 72 ...	7 henries, 5 amps. D.C., 700 volts insulation.		C	"	1
2297	Type 73 ...	7 henries, 3 amps., 2,000 volts insulation.		C	"	1
2298	Type 74 ...	100 mA, 215 ohms, 500 volts ...		C	"	1
2367	Type 75 ...	D.C. working, 47.7 henries. Used in pairs with transformer, Type 210, Ref. No. 10KB/31.		C	"	1
2446	Type 76 ...	1,200 henries \pm 20 per cent. ...		C	"	1
2376	Type 77		C	"	1
2552	Type 79 ...	Iron core ...		C	"	1
2555	Type 80 ...	Smoothing ...		C	"	1
2570	Type 82 ...	10 henries at 500 mA D.C. ...		C	"	1
2576	Type 83 ...	Smoothing, 10 henries inductance at 50 mA, $3\frac{1}{2}$ in. \times $2\frac{3}{4}$ in. \times 4 in., overall, $2\frac{1}{8}$ in. \times $3\frac{1}{8}$ in. fixing centres, 3lb. nett.		C	"	1
2580	Type 84 ...	1,000 cycles, smoothing, tropical		C	"	1
2582	Type 86 ...	Tapped smoothing, 5.2 henries \pm 5 per cent. + 4 henries \pm 5 per cent. Open type, 3 in. \times 2 in. \times $3\frac{1}{2}$ in. high, with tag panel at base.		C	"	1
2595	Type 88 ...	Smoothing ...		C	"	1
2596	Type 89 ...	Smoothing ...		C	"	1
2601	Type 90 ...	Open type, $2\frac{1}{8}$ in. \times $1\frac{1}{2}$ in. \times 2 in. high, with tag panel; tropical, black varnish, impregnated.		C	"	1
2643	Type 91 ...	6 henries, 130 mA D.C. Open type, $2\frac{1}{2}$ in. \times 2 in. \times 3 in. high.		C	"	1
2692	Type 92 ...	Tapping switch reaction, for use with transformer, Type 226 (10K/57). With choke, 7.7 volts at 2.5 A. Not more than 10.8 volts at 5 A.		C	"	1
2761	Type 94001 mA, mica moulded, 1,000 volts.		C	"	1
2763	Type 95 ...	100 henries, .005 amps. ...		C	"	1
2764	Type 96 ...	10 volts at 7 amps. and 14 volts at 14 amps.		C	"	1
2765	Type 97 ...	1.7 volts at 7 amps. and 2.5 volts at 14 amps.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
2851	Type 98 ...	Ind. 8 H ± 10 per cent., at 250 m/amps., D.C., oil filled; overall size 4 in. × 4 ⁵ / ₃₂ in. × 5 ³ / ₄ in.		C	each	1
2858	Type 99 ...	Ind. 4.2 henries, 3 amps. D.C....		C	"	1
2866	Type 100 ...	3 henries at 60 mA D.C. Resistances 200 ohms D.C. Enclosed in tank filled with Kingworth compound.		C	"	1
3017	Type 104 ...	Ind. 17 H. Current 60 m/amps. D.C.		C	"	1
3019	Type 105 ...	20 henries		C	"	1
3145	Type 109 ...	20 henries		C	"	1
3146	Type 110		C	"	1
3147	Type 111 ...	50/30 henries, 0/50 mA, 600 ohms, 500 volts D.C.		C	"	1
10699	Type 114		C	"	1
10780	Type 116 ...	Coil. Taken out for Oscillator, T.12.		C	"	1
3428	Type 117 ...	60 henries, 50 mA		C	"	1
3429	Type 118 ...	6 henries, 1.2 amps., D.C., 30 henries, 12 amps.		C	"	1
3460	Type 119 ...	7 henries, 180 mA		C	"	1
3520	Type 122 ...	40 henries, 20 mA, 10 henries, 180 mA.		C	"	1
3522	Type 124		C	"	1
3523	Type 125		C	"	1
3653	Type 130 ...	20 henries, laminated, 200 mA, 250 ohms max., 4 ³ / ₈ in. × 3 ³ / ₈ in. × 4 in. overall.		C	"	1
3682	Type 134 ...	15 henries, 330 mA, 100 ohms, swinging.		C	"	1
3685	Type 137 ...	27 henries, 250 mA, 130 ohms		C	"	1
3733	Type 141 ...	Ind. 25 H, current 250 mA ...		C	"	1
3736	Type 144 ...	20 henries, 60 mA		C	"	1
3739	Type 147 ...	Ind. 20 henries, current 500 mA		C	"	1
3742	Type 148 ...	10 henries		C	"	1
3771	Type 159 ...	G.B. smoothing		C	"	1
3895	Type 160 ...	H.T. smoothing		C	"	1
3896	Type 161		C	"	1
3971	Type 163 ...	Double smoothing		C	"	1
3973	Type 165 ...	8 henries, 120 mA, 225 ohms ...		C	"	1
3974	Type 166		C	"	1
4073	Type 167 ...	5 henries, .3 amp., 27 ohms, D.C. resistance.		C	"	1
4074	Type 168		C	"	1
4075	Type 169		C	"	1
4076	Type 170		C	"	1
4083	Type 173 ...	Ind. 5 H. D.C. resistance, 55 ohms, max. 35 watts, iron cored, smoothing. Max. dissipation, etc.		C	"	1
4084	Type 174		C	"	1
4086	Type 176 ...	Double smoothing in M.S. can		C	"	1
4087	Type 177 ...	Special		C	"	1
4088	Type 178		C	"	1
4280	Type 181 ...	Inductance 25 H, current 110 mA D.C., resistance 100 ohms.		C	"	1
4465	Type 186 ...	Output. In "Senator" case, with terminals.		C	"	1
4522	Type 188 ...	Double choke		C	"	1
4523	Type 189 ...	1 henry, 140 mA, laminated iron core, 1,200 turns of 32 S.W.G. en. copper wire.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
4524	Type 190 ...	1 henry, 40 mA, laminated iron core, 1,600 turns of 37 S.W.G. en. copper wire.		C	each	1
4525	Type 191 ...	3.2 henries, 40 mA, 360 ohms...		C	..	1
4592	Type 193 ...	Coil lay wound with enam. copper wire, paper interleaved. Test voltage 1,000 volts A.C. etc. Open type, $1\frac{5}{16}$ in. \times $1\frac{3}{4}$ in. high, approx., with leads.		C	..	1
4593	Type 194 ...	Coil layer, wound with enam. C. wire, paper interleaved. Test voltage 1,000 volts A.C. Open type, 2 in. \times $1\frac{1}{2}$ in. high, approx., with leads.		C	..	1
4710	Type 19901 in. spacing		C	..	1
4711	Type 200		C	..	1
4712	Type 201 ...	12 henries at 50 volts, 50 cycles, ripple, 120 mA, D.C., 2,700 turns of 36 gauge enam. and S.C.C. copper wire on former.		C	..	1
4713	Type 202 ...	Reactor		C	..	1
4714	Type 203 ...	20 henries, 100 mA		C	..	1
4715	Type 204 ...	200 henries, 6 mA, special ...		C	..	1
4845	Type 214 ...	15 henries		C	..	1
4846	Type 215		C	..	1
5059	Type 219		C	..	1
5060	Type 220 ...	50 henries, 5 mA, D.C., 450 ohms		C	..	1
5061	Type 221 ...	1,800 turns .0048 in. dia. enam. S.S.C. copper wire. $1\frac{1}{2}$ in. \times $1\frac{3}{4}$ in. \times 2 in. overall.		C	..	1
5080	Type 225 ...	40 H, 3 mA, 250 volts R.M.S. A.C., 100 cycles, open type. Air cooled. Tropical. $3\frac{1}{4}$ in. long \times $2\frac{3}{4}$ in. deep \times 4 in. high.		C	..	1
5082	Type 227 ...	$2\frac{3}{4}$ in. \times $1\frac{3}{4}$ in. \times $1\frac{11}{16}$ in. metal case.		C	..	1
5084	Type 229 ...	Ind. 300 mA \pm 5 per cent. D.C. resistance. 165 turns 22 S.W.G. enam. copper wire wound on former $1\frac{1}{4}$ in. \times $\frac{7}{8}$ in. long.		C	..	1
5085	Type 230 ...	10 henries at 500 mA... ..		C	..	1
5086	Type 231 ...	50 henries at 25 mA		C	..	1
5087	Type 232 ...	80 henries at 5 mA		C	..	1
5130	Type 239 ...	10 henries at 60 mA		C	..	1
5131	Type 240 ...	10 henries \pm 10 per cent. at 300 m/amps. D.C., 50 cycles D.C. resistance, 100 ohms \pm 10 per cent. $4\frac{15}{16}$ in. \times $5\frac{3}{8}$ in. \times $16\frac{13}{16}$ in. overall.		C	..	1
5132	Type 241 ...	Ind. 45 H. Current 30 mA, D.C. resistor 1,090 meg. 250 volts, D.C. resistance 1,090 ohms; contained in tank filled with Kingsworth compound, plug connections. $3\frac{1}{2}$ in. \times $3\frac{1}{2}$ in. \times $5\frac{11}{16}$ in. overall size.		C	..	1

SECTION 100—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
5133	Type 242 ...	17 henries \pm 20 per cent at 60m. 1 amp. 60 D.C., 20 volt. 50 cycles, D.C. resistance 273 ohms. 5 per cent. Contained in tank filled with Kingsworth compound, plug connections. Overall size $3\frac{1}{2}$ in. \times $3\frac{3}{8}$ in. \times $5\frac{3}{16}$ in.		C	..	1
5286	Type 244 ...	32 henries shrouded, 350 ohms, D.C. resistance.		C	..	1
5288	Type 245 ...	6 coils, each of 96 turns of 34 S.W.G. enam. copper wire, wound on 1 in. dia. tubular former, approx. $9\frac{5}{8}$ in. long.		C	..	1
5290	Type 247 ...	88 henries, 60 henries at max. current at 8.7 mA, D.C. resistance 1,460 ohms; $2\frac{1}{2}$ watts.		C	..	1
5291	Type 248 ...	35 henries, max., current 20 mA, resistance 1,800 ohms, $2\frac{1}{2}$ watts.		C	..	1
5292	Type 249 ...	10 henries at 50 mA. Open type, $2\frac{1}{8}$ in. \times $2\frac{1}{4}$ in. \times 3 in. high, with tag panel. Tropical.		C	..	1
5379	Type 255 ...	Anode valve 3, 2 in. \times $1\frac{1}{2}$ in. \times $1\frac{1}{2}$ in.		C	..	1
5395	Type 256 ...	Smoothing screened, 2 in. \times $1\frac{1}{2}$ in. \times $1\frac{1}{2}$ in.		C	..	1
5399	Type 260 ...	20 H, 150 mA, D.C.		C	..	1
5405	Type 262 ...	12 henries, 200 mA		C	..	1
5406	Type 263 ...	25 henries		C	..	1
5407	Type 264 ...	20 henries		C	..	1
5486	Type 265 ...	Air cooled, iron cored, 1 amp. D.C., 2,500 volts D.C. working, 1,550 R.M.S. A.C. working. Tropical.				
5487	Type 266 ...	100 henries \pm 10 per cent. at 8 m/amp., D.C., 20 volts A.C. D.C. resistance = 2,190 ohms, 10 per cent. contained in tank filled with Kingsworth compound. Overall $3\frac{1}{2}$ in. \times $3\frac{1}{2}$ in. \times $5\frac{11}{16}$ in. etc.		C	each	1
5623	Type 274 ...	Winding, 5,000 turns of 36 S.W.G. enam. copper wire on $\frac{1}{8}$ in. dia. former.		C	..	1
5723	Type 282 ...	Coil, iron former, $3\frac{1}{4}$ in. \times 2 in. \times $1\frac{3}{4}$ in.; 2 in. fixing holes, $2\frac{3}{4}$ in. centres.		C	..	1
5724	Type 283 ...	154 m/henries \pm 5 per cent., 68 turns of 40 S.W.G. D.S.C. wire; coil approx. $\frac{5}{8}$ in. dia. \times $\frac{1}{8}$ in., with $\frac{1}{2}$ in. dia. iron core; connections to side pins; complete with fixing panel, 1 in. \times $1\frac{1}{4}$ in.; overall height approx. $1\frac{1}{2}$ in. not shrouded.		C	..	1
5725	Type 284 ...	154 mH \pm 5 per cent. 68 turns of 40 S.W.G. D.S.C. wire; coil approx. $\frac{5}{8}$ in. dia. \times $\frac{1}{8}$ in., with $\frac{1}{2}$ in. dia. iron core; connections to side tags; complete with fixing panel, 1 in. \times $1\frac{1}{4}$ in. Overall height, approx. $1\frac{1}{2}$ in.; not shrouded.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
5730	Type 285 ...	278 mH \pm 5 per cent. 91 turns of 40 S.W.G. D.S.C. wire; coil approx. $\frac{5}{8}$ in. dia. \times $\frac{1}{8}$ in., with $\frac{1}{2}$ in. dia. iron core; connections to side pins; complete with fixing panel, 1 in. \times $1\frac{1}{4}$ in.; overall height, approx. $1\frac{1}{2}$ in.; not shrouded.		C	each	1
5731	Type 286 ...	91 turns 40 S.W.G. D.S.C. wire; coil approx. $\frac{5}{8}$ in. dia. \times $\frac{1}{8}$ in., with $\frac{1}{2}$ in. dia. iron core; connections to side tags, complete with fixing panel 1 in. \times $1\frac{1}{4}$ in.; overall height, approx $1\frac{1}{2}$ in.; not shrouded.		C	"	1
5845	Type 291 ...	10 henries at 110 mA, continuous air cooled, shell type, 6 in. \times $6\frac{3}{4}$ in. \times $5\frac{1}{2}$ in.		C	"	1
5905	Type 293 ...	60 volts, 50 meg. ohms. Contained in tank, etc.; overall 4 in. \times 4 in. \times 5 in.		C	"	1
5906	Type 294 ...	10 volts, 50 meg. ohms. Contained in tank, etc.; overall $4\frac{1}{2}$ in. \times $2\frac{3}{8}$ in. \times $5\frac{3}{16}$ in.		C	"	1
5916	Type 298 ...	2 windings, 930 turns 34 S.W.G., tags 256–264 henries; metal case, 2 in. high, $1\frac{3}{4}$ in. \times $\frac{3}{4}$ in.		C	"	1
11025	Type 305 ...	2 henries, current rates 100 mA, ohmic resistance 100 ohms. \pm 5 per cent.		C	"	1
11043	Type 306 ...	20 henries, 100 mA. Tropical		C	"	1
11167	Type 307		C	"	1
11221	Type 309 ...	Ind. + 10 H, currents 150 mA. Resistance 180 megs. $3\frac{1}{2}$ in. \times 4 in. \times $2\frac{3}{4}$ in. to lug centres.		C	"	1
11234	Type 313 ...	10 henries, 4,250 turns of 28 S.W.G. en. cu. wire, $1\frac{1}{2}$ in. pack, no laminations.		C	"	1
11300	Type 314 ...	Ind. 20H, current 70 mA. Choke 25 A.		C	"	1
11301	Type 315 ...	10 henries, 70 mA, D.C. ...		C	"	1
11302	Type 316 ...	3 henries, 100 mA, 92 ohms D.C., shrouded.		C	"	1
11303	Type 317 ...	3,300 turns No. 38 S.W.G. en. cu. wire wound on Pye former. D.C. resistance 350 ohms. Inductance 11 henries \pm 10 per cent. at 30 mA D.C.		C	"	1
11304	Type 318 ...	3 henries, 100 ohms. Open type, $2\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. high, black, impregnated.		C	"	1
11322	Type 319 ...	20 henries. Iron core, miniature, 6,000 turns.		C	"	1
11323	Type 320 ...	400 ohms approx., 20 henries, 6,500 turns .0084 in. S.S. en. cu. wire; dims. $3\frac{1}{2}$ in. \times $2\frac{3}{8}$ in. \times $2\frac{1}{2}$ in.		C	"	1
11324	Type 321 ...	3 henries, 200 mA ...		C	"	1
11325	Type 322 ...	2.5 H nominal value, 20 mA. To be not less than 2.4 H. 2,200 turns of 42 S.W.G. en. and S.S.C.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
11332	Type 323 ...	2.5 henries ± 5 per cent. 120 2,000 turns of 34 S.W.G. E.S.S.C.; D.C. resistance approx. 92.5 ohms.		C	each	1
11313	Type 324 ...	30–40 henries, 50 mA. 3¼ in. × 1½ in. × 2½ in. 4 fixing lugs.		C	"	1
11338	Type 326 ...	4 henries, 250 mA. L.F. ...		C	"	1
11339	Type 327 ...	9 henries, 125 mA. L.F., shrouded.		C	"	1
11340	Type 328 ...	15 henries, 50 mA. F.F., shrouded.		C	"	1
11357	Type 329 ...	Ind. 20 H. Current 25 mA. 550 megs.		C	"	1
11429	Type 330 ...	Smoothing, impregnated, in metal case, 2½ K. volts.		C	"	1
11430	Type 331 ...	Smoothing, 200 mA ...		C	"	1
11442	Type 332 ...	11 henries, 80 mA ...		C	"	1
11445	Type 333 ...	120 henries ± 20 per cent. at 80 mA peak, 26 mA mean current. Peak voltage across choke 13 KV. insulated to 21 KV.		C	"	1
11446	Type 334 ...	Air insulated, 2 sections, 2.5 and 3.5 henries, variable 5 to 7 henries.		C	"	1
11504	Type 335 ...	25 mH. Current 3 amps. with 3.5 V.R.M.S. A.C. 50 cycles, applied resistance .5 approx. Tropical.		C	"	1
11524	Type 336 ...	5 henries, 3,000 turns 34 S.W.G. en. cu. wire; open type, 2½ in. × 1½ in. × 2¾ in. high, with tag panel.		C	"	1
11611	Type 338 ...	Smoothing choke, 10 henries, 30 mA.		C	"	1
11609	Type 339 ...	2 henries at 200 mA D.C. + 10 volts, 50 cycles, A.C. resistance, 77 ohms ± 20 per cent., 1,800 turns of 34 S.W.G. enamel; open type, 2¾ in. × 1½ in. × 2 in. high approx., with tag panel.		C	"	1
11610	Type 340 ...	2 henries at 130 mA D.C. + 10 volts A.C., 50 cycles; 2,400 turns of 34 S.W.G. en. cu. wire; open type, 2½ in. × 1¾ in. × 1¾ in. high.		C	"	1
11779	Type 344 ...	Modulation ...		C	"	1
11846	Type 347 ...	20 henries, 20 mA ...		C	"	1
11873	Type 349 ...	350 turns, quarter wave-wound, 24 S.W.G. D.C.C. bound, former bakelised paper, 1.625 in. long, 1½ in. dia.		C	"	1
11943	Type 351 ...	12 henries ...		C	"	1
11971	Type 352 ...	21 henries at 40 mA D.C., 5,500 turns of 38 S.W.G., pressphan former 1½ in. square.		C	"	1
11972	Type 353 ...	5 henries at 10 mA. 1¾ in. × 2½ in. 2 fixing holes, 3,200 turns of 37 S.W.G.		C	"	1
11978	Type 354 ...	8 henries, with no D.C. flowing, 600 ohms ± 15 per cent., open type, 2 in. × 2 in. × 2 in., with tag panel.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
12008	Type 357 ...	25 henries, 25 mA p 1,000 ohms \pm 15 per cent.		C	each	1
12018	Type 358 ...	8 henries, 200 ohms, D. C. resistance.		C	..	1
12019	Type 359 ...	100 henries, 3,500 ohms, D. C. resistance.		C	..	1
12021	Type 3605 henries, 250 mA. 2 K.V.A. insulation; approx. 3 in. \times 2 in. \times 2 in. high; tag panel.		C	..	1
12022	Type 361 ...	10 mH, .4 ohms; approx. 3 in. \times 2 in. \times 2 in. high.		C	..	1
12115	Type 363 ...	1 henry \pm 15 per cent.; iron core; 2 $\frac{3}{8}$ in \times 1 $\frac{3}{8}$ in. \times 1 $\frac{3}{4}$ in. overall.		C	..	1
12127	Type 365 ...	Coil, wound on former, 2 $\frac{7}{16}$ in. long \times $\frac{1}{2}$ in. overall; 140 $\frac{1}{2}$ turns .0092 in. en. copper wire, close wound.		C	..	1
12134	Type 367		C	..	1
12137	Type 370 ...	3.6 henries at 2 volts, 800 cycles, with 50 mA D.C., 260 ohms D. C.; moulded former; tropical.		C	..	1
12154	Type 372 ...	1.7 henries at 100 mA D.C. ...		C	..	1
12190	Type 376 ...	5.5 henries at 50 mA, 400 ohms D.C. resistance.		C	..	1
12331	Type 3875 henries D.C. 1 ohm resistance; 24 volt.		C	..	1
12369	Type 388 ...	Smoothing, .86 henries, 180 mA, 1,000 cycles.		C	..	1
12469	Type 394 ...	26 amps. D.C., .0023 henries ...		C	..	1
12471	Type 395 ...	320 mA D.C., 12 to 14 henries		C	..	1
12472	Type 396 ...	Ind., .004—0.06 H. Current, 14 amps. D.C.		C	..	1
12473	Type 397 ...	Ind., 10—12 H. Current 120 mA. Complete with 2 terminal boards.		C	..	1
12583	Type 398 ...	4 henries at 60 mA, flattened cheeks.		C	..	1
12584	Type 39917 henries at 450 mA ...		C	..	1
11993	Type 402 ...	Smoothing, 1 henry at 200 mA, iron core.		C	..	1
12661	Type 404 ...	18 henries at 26 volts A.C., 60 mA D.C. resistance, 435 ohms'		C	..	1
12691	Type 406 ...	2 henries, 100 mA, metal can. For inverted chassis mounting.		C	..	1
12745	Type 408		C	..	1
12762	Type 409 ...	4,600 turns of 32 S.W.G. en. S.C.C. on bakelite former to be:—(a) not less than .76 H at 1,000 c/s, (b) not less than 22 H at 100 c/s.		C	..	1
12770	Type 412 ...	5,300 turns 35 S.W.G. en. copper, 435 ohms; 18 henries at 60 mA D.C. plus 26 volts A.C.; open type; approx. 3.69 in. \times 2.56 in. \times 2.19 in. high. Tropical finish.		C	..	1
12844	Type 418 ...	10 henries, 120 mA, 100 ohms...		C	..	1
12899	Type 420 ...	2.6 henries at 200 mA, 1 KV. insulation. Laminated iron core; 2,100 turns at 33 S.W.G.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
12919	Type 428 ...	25 H. Current 50 mA. 5,000 turns 36 S.W.G.		C	each	1
13037	Type 433 ...	Ind. 10 H. Current 150 mA		C	..	1
13101	Type 438 ...	10 henries at 1.2 amps, 300 ohms, D.C. resistance.		C	..	1.
13102	Type 439 ...	10 henries at 420 mA, 150 ohms, D.C. resistance.		C	..	1
13103	Type 440 ...	20 henries at 100 mA, 300 ohms, D.C. resistance.		C	..	1
13104	Type 441 ...	20 henries at 60 mA, 300 ohms, D.C. resistance.		C	..	1
13105	Type 442 ...	10 henries at .8 amp., 30 ohms, D.C. resistance.		C	..	1
13106	Type 443 ...	10 henries at 210 mA, 150 ohms, D.C. resistance.		C	..	1
13161	Type 444 ...	Mains smoothing choke, 20 henries, 120 mA.		C	..	1
13182	Type 446 ...	1.7 henries, 10 ohms, 200 mA, D.C.		C	..	1
13206	Type 448 ...	15–20 henries, 50 mA, 600 ohms, D.C. resistance; 2 in. × 2½ in. × 3¾ in. high overall dims.		C	..	1
13224	Type 449 ...	20 henries, 120 mA, mains smoothing choke. Impregnated to WT.1,000.		C	..	1
13228	Type 450 ...	Smoothing, 20 henries at 100 mA.		C	..	1
13277	Type 452 ...	D.C. resistance, 200 ohms, 6,200 turns 28 S.W.G. en. cu. D.S. Size, 4 ft. 5 in. × 4 ft. 5 in. × 3 in. overall, inc. tag panel.		C	..	1
13350	Type 455 ...	230 volts, 50 cycles, for H.P. mercury vapour lamp.		C	..	1
13386	Type 457 ...	Adjustable movable cores, 2 coils in series, fixing centres 2½ in. × 2 in., 2 B.A.		C	..	1
13387	Type 458 ...	19 henries, 200 mA, 1.006 amp. turns.		C	..	1
13390	Type 459 ...	Wound 4,350 turns of 40 S.W.G. en. copper wire on silicon steel core. Approx. 20 henries.		C	..	1
13434	Type 461 ...	20 henries, 200 mA		C	..	1
13473	Type 464 ...	90 H ± 10 per cent. 15 mA ...		C	..	1
13492	Type 466 ...	18 S.W.G. tinned copper on moulded former 1½ in. × ½ in.		C	..	1
13533	Type 469 ...	8 henries, 200 ohms, D.C. resistance. Similar to Types 358 and 445, with special fixing position.		C	..	1
13571	Type 474 ...	14 H. 70 milliamps. D.C. 480 ohms. Shell type, with iron core.		C	..	1
13620	Type 477 ...	4.5 H at 75 mA D.C. resistance 190 ohms ± 20 per cent.		C	..	1
13643	Type 478 ...	4,500 turns 32 S.W.G., using 72 crs. laminations M.E.A. No. 59A, .014 Silcor 11, 2 in. × 2½ in. fixing centres.		C	..	1
13645	Type 479 ...	875 turns 21 S.W.G. en. 80 Pos. M.E.A. laminations No. 4A, Silcor 11, 4 fixing holes, 2½ in. × 2½ in.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
13670	Type 481	Ind. 16 henries. Current .25 100 ohms ripple of 400 volts peak.		C	each	1
13692	Type 482	60 H at 50 mA D.C., 1 KVA., 350 cycles. Charging choke.		C	"	1
13693	Type 483	75 H at 55 mA D.C., 1 KVA., 100 cycles. Smoothing choke.		C	"	1
13705	Type 491	3 H, 125 mA D.C. ...		C	"	1
13719	Type 492	Ind. 2 henries. Current 75 mA D.C. Res. 200 ohms.		C	"	1
13720	Type 493	Ind. .7 henries. Current 125 mA D.C. Res. 30 ohms.		C	"	1
13729	Type 495	Ind. 3.5 henries, 1.5 amps. Oil immersed in metal container, 16½ in. × 13 in. × 19 in. overall.		C	"	1
13737	Type 496	Ind. at 25 volts, 50 cycles to be greater than 15 henries after impregnation.		C	"	1
13760	Type 497	200 ohms ± 10 per cent. D.C. resistance, inductance 16 hen- ries ± 20 per cent.		C	"	1
13775	Type 498	2 H at 60 mA ...		C	"	1
13783	Type 499	Choke L.F. Type 27 modified by addition of Spark Gap T.6.		C	"	1
13784	Type 500	Part of Transmitter, Type T. 1131.		C	"	1
13846	Type 502	1 H at 2 mA D.C. ...		C	"	1
13854	Type 503	6 henries. Current 2.5 amps. D.C. Resistance 12 ohms.		C	"	1
13856	Type 504	27 H, 50 mA ...		C	"	1
13877	Type 507	24 H, 95 mA ...		C	"	1
13878	Type 508	27 H, 50 mA ...		C	"	1
13879	Type 509	22 H, 80 mA ...		C	"	1
13880	Type 510	25 H, 160 mA ...		C	"	1
13904	Type 512	6,200 turns 28 S.W.G. en cu. D.C. resistance 200 ohms. Approx. size, 4.5 in. × 4.5 in. × 3.0 in. overall, including vertical tag panel.		C	"	1
13909	Type 513	12 H. D.C. resistance 100 ohms. Continuous D.C. current 200 mA. Ripple current .14 A. peak at 100 cycles.		C	"	1
13933	Type 514	1,300 turns .0148 in. en. cu. wire. Open type, 2.5 in. × 1.75 in. × 2.25 in. high, with feet and tagboard at top.		C	"	1
13955	Type 517	...		C	"	1
13957	Type 518	50 H, 65 mA. D.C. resistance 500 ohms.		C	"	1
13958	Type 519	100 H at 30 mA. 23 H at 47 mA. D.C. resistance 500 ohms max.		C	"	1
14014	Type 523	20 H, 50 mA ...		C	"	1
14015	Type 524	20 H, 200 mA ...		C	"	1
14016	Type 525	40 H, 25 mA ...		C	"	1
14033	Type 526	2 coil. 2.4 H. 2,000 turns 36 D.S.C. Former 1 in. × ½ in.		C	"	1
14112	Type 530	200 mH. 960 turns of 30 S.W.G. en. copper wire.		C	"	1
14132	Type 533	250 μH at 250 mA. 5½ in. × 4¼ in. × 4 in.		C	"	1
14161	Type 536	Ind. 100, 100 ± 10 per cent. Current 70 mA. Iron core.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
14162	Type 537 ...	Ind. 4 mH ± 10 per cent. ...		C	each	1
14212	Type 548 ...	Ind. 20 H, 120 mA, smoothing		C	"	1
14263	Type 552 ...	Smoothing, 11 H at 60 mA ...		C	"	1
14292	Type 553 ...	Ind. 50 H ± 10 per cent. Current 30 mA. D.C. resistance 604 ohms.		C	"	1
14293	Type 554		C	"	1
14325	Type 557 ...	400 μH, 1,000 cycles per second. 376 turns in 4 sections of 34 turns of 40 S.W.G. en. cu. wire.		C	"	1
14378	Type 558 ...	5 H ± 2 per cent. Coil tapped. 2 ³ / ₁₆ in. high × 1 ⁷ / ₈ in. × 1 ³ / ₈ in. Fixing centres 1 ⁹ / ₁₆ in. × 1 ³ / ₁₆ in.		C	"	1
14379	Type 559 ...	As Type 558 but single coil ...		C	"	1
14477	Type 563 ...	Smoothing, 20 H, 4 mA ...		C	"	1
14497	Type 564 ...	En. wire with gap of .005, 4,000 turns of 36 S.W.G. 13 Hy. min. (at 50 mA). Resistance 340 ohms.		C	"	1
14519	Type 566 ...	Ind. 5 H. Current 130 mA. D.C. resistance 130 ohms. Filter choke.		C	"	1
14618	Type 569 ...	4 H at 120–150 mA. D.C. resistance 150 ohms. 3 ¹ / ₂ in. × 2 ¹ / ₈ in. × 2 ¹ / ₄ in. 3 ¹ / ₂ in. fixing centres.		C	"	1
14621	Type 570 ...	Ind. 50 H, 5 mA. 7,950 turns of 32 S.W.G. enam. copper wire on laminated core.		C	"	1
14632	Type 571 ...	Ind. 20 H. Current at 150 mA. 4,800 turns of No. 20 S.W.G. en. cu. wire on laminated core.		C	"	1
14633	Type 572 ...	Ind. 10 H. Current 200 mA. 200 ohms D.C. resistance. 2,000 volts test.		C	"	1
14694	Type 574 ...	Ind. 3 H. Current 100 mA. Complete with mounting brackets.		C	"	1
14695	Type 575 ...	Ind. 4 H. Current 50 mA. Smoothing chokes.		C	"	1
14700	Type 576 ...	Ind. 6 H. Current 40 mA ...		C	"	1
14701	Type 577 ...	Ind. 1 H. Current 65 mA ...		C	"	1
14713	Type 578 ...	Iron core with coil inductor 270 μH ± 10 per cent. Overall dims. 3 in. × 1 ¹¹ / ₁₆ in. × 2 ¹ / ₁₆ in. Fixing centres 2 ⁵ / ₈ in. × 1 ³ / ₁₆ in.		C	"	1
14727	Type 580 ...	2,800 turns 28 S.W.G. "Bicolon M" covered copper wire. 34 layers of 83 turns per layer. Lengths of layer 1 ¹ / ₂ in. D.C. resistance 90 ohms.		C	"	1
14728	Type 281 ...	15 turns of 16 S.W.G. "Bicolon M" covered on shrouded laminated core, 2 ¹ / ₂ in. × 1 ¹ / ₂ in. × 1 in. D.C. resistance 90 ohms.		C	"	1
14729	Type 582 ...	10 H, 200 mA		C	"	1
14765	Type 585 ...	Ind. 50 henries. Current 50 mA		C	"	1
14859	Type 589 ...	Ind. 30–40, 50 mA. 2,560 turns of 36 gauge wire for 200 ohms resistance. 3 ¹ / ₂ in. × 1 ³ / ₄ in. × 2 ¹ / ₂ in. 4 fixing lugs.		C	"	1

SECTION 100—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
14860	Type 590 ...	Ind. 15 H. 4,250 turns of 36 S.W.G. en. copper wire.		C	each	1
14873	Type 591 ...	Ind. 27 H. Current 10 mA. 2 volt A.C. D.C. resistance. Insulation 1,000 volts between core and copper.		C	"	1
14885	Type 593 ...	Ind. 20 H. Current 20 mA. Size 3 in. × 2 in. × 2 in. overall. 7,500 turns of .006 in. en. cu. wire. Fixing centres 2 $\frac{3}{4}$ in.		C	"	1
14922	Type 595 ...	Ind. 14 henries. Current .4 amp. Metal case 7 $\frac{7}{8}$ in. × 5 $\frac{7}{8}$ in. × 6 $\frac{1}{8}$ in.		C	"	1
14992	Type 596 ...	Ind. 10 henries. Current 10 mA low capacity. Wave-wound.		C	"	1
15003	Type 597 ...	Smoothing choke, iron dust core. 2,300 turns 40 S.W.G. en. cu. wire on former. Ind. not less than 4-5 H at 50 ohms.		C	"	1
15064	Type 599 ...	Ind. 1 H. Current 200 mA. Size 2 $\frac{1}{2}$ in. long × 2 in. high, approx.		C	"	1
15180	Type 605 ...	Ind. .6 H ± 20 per cent. D.C. resistance 34 ohms ± 10 per cent. Size 1 $\frac{7}{8}$ in. × 2 $\frac{3}{8}$ in. × 1 $\frac{3}{8}$ in. approx.		C	"	1
15181	Type 606 ...	Ind .95 H. D.C. resistance 120 ohms ± 10 per cent. Size 1 $\frac{7}{8}$ in. × 2 $\frac{3}{8}$ in. × 1 $\frac{3}{8}$ in. approx.		C	"	1
15182	Type 607 ...	Ind. 7 H, 50 mA. D.C. resistance 250 ohms. Size overall 3 $\frac{11}{16}$ in. × 2 $\frac{9}{16}$ in. × 1 $\frac{15}{16}$ in.		C	"	1
15200	Type 608 ...	Ind. 10 H. Current 250 mA. Size 3 $\frac{1}{8}$ in. × 3 $\frac{3}{8}$ in. × 4 $\frac{7}{8}$ in. overall dims.		C	"	1
15214	Type 610 ...	Ind. 5 H. Current 60 mA ...		C	"	1
15228	Type 611 ...	Ind. 6 H, 150 mA. D.C. resistance 140 ohms ± 10 per cent. Dims., case, 2 $\frac{1}{2}$ in. × 2 $\frac{3}{8}$ in. × 3 in. high.		C	"	1
15229	Type 612 ...	65 H ± 00 per cent. at 90 mA and 5 volts, 50 cycles. D.C. resistance 61 ohms ± 20 per cent.		C	"	1
15277	Type 620 ...	2,100 turns 32 S.W.G. enam. cu. wire. Complete with fixing brackets and tag panel.		C	"	1
15278	Type 621 ...	5,300 turns 40 S.W.G. en. cu. wire. Complete with fixing brackets and tag panel.		C	"	1
15904	Type 623 ...	Ind. 15 H. Current 20 mA. D.C. resistance 700 ohms. Overall dims. 2 $\frac{9}{16}$ in. × 3 $\frac{3}{8}$ in. × 2 $\frac{3}{8}$ in. with 3 $\frac{1}{8}$ in. fixing centres.		C	"	1
15905	Type 624 ...	20 H, 60 mA. D.C. Overall dims. 2 $\frac{11}{16}$ in. × 2 $\frac{11}{16}$ in., with 2 in. × 2.5 in. fixing centres.		C	"	1
15912	Type 625 ...	Ind. 2.5 H. Iron cored smoothing choke.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
15962	Type 630 ...	Ind. 5 H. Current 10 mA. 1,950 turns of 37 S.W.G. en. cu. wire. Bakelite bobbin, 1,000 volts A.C. test to core. Overall dims., excluding mounting, feet and tags, 1.89 in. × 1.312 in. × 1.609 in.		C	each	1
15968	Type 631 ...	Smoothing, 3.5–14 henries, with series parallel links on terminal board .8–.4 amp. D.C. rating 20–80 ohms. D.C. resistance. Metal case 6 $\frac{3}{8}$ in. × 7 $\frac{7}{8}$ in. × 7 $\frac{1}{8}$ in.		C	..	1
15979	Type 632 ...	Ind. 2.75–5 henries, 35 mA, 500 volts peak. 2 $\frac{1}{4}$ in. × 1 $\frac{3}{4}$ in. × 1 $\frac{13}{16}$ in.		C	..	1
15985	Type 633 ...	Ind. 6 H + 100 per cent — 10 per cent. Current 20 mA. D.C. resistance 4.4 ohms ± 10 per cent.		C	..	1
15996	Type 634 ...	Ind. 5 H. Current 10 mA. 150 ohms. 1,950 turns of 37 S.W.G. en. cu. wire. Bakelite bobbin 1,000 volts A.C. test to core. Overall dims, excluding mounting feet and tags, size 1.89 in. × 1.312 in. × 1.609 in.		C	..	1
15998	Type 635 ...	Ind. 1 H. Current 75 mA ...		C	..	1
16017	Type 638 ...	Ind. 2 H, 500 mA ...		C	..	1
16018	Type 639 ...	Ind. 2 H, 60 mA ...		C	..	1
16058	Type 640 ...	Ind. 25 H ± 10 per cent. at 50 volts. Current 50 cycles, 40 mA D.C. D.C. resistance 50 ohms ± 10 per cent.		C	..	1
16117	Type 643 ...	Ind. 20 henries. 95 turns 37 S.W.G. S.S. enam., $\frac{1}{2}$ wave-wound. Moulded former $\frac{3}{8}$ in. dia. × $\frac{3}{8}$ in., with flange at each end.		C	..	1
16152	Type 644 ...	Ind. 2 H. Current 200 mA ...		C	..	1
16153	Type 645 ...	Ind. 2 H. Current 200 mA ...		C	..	1
16154	Type 646 ...	Ind. 5 H. Current 75 mA. Hermetically sealed, oil filled.		C	..	1
16185	Type 647 ...	24 H max., 14.5 H min., at 120 mA D.C. and 60 volts c/s. D.C. resistance 164 ohms ± 10 per cent.		C	..	1
16186	Type 648 ...	Two separate windings, each 3,680 turns 30 S.W.G. D.W.S. copper wire, 1 $\frac{1}{4}$ iron core, air cooled, 5 in. × 3 $\frac{3}{8}$ in. × 5 in. deep casing.		C	..	1
16188	Type 649 ...	Ind. 20 H. Current 200 mA ...		C	..	1
16189	Type 650 ...	Ind. 20 H. Current 200 mA ...		C	..	1
16191	Type 652 ...	Ind. 60 H, .88, .177. Metal tank 18 $\frac{3}{4}$ in. × 12 $\frac{1}{4}$ in. × 20 in. deep. Oil immersed. Total 325 lb.		C	..	1
16200	Type 654 ...	Ind. 100 H. Current 20 mA ...		C	..	1
16201	Type 655 ...	Ind. 20 H. Current 120 mA ...		C	..	1
16202	Type 656 ...	Ind. 20 H. Current 20 mA ...		C	..	1
16208	Type 657 ...	Ind. 2 H. Current 80 mA ...		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
16192	Type 658 ...	Ind. 1.5 H each section—2 sections, iron core.		C	each	1
16257	Type 660 ...	Ind. 20 H. Current 60 mA ...		C	..	1
16270	Type 663 ...	Ind. 4 H. Current 130 mA. D.C. resistance 140 ohms \pm 20 per cent., 5 volts, 50 cycles, A.C. (Inductance to be greater than 4 H.)		C	..	1
16271	Type 664 ...	Ind. 7 H at 5 volts. Current 30 mA D.C. D.C. resistance. Polarising current 50 c/s A.C. (Inductance to be greater than 7 H.)		C	..	1
16272	Type 665 ...	Ind. 4.2 H at 2 volts. Current 10 mA D.C. D.C. resistance 330 ohms \pm 20 per cent. 50 cycles A.C. polarising current.		C	..	1
16276	Type 667 ...	Ind. 7.8 H. 4 volts A.C. 50 cycles across winding D.C. reserve 235 ohms approx.		C	..	1
16277	Type 668 ...	8 volts A.C. across winding, D.C. reserve 7.2 ohms approx.		C	..	1
16556	Type 673 ...	2,260 turns 34 S.W.G. en. cu. wire. D.C. resistance 92 ohms. Tropical finish. Overall size 2½ in. \times 2 in. \times 3 in.		C	..	1
16674	Type 681 ...	Ind. 10 H. Current 90 mA. 4½ in. \times 3½ in. \times 3 in. overall.		C	..	1
16678	Type 682 ...	Ind. 2.6 H. Current 450 mA. 25 ohms. Tropical.		C	..	1
16679	Type 683 ...	Tropical		C	..	1
16784	Type 688 ...	Replacement for 10C/14721 but with stud type terminals fitted and sealed. Tropical.		C	..	1
16790	Type 690 ...	Ind. 20 H. Current 80 mA ...		C	..	1
16807	Type 693 ...	Ind. 4.5 H. Current 90 mA. 5 volts A.C. D.C. 2 as one unit.		C	..	1
16826	Type 694 ...	Non-shrouded, 7,250 turns of 44 S.W.G. "LEWMAX" wire tapped at 700 and 3,250 from start, soldering tag connections.		C	..	1
16827	Type 695 ...	Non-shrouded, 7,250 turns of 44 S.W.G. "LEWMAX", soldering tag connections.		C	..	1
16880	Type 698 ..	Ind. 1 H. Current 180 mA. Sealed in metal case 2 in. \times 3 in. \times 1½ in.		C	..	1
16887	Type 699 ...	Ind. .65 \pm 4 per cent at 1 volt or less at 1,000 c.p.s.		C	..	1
16918	Type 702 ...	Series choke, mains		C	..	1
16920	Type 704 ...	H.T.		C	..	1
16922	Type 706 ...	Ind. 10 H. Current 100 mA. D.C. resistance 250 ohms, non-shrouded.		C	..	1
16923	Type 707 ...	Ind. .4 H. Current 100 mA. 4 ohms D.C. resistance, non-shrouded.		C	..	1
16926	Type 710 ...	Ind. 6H. Current 100 mA ...		C	..	1
16927	Type 711 ...	Ind. 2 H. Current 3 amps. D.C.		C	..	1
16935	Type 714 ...	Ind. 12.5 H, 7,000 ohms, current 46 mA, 2.5 watts.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
16936	Type 715 ...	Ind. 88 H, 60 H at max. circuit of 8·7 amps. D.C. resistance 1,460 ohms, 1·5 watt.		C	each	1
16937	Type 716 ...	Ind. 35 H, 20 mA. Resistance 1,800 ohms, 2·5 watts.		C	„	1
16943	Type 718 ...	Ind. 1·4 H at 2 amps. D.C. Core aluminium finish.		C	„	1
16945	Type 719 ...	Ind. 3 H, 250 volts, current 50 mA, 250 volts.		C	„	1
16950	Type 721 ...	2 coils, each of 4·5 H, 90 mA, in sealed can.		C	„	1
16956	Type 723 ...	Current, 200 mA. Double coil choke, each 2 H ± 20 per cent. 10 volts A.C., 50 ohms, resistance 77 ohms.		C	„	1
16967	Type 725 ...	5 per cent. wax impregnated sealed metal can. Inductance 4 mH.		C	„	1
16972	Type 726 ...	Ind. 20 H. Current 150 mA...		C	„	1
16973	Type 727 ...	Ind. 100 H. Current 25 mA ...		C	„	1
16974	Type 728 ...	Ind. 20 H. Current 5 mA ...		C	„	1
16975	Type 729 ...	Ind. 10 H. Current 250 mA...		C	„	1
16976	Type 730 ...	Ind. 20 H. Current 60 mA ...		C	„	1
16977	Type 731 ...	Ind. 20 H. Current 100 mA ...		C	„	1
16979	Type 732 ...	Ind. 20 H. Current 20 mA ...		C	„	1
16983	Type 733 ...	Used on Trainer T.31 ...		C	„	1
16984	Type 734 ...	Used on Trainer T.31 ...		C	„	1
16985	Type 735 ...	Used on Trainer T.31 ...		C	„	1
16995	Type 737 ...	Ind. 10 H. Current 50 mA, 50 cycles. D.C. resistance 260 ohms.		C	„	1
17506	Type 738 ...	Ind. 6–18 H. Current, ·8 amp.		C	„	1
17507	Type 739 ...	Ind. 50 H. Current 50 mA ...		C	„	1
17516	Type 740 ...	Ind. 9 H. Current 128 mA ...		C	„	1
17554	Type 747 ...	2 coils, each 1,800 turns 34 S.W.G., in sealed metal can.		C	„	1
17555	Type 748 ...	90 mA D.C., 5 volts, 50 cycles, A.C. D.C. resistance 15 ohms ± 20 per cent.		C	„	1
17563	Type 749 ...	Ind. 10 H. Current 90 mA. Enclosed in silver-plated can, 3 in. × 3½ in. × 4½ in. overall approx.		C	„	1
17608	Type 751 ...	Smoothing choke, iron cored, in metal case bitumen filled, with 8-pin terminal insulator. 2,100 turns 34 en. cu. wire.		C	„	1
17618	Type 753 ...	Smoothing, 10 henries, 230 mA. 50 ohms max. D.C. resistance. Max. dims. 5 in. × 4 in. × 5½ in.		C	„	1
17640	Type 754 ...	Ind. 17 H. Current 70 mA ...		C	„	1
17642	Type 755 ...	Ind. 4 H ...		C	„	1
17652	Type 757 ...	Not less than 35 henries at 1,000 c.p.s. 6 mA D.C. current. 1,000 ohms max. D.C. resistance. 2 in. × 3¾ in. × 5¾ in. overall. Top terminals.		C	„	1
17664	Type 758 ...	At 50 mA for 20 volts. 400 ohms D.C. resistance.		C	„	1
17668	Type 759 ...	2 matched capacitors ...		C	„	1
17669	Type 760 ...	12 ohms D.C. resistance ...		C	„	1
17694	Type 762 ...	7,500 turns of ·006 en. cu. wire		C	„	1
17744	Type 769 ...	Ind. 2,200 turns 34 S.W.G. D.C. resistance 92 ohms.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
17748	Type 770 ...	Ind. 20 henries. Current 60 mA. D.C. resistance 500 ohms.		C	each	1
17772	Type 775 ...	2 sections, each section 17 H 140 mA with D.C. resistance 200 ohms. Insulation 2 KV. Overall dims. $8\frac{1}{2}$ in. high \times $3\frac{3}{8}$ in. \times $3\frac{3}{8}$ in. For centres $3\frac{1}{8}$ in. \times $1\frac{11}{16}$ in.		C	"	1
17773	Type 776 ...	2 sections, each section 10 H. 40 mA. D.C. resistance, 2,000 ohms; insulation 2 KV. Overall dims. 5 in. high \times $2\frac{1}{2}$ in. \times $1\frac{7}{8}$ in. Fixing centres $1\frac{1}{4}$ in. \times $1\frac{3}{16}$ in.		C	"	1
17787	Type 777 ...	Oil filled, potted. Overall dims. $3\frac{3}{4}$ in. \times $3\frac{3}{4}$ in. \times $3\frac{1}{2}$ in. Ind. $90 H \pm 10$ per cent. 70 mA.		C	"	1
17788	Type 778 ...	Ind. $1 H \pm 20$ per cent. Current 35 mA. Potted.		C	"	1
17835	Type 790 ...	Tropical version of 10C/16556 (T.673) in sealed can.		C	"	1
17836	Type 791 ...	Ind. .011 henries. $\frac{1}{16}$ in. air gap. $3\frac{1}{8}$ in. \times 2 in. fixing centres.		C	"	1
17845	Type 792 ...	Ind. 10 henries. Current 200 mA		C	"	1
17852	Type 793 ...	Ind. 20 henries. Current 250 mA		C	"	1
17870	Type 794 ...	Ind. 5/10 henries. Resistance 100 ohms. Contained in hermetically sealed can. Approx. dims. $3\frac{1}{16}$ in. \times $3\frac{3}{8}$ in. \times $3\frac{3}{8}$ in.		C	"	1
18009	Type 795		C	"	1
18006	Type 796		C	"	1
18011	Type 800 ...	6.7 henries at 120 amps. 24 in. high \times 16 in. \times 11 in. approx. 2 lifting eyes. L.T. with cover.		C	"	1
18023	Type 803 ...	Ind. 10–14 henries. 500 mA, 200 volts, 50 cycles. $1\frac{1}{4}$ in. sq. core. 7 in. \times $7\frac{1}{4}$ in. \times $5\frac{3}{8}$ in.		C	"	1
18024	Type 804 ...	Ind. 1.4 henries at 1–5 amps; .205 in. air gap. 6 in. high \times 7 in. \times 4 in. $1\frac{1}{4}$ in. core. Bitumen dipped. For grid negative circuit.		C	"	1
17967	Type 806 ...	Ind. 4.3 H ...		C	"	1
17968	Type 811 ...	Double choke. 1.5 H at 100 mA. D.C. winding resistance:— 55 ohms \pm 20 per cent. for each choke. 2 coils each comprising 1,600 turns of 32 S.W.G. en. cu. wire, wound on formers and enclosed in metal can. Overall dims. 5.6 in. \times 2.7 in. \times 2.2 in. Fixing centres 1.85 in. \times 1.5 in.		C	"	1
17988	Type 813 ...	Ind. 10 H. Current 100 mA. D.C. resistance 243 ohms. 4,400 turns of S.W.G. en. cu. wire on former. Leads 6 in. long. Resistance at 15–60 C:— 243 ohms.		C	"	1
18085	Type 814 ...	6.5 mH at 25 amps. D.C. coil resistance .043 amp. 8.187 in. \times 7.625 in. \times 6.750 in.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	CHOKES—cont.					
	L.F.—cont.					
18086	Type 817 ...	74 henries at 1 volt 300 pps. 500 m/ohms resistance. 500 volts A.C. $2\frac{3}{8}$ in. \times $2\frac{1}{8}$ in. \times $2\frac{3}{8}$ in.		C	each	1
18087	Type 818 ...	8.8–13.2 henries. 300 pps. 1 volt. 500 volts A.C. test. $2\frac{3}{8}$ in. \times $2\frac{1}{8}$ in. \times $2\frac{3}{8}$ in.		C	..	1
18088	Type 819 ...	19–31 henries. 300 pps. 1 volt. 500 volts A.C. test. $2\frac{3}{8}$ in. \times $2\frac{1}{8}$ in. \times $2\frac{3}{8}$ in.		C	..	1
18089	Type 820 ...	80 mH at 3 amps. D.C. 330 turns 16 S.W.G. + coil res. 5 ohms. 6.750 in. \times 8.750 in. \times 5.250 in. Open type.		C	..	1
18090	Type 821 ...	1 mH 14 amp. D.C. resistance with cover. A.C. voltage.		C	..	1
18091	Type 822 ...	2 mH. 2 amps. mA at 800 cycles		C	..	1
18106	Type 823 ...	10 H at 100 mA. D.C. resistance 300 ohms. Overall dims. $3\frac{11}{16}$ in. \times $3\frac{3}{16}$ in. \times $4\frac{7}{8}$ in. high. Fixing centres $3\frac{3}{16}$ in. \times $2\frac{15}{16}$ in.		C	..	1
18095	Type 824 ...	1.25 H, 6 amps. 3 in. twin iron core. 1 ft. 6 in. \times 1 ft. 5 in. high \times 1 ft. $8\frac{1}{2}$ in. overall. Terminals.		C	..	1
18205	Type 828 ...	2.5 henries, 224 ohms, 300 pps. R.M.C. 2.905 in. \times 2.125 in. \times 1.245 in.		C	..	1
18224	Type 831 ...	3 Toroidal windings, 6 tapplings. 1.4–3.8 mH at 3.6 ohms 1 m/amp. 5.6 = 3.26 mH at 68 ohms 1 m/amp.		C	..	1
18227	Type 832 ...	12 H. .5 ohms. Reg. 5 amps., 50 c.p.s., 233 volts. 8 in. \times $5\frac{1}{8}$ in. \times 6 in.		C	..	1
18232	Type 833		C	..	1
18233	Type 834		C	..	1
18155	Type 837 ...	10 H., 140 mA. In sealed metal can, $3\frac{3}{8}$ in. \times 4 in. \times $5\frac{1}{4}$ in. high. Two $\frac{1}{16}$ in. terms. on base. 4 fixing holes tapped 2 B.A. on $3\frac{1}{8}$ in. \times $2\frac{1}{4}$ in. centres.		C	..	1
	R.F.:					
17042	R.F. No. 175 ...	Design "D" W/T installations, Type 272.		C	..	1
17046	R.F. ...	0–6- μ H, 1 meg. ohm, $\frac{1}{4}$ watt...		C	..	1
16886	CHOKE ASSEMBLIES.	Includes 1 choke T.53, and 1 resistor each of T.726 and T.6083.		C	..	1
15956	CHOKE ASSEMBLIES.	L.F. with cover, stand and terminals. 5,000 turns of 42 S.W.G. D.S.C.C.		C	..	1
	CHOKE UNITS:					
8463	Type 1 ...	Filament ...		C	..	1
8464	Type 2 ...	H.T. key and microphone ...		C	..	1
2943	Type 8 ...	3 coils wound on paxolin tubular former.		C	..	1
3615	Type 11 ...	Grid choke and grid lines (2), comprising 16 turns 30 S.W.G. D.S.C. wire on former.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	CHOKES UNITS —cont.					
3815	Type 15	First used on R.3030		C	each	1
4467	Type 17	Filter. First used on R.3016 ...		C	"	1
4473	Type 18	3 coils wound on S.R.P. tube:— Coil 1. 323½ turns of 29 D.S.C. wire. Coil 2. 462 turns of 36 D.S.C. wire. Coil 3. 300 turns of 37 D.S.C. wire.		C	"	1
5848	Type 22		C	"	1
11255	Type 25		C	"	1
11536	Type 29	Screened assembly, complete with L.T. choke and capaci- tor, Type 133 (10C/8010).		C	"	1
11537	Type 30	Screened assembly, complete with H.T. choke and capaci- tor, Type 133 (10C/8010).		C	"	1
12622	Type 36	Two chokes, wound on iron cores, 1½ in. × ¾ in.:—40 henries, 10 mA, D.C. resist- ance approx. 170 ohms.		C	"	1
13153	Type 43	3 chokes on mounting strip ...		C	"	1
13560	Type 45	Crystal compensator unit. S.R.B. panel. 1.38 in. × 1.75 in. × .06 in. 4 tags. 2 fixing holes .120 in. dia. at 1.37 in. centres.		C	"	1
13667	Type 48	Matched choke and capacitor, iron core.		C	"	1
15883	Type 57	Assembly on brass base plate, 11 in. × 8½ in. × ½ in. (19 in. × 13¾ in.).		C	"	1
5716	CLAMPS	Assembly of stud, ¼ in. dia. × 4½ in. long. Screwed 0 B.A. 1½ in. from one end, and clamping disc. 1½ in. × ¾ in. × 1½ in. A/F.		C	"	1
15803	CLAMPS, Brass ...	Brass. ¾ in. o/d, ⅝ in. i/d × ¾ in. 0 B.A. at 1 in. stud.		C	"	10
5715	CLAMPS, Brass ...	Brass. ¾ in. × 7/16 in. × 2½ in. i/d, with fixing lugs.		C	"	1
2644	CLAMPS, Capacitor	For capacitor, Type 857 ...		C	"	1
15970	CLAMPS, Capacitor T.H.1.		C	"	1
16301	CLAMPS, Capacitor T.H.2.	Required as initial stock on Radio R.A.E.		C	"	10
17795	CLAMPS, Capacitor		C	"	1
14761	CLAMPS, Capacitor T.V.1.	Vertical mounting		C	"	1
14756	CLAMPS, Capacitor T.V.2.	Vertical mounting		C	"	1
14760	CLAMPS, Capacitor T.V.3.	Vertical mounting 1½ in. dia. can		C	"	10
15224	CLAMPS, Capacitor T.V.4.	Vertical mounting 2 in. dia. can		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
14321	COIL ASSEMBLIES	10 × C2/coil, 1,400 turns 42 D.S.E. Wound on Cossor former, with variable iron core and 30 p.f. ± 10 per cent. ceramic disc.		C	each	1
14322	COIL ASSEMBLIES	2/MC/S coil, 60 turns 36 S.W.G. D.S.E. Wound on Cossor former, with variable iron core and 3 p.f.d. ± 10 per cent. ceramic disc.		C	..	1
15802	COILS, Coupling ...	Copper, tubular, $\frac{5}{8}$ in. o/d × $\frac{1}{2}$ in. i/d, with extension rod and spindle, wound to $5\frac{1}{4}$ in. o/d coil × $8\frac{1}{2}$ in. long.		C	..	1
5717	CONTACTS ...	Brass. 1.65 in. dia. × .02 in., $\frac{1}{4}$ in. hole.		C	..	1
2822	CONTACTS, FOIL ...	Capacitor. Phosphor bronze...		C	..	1
12395	CORES (Inductor) ...	Brass rod, $1\frac{1}{8}$ in. long × $\frac{1}{4}$ in. dia., screw for $1\frac{1}{4}$ in. slotted head.		C	..	1
	CORES, IRON DUST:—					
5826	10 mm. dia. × 17 mm. long.	Complete with adjusting screw, 4 B.A. × 30 mm. long. For use with Inductors, Type 501, 502, 503, and 504.		C	..	1
12578	Type 137 in. dia. × .5 in., on brass spindle 1.5 in. long.		C	..	1
12579	Type 237 in. dia. × .5 in., on brass spindle 1.5 in. long.		C	..	1
13338	Type 6		C	..	1
13968	Type 11	Screwed, screwdriver slot one end, $\frac{5}{8}$ in. long.		C	..	1
17841	Type 18	Type 16 less insulating sleeving		C	..	1
17860	Type 19	Threaded portion 1 in. × 4 B.A. Plain portion 1 in. × $\frac{5}{8}$ in. dia.		C	..	1
	INDUCTORS:—					
409	Type 6	A.M. allocation only		C	..	1
416	Type 13		C	..	1
419	Type 16		C	..	1
420	Type 17		C	..	1
421	Type 18		C	..	1
422	Type 19		C	..	1
12041	Type 23		C	..	1
10805	Type 25	Retard coil; 6 henries at 50 mA, D.C. resistance 150 ohms.		C	..	1
10790	Type 31	Aerial coil		C	..	1
11081	Type 32		C	..	1
11082	Type 33		C	..	1
11083	Type 34		C	..	1
11084	Type 35		C	..	1
771	Type 50		C	..	1
772	Type 5165 microhenries		C	..	1
773	Type 52	Inductance 50 μH		C	..	1
776	Type 53		C	..	1
778	Type 54	Inductance 99 μH		C	..	1
779	Type 55	Inductance .35 μH		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS —cont.					
780	Type 56	Inductance 1.24 μ H		C	each	1
781	Type 57	Inductance .77 μ H		C	"	1
831	Type 60		C	"	1
833	Type 61		C	"	1
834	Type 62		C	"	1
835	Type 63		C	"	1
893	Type 66		C	"	1
10658	Type 70	Choke coil		C	"	1
10804	Type 88		C	"	1
908	Type 10043 henries. 3 taps including centre tap.		C	"	1
912	Type 10259 millihenries approx. 7 turns 20 S.W.G. bare copper wire, wound anti-clockwise on grooved 4 rib ceramic former.		C	"	1
913	Type 103	Ind. .29 millihenries. Approx. 4 turns 20 S.W.G. bare copper wire, wound anti-clockwise on grooved 4 rib ceramic former.		C	"	1
914	Type 10421 mH. Approx. 4 turns 20 S.W.G. bare copper wire, wound anti-clockwise on grooved 4 rib ceramic former.		C	"	1
2099	Type 108	68 microhenries \pm 5 per cent. 1,000 cycles.		C	"	1
2111	Type 109	1.322 microhenries. With bakelite base. 10 turns of 10 S.W.G. bare cu. wire. Length of coil 2 in.		C	"	1
2140	Type 117	126 microhenries \pm 20 per cent. Iron cored. Overall size 1 $\frac{1}{2}$ in. \times $\frac{3}{8}$ in. dia.		C	"	1
2152	Type 119	1.26 microhenries. With mounting base. 10 turns of 10 S.W.G. bare cu. wire. Coil 2 in. \times 1 $\frac{3}{16}$ in. dia.		C	"	1
2153	Type 12093 microhenries. With mounting base. 8 turns of 10 S.W.G. bare cu. wire. Coil 1 $\frac{3}{8}$ in. \times 1 $\frac{3}{16}$ in. dia.		C	"	1
2154	Type 12179 microhenries. With mounting base. 8 turns of 10 S.W.G. bare cu. wire. Coil 2 $\frac{1}{8}$ in. \times 1 $\frac{3}{16}$ in. dia.		C	"	1
2201	Type 123	Oscillator coil		C	"	1
2202	Type 124	Shaping coil		C	"	1
2266	Type 125	S.W. intermediate frequency coil. Centre tapped		C	"	1
2608	Type 133	Shift coil assembly; comprises 2 coils each on formers. 4 $\frac{1}{2}$ in. long \times 1 in. dia., 1 coil mounted on each leg of U-shaped iron core 8 $\frac{1}{2}$ in. \times 5 $\frac{1}{2}$ in. \times $\frac{1}{2}$ in.		C	"	1
2609	Type 134	Di-placer coil assembly. Flat coil 2 $\frac{1}{8}$ in. dia. \times $\frac{1}{2}$ in., with mounting.		C	"	1
2632	Type 136	Primary: 250 microhenries. Secondary: (tuned, centre tapped) 58 microhenries. Iron core $\frac{5}{8}$ in. sq., coil former cheeks 1 $\frac{1}{4}$ in. dia.		C	"	1
11107	Type 137		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
2754	Type 138 ...	140 microhenries $\pm 2\frac{1}{2}$ per cent. Coil $1\frac{3}{4}$ in. dia. $\times \frac{3}{8}$ in.; former, tufnol, 1 in. $\times \frac{1}{2}$ in. dia.		C	each	1
2771	Type 140		C	"	1
2776	Type 141		C	"	1
2786	Type 148		C	"	1
2789	Type 151		C	"	1
2842	Type 153		C	"	1
2843	Type 154		C	"	1
2844	Type 155		C	"	1
2845	Type 156		C	"	1
2855	Type 160 ...	H.F. coil. Bare wire wound on moulded ceramic former, 7 turns, centre and 2 other tapings.		C	"	1
2856	Type 161		C	"	1
2857	Type 162 ...	H.F. coil. Bare wire on moulded ceramic former. 7 turns, centre and 2 other tapings.		C	"	1
2910	Type 163 ...	Aerial transformer, 20,000 kc/s to 1,500 kc/s.		C	"	1
2911	Type 164 ...	Amplifier, 20,000 kc/s to 1,500 kc/s.		C	"	1
2912	Type 165 ...	First stage		C	"	1
2913	Type 166 ...	First stage		C	"	1
2914	Type 167 ...	Second stage		C	"	1
2915	Type 168 ...	Second stage		C	"	1
2917	Type 172 ...	Range coil for wavemeter		C	"	1
2958	Type 177 ...	Iron cored, special		C	"	1
2959	Type 178 ...	Iron cored, special		C	"	1
2992	Type 181 ...	$3\frac{1}{2}$ turns 16 S.W.G. bare copper wire. Coil diameter $\frac{7}{16}$ in. internal. Iron dust core adjustable by cams.		C	"	1
2994	Type 183 ...	Wire-wound on loaded ebonite former. Spec. K.109— $\frac{7}{8}$ in. dia.		C	"	1
3151	Type 188 ...	Two windings (6 turns of 26 S.W.G. and 10 turns of 20 S.W.G. enam. wire) on ribbed former, with base and leads.		C	"	1
3156	Type 199 ...	Fixed		C	"	1
3159	Type 202 ...	Fixed		C	"	1
3166	Type 209 ...	Compensation coil		C	"	1
3167	Type 210 ...	I.F. coil grid		C	"	1
3168	Type 211 ...	I.F. coil anode		C	"	1
3169	Type 212 ...	I.F. coil diode		C	"	1
3232	Type 215 ...	190 millihenries, wound on moulded former.		C	"	1
3234	Type 217 ...	1,000 microhenries, creed, Part No. 2266/1.		C	"	1
3235	Type 218 ...	1,000 microhenries, $1\frac{1}{2}$ in. dia. $\times \frac{7}{16}$ in.		C	"	1
3495	Type 233 ...	Ind. No. of turns 150. C.R.T. deflecting cores, 5 sections of 150 turns per section .006 in. dia. D.S.C. copper.		C	"	1
3496	Type 234 ...	H.F. transformers, 4 sections. Primary 60 turns, secondary 133-133-133 No. 36 D.S.C. copper.		C	"	1
3497	Type 235 ...	Ind. Wavemeter. Primary 11 turns, secondary 1-1 turn .040 in. dia. copper.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
3498	Type 236 ...	C.R.T. tuner, 3 turns .064 in. dia. copper, tapped.		C	each	1
3542	Type 237 ...	2nd stage. 1.5 to .3 mc/s ...		C	"	1
3619	Type 241 ...	I.F. iron dust core ...		C	"	1
3816	Type 250 ...	$\frac{7}{8}$ in. outside dia. tubular former wound with closely spaced enam. cu. wire.		C	"	1
3817	Type 251 ...	$\frac{7}{8}$ in. outside dia. tubular former wound with closely spaced enam. cu. wire.		C	"	1
3818	Type 252 ...	$\frac{3}{8}$ in. dia. cylindrical former with 8 grooves—6 grooves wound with a total of 455 $\frac{1}{2}$ turns of 38 S.W.G. en. cu. wire.		C	"	1
3819	Type 253 ...	$\frac{3}{8}$ in. cylindrical former wound with 86 $\frac{1}{2}$ turns of 38 S.W.G. en. cu. wire.		C	"	1
3825	Type 254 ...	3 $\frac{1}{2}$ turns of $\frac{1}{8}$ in. copper rod ...		C	"	1
3826	Type 255 ...	4 turns of $\frac{1}{8}$ in. copper rod ...		C	"	1
3827	Type 256 ...	Helical coil, 2 turns of 14 S.W.G. cu. wire silver-plated.		C	"	1
3829	Type 258 ...	Helical coil, 3 turns of 14 S.W.G. cu. wire silver-plated.		C	"	1
3967	Type 262 ...	1 mH. 90 + 90 turns of 36 S.W.G. Trolitol, large round bobbin.		C	"	1
4045	Type 270 ...	Plug-in polystyrene former, 1 $\frac{1}{8}$ in. dia. across ribs \times 2 in., with 4 pins on strip. Windings, 50 turns and 16 turns, close wound.		C	"	1
4048	Type 273 ...	Complete on screwing Unit with wave switch H. F. sub-assembly.		C	"	1
4049	Type 274 ...	I.F. coupling variable \pm 2 per cent.; iron core.		C	"	1
4054	Type 279 ...	1 $\frac{1}{2}$ in. dia. former ...		C	"	1
4077	Type 280 ...	1 $\frac{1}{2}$ in. dia. ...		C	"	1
4078	Type 281		C	"	1
4124	Type 284 ...	3rd I.F. sub-assembly ...		C	"	1
4125	Type 285 ...	4th I.F. sub-assembly ...		C	"	1
4126	Type 286 ...	5th I.F. sub-assembly ...		C	"	1
4227	Type 301 ...	10 turns 20 S.W.G. wire. $\frac{1}{2}$ in. dia. \times $\frac{5}{8}$ in.		C	"	1
4228	Type 302 ...	9 turns 20 S.W.G. wire. $\frac{1}{2}$ in. dia. \times $\frac{5}{8}$ in.		C	"	1
4298	Type 307 ...	Ind. 780–1,719 k/c, 76 turns of 36 D.S.C. cu wire.		C	"	1
4301	Type 310 ...	4.6–10. 25 m/c 1 section. 26 turns of 28 D.S.C. cu. wire.		C	"	1
4302	Type 311 ...	9.3–21.5 m/c. 9 turns 18 enam. D.S.C., moulded former \times 262.		C	"	1
4303	Type 312 ...	Used on 1273 ...		C	"	1
4304	Type 313		C	"	1
4314	Type 314		C	"	1
4315	Type 315		C	"	1
4316	Type 316 ...	2 range coil unit ...		C	"	1
4317	Type 317		C	"	1
4364	Type 318		C	"	1
4365	Type 319		C	"	1
4366	Type 320		C	"	1
4380	Type 334		C	"	1
4381	Type 335		C	"	1
4382	Type 336		C	"	1

SECTION 100—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
4383	Type 337		C	each	1
4384	Type 338		C	"	1
4385	Type 339 ...	L.F. Filter ...		C	"	1
4450	Type 365 ...	I.F. Coil grid ...		C	"	1
4451	Type 366 ...	I.F. Anode and diode ...		C	"	1
4453	Type 368 ...	1st R.F. Coil and bracket assembly.		C	"	1
4454	Type 369 ...	2nd R.F. Coil and bracket assembly.		C	"	1
4458	Type 373 ...	6 turns of No. 18 tinned copper wire.		C	"	1
4459	Type 374 ...	46 turns of 25 enam. copper wire		C	"	1
4728	Type 378 ...	Wire-wound oscillator assembly, mounted on bakelite base, with brass core and distrene sleeve.		C	"	1
4729	Type 379 ...	Wire-wound, 1st R.F. assembly, mounted on bakelite base, with brass core and distrene sleeve.		C	"	1
4730	Type 380 ...	Wire-wound, 2nd R.F. assembly, mounted on bakelite base, with brass core and distrene sleeve.		C	"	1
4731	Type 381 ...	Wire-wound, aerial assembly, mounted on bakelite base, with brass core and distrene sleeve.		C	"	1
4733	Type 383 ...	22 turns of 36 gauge enam. S.S.C. cu. wire on $\frac{1}{2}$ in. dia. former.		C	"	1
4734	Type 384 ...	18 turns of 36 gauge enam. S.S.C. cu. wire on $\frac{1}{2}$ in. dia. former.		C	"	1
4833	Type 388		C	"	1
4835	Type 390		C	"	1
4838	Type 393 ...	Cylindrical former, twin lug fixing, 3 section winding, 527.6 millihenries.		C	"	1
4839	Type 394 ...	Cylindrical former, twin lug fixing, 3 section winding, 521.7 millihenries.		C	"	1
4858	Type 396 ...	13 turns 36 gauge enam. S.S.C. cu. wire on $\frac{1}{2}$ in. dia. former.		C	"	1
5002	Type 404 ...	32 turns cu. wire single weave, Trolitol former $\frac{3}{8}$ in. o/d, with dust iron core.		C	"	1
5077	Type 422 ...	35 millihenries, 10 mA, $1\frac{1}{2}$ in. max. dia. Wave-wound coil on tubular bakelite former $1\frac{1}{8}$ in. long approx., complete with pins.		C	"	1
5109	Type 436 ...	Ind. 75 mH. Paxolin former $2\frac{3}{4}$ in. \times 2 in. dia.		C	"	1
5122	Type 439 ...	650 microhenries, wire-wound on iron core, with upper and lower mountings.		C	"	1
5381	Type 456 ...	$\frac{3}{4}$ in. o/d \times $1\frac{3}{8}$ in. 5 turns $\frac{1}{8}$ in. dia. cu. wire, silver-plated. 2 spills soldered one turn from each end.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
5382	INDUCTORS —cont. Type 457 ...	Tuning coil assembly, comprising $4\frac{1}{2}$ turns of 24 S.W.G. D.S.C. cu. wire, wound on bakelite former (A.16212). Complete with collet (A.16199), slug (A.16196), assembled on mounting plate, $2\frac{1}{2}$ in. \times $1\frac{1}{8}$ in. \times .64 in. thick M.S.		C	each	1
5384	Type 45946 mH approx. 6 turns 20 S.W.G. bare cu. wire wound clockwise on grooved 4 ribbed ceramic former.		C	..	1
5385	Type 460 ...	Windings:—Primary, 150 turns of 42 S.W.G. S.S. en. cu. wire, centre tapped. Secondary, 450 turns (3×150) of 42 S.W.G. S.S. en. cu. wire; inductance 7 millihenries, $Q = 70$.		C	..	1
5386	Type 461 ...	Windings.—Primary, 450 turns (3×150) of 42 S.W.G. S.S. en. cu. wire, inductance 7 millihenries, $Q = 70$. Secondary, 40 turns of 36 S.W.G. S.S. enam. cu. wire.		C	..	1
5388	Type 463 ...	Windings:—Primary, 396 turns (3×132) of 42 S.W.G. S.S. en. cu. wire, inductance 3.7 millihenries, $Q = 75$. Secondary, 44 turns of 36 S.W.G. S.S. en. cu. wire, inductance .09 millihenries.		C	..	1
5389	Type 464 ...	Windings:—Primary, 40 turns of 36 S.W.G. S.S. en. cu. wire. Secondary, 450 turns (3×150) 42 S.W.G. S.S. en. cu. wire, Inductance 7 millihenries, $Q = 70$.		C	..	1
5394	Type 466 ...	Coil assembly ...		C	..	1
5500	Type 467 ...	H.T., S.R.B. paper tube, $2\frac{5}{16}$ in. long \times $\frac{3}{4}$ in. dia.; spigot mounting; 55 turns of 24 S.W.G. enam. cu. wire, close wound, tags.		C	..	1
5501	Type 468 ...	L.T. S.R.B. paper tube, $2\frac{5}{16}$ in. long \times $\frac{3}{4}$ in. dia.; spigot mounting; 16 turns of 16 S.W.G. enam. cu. wire, close wound, tags.		C	..	1
5520	Type 487 ...	No. of turns 22, $\frac{1}{2}$, 24 D.S.C., tapped at 14, $\frac{1}{2}$ and 7, $\frac{3}{4}$ turns. Iron core.		C	..	1
5606	Type 496 ...	Windings:—2 turns and 9 turns of 22 S.W.G. tinned cu. wire, spaced $\frac{1}{8}$ in. apart. Coil of 9 turns, tapped 3 turns from bottom; 2 turns wound at "earthy" end of former.		C	..	1
5736	Type 498 ...	Tuned by dust iron cores, 380 turns of 9/46 Litz en. wire; 1,750 microhenries \pm 5 per cent.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
5737	Type 4999 millihenries, Tufnol tubular former (76/13/1), wave-wound with 142 + 135 turns of 40 S.W.G. D.S.C. cu. wire, air core.		C	each	1
5738	Type 500 ...	10 millihenries, Tufnol tubular former (76/13/1), wave-wound with 435 + 405 turns of 40 S.W.G. D.S.C. cu. wire, air core.		C	..	1
5828	Type 502 ...	2.74 millihenries (without core), Tufnol tubular former (76/12/1), wave-wound with (125 + 125) + 250 turns of 38 S.W.G. D.S.C. cu. wire.		C	..	1
5829	Type 503 ...	26 millihenries (without core), Tufnol tubular former (76/12/1), wave-wound with (445 + 445) + 890 turns of 40 S.W.G. D.S.C. cu. wire.		C	..	1
5830	Type 504 ...	170 millihenries (without core), Tufnol tubular former (76/12/1), wave-wound with (990 + 990) + 1,980 turns of 40 S.W.G. D.S.C. cu. wire.		C	..	1
5833	Type 505 ...	10 turns of 20 S.W.G. cu. wire wound on Trolitol former. Inductance .58 mH.		C	..	1
5834	Type 506 ...	15 turns of 23 S.W.G. D.S. cu. wire on vulcanite former, ½ in. dia. × ¾ in.		C	..	1
5920	Type 507 ...	Iron core, paper former, 120 turns; paxolin bracket; 298 microhenries.		C	..	1
5923	Type 510 ...	1.8 millihenries		C	..	1
5924	Type 511 ...	Inductance 138 mH. Calibration coil: 1.5 per cent., 1 ¼ in. dia. × ¾ in. approx. on former, complete with angle mounting bracket, 2,730 turns 38 D.S.C.		C	..	1
5925	Type 512 ...	I.F. coupling, 60 turns of 40 S.W.G. D.S.C.		C	..	1
5936	Type 515 ...	4 ½ turns and 1 turn. Steatite former, oval foot, 1 ⅙ in. fixing centres, 6 B.A. holes, hex. former 2 ½ in. high, threaded 10 t.p.i.; trimmer cap.		C	..	1
11045	Type 517 ...	Moulded former, 1 ½ in. dia. × 2 ⅝ in. long; air core, 16 ½ turns, 5.6 microhenries.		C	..	1
11046	Type 518 ...	Moulded former, 1 ½ in. dia. × 2 ⅝ in. long; air core, 29 ½ turns, 18.5 microhenries.		C	..	1
11047	Type 519 ...	Moulded former, 1 ½ in. dia. × 2 ⅝ in. long; air core, with terminal strip, 344 turns, 2,266 microhenries, 8 sections, tapped 3rd and 5th sections.		C	..	1
11108	Type 521 ...	2.4 mH, .5 mH, No. of turns 313 ½, 140, 36 S.W.G. Tuning and reaction tapped at 7 ½ turns. D.S.C copper coupling coil, 3 in. × ½ in. paxolin former, etc.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
11152	Type 525 ...	9 turns 24 en. cu. wire, dust iron core.		C	each	1
11153	Type 526 ...	3½ turns 24 en. cu. wire, dust iron core.		C	"	1
11166	Type 528		C	"	1
11242	Type 541 ...	Aerial coil and bracket assembly, 4 5/6 turns + 5/6, coupling turn.		C	"	1
11244	Type 543 ...	Coil tuning ...		C	"	1
11318	Type 550 ...	Brass, 1 in. × ½ in. × 2½ in. long, cut away 1½ in. × ⅜ in.		C	"	1
11347	Type 552 ...	Comprise 1 resistor 1,000 ohms, 400 turns 38 S.W.G. D.S.C. wire; 10 capacitors 23 μμF., 1 capacitor 7.5 μμF., all waxed; dipped after assembly.		C	"	1
11348	Type 553 ...	1 in. × 1⅜ in. long. 1 turn of 12 S.W.G. wire.		C	"	1
11349	Type 554 ...	1⅜ in. × 2¼ in. long, lead 1⅜ in. long. 1 turn of 12 S.W.G. wire.		C	"	1
11350	Type 555 ...	1 turn of 12 S.W.G. wire. 1⅜ in. × 2 in.		C	"	1
11354	Type 558 ...	1 turn of 12 S.W.G. wire. 1½ in. dia.		C	"	1
11355	Type 559 ...	½ turn of 12 S.W.G. wire. ⅞ in. rod.		C	"	1
11356	Type 560 ...	1 turn of 12 S.W.G. wire. 1⅞ in. dia.		C	"	1
11438	Type 580 ...	4 turns of 20 S.W.G. cu. wire on ¼ in. former.		C	"	1
11456	Type 583 ...	6 turns ...		C	"	1
11457	Type 584 ...	1st and 2nd R.F. ...		C	"	1
11458	Type 585 ...	Grid ...		C	"	1
11503	Type 587 ...	4 turns ...		C	"	1
11518	Type 591 ...	Range 1, wave-wound coils on moulded formers.		C	"	1
11519	Type 592 ...	Range 2, wave-wound coils on moulded formers.		C	"	1
11520	Type 593 ...	Beacon, wave-wound coils on moulded formers.		C	"	1
11522	Type 594 ...	I.F. coil unit, bakelite former (C.13145) on S.R.B.P. sheet (A.16788), 1½ in. × ⅞ in. × 1½ in., adjustable solid iron core.		C	"	1
11531	Type 599 ...	H.F. 1½ turns of 1 mm. tinned cu. wire, 2 mm. pitch; length before winding, 60 mm.; internal dia. 8 mm.		C	"	1
11532	Type 600 ...	H.F. 1½ turns of 2 mm. tinned cu. wire, 4 mm. pitch; length before winding 110 mm.; internal dia. 8 mm.		C	"	1
11533	Type 601 ...	H.F. 2½ turns of 1 mm. tinned cu. wire; internal dia. 8 mm.; length 14 mm.		C	"	1
11534	Type 602 ...	H.F. 3 turns of 2 mm. tinned cu. wire, 4 mm. pitch; length 25 mm.; internal dia. 13 mm.		C	"	1
11535	Type 603 ...	H.F. 2¼ turns of 2 mm. tinned cu. wire; length 23 mm.; internal dia. 13 mm.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
11584	Type 606 ...	Steatite former, $4\frac{1}{4}$ in. long, 2 in. dia., 6 ribs grooved, 10 turns, centre tapped, spigot mounted.		C	each	1
11615	Type 611 ...	Half loop, $\frac{15}{8}$ radius, 20 S.W.G.		C	"	1
11640	Type 615 ...	10 coils, 11 capacitors and 1 resistor assembled on insulating rod, and the whole wax coated, mounted on bracket (D.P.4472).		C	"	1
11710	Type 622 ...	1 turn of 20 S.W.G. \times $\frac{1}{4}$ in. wide, S.P. copper.		C	"	1
11735	Type 624 ...	10 coils mounted on brackets, with terminal plate; includes cover.		C	"	1
11820	Type 628 ...	36 to 54 mc/s., ebonite former, $\frac{1}{2}$ in. \times 1 in. \times $2\frac{1}{2}$ in. long. Diagonally wound $2\frac{3}{4}$ turns of 20 S.W.G. en. cu. wire.		C	"	1
11876	Type 635 ...	632 mH. No. of turns 286, 40 S.W.G., 32 ohms. Secondary, 317 turns 34 S.W.G., 600 μ F., 9.2 ohms, en. cu. wire.		C	"	1
11877	Type 636 ...	No. of turns, 600 primary 40 S.W.G., 687 secondary 40 S.W.G. en. cu. wire.		C	"	1
11878	Type 637 ...	Primary, 80 turns of 40 S.W.G., 82 micro-H, 9-7 ohms. Secondary, 101 turns of 24 S.W.G., 75 micro-H, 0.57 ohms. En. cu. wire.		C	"	1
11879	Type 638 ...	No. of turns, 190 primary, 221 secondary, 40 S.W.G., 30 S.W.G. en. cu. wire.		C	"	1
11880	Type 639		C	"	1
11882	Type 641 ...	600 microhenries ...		C	"	1
11883	Type 642 ...	2,400 microhenries ...		C	"	1
11901	Type 653 ...	Primary, 117 turns 40 S.W.G., 116 mH D.C., 13.6 ohms. Secondary, 317 turns 34 S.W.G., 600 μ H, 9.2 ohms. En. cu. wire.		C	"	1
11904	Type 655 ...	Delay network fitted with 12 Leeson wound coils.		C	"	1
11913	Type 657 ...	531 micro-H, wound with 27/46 S.W.G. on S.S.C. cu. wire.		C	"	1
11924	Type 658 ...	Moulded former, $1\frac{1}{2}$ in. dia. \times $2\frac{3}{8}$ in. long, 8.5 micro-H, air core, 21 turns, tapped at 7, 9 and 15 turns.		C	"	1
11925	Type 659 ...	Moulded former, $1\frac{1}{2}$ in. dia. \times $2\frac{3}{8}$ in. long, 28.6 micro-H, air core, 40 turns, tapped at 17 and 28 turns.		C	"	1
11941	Type 661 ...	8 mH ...		C	"	1
12006	Type 663 ...	Variable H.F. current, phasing coil assembly of wire-wound former, iron dust core, etc.		C	"	1
12009	Type 664 ...	3,000 turns 40 S.W.G. C. and and S.S.C., $1\frac{3}{4}$ in. long $\frac{1}{2}$ in. former, 125 mH.		C	"	1
12010	Type 665 ...	350 turns 34 S.W.G. C. and and S.S.C., $\frac{3}{16}$ in. long, $\frac{1}{2}$ in. former, 2 mH, without core.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
12011	Type 666 ...	16 turns 36 S.W.G. enam., $\frac{1}{2}$ in. former, centre tapped.		C	each	1
12028	Type 671 ...	$1\frac{1}{2}$ turns 10 S.W.G. tinned cu. wire, silver-plated, $1\frac{1}{4}$ in. i/d.		C	..	1
12029	Type 672 ...	$\frac{3}{4}$ turns 10 S.W.G. tinned cu. wire, silver-plated, $2\frac{1}{4}$ in. i/d.		C	..	1
12030	Type 673 ...	1 turn $\frac{1}{4}$ in. copper tube, silver-plated, $3\frac{1}{2}$ in. dia., with clip.		C	..	1
12045	Type 675 ...	400 \pm 25 kc/s., 66 turns + 315 turns, tapped, 38 S.W.G. D.S.C., wound on moulded hexagonal former, $\frac{17}{32}$ in. across flats \times $1\frac{11}{16}$ in.		C	..	1
12119	Type 678 ...	2 windings, each 425 .0052 enamel and S.C.C. cu. wire, in series, on bakelite former $\frac{1}{2}$ in. o/d, with adjustable iron dust core.		C	..	1
12121	Type 680 ...	6 turns of 20 S.W.G., tapped at $2\frac{1}{2}$ turns, on hollow dystrene former $\frac{1}{8}$ in. o/d, with adjustable brass slug.		C	..	1
12122	Type 681 ...	17 turns of .007 in. S.C.C., on bakelite former $\frac{1}{2}$ in. o/d, with adjustable iron dust core.		C	..	1
12123	Type 682 ...	4 turns of 20 S.W.G. bare tinned cu. wire, tapped at 2 turns; former $\frac{5}{16}$ in. o/d.		C	..	1
12163	Type 684 ...	25 micro-H, 55 turns of 22 S.W.G. en. cu. wire, spaced .02 in., tapped at 29 turns; S.R.B.P. former 4.37 in. \times 1 in. dia.; complete with leads.		C	..	1
12170	Type 690 ...	12 turns of 24 S.W.G. en. wire on hollow Trolitol former, $\frac{1}{2}$ in. o/d \times $1\frac{1}{2}$ in. long.		C	..	1
12199	Type 693 ...	2 windings, 6 + 11 turns of 30 S.W.G. cu. wire on vulcanite former, with 3 soldering pins.		C	..	1
12200	Type 694 ...	86.5 turns of 38 S.W.G. cu. wire on loaded ebonite former, .37 in. dia. \times 2 in.		C	..	1
12209	Type 698 ...	17 turns of No. 22E/cu. wire on .5 in. dia. former, in metal screening can.		C	..	1
12280	Type 716 ...	Used on A.R.I.5513 ...		C	..	1
12297	Type 717 ...	Used on A.R.I.5194 ...		C	..	1
12298	Type 718 ...	H.F. coil. Used on A.R.I.5194		C	..	1
12299	Type 719 ...	Oscillator. Used on A.R.I.5194		C	..	1
12300	Type 720 ...	Aerial coil. S.R.B.P. tube, $\frac{3}{4}$ in. dia. \times $2\frac{1}{4}$ in. long; 6 turns 18 S.W.G. T. wire, tapped.		C	..	1
12328	Type 721 ...	Focussing coil ...		C	..	1
12329	Type 722 ...	Deflection coil ...		C	..	1
12360	Type 723 ...	Former, WT.16930/1A. Wound 6 turns 26 S.W.G. D.S.C. per slot, clamped between 2 brackets.		C	..	1
12364	Type 724 ...	18 turns 36 S.W.G. en. cu. wire on former, $\frac{1}{2}$ in. dia. \times $1\frac{1}{4}$ in. long, with tags.		C	..	1
12365	Type 725 ...	16 turns of 36 S.W.G. en. cu. wire on former, $\frac{1}{8}$ in. dia. \times $1\frac{1}{4}$ in. long, with 4 tags.		C	..	1

SECTION 100—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	INDUCTORS—cont.					
12366	Type 726 ...	19 + 2 turns 36 S.W.G. en. cu. wire on former, 1½ in. dia. × 1¼ in. long, with tags.		C	each	1
12367	Type 727 ...	100 turns 38 E.S.S. wire wound on ¼ in. dia. former. Coil, ⅜ in. long, 13.5 mH.		C	„	1
12546	Type 750 ...	1.5 mH. 165 + 165 turns 38 E.S.S. wire, with core.		C	„	1
12547	Type 751 ...	17 + 2 turns 36 S.W.G. en. cu. wire on former, ½ in. dia. × 1¼ in. long, with 4 tags.		C	„	1
12576	Type 759 ...	3 turns 14 S.W.G. cu. wire, silver-plated, mounted on S.R.B.P. panel, 1.25 in. × .69 in., with brass tag plates.		C	„	1
12580	Type 761 ...	2.77 μH. 17 turns .0148 in. cu. wire on former, .5 in. dia. × 1.37 in.		C	„	1
12604	Type 766 ...	I.F. coil ...		C	„	1
12639	Type 772 ...	16 turns of 26 S.W.G. en. cu. wire, double spaced, on former, 2 in. × ⅝ in. dia. Complete with diode clip.		C	„	1
12640	Type 773 ...	1,000 turns of 40 S.W.G. on former, 1½ in. × ½ in. dia.		C	„	1
12648	Type 775 ...	28.6 mH ± 5 per cent. at 1 m/c. 48 turns 34 S.W.G. en. cu. wire.		C	„	1
12692	Type 776 ...	600 μH. 200 turns 34 D.S.C. cu. wire on Tufnol former, 1½ in. × ½ in. dia. single pie, ½ in. wide.		C	„	1
12717	Type 785 ...	Oscillator, band 3. Main winding, 6¾ turns of 26 S.W.G. D.S.C. wire. Tap at 1½ turns, twisted and soldered to main coil. Subsidiary winding, 3¼ turns of 30 S.W.G. D.S.C. wire.		C	„	1
12721	Type 789 ...	Oscillator, band 4. Main winding, 3¾ turns of 22 S.W.G. en. cu. wire. Tap at 1½ turns and solder to main coil. Subsidiary winding, 3¼ turns of 26 S.W.G. D.S.C. wire, 1½ turns to be interwound with main winding.		C	„	1
12722	Type 790 ...	2nd R.F., band 4. Main winding, 5¾ turns of 22 S.W.G. en. cu. wire. Overall length of main coil centre to centre of wire = ⅝ in. Tap at 2½ turns and solder to main coil.		C	„	1
12723	Type 791 ...	1st R.F., band 4. Main winding, 5¾ turns of 22 S.W.G. en. cu. wire. Overall length of main coil centre to centre of wires = ⅝ in. Tap at 1½ turns and solder to main coil.		C	„	1
12726	Type 794 ...	2nd R.F., band 5. Main winding, 3½ turns of 18 S.W.G. tinned cu. wire. Tap at 1½ and ¾ of a turn. Overall length of main winding, centre to centre of wire = ⅝ in.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
12727	Type 795	1st R.F., band 5. Main winding, $3\frac{3}{4}$ turns of 18 S.W.G. tinned cu. wire. Tap at $\frac{5}{8}$ of a turn and solder to end. Overall length of main winding, centre to centre of wires = $\frac{9}{32}$ in.		C	each	1
12728	Type 796	Aerial, band 5. Main winding, $3\frac{1}{4}$ turns of 18 S.W.G. tinned cu. wire. Tap at $\frac{3}{8}$ of a turn and solder to main coil. Overall length of main winding, centre to centre of wires = $\frac{9}{32}$ in.		C	..	1
12781	Type 801	Wire wound on former, 2 turns 22 S.W.G. tinned copper.		C	..	1
12782	Type 802	1 turn of 28 S.W.G. $\times \frac{5}{32}$ in. copper strip.		C	..	1
12818	Type 828	2,280 mH. 40 S.W.G. wire wound on Ferromould former, with iron dust core. 9/44 Litz. 40 S.W.G. double silk covered. 207 mH. 4 sections.		C	..	1
12887	Type 847	88 mH. 5/44 Litz. 3 sections, $17\frac{7}{8}$, 17 and 17 turns.		C	..	1
12935	Type 858	Bakelite former (A.28931), with 2,010 turns of 40 S.W.G. D.S.C. wire, tapped at 845 and 1,030 turns. Range coil No. 3.		C	..	1
13054	Type 877	Copper wire coil, 14 S.W.G., silver-plated; 4 turns, $\frac{1}{8}$ in. pitch, $\frac{1}{2}$ in. dia. mandrel.		C	..	1
13055	Type 878	Copper wire coil, 14 S.W.G., silver-plated; 3 turns, $\frac{1}{8}$ in. pitch, on $\frac{5}{8}$ in. dia. mandrel.		C	..	1
13056	Type 879	Copper wire coil, 14 S.W.G., silver-plated; 2 turns, $\frac{1}{8}$ in. pitch, on $\frac{5}{8}$ in. dia. mandrel.		C	..	1
13090	Type 881	Aerial coupling, 3 turns 12 S.W.G. silver-plated cu. wire on 14 mm. dia. mandrel, $2\frac{7}{16}$ in. $\times 1\frac{3}{8}$ in. overall dims.		C	..	1
13091	Type 882	Final anode. 6 turns $\frac{1}{2}$ in. dia. silver-plated cu. tube on 23 mm. dia. mandrel, 2 in. long.		C	..	1
13092	Type 883	Penultimate anode. $5\frac{1}{2}$ turns $\frac{1}{2}$ in. dia. silver-plated copper tube on 14 mm. mandrel, $\frac{1}{2}$ in. pitch, $1\frac{3}{8}$ in. long.		C	..	1
13147	Type 907	A.G.S. coil. Used on A.R.I. 5131.		C	..	1
13196	Type 909	L.2		C	..	1
13198	Type 911	L.4		C	..	1
13199	Type 912	L.1		C	..	1
13200	Type 913	L.7		C	..	1
13201	Type 914	L.3		C	..	1
13202	Type 915		C	..	1
13246	Type 916	Enam. and cotton braided, 19 in. \times 11 in. dia. Tapped every eight turns. 128 turns 243/0006 Litz wire.		C	..	1
13270	Type 917	I.F. coupling. 142 microhenries. 67 turns 40 S.W.G. enam. S.S.C.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
13378	Type 921 ...	25 turns of wire on former, $\frac{1}{2}$ in. dia. \times $1\frac{1}{4}$ in. long.		C	each	1
13379	Type 922 ...	24 turns 23 S.W.G. on former, without bracket.		C	..	1
13380	Type 923 ...	24 turns 23 S.W.G. en. cu. wire, with bracket.		C	..	1
13394	Type 925 ...	25 H, 30 mA D.C. Resistance 750 ohms.		C	..	1
13403	Type 926 ...	Secondary winding of I.F. transformer, Type 311, 20 ft. 30 S.W.G. D.S.C., 92 turns.		C	..	1
13404	Type 927 ...	Primary winding of I.F. transformer, Type 311, 16 ft. 30 S.W.G. D.S.C., 75 turns.		C	..	1
13405	Type 928 ...	Secondary winding of diode transformer, Type 349.		C	..	1
13406	Type 929 ...	Primary winding of diode transformer, Type 349.		C	..	1
13401	Type 931 ...	10 turns 26 S.W.G. en. cu. wire on Trolitol former (Former coil, Type 1), dust core.		C	..	1
13417	Type 932 ...	66.1 microhenries \pm 5 per cent at 1,000 cycles, 14 ft. 38 S.W.G. D.S.C.		C	..	1
13418	Type 933 ...	I.F. 154 microhenries, 72 turns 40 S.W.G.		C	..	1
13419	Type 934 ...	I.F. 278 microhenries, 96 turns 40 S.W.G.		C	..	1
13428	Type 939 ...	16 μ H, 1,070 μ H, 5 per cent. 26T 1 per cent. 230 T 40 D.E. 40 D.E. Rect-angular screening can slotted; fixed feet winding tags, 1-2, 3-4.		C	..	1
13526	Type 958 ...	400 μ H. 2 sections of 155 turns $\frac{3}{8}$ in. apart.		C	..	1
13527	Type 959 ...	600 μ H. 2 sections of 180 turns $\frac{3}{8}$ in. apart.		C	..	1
13528	Type 960 ...	700 μ H. 2 sections of 250 turns $\frac{1}{4}$ in. apart.		C	..	1
13541	Type 965 ...	76 $\frac{1}{2}$ turns of 40 S.W.G. en. cu. wire on former, $\frac{1}{2}$ in. dia., with bracket.		C	..	1
13562	Type 968 ...	Coil on former in can. $1\frac{1}{2}$ in. sq. \times $3\frac{3}{8}$ in. External lead $3\frac{1}{2}$ in. long.		C	..	1
13563	Type 969 ...	Coil on former in can. $1\frac{1}{2}$ in. sq. \times $3\frac{3}{8}$ in. External lead $4\frac{1}{2}$ in. long.		C	..	1
13564	Type 970 ...	2 coils on iron core, complete with 2 capacitors in can, $1\frac{3}{4}$ in. sq. \times 3 in.		C	..	1
13565	Type 971 ...	Voltmeter coil, 3 coils on former. Coils "A" and "C" each 170 turns of 3/44 Litz. S.S.C. Coil "B" 15 turns of 38 S.W.G. cu. wire wound between "A" and "C". The whole contained in can.		C	..	1
13572	Type 972 ...	850 μ H \pm 1 per cent. ...		C	..	1
13573	Type 973 ...	H.F. transformer, 150 kc/s, 20,000 ohms: 75 ohms. Rect-angular screened. 2 hole base fixing, $2\frac{3}{8}$ in. centres.		C	..	1

SECTION 100—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom of Qty	Carton Unit Qty
1	2	3	4	5	6	7
	INDUCTORS—cont.					
13598	Type 979 ...	500 turns 39 S.W.G. D.S.C. wire, tapped at 50 turns, on former 1 in. \times $\frac{1}{2}$ in. dia. 4 tags and stud, screwed 4 B.A. \times $\frac{3}{8}$ in. long.		C	each	1
13618	Type 980 ...	775 turns 38 S.W.G. en. cu. wire, wave-wound (10 μ H approx.).		C	..	1
13639	Type 982 ...	53 μ H \pm 20 per cent., 155 turns of 27/46 wire, iron dust core in screening case (Inductor).		C	..	1
13640	Type 983 ...	Primary, 200 μ H \pm 5 per cent. Secondary, 1,330 μ H \pm 5 per cent. Valence \pm 1 per cent. Iron dust core in screening case. 2 hole fixing.		C	..	1
13704	Type 987 ...	4 banks each 175 turns 38 S.W.G. double silk covered, wound on paxolin former, with wire ends, $1\frac{1}{4}$ in. \times $1\frac{1}{4}$ in. overall dims.		C	..	1
13715	Type 991 ...	77 μ H. 8 turns; centre tapped for even numbers of turns.		C	..	1
13724	Type 992 ...	Silver-plated assembly. Slotted brass bar, $2\frac{1}{2}$ in. \times $1\frac{1}{16}$ in. \times $\frac{1}{2}$ in., with spring clips. 150–300 mc/s.		C	..	1
13725	Type 993 ...	Wire-wound assembly of ebonite block, 1 in. \times $\frac{1}{2}$ in. \times $2\frac{1}{2}$ in., with 2 sockets and spring clips, 35–58 mc/s.		C	..	1
13726	Type 994 ...	Wire-wound assembly of ebonite block, 1 in. \times $\frac{1}{2}$ in. \times $2\frac{1}{2}$ in., with 2 sockets and spring clips, 10–18 mc/s.		C	..	1
13748	Type 997 ...	70 turns 40 S.W.G. en. cu. wire on Tufnol former, $1\frac{3}{16}$ in. \times $\frac{3}{8}$ in.		C	..	1
13755	Type 999 ...	Aerial coil. 2 turns of 16 S.W.G. bare T.C. wire, spaced .16 in., i/d $\frac{5}{32}$ in.		C	..	1
13756	Type 1000	T.R.F. coil, 3 turns of 16 S.W.G. bare T.C. wire, spaced .125 in., i/d $\frac{5}{32}$ in.		C	..	1
13757	Type 1001	T.R.F. coil, $3\frac{1}{2}$ turns of 16 S.W.G. bare T.C. wire, spaced .125 in., i/d $\frac{5}{32}$ in.		C	..	1
13758	Type 1002	I.F. coil, 8 turns on Tufnol former. Dust iron core trimmed.		C	..	1
13759	Type 1003	I.F. transformer. Primary 10 turns 26 S.W.G. enam. wire. Secondary 1 turn 26 S.W.G. enam. wire. Dust iron core trimmed.		C	..	1
13822	Type 1012	$9\frac{1}{2}$ turns 26 S.W.G. en. cu. wire on hollow Trolitol former (Pye 55276). Dust iron cored (10B/1336, Type 2, Neosid T.C.8/1-25 M.N.X.).		C	..	1
13900	Type 1019	Paxolin former, $\frac{1}{2}$ in. dia. \times $1\frac{3}{4}$ in. long; 4 solder tags, $7\frac{3}{4}$ turns tapped $4\frac{3}{4}$ from grid end. 2 coupling turns close wound, 32 S.W.G. en. cu. wire.		C	..	1

SECTION 100—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
13901	Type 1020 ...	Paxolin former, $\frac{1}{2}$ in. dia. \times $1\frac{3}{4}$ in. long; 4 solder tags, $7\frac{3}{4}$ turns tapped $4\frac{3}{4}$ from grid end. 2 coupling turns closewound, 32 S.W.G. en. cu. wire.		C	each	1
13920	Type 1024 ...	3 turns 16 S.W.G. en. wire, .345 in. i/d at .109 in. pitch, extended ends.		C	"	1
13921	Type 1025 ...	As Type 1024, but with additional connecting strip.		C	"	1
13922	Type 1026 ...	3 turns 16 S.W.G. en. wire, .290 in. i/d at .109 in. pitch, extended ends.		C	"	1
13923	Type 1027 ...	16 turns .0124 in. en. cu. wire on vulcanite former, .5 in. dia. \times 1.37 in.		C	"	1
13924	Type 1028 ...	7 turns 16 S.W.G. tinned cu. wire wound on grooved vulcanite former, .953 in. o/d \times .75 in. i/d \times 1.281 in.		C	"	1
13925	Type 1029 ...	11 turns 18 S.W.G. tinned cu. wire wound on grooved vulcanite former, .95 in. o/d \times .75 in. i/d.		C	"	1
13926	Type 1030 ...	3 turns 16 S.W.G., .462 in. i/d at .25 in. pitch, extended ends.		C	"	1
13927	Type 1031		C	"	1
13956	Type 1033 ...	Quench oscillation, 265 turns 34 S.W.G. D.S.C., tapped at 230.		C	"	1
13993	Type 1036 ...	4 turns 32 S.W.G. en. cu. wire on former.		C	"	1
13994	Type 1037 ...	1 and 7 turns 27 S.W.G. en. cu. wire on former.		C	"	1
13995	Type 1038 ...	6 turns 36 S.W.G. en. cu. wire on former.		C	"	1
13996	Type 1039 ...	1 and 6 turns 27 S.W.G. en. cu. wire on former.		C	"	1
14010	Type 1041 ...	Ind. 4 mH, 10 turns. Coil on moulded ebonite former.		C	"	1
14012	Type 1043 ...	10 turns 26 S.W.G. en. cu. wire, wound clockwise on former (10A/14279), with variable iron dust core (10B/1336).		C	"	1
14013	Type 1044 ...	11 turns, then 2 turns, 26 S.W.G. en. cu. wire, wound clockwise on former (10A/14270), with variable iron dust core (10B/1336).		C	"	1
14054	Type 1054 ...	Top boost coil, ind. 295 μ H, on bakelite former (C. 12098), wound with one coil, complete with 6.8 K resistor.		C	"	1
14055	Type 1055 ...	Top boost coil, 420 μ H, on bakelite former, with 1 resistor T.6433 (10C/6433).		C	"	1
14063	Type 1056 ...	Inductor T.365 mod. by removing coil and rebinding with 3 turns 20 S.W.G. cu. wire.		C	"	1
14094	Type 1060 ...	330 μ H \pm 2 per cent. ...		C	"	1
14095	Type 1061 ...	497 μ H \pm 2 per cent. ...		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS —cont.					
14105	Type 1064 ...	Bakelite former, $2\frac{3}{16}$ in. o/d, 2 windings:—(1) $14\frac{3}{4}$ turns 36 S.W.G. en. cu. wire, wound 114 T.P.I. (2) $3\frac{1}{4}$ turns 26 S.W.G. E.C. wire, close wound.		C	each	1
14106	Type 1065 ...	Bakelite former, $2\frac{3}{16}$ in. \times 1 in. o/d, 2 windings:—(1) $19\frac{1}{4}$ turns 36 S.W.G. en. cu. wire. (2) $14\frac{3}{4}$ turns of 36 S.W.G. en. cu. wire.		C	..	1
14107	Type 1066 ...	Bakelite former, $2\frac{3}{16}$ in. \times 1 in. o/d, 4 windings:—(1) $11\frac{3}{4}$ turns 36 S.W.G. en. cu. wire. (2) $18\frac{7}{8}$ turns 36 S.W.G. en. cu. wire. (3) $18\frac{7}{8}$ turns 36 S.W.G. en. cu. wire. (4) $9\frac{3}{4}$ turns 36 S.W.G. en. cu. wire.		C	..	1
14206	Type 1079 ...	26 turns of 18 S.W.G. en. cu. wire on former 3 in. \times 1 in. dia. 1st doubler coil.		C	..	1
14207	Type 1080 ...	9 turns of 18 S.W.G. en. cu. wire on former $1\frac{3}{8}$ in. \times 1 in. dia. 2nd doubler coil.		C	..	1
14241	Type 1088 ...	Centre aerial amplifier grid coil		C	..	1
14243	Type 1090 ...	Outer aerial amplifier coil ...		C	..	1
14244	Type 1091 ...	Outer aerial amplifier coil ...		C	..	1
14245	Type 1092 ...	Outer aerial amplifier coil ...		C	..	1
14246	Type 1093 ...	Outer aerial amplifier coil ...		C	..	1
14274	Type 1099 ...	Pile wound, 800 turns 40 S.W.G. en. cu. wire, complete with bobbin and cheek.		C	..	1
14275	Type 1100 ...	1,250 turns 38 E.S.S., wound on $\frac{1}{4}$ in. dia. former.		C	..	1
14276	Type 1101 ...	17 turns 36 S.W.G. en. cu. on former, $\frac{1}{2}$ in. dia. \times $1\frac{1}{4}$ in. long.		C	..	1
14312	Type 1117 ...	10 turns 26 S.W.G. en. cu. on former (10A/14279).		C	..	1
14313	Type 1118 ...	Primary 8 turns, secondary 2 turns of 26 S.W.G. en. wire on former (10A/14279).		C	..	1
14315	Type 1120 ...	$9\frac{3}{4}$ turns 20 gauge tinned copper wire, wound on Buller former.		C	..	1
14316	Type 1121 ...	$4\frac{1}{2}$ turns 20 gauge tinned copper wire, wound on Buller former.		C	..	1
14339	Type 1123 ...	Assembly of winding and former		C	..	1
14347	Type 1126 ...	M.C.W. coil assembly. Primary, 6,000 turns 36 S.W.G. D.S.C. Secondary, 3,000 turns 42 S.W.G. enam. and S.S.C. 3 in. dia. \times 3 in. over stud.		C	..	1
14358	Type 1132 ...	7 turns 20 S.W.G. Tapped at 2 points, 4 T. and $5\frac{1}{2}$ T. No coil former, unglazed.		C	..	1
14360	Type 1134 ...	8 turns 30 S.W.G. en. cu. Tuning inductance, with dust core, coded green.		C	..	1
14410	Type 1136 ...	$7\frac{1}{2}$ turns 30 S.W.G. en. cu. Tuning inductance, with dust core, coded red.		C	..	1
14411	Type 1137 ...	7 and 11 turns 30 S.W.G. en. cu., 2 parts. Tuning inductance, with dust core, coded black.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
14414	Type 1140 ...	165 turns 38 S.W.G. en. and S.S.C. copper. 4 sections of 650 μ H and 1 section of 325 μ H \pm 10 per cent. Small coil mounted at opposite end to white mark.		C	each	1
14478	Type 1146		C	"	1
14479	Type 1147		C	"	1
14514	Type 1149 ...	32 \pm 5 μ H min. to 440 \pm 25 μ H max. 7 tappings. 20 in. \times 16 in. overall. Couplings coil arrangement put on to end plate tuning coil modified.		C	"	1
14578	Type 1170 ...	3 $\frac{1}{4}$ turns \times .048 in. tinned cu. wire, with distrene insulating sleeve, and brass plunger on bakelite mounting.		C	"	1
14613	Type 1175 ...	1 turn of 10 S.W.G. wire ...		C	"	1
14617	Type 1176 ...	17.8 μ H \pm 1.25 per cent., .25 ohms, 34 turns 26 S.W.G. H.C. en. cu. wire on tubular former, .87 in. dia. \times 2 in.		C	"	1
14636	Type 1178 ...	67 turns 28 S.W.G. Single winding section wound 28 S.W.G. on moulded former.		C	"	1
14637	Type 1179 ...	10 turns 28 S.W.G. Dust cored inductance, single winding.		C	"	1
14638	Type 1180 ...	2 turns 28 S.W.G. Dust cored inductance. 1 winding of 2 turns 28 S.W.G.		C	"	1
14639	Type 1181 ...	10 turns 28 S.W.G. Dust cored		C	"	1
14640	Type 1182 ...	15 turns 28 S.W.G. 2 windings en. cu. on moulded former.		C	"	1
14641	Type 1183 ...	48 turns 28 S.W.G. Single winding en. cu. wire, on moulded former.		C	"	1
14642	Type 1184 ...	4 $\frac{1}{2}$ turns 28 S.W.G. Iron dust cored, en. cu. wire, on moulded former.		C	"	1
14643	Type 1185 ...	7 $\frac{1}{2}$ turns and 1 of 28 S.W.G. Iron dust cored.		C	"	1
14644	Type 1186 ...	11 $\frac{1}{2}$ turns and 1 of 28 S.W.G. tinned cu. wire, $\frac{5}{16}$ in. i/d.		C	"	1
14645	Type 1187 ...	6 $\frac{1}{2}$ turns 28 S.W.G. Iron dust cored, 1 winding.		C	"	1
14687	Type 1191 ...	Trimmer adjustable iron core in former, with wound coil, 2 $\frac{1}{2}$ turns.		C	"	1
14691	Type 119351 mH, 259 turns 36 S.W.G. double silk covered cu wire.		C	"	1
14731	Type 1201 ...	2 honeycomb coils on $\frac{3}{8}$ in. dia. former, with adjustable iron core.		C	"	1
14747	Type 1202 ...	Coil ...		C	"	1
14764	Type 1204 ...	1,000 turns 40 S.W.G. E. and S.S. wire.		C	"	1
14786	Type 1205 ...	31 turns 36 S.W.G. and 1 turn on flanged former.		C	"	1
14787	Type 1206 ...	31 turns 36 S.W.G. on flanged former.		C	"	1
14788	Type 1207 ...	27 $\frac{1}{2}$ turns 36 S.W.G., tapped at 13 $\frac{1}{4}$ turns and 12 turns.		C	"	1
14790	Type 1208 ...	Iron dust core, 7 $\frac{1}{4}$ turns 24 S.W.G., tapped 5 $\frac{1}{4}$ turns from start. Second winding 5 $\frac{1}{2}$ turns.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS —cont.					
14791	Type 1209 ...	Iron dust core, $12\frac{3}{4}$ turns, tapped on $10\frac{3}{4}$ turns from start. Second winding $7\frac{1}{2}$ turns.		C	each	1
14792	Type 1210 ...	Iron dust core, $21\frac{1}{2}$ turns, tapped $19\frac{1}{2}$ turns from start. Second winding $10\frac{1}{2}$ turns.		C	..	1
14793	Type 1211 ...	Iron dust core, $39\frac{1}{2}$ turns, tapped $36\frac{1}{2}$ turns from start. Second winding $12\frac{1}{2}$ turns.		C	..	1
14794	Type 1212 ...	46 turns 38 S.W.G. and 16 turns 40 S.W.G. Iron dust core.		C	..	1
14795	Type 1213 ...	$7\frac{1}{2}$ turns 24 S.W.G. Iron dust core.		C	..	1
14796	Type 1214 ...	14 turns 24 S.W.G. Iron dust core.		C	..	1
14797	Type 1215 ...	24 turns 34 S.W.G. Iron dust core.		C	..	1
14798	Type 1216 ...	6 turns 38 S.W.G. Iron dust core.		C	..	1
14806	Type 1217 ...	$7\frac{1}{2}$ turns 24 S.W.G. Iron dust core.		C	..	1
14807	Type 1218 ...	14 turns 24 S.W.G. and 12 turns 40 S.W.G. Iron dust core.		C	..	1
14808	Type 1219 ...	24 turns 34 S.W.G. and 11 turns 40 S.W.G. Iron dust core.		C	..	1
14810	Type 1220 ...	7 turns 24 S.W.G. and $1\frac{3}{4}$ turns 40 S.W.G., tapped $\frac{1}{2}$ turn from start. Iron dust core.		C	..	1
14811	Type 1221 ...	14 turns 24 S.W.G. and $2\frac{2}{3}$ turns 40 S.W.G., tapped $1\frac{1}{2}$ turns from start. Iron dust core.		C	..	1
14812	Type 1222 ...	23 turns 34 S.W.G. and $3\frac{1}{2}$ turns 40 S.W.G., tapped $1\frac{1}{2}$ turns from start. Iron dust core.		C	..	1
14813	Type 1223 ...	44 turns 38 S.W.G. and $4\frac{3}{4}$ turns 40 S.W.G., tapped $2\frac{1}{2}$ turns from start. Iron dust core.		C	..	1
14833	Type 1231		C	..	1
14836	Type 1232 ...	$84\frac{3}{4}$ turns 36 S.W.G. and 2 turns 36 S.W.G.		C	..	1
14837	Type 1233 ...	85 turns 36 S.W.G., close wound		C	..	1
14838	Type 1234 ...	$43\frac{3}{4}$ turns 36 S.W.G., tapped at $21\frac{1}{2}$ turns from start and 21 turns.		C	..	1
14839	Type 1235 ...	Former $\frac{27}{32}$ in. long, 4 coils wave-wound, 153 turns 38 S.W.G. en. S.S.C. copper wire, $192 \mu\text{H} \pm 5$ per cent. 2 coils, wave-wound, 110 turns 38 S.W.G. en. S.S.C. copper wire, $96 \mu\text{H} \pm 5$ per cent.		C	..	1
14855	Type 1240 ...	1 mH. 230 turns 9/46 Litz wire		C	..	1
14856	Type 1241 ...	$25 \mu\text{H}$. 1,300 turns 9/46 Litz wire.		C	..	1
14883	Type 1246 ...	$480 \mu\text{H} \pm 5$ per cent. 3 coils, wave-wound, 234 turns each of 38 S.W.G. 2 end coils, wave-wound, 172 turns 38 S.W.G., $240 \mu\text{H}$, 5 per cent.		C	..	1
14887	Type 1247 ...	Anode coil, 10 coils plus 3 turns interwound 28 S.W.G. enam. wire, iron dust core.		C	..	1
14888	Type 1248 ...	Grid coil, 8 turns plus 1 turn interwound 28 S.W.G. en. wire, iron dust core.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS—cont.					
14902	Type 1249 ...	2 turns approx., .5 in. dia., 14 S.W.G. silver-plated copper wire.		C	each	1
14977	Type 1250 ...	120 μ H + 10 μ H, 57 turns of 32 S.W.G.		C	..	1
14989	Type 1254 ...	8 $\frac{3}{4}$ turns 28 S.W.G. Wound clockwise on former fitted with core.		C	..	1
14990	Type 1255 ...	No. of turns:—Coupling 1, grid coil 9, 28 S.W.G. 28 S.W.G. moulded former, fitted with core.		C	..	1
14991	Type 1256 ...	No. of turns:—Coupling 1, anode coil 11 $\frac{3}{4}$, 28 S.W.G. 28 S.W.G. moulded former, fitted with coil.		C	..	1
15009	Type 1262 ...	Inductors T.358, number of turns modified to 3 $\frac{1}{2}$.		C	..	1
15010	Type 1263		C	..	1
15011	Type 1264		C	..	1
15033	Type 1277 ...	2 $\frac{1}{4}$ turns 26 S.W.G. Dust iron core. Bakelite former (WD. 15684).		C	..	1
15034	Type 1278 ...	1 $\frac{1}{2}$ turns 26 S.W.G. Dust iron core. Bakelite former (WD. 15684).		C	..	1
15035	Type 1279 ...	3 turns 26 S.W.G. Dust iron core. Bakelite former (WD. 15684).		C	..	1
15036	Type 1280 ...	Bakelite former fitted with 4 turns 26 S.W.G. wire. Dust iron core.		C	..	1
15044	Type 1281 ...	12.5 μ H, 2.5 ohms, 28 turns full wave-wound .0148 in. dia. D.C. enam. wire on vulcanite former. .5 in. dia. \times 1.37 in. Complete with bushes and 4 B.A. \times .43 in. ch/hd. screw.		C	..	1
15076	Type 1296 ...	8 turns 28 S.W.G., $\frac{1}{32}$ in. spacing on K.90667 former.		C	..	1
15087	Type 1297 ...	8 μ H \pm 10 per cent. 43 turns 22 S.W.G. D.S.C. on former.		C	..	1
15088	Type 1298 ...	1 μ H \pm 10 per cent. 9 turns 22 S.W.G. D.S.C. on former.		C	..	1
15089	Type 1299 ...	500 μ H \pm 10 per cent. 237 turns 36 S.W.G. en. cu. Circular base, with 3 fixing holes.		C	..	1
15090	Type 1300 ...	8 μ H \pm 10 per cent. 26 turns 22 S.W.G. S.S.C. en. cu. Two short connectors, $\frac{3}{8}$ in. long, on one side.		C	..	1
15091	Type 1301 ...	4 μ H \pm 10 per cent. 25 turns 22 S.W.G. S.S.C. en. cu.		C	..	1
15092	Type 1302 ...	8 μ H \pm 10 per cent. 26 turns 22 S.W.G. S.S.C. en. cu. wire. Two hook connectors, 2 in. long, on one side.		C	..	1
15139	Type 1310 ...	5.8 mH. Can dims. 2 $\frac{3}{8}$ in. \times 1 $\frac{3}{16}$ in. \times 1 $\frac{9}{16}$ in. Two studs fixing No. 4 B.A.		C	..	1
15213	Type 1314 ...	500 turns of 40 S.W.G. wire, wound on $\frac{1}{4}$ in. dia. former coil, $\frac{3}{4}$ in. dia. \times $\frac{1}{4}$ in. wide. Peaking coil.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS —cont.					
15219	Type 1315 ...	No. of turns:—Primary, 25 turns of 40 S.W.G. en. cu. wire. Secondary, 350 turns of the same wire.		C	each	1
15252	Type 1316 ...	18 + 12 turns 36 S.W.G. en. cu. wire on bakelite former, 1¼ in. long × ½ in. dia., with tags.		C	„	1
15253	Type 1317 ...	18 turns 36 S.W.G. en. cu. wire on bakelite former, 1¼ in. × ½ in. dia., with tags.		C	„	1
15906	Type 1323 ...	8 turns 28 en. cu. wire, wound on moulded former.		C	„	1
16041	Type 1339 ...	3 open turns of 14 S.W.G. plated cu. wire, 1 in. dia., overall length 1¾ in.		C	„	1
16061	Type 1340 ...	2 coils:—(1) 50 turns 30 S.W.G. en. cu. wire, (2) 20 turns 36 S.W.G. en. cu. wire, wound on former, 1 in. × 2½ in. long.		C	„	1
16080	Type 1347		C	„	1
16111	Type 1353 ...	1.2 μH ± 5 per cent. 4 sections of 180 38 S.W.G. S.S.C. en. cu. wire. Size 1⅝ in. × ¼ in. D.C. ohms. Wave-wound on hollow S.R.B.P. former, with connecting tags.		C	„	1
16112	Type 1354 ...	12 μH ± 5 per cent. 830 turns 40 S.W.G. S.S.C. en. cu., 1½ in. long. Overall dia. 1 in. D.C. resistance 83 ohms. Wave-wound on hollow S.R.B.P. former.		C	„	1
16113	Type 1355 ...	300 turns 40 S.W.G. S.S.C. en. cu. 1:1 mH ± 5 per cent. Main portion, 5 μH ± 5 per cent. Tapped portion, D.C. resistance 23 ohms. Tapped at 50 turns.		C	„	1
16253	Type 1357 ...	110 turns 34 S.W.G. D.C. cu. wire. Single wave-wound on hollow S.R.B.P. former. Spindle ½ in. long, ¼ in. overall dia., ⅜ in. wall.		C	„	1
16278	Type 1359 ...	3¼ turns L.H. wound 26 S.W.G. en. cu. wire.		C	„	1
16279	Type 1360 ...	2¾ turns L.H. wound 26 S.W.G. en. cu. wire.		C	„	1
16280	Type 1361 ...	4¾ turns L.H. wound 26 S.W.G. en. cu. wire.		C	„	1
16281	Type 1362 ...	9 turns 26 S.W.G. en. cu. wire. Iron dust cored.		C	„	1
16282	Type 1363 ...	1½ turns and 7 turns 26 S.W.G. en. cu. wire. Iron dust cored, 10 turns S.W.G. en. cu. wire.		C	„	1
16283	Type 1364 ...	10 turns 26 S.W.G. en. cu. wire		C	„	1
16284	Type 1365 ...	8 turns and 2 turns S.W.G. en. cu. wire. Iron dust cored.		C	„	1
16285	Type 1366 ...	12 turns and 3 turns 26 S.W.G. en. cu. wire. Iron dust cored.		C	„	1
16286	Type 1367 ...	2 turns 18 S.W.G. T.C. wire (no former), ⅜ in. o/d, ⅞ in. tag.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS —cont.					
16785	Type 1373 ...	6 turns 28 S.W.G. en. and S.A.S. covered cu. wire, wound on moulded former fitted with core.		C	each	1
16824	Type 1380 ...	Iron dust cored. 2 coils each of 75 turns of 30/48 Litz, spaced $\frac{1}{8}$ in.		C	..	1
16825	Type 1381 ...	Iron dust cored. 2 coils each of 75 turns, and 1 coil of 2 turns, all of 30/48 Litz, spaced $\frac{1}{8}$ in.		C	..	1
16828	Type 1382 ...	Iron dust cored. 2 wave-wound coils each of 75 turns of 30/48 Litz.		C	..	1
16829	Type 1383 ...	Iron dust cored. 2 wave-wound coils each of 75 turns of 30/48 Litz.		C	..	1
16830	Type 1384 ...	Iron dust cored. 2 coils each of 75 turns of 30/48 Litz, spaced $\frac{1}{8}$ in., on moulded former.		C	..	1
16831	Type 1385 ...	Iron dust cored. 2 coils each of 75 turns, and 1 coil of 30/48 Litz, on moulded former.		C	..	1
16832	Type 1386 ...	Iron dust cored. 2 coils each of 75 turns, and 1 coil of 1 turn of 30/48 Litz, on moulded former.		C	..	1
16833	Type 1387 ...	Iron dust cored. Single coil, 215 turns of 40 S.W.G. double rayon covered wire on moulded former.		C	..	1
16834	Type 1388 ...	Iron dust cored. Single coil, 44 turns of 34 S.W.G. "Kewmax" close wound.		C	..	1
16870	Type 1401 ...	150 V.H., T. \pm 20 per cent. 100 turns 34 S.W.G. D.S.C. wire on former.		C	..	1
16871	Type 1402 ...	On former (Ericsson's, Type P.49391), 25 ULL. 5 per cent. 60. 36 S.W.G.		C	..	1
17509	Type 1407 ...	16 turns 36 gauge en. cu. wire; bakelite former $\frac{1}{2}$ in. dia. \times 1.165 in. long; base $\frac{3}{4}$ in. \times 1 in.; tapped No. 6 B.A.		C	..	1
17510	Type 1408 ...	Aerial assembly. 6 $\frac{1}{2}$ turns on bakelite base, brass core, and distrene sleeve.		C	..	1
17556	Type 1409 ...	350 turns of 40 S.W.G. S.S.C. en. cu. wire, $\frac{1}{2}$ wave-wound; 25 turns of 40 S.W.G. en. cu. $\frac{1}{2}$ wave-wound.		C	..	1
17562	Type 1410 ...	Coil I.F. 1st (Ind. 1124) mod. by adding 1.5 $\mu\mu$ F. capacitor.		C	..	1
17628	Type 1415 ...	1st and 2nd I.F. transformers		C	..	1
17629	Type 1416 ...	3rd I.F. transformers ...		C	..	1
17630	Type 1417 ...	S.W. oscillator coil ...		C	..	1
17631	Type 1418 ...	M.W. oscillator coil ...		C	..	1
17632	Type 1419 ...	L.W. oscillator coil ...		C	..	1
17633	Type 1420 ...	Aerial coil S.W. ...		C	..	1
17634	Type 1421 ...	Aerial coil M.W. ...		C	..	1
17635	Type 1422 ...	Aerial coil L.W. ...		C	..	1
17636	Type 1423 ...	S.W. R.F. coil ...		C	..	1
17637	Type 1424 ...	M.W. R.F. coil ...		C	..	1
17638	Type 1425 ...	L.W. R.F. coil ...		C	..	1
17639	Type 1426 ...	I.F. filter choke ...		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS —cont.					
17665	Type 1428 ...	733.5 mH \pm 2 per cent. 2,000 turns.		C	each	1
17666	Type 1429 ...	8374 henries \pm 2 per cent. 2,400 turns.		C	..	1
17682	Type 1431 ...	20 mH, 5 per cent. 970 turns approx. 40 S.W.G. wire, bobbin and S.R.B.P. mounting block, 1½ in. sq. \times 1¼ in. overall.		C	..	1
17740	Type 1451 ...	45 turns 34 S.W.G. en. cu. wire, 26 μ H \pm 2 per cent.		C	..	1
17741	Type 1452 ...	39 turns 34 S.W.G. en. cu. wire		C	..	1
17828	Type 1480 ...	Oscillator trans., modification of Inductor T.1355 (10C/16113), tropicalised.		C	..	1
17829	Type 1481 ...	Compensating coil, modification of Inductor T.1354 (10C/16112), tropicalised.		C	..	1
17830	Type 1482 ...	Compensating coil, modification of Inductor T.1353 (10C/16111), tropicalised.		C	..	1
17831	Type 1483 ...	Compensating coil, 2.15 mH \pm 5 per cent. Tropical version of Choke, H.F. type (10C/16220).		C	..	1
17832	Type 1484 ...	Compensating coil, 8.5 mH \pm 5 per cent. Tropical version of Type 739 (10C/16070).		C	..	1
17837	Type 1485 ...	300 turns 40 S.W.G. en. cu. wire, half wave-wound, on moulded former, 1⅞ in. high \times .437 in. dia. Mounted on base with ¾ in. fixing centres.		C	..	1
17838	Type 1486 ...	1,417 turns, tapped at 1,202 and 1,030 turns, 40 S.W.G. D.S.C. en. cu. wire, wave-wound on moulded former, 1⅞ in. high \times .437 in. dia. Mounted on base with ¾ in. fixing centres.		C	..	1
17839	Type 1487 ...	690 turns, tapped at 350 and 390 turns, of 40 S.W.G. D.S.C. in copper wire, wave-wound on moulded former, 1⅞ in. high \times .437 in. dia. Mounted on base with ¾ in. fixing centres.		C	..	1
17840	Type 1488 ...	4 sections, each of 450 turns 40 S.W.G. in D.S.C. cu. wire, on moulded former, 2⅞ in. long \times .48 in. dia. Base 1¼ in. dia., fixing centres ⅞ in.		C	..	1
17842	Type 1489 ...	30 turns 32 S.W.G. D.S.C. copper wire, close wound on bakelite former. Size 1¼ in. long overall.		C	..	1
17843	Type 1490 ...	160 turns 9/46 Litz wire, wave-wound on bakelite former. Size 1¼ in. long overall.		C	..	1
17844	Type 1491 ...	75 turns 38 S.W.G. D.S.C. copper, wave-wound on ½ in. moulded bakelite former.		C	..	1
17853	Type 1492 ...	2.4 mH (without core). 400 + 400 turns of 30 S.W.G. wire on moulded former.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTORS —cont.					
17854	Type 1493 ...	71·7 mH. 1,880 + 1,880 turns 40 S.W.G. wire on moulded former.		C	each	1
17855	Type 1494 ...	30·28 mH, without core, 1,350 + 1,350 turns 40 S.W.G. wire on moulded former.		C	„	1
17856	Type 1495 ...	15·5 mH, without core, 935 + 935 turns 40 S.W.G. wire on moulded former.		C	„	1
17857	Type 1496 ...	5·13 mH, without core, 575 + 575 turns 40 S.W.G. wire on moulded former.		C	„	1
17858	Type 1397 ...	1·25 mH, 416 + 416 turns 46 S.W.G. wire on moulded former.		C	„	1
17859	Type 1498 ...	330 mH, 225 + 225 turns 46 S.W.G. wire on moulded former.		C	„	1
17869	Type 1504 ...	8 windings each 86 turns of 38 S.W.G. S.S.C en. cu. wire. Inductance of each coil 52 μ H \pm 5 per cent. Moulded in polythene. Approx. dims. 4 in. long \times $\frac{1}{2}$ in. dia.		C	„	1
18014	Type 1507 ...	14 + 6 turns 30 S.W.G. en. cu. wire, wound on Cossor former. Iron cored.		C	„	1
18015	Type 1508 ...	25 + 5 turns 34 S.W.G. en. cu. wire, wound on Cossor former. Iron cored.		C	„	1
18016	Type 1509 ...	9 turns 24 S.W.G. en. cu. wire, wound on Cossor former. Iron cored.		C	„	1
17890	Type 1510 ...	20 mH, 1,205 turns 40 S.W.G. tapped at 241 turns. Iron dust cored.		C	„	1
17891	Type 1511 ...	200/ $\frac{3}{8}$ H, 40 S.W.G. D.S.C., tapped at $\frac{1}{2}$ number of turns (31 $\frac{1}{2}$), $\frac{1}{2}$ wave-wound. Iron dust cored (Core is 10DB/6052).		C	„	1
18025	Type 1512 ...	·797 henries. Iron core, 2 windings, 4 terminals. Test at 400 pps. S. of C. 2·968 in. \times 2·562 in. \times 1·141 in.		C	„	1
18026	Type 1513 ...	1·274 henries. Iron core, 2 windings, 4 terminals. Test at 400 pps. S. of C. 2·968 in. \times 2·562 in. \times 1·141 in.		C	„	1
18027	Type 1514 ...	·709 henries. Iron core, 2 windings, 4 terminals. Test at 400 pps. S. of C. 2·968 in. \times 2·562 in. \times 1·141 in.		C	„	1
18028	Type 1515 ...	·797 henries. Iron core, 2 windings, 4 terminals. Test at 500 pps. S. of C. 2·968 in. \times 2·562 in. \times 1·141 in.		C	„	1
18029	Type 1516 ...	1·274 henries. Iron core, 2 windings, 4 terminals. Test at 500 pps. S. of C. 2·968 in. \times 2·562 in. \times 1·141 in.		C	„	1
18030	Type 1517 ...	·716 henries. Iron core, 2 windings, 4 terminals. Test at 500 pps. S. of C. 2·968 in. \times 2·562 in. \times 1·141 in.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
18031	INDUCTORS —cont. Type 1518797 henries. Iron core, 2 windings, 4 terminals. Test at 700 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	each	1
18032	Type 1519 ...	1.274 henries. Iron core, 2 windings, 4 terminals. Test at 700 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18033	Type 1520725 henries. Iron core, 2 windings, 4 terminals. Test at 700 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18034	Type 1521797 henries. Iron core, 2 windings, 4 terminals. Test at 800 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18035	Type 1522 ...	1.274 henries. Iron core, 2 windings, 4 terminals. Test at 800 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18036	Type 1523729 henries. Iron core, 2 windings, 4 terminals. Test at 800 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18037	Type 1524797 henries. Iron core, 2 windings, 4 terminals. Test at 900 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18038	Type 1525 ...	1.274 henries. Iron core, 2 windings, 4 terminals. Test at 900 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18039	Type 1526739 henries. Iron core, 2 windings, 4 terminals. Test at 900 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18040	Type 1527797 henries. Iron core, 2 windings, 4 terminals. Test at 1,000 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18041	Type 1528 ...	1.274 henries. Iron core, 2 windings, 4 terminals. Test at 1,000 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18042	Type 1529743 henries. Iron core, 2 windings, 4 terminals. Test at 1,000 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18043	Type 1530747 henries. Iron core, 2 windings, 4 terminals. Test at 1,140 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18044	Type 1531 ...	1.274 henries. R.M.C. Iron core, 2 windings, 4 terminals. Test at 1,140 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18045	Type 1532743 henries. R.M.C. Iron core, 2 windings, 4 terminals. Test at 1,140 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18046	Type 1533797 henries. R.M.C. Iron ring R.M.C., 2 windings, 4 terminals. Test at 1,300 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty
1	2	3	4	5	6	7
	INDUCTORS—cont.					
18047	Type 1534 ...	1.275 henries. R.M.C. Iron ring, 2 windings, 4 terminals. Test at 1,300 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	each	1
18048	Type 1535751 henries. R.M.C. Iron ring, 2 windings, 4 terminals. Test at 1,300 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18049	Type 1536979 henries. Iron core, 2 windings, 4 terminals. Test at 1,400 pps. R.M.C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18050	Type 1537 ...	1.274 henries. Details as Type 1536.		C	..	1
18051	Type 1538753 henries. Details as Type 1536.		C	..	1
18052	Type 1539797 henries. Iron core, 2 windings, 4 terminals. Test at 1,500 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18053	Type 1540 ...	1.274 henries. Details as Type 1539.		C	..	1
18054	Type 1541755 henries. Details as Type 1539.		C	..	1
18055	Type 1542797 henries. Enclosed iron ring, 2 windings, 4 terminals. Test at 1,400 pps. R.M.C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18056	Type 1543 ...	1.274 henries. Details as Type 1542.		C	..	1
18057	Type 1544753 henries. Details as Type 1542.		C	..	1
18058	Type 1545797 henries. Iron core, 2 windings, 4 terminals. Test at 1,700 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18059	Type 1546 ...	1.274 henries. Details as Type 1545.		C	..	1
18060	Type 1547760 henries. Details as Type 1545.		C	..	1
18061	Type 1548 ...	1.595 henries. Iron core, 2 windings, 4 terminals. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18062	Type 1549 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 500 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18063	Type 1550 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 700 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18064	Type 1551 ...	1.594 henries. Iron core, 2 windings, 4 terminals. Test at 800 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18065	Type 1552 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 900 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1
18066	Type 1553 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 1,000 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
18067	INDUCTORS —cont. Type 1554 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 1,140 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	each	1
18068	Type 1555 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 1,300 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18069	Type 1556 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 1,400 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18070	Type 1557 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 1,500 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18071	Type 1558 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 1,600 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
18072	Type 1559 ...	1.595 henries. Iron core, 2 windings, 4 terminals. Test at 1,700 pps. S. of C. 2.968 in. × 2.562 in. × 1.141 in.		C	„	1
17966	Type 1560 ...	2 turns 16 S.W.G. tinner copper (H.C.), i/d $\frac{3}{4}$ in. Fixed by flattened ends drilled and bent to "L" shape.		C	„	1
17989	Type 1574 ...	R.F. pots type; internally mounted dust cover. Adj. $1\frac{3}{8}$ in. dia., $1\frac{3}{8}$ in. deep, with 6 pins, .64 in. dia., between terms 1-6; 260 μ H 10 per cent. between terms 1-5; 115 μ H 10 per cent. 2-3. 1 turn nominal.		C	„	1
18105	Type 1575 ...	500 turns (in four sections) of 36 S. W. G. en. cu. wire. Resonates at 161 kc/s. Sealed in metal can. $1\frac{5}{8}$ in. dia. × $2\frac{3}{4}$ in. high.		C	„	1
	INDUCTOR ASSEMBLIES:—					
17038	I.F. No. 1 ...	Used on R/RDF No. 7 ...		C	„	1
17039	I.F. No. 2 ...	Used on R/RDF No. 7 ...		C	„	1
17044	No. 6		C	„	1
	INDUCTOR CAPACITOR UNITS:—					
3478	Type 3 ...	2 wire-wound inductors, .213 microhenries each (4 turns), mounted in international octal valve base, cover engraved 42-50 Mc/s, 90°.		C	„	1
3479	Type 4 ...	3 and 4 turns 32 S.W.G. D.S.C. copper on bobbin, mounted in international octal valve base, cover engraved 42-55 Mc/s, 90°.		C	„	1
4223	Type 6 ...	Delay network comprising coils and capacitors in sealed wooden box filled.		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTOR CAPACITOR UNITS—cont.					
4640	Type 9	Delay network comprising 11 "Leesona" wound coils, 10 capacitors, and 2 resistors, in sheet brass box, 5½ in. × 2¼ in. × 1¼ in.		C	each	1
11335	Type 21	Delay network; 80 ohms, 1 micro second.		C	"	1
11443	Type 22	Assembly of suppressor ...		C	"	1
11444	Type 23	Delay network, comprising 6 inductors, 5 of 42 mH and 1 of 84 mH; and 5 capacitors 670 pfd.		C	"	1
11451	Type 24	Includes Inductor, Type 123, and variable capacitor.		C	"	1
11521	Type 25	Marker unit in sheet brass screening case, 4 in. × 1 in. × 1½ in. approx.		C	"	1
11502	Type 26		C	"	1
11965	Type 29	2 units on common mounting:— (1) Single transit delay of 1 microsecond, and characteristic impedance of 2,000 ohms. (2) Single transit delay of .5 microsecond and characteristic impedance of 4,000 ohms.		C	"	1
11966	Type 30	Single transit delay of 2 micro-seconds and characteristic impedance of 270 ohms.		C	"	1
11967	Type 31	Single transit delay of 8 micro-seconds and characteristic impedance of 1,000 ohms.		C	"	1
13205	Type 43	Delay network comprising 6 inductors (5 × 42 μH) and 5 × 670 μμF. fixed capacitors (in block) oil filled.		C	"	1
13412	Type 50	½ μ-sec., 80 ohms impedance ...		C	"	1
13439	Type 52		C	"	1
13772	Type 59	38 μH + 5 per cent. approx. 1,200 turns 42 S.W.G. D.S.C. on ¾ in. paxolin former, with paxolin tagboard mounting 2 capacitors.		C	"	1
13773	Type 60	116 turns 3/48 Litz wire wound on ½ in. dia. former, with tag-board mounting 1 capacitor.		C	"	1
14019	Type 65	Delay network comprising one 4.7 K resistor, four 25 μμF capacitors, and 5 inductors.		C	"	1
14060	Type 67	Delay network, comprising inductors, resistors, and capacitors (wax coated) to form 1 unit not separately replaceable and complete with switch (C.17895) and tag panel. All mounted on M.S. bracket, 4¾ in. × 2¼ in., complete.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTOR CAPACITOR UNITS—cont.					
14113	Type 68	6 sections, inductance of each 307 μ H, 6 capacitors 50 pF + 5 per cent. Silvered mica waxed in as one unit.		C	each	1
14175	Type 72	1 μ -sec., 75 ohms		C	"	1
14542	Type 85	Delay network 7,000 μ H. 24 sections and 2 half sections. Inductance 280 μ H per sec., 140 μ H per half-sec. Mounted on tagboard with feet.		C	"	1
14620	Type 86	Delay $\frac{1}{2}$ micro-sec. Impedance 60 ohms, 7 $\frac{1}{2}$ KV. working.		C	"	1
14730	Type 88	2 honeycomb coils and 1 capacitor in cylindrical metal can, with 2 screened leads.		C	"	1
14919	Type 92	Comprises capacitor, Type 5032, 4 coils of 300 mH each, 2-47 K \pm 20 per cent., 1 watt, carbon resistors, and .1 mf. \pm 10 per cent., 1,500 volts, paper tubular capacitor, 20 coils of 200 mH each.		C	"	1
14963	Type 93	Delay line and switch assembly, with 20 capacitors and 3 resistors and switch.		C	"	1
16028	Type 115	Assembly of coil and capacitors in can.		C	"	1
16207	Type 119	Delay $\frac{1}{2}$ μ -sec. μ H. 80 ohms, 7 KVs.		C	"	1
16872	Type 126	Delay network wax filled sealed can, 5 $\frac{3}{4}$ in. \times 3 in. \times 1 in. approx. containing 2 off resistors, 8 off capacitors, and coil assembly.		C	"	1
16873	Type 127	Delay network wax filled sealed can, 5 $\frac{3}{4}$ in. \times 3 in. \times 1 in. overall approx., containing 1 off resistor, 7 off capacitors, and coil assembly.		C	"	1
16962	Type 128	Delay network, 4 off capacitors (10C/16244), with 2 sets of coils and end pieces. Sealed in metal box.		C	"	1
17671	Type 129	Oscillator coil assembly		C	"	1
	INDUCTOR UNITS:—					
12594	Mounting assemblies		C	"	1
12585	Type 17	Coil assembly of 2 coils of 8 turns of 14 S.W.G. silver-plated wire.		C	"	1
12586	Type 18	Coil assembly of 2 coils of 12 turns of 14 S.W.G. silver-plated wire.		C	"	1
12664	Type 19	Coil assembly of 2 coils of 10 turns of 14 S.W.G. silver-plated wire.		C	"	1
12743	Type 20	Coil assembly of 2 coils of 7 turns of 14 S.W.G. silver-plated wire.		C	"	1
13437	Type 21	Coil assembly of 2 coils of 14 S.W.G., each of 5 turns, 2 in. internal dia. Coil turns spaced .3 in. Coils spaced .6 in.		C	"	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	INDUCTOR UNITS					
	—cont.					
13438	Type 22 ...	2 coils of 15 S.W.G., 5 turns each, 2 in. dia. Coil turn spaced .5 in. Coils spaced .75 in.		C	each	1
13444	Type 23 ...	2 coils, 4 turns each of 14 S.W.G. Dia. coils 2 in. i/d Coil turns spaced .4 in. Coils spaced .6 in.		C	„	1
14024	Type 35 ...	4 windings (wave-wound) of 250 μ H each.		C	„	1
14025	Type 36 ...	3 windings of 13, 6, and 13 turns on former S.D.1770.		C	„	1
14177	Type 37 ...	Trace separator coils, bobbin wound, mounted on ebonite or paxolin plate, fitted to adjustable bracket.		C	„	1
14264	Type 39 ...	Inductor and capacitor sub-assembly.		C	„	1
14332	Type 43 ...	2nd oscillator assembly ...		C	„	1
14333	Type 44 ...	3rd oscillator assembly ...		C	„	1
14334	Type 45 ...	2nd I.F. assembly ...		C	„	1
14335	Type 46 ...	3rd I.F. assembly ...		C	„	1
14336	Type 47 ...	4th I.F. assembly ...		C	„	1
14337	Type 48 ...	5th I.F. assembly ...		C	„	1
14338	Type 49 ...	6th I.F. assembly ...		C	„	1
14341	Type 50 ...	H.F. Part of R.1547 ...		C	„	1
14342	Type 51 ...	Aerial. Part of R.1547 ...		C	„	1
14343	Type 52 ...	Mixer. Part of R.1547 ...		C	„	1
14349	Type 53 ...	Coil assembly. Buffer, 3 in. dia. $\times \frac{5}{8}$ in. long overall.		C	„	1
14350	Type 54 ...	Coil assembly. Driver, 3 in. dia. $\times \frac{5}{8}$ in. long overall.		C	„	1
14351	Type 55 ...	Coil oscillator crystal assembly, 3 in. dia. $\times \frac{5}{8}$ in. long.		C	„	1
14354	Type 56 ...	Coil buffer crystal assembly ...		C	„	1
14368	Type 57 ...	Output. First used on Oscillator Units T.25.		C	„	1
14369	Type 58 ...	Buffer. First used on Oscillator Units T.25.		C	„	1
14370	Type 59 ...	Oscillator. First used on Oscillator Units T.25.		C	„	1
14345	Type 60 ...	Oscillator. Part of R.1547 ...		C	„	1
14652	Type 62 ...	Assembly of (3 inductors on formers) 5 honeycomb coils on former.		C	„	1
14711	Type 64 ...	5 coils of 42 μ H and 1 coil of 84 μ H mounted on former.		C	„	1
14732	Type 65 ...	Variable inductor unit, $\frac{1}{4}$ in. spindle, 2 coils, and moving plate, in cylindrical metal can.		C	„	1
17653	Type 85 ...	1,445 c/ps. Q factor 50. M.S. case (S.C.A/32), 2.25 in. \times 1.62 in. \times 3.06 in. No base.		C	„	1
17654	Type 86 ...	935 c/ps. Q factor 50. M.S. case (S.C.A/32), 2.25 in. \times 1.62 in. \times 3.06 in. No base.		C	„	1
17707	Type 87 ...	Inductor assembly (I.F. No. 3) for Rec. Unit T.103.		C	„	1
18017	Type 89 ...	18 turns 30 S.W.G. en. cu. wire wound on R.4 10W/10336 resistor T.3292. 82 ohms, $\frac{1}{4}$ watt.		C	„	1
17045	JACKS, No. 3 ...	R.D.F. No. 1 ...		C	„	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
15820	LEVERS	Fibre, dims. $2\frac{1}{8}$ in. \times $\frac{5}{8}$ in. \times $\frac{1}{2}$ in.		C	each	2
15821	LEVERS	Fibre, dims. $2\frac{1}{8}$ in. \times $\frac{5}{8}$ in. \times $\frac{1}{2}$ in.		C	..	2
15273	LINKS	$7\frac{1}{16}$ in. ebonite or equivalent, $\frac{3}{4}$ in. \times $\frac{3}{16}$ in.		C	..	1
14934	LINKS	Mycalex bar, $\frac{1}{4}$ in. \times $\frac{5}{8}$ in. \times $11\frac{7}{16}$ in., with end forks 1 ft. $\frac{13}{16}$ in., fixing centres.		C	..	1
14957	LINKS	$12\frac{3}{4}$ in. \times $\frac{5}{8}$ in. \times $\frac{1}{2}$ in. Mycalex or equivalent, with brass end plates, 1 ft. $2\frac{5}{16}$ in. centres.		C	..	1
14958	LINKS	$2\frac{3}{16}$ in. \times $\frac{1}{2}$ in. dia. Bakelite or equivalent, with ball joint, $3\frac{1}{8}$ in. centres.		C	..	1
15247	LINKS	1 in.— $2\frac{1}{2}$ in. centres. Assembly of mycalex (or equivalent) strip, 1 ft. $2\frac{3}{8}$ in. \times $\frac{1}{2}$ in. \times $\frac{3}{8}$ in., with brass end plates.		C	..	1
15248	LINKS	1 in.— $4\frac{3}{32}$ in. centres, Assembly of mycalex (or equivalent) strip, 1 ft. $2\frac{3}{16}$ in. \times $\frac{3}{4}$ in. \times $\frac{3}{8}$ in., with brass end plates.		C	..	1
15256	LINKS	Mycalex, $4\frac{3}{4}$ in. \times $\frac{3}{4}$ in. \times $\frac{1}{4}$ in.		C	..	1
15257	LINKS	Loaded ebonite, 1 ft. $5\frac{9}{16}$ in. $\frac{5}{8}$ in. \times $\frac{1}{2}$ in., with brass end plates.		C	..	1
15258	LINKS	Loaded ebonite or equivalent, 1 ft. $5\frac{3}{8}$ in. \times $\frac{5}{8}$ in. \times $\frac{1}{2}$ in., with brass end plate.		C	..	1
15246	LINKS COUPLING	Mycalex 11, dims. $4\frac{1}{2}$ in. \times $\frac{5}{8}$ in. \times $\frac{3}{8}$ in., with 4 brass end plates, 1 ft. 6 in. centres.		C	..	1
3746	MICA	$2\frac{1}{2}$ in. \times $2\frac{1}{2}$ in. \times .003 in. For capacitor assembly.		C	..	1
3747	MICA	$3\frac{3}{4}$ in. \times $2\frac{1}{2}$ in. \times .002 in. For capacitor assembly.		C	..	1
5718	MOUNTINGS ..	Assembly of brass tube, $1\frac{1}{2}$ in. o/d \times $2\frac{7}{8}$ in. long, terminal plate $\frac{1}{8}$ in. thick, clamping ring and terminal rod. $1\frac{5}{8}$ in. \times $\frac{1}{2}$ in. dia.		C	..	1
2646	NUTS		C	..	1
14951	PLATES:— Balancing adjustable.	Brass, 1 ft. 5 in. \times $7\frac{1}{4}$ in. \times 14 S.W.G.		C	..	1
15030	Capacitor	Back plate, $1\frac{5}{8}$ in. \times $1\frac{1}{4}$ in. \times $\frac{1}{4}$ in. deep; rounded corners.		C	..	5
15259	Capacitor	Brass, 12 in. \times 3 in. \times 14 S.W.G.		C	..	1
15804	Capacitor	Brass, $8\frac{1}{2}$ in. \times 4 in. $\frac{1}{4}$ in. ...		C	..	10
18020	Capacitor	Copper, $2\frac{1}{4}$ in. long, 2 in. \times $\frac{3}{16}$ in.		C	..	1

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
	PLATES—cont.					
4738	Capacitor	3 $\frac{3}{8}$ in. \times $\frac{3}{4}$ in.		C	each	1
11072	Capacitor	For grid, 2 in. dia. metal disc with stud, holding block and adjusting spindle.		C	„	1
13820	Capacitor, fixed	L.H. Brass sheet, 8 in. \times 8 $\frac{3}{4}$ in., with lugs.		C	„	1
15811	Capacitor, fixed ...	3 $\frac{3}{4}$ in. \times 2 $\frac{1}{4}$ in. \times $\frac{1}{8}$ in. ...		C	„	1
15812	Capacitor, moving	3 $\frac{1}{4}$ in. \times 2 $\frac{1}{8}$ in. \times $\frac{1}{8}$ in. Brass ...		C	„	5
15260	Fixed	Aluminium, 1 ft. 0 in. \times 8 $\frac{3}{4}$ in. \times $\frac{3}{16}$ in.		C	„	1
15262	Fixed	Aluminium, 1 ft. 0 in. \times 9 $\frac{5}{16}$ in. \times $\frac{3}{16}$ in.		C	„	1
15270	Fixed	Brass, 3 in. \times 1 $\frac{1}{8}$ in. \times 20 S.W.G.		C	„	5
14955	Fixed	Brass, 11 $\frac{1}{4}$ in. \times 6 $\frac{1}{2}$ in. \times 14 S.W.G.		C	„	1
13594	Fixed assembly ...	Plate, dims. 3 $\frac{5}{16}$ in. \times 2 $\frac{3}{8}$ in. \times $\frac{1}{8}$ in., brass silver-plated, 2 holes .125 in. dia., brazed-on connector (DA.3436) mounted on dystrene block.		C	„	1
15263	Fixed balancing ...	Left-hand. Aluminium, 1 ft. 4 $\frac{3}{8}$ in. \times 8 $\frac{3}{4}$ in. \times $\frac{3}{16}$ in.		C	„	1
15264	Fixed balancing ...	Aluminium, 1 ft. 4 $\frac{3}{8}$ in. \times 8 $\frac{3}{4}$ in. \times $\frac{3}{16}$ in.		C	„	1
14948	Fixed trimmer ...	Brass, 9 $\frac{3}{4}$ in. \times 3 $\frac{5}{8}$ in. \times 14 S.W.G.		C	„	1
14947	Fixed main	Brass mycalex, 9 $\frac{3}{4}$ in. \times 3 $\frac{5}{8}$ in. \times 14 S.W.G.		C	„	5
15813	Front	Mycalex, 6 $\frac{13}{16}$ in. \times 5 $\frac{1}{4}$ in. \times $\frac{1}{4}$ in.		C	„	5
15261	Moving	Aluminium, 1 ft. 3 in. \times 10 in. \times $\frac{3}{16}$ in.		C	„	1
15271	Moving	Brass, 3 $\frac{1}{4}$ in. \times 2 $\frac{1}{16}$ in. \times 20 S.W.G.		C	„	1
15265	Moving balancing	Aluminium, 7 $\frac{3}{16}$ in. \times 9 in. \times $\frac{3}{16}$ in.		C	„	1
14949	Moving main	Brass, 9 in. \times 5 $\frac{1}{2}$ in. \times 14 S.W.G.		C	„	1
14950	Moving trimmer	Brass, 9 in. \times 9 $\frac{7}{16}$ in. \times 14 S.W.G.		C	„	1
	Neutralising:—					
3880	Type 1	Left-hand, fixed connection to insulator and variable capacitor, brass sheet.		C	„	1
3881	Type 2	Right-hand, otherwise as Type 1		C	„	1
3882	Type 3	Left-hand, fixed connection to variable capacitor, brass sheet.		C	„	1
3883	Type 4	Right-hand, otherwise as Type 3		C	„	1
3884	Type 5	Movable, slotted steel plate ...		C	„	1
12202	Type 7	Left-hand. Brass link, fixed capacitor to insulator and variable capacitor.		C	„	1
12203	Type 8	Right-hand, otherwise as Type 7		C	„	1
3743	Padding	2 in. dia. with clamping screw and locknut.		C	„	1
15805	Plates	Mycalex, 9 in. \times 1 in., 2 $\frac{1}{2}$ in. \times $\frac{1}{2}$ in. platform.		C	„	1
15814	Rear	Mycalex, 4 $\frac{3}{4}$ in. \times 3 $\frac{3}{8}$ in. \times $\frac{1}{4}$ in.		C	„	1
3765	Screening	Trimming capacitor, vernier trimmer device.		C	„	1

SECTION 100—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
15250	POINTERS:— Capacitor ...	Assembly of Keramot link and brass clamp, $\frac{1}{4}$ in. \times $\frac{3}{4}$ in., angled.		C	each	5
14763	REJECTORS:— Coil assemblies ...	Bracket mounted assembly of coil capacitors and resistors.		C	..	1
15825	SPACERS ...	Mycalex, 2 in. \times $\frac{3}{8}$ in. \times 1-1 $\frac{1}{2}$ in.		C	..	5
15822	SPRINGS, STEEL ...	9 turns 36 S.W.G., 1 $\frac{1}{8}$ in. free length \times $\frac{13}{32}$ in. o/d, lead coated, cadmium plated.		C	..	10
13368	STRIPS ...	Capacitor mounting. Mycalex, 5 $\frac{3}{4}$ in. \times 2 in. \times $\frac{3}{8}$ in. thick, with 8 inserts.		C	..	1
14942	STRIPS ...	Mycalex, 1 $\frac{1}{2}$ in. \times 3 $\frac{1}{2}$ in. \times $\frac{1}{4}$ in. Trimmer capacitor support.		C	..	5
14943	STRIPS ...	Mycalex, 1 $\frac{1}{2}$ in. \times 3 $\frac{1}{2}$ in. \times $\frac{1}{4}$ in. Trimmer capacitor support.		C	..	5
14944	STRIPS ..	Mycalex, 1 $\frac{1}{2}$ in. \times 3 $\frac{1}{2}$ in. \times $\frac{1}{4}$ in. Trimmer capacitor support.		C	..	5
18001	STRIPS ...	Mycalex, 1 ft. 4 $\frac{1}{2}$ in. \times 8 $\frac{3}{4}$ in. \times $\frac{1}{4}$ in.		C	..	1
18002	STRIPS ...	Mycalex, 4 $\frac{1}{2}$ in. \times 1 ft. \times $\frac{1}{4}$ in.		C	..	1
18003	STRIPS ...	Mycalex, 8 $\frac{1}{2}$ in. \times 4 $\frac{5}{8}$ in. \times $\frac{1}{4}$ in.		C	..	1
18004	STRIPS ...	Mycalex bar		C	..	1
14945	STRIPS ...	Mycalex, 1 in. \times 7 $\frac{1}{4}$ in. \times $\frac{1}{2}$ in. Main capacitor supports (top).		C	..	1
14946	STRIPS ...	Mycalex, 1 $\frac{1}{4}$ in. \times 9 $\frac{3}{4}$ in. \times $\frac{1}{2}$ in. Moving plate bearing support (top).		C	..	1
14952	STRIPS ...	Mycalex, 1 ft.-1 $\frac{9}{16}$ in. \times $\frac{3}{4}$ in. \times $\frac{1}{4}$ in. Main capacitor drive lever. Upper.		C	..	1
14953	STRIPS ...	Mycalex, 11 $\frac{33}{32}$ in. \times $\frac{3}{4}$ in. \times $\frac{1}{4}$ in. Trimming capacitor drive lever. Lower.		C	..	1
14960	STRIPS ...	Mycalex, 1 $\frac{1}{2}$ in. \times $\frac{1}{2}$ in. \times 1 ft. 10 in.		C	..	1
15272	STRIPS ...	Capacitor base. Mycalex, 5 $\frac{1}{4}$ in. \times 3 $\frac{7}{8}$ in. \times $\frac{1}{4}$ in.		C	..	5
18021	STRIPS ...	Mycalex, 1 ft. 3 in. \times 1 $\frac{1}{2}$ in. \times $\frac{3}{8}$ in.		C	..	1
18022	STRIPS ...	Mycalex, 1 ft. 3 in. \times 1 $\frac{1}{2}$ in. \times $\frac{3}{8}$ in.		C	..	1
15823	SUPPORTS ...	Mycalex, 1 ft. 0 in. \times 10 $\frac{3}{4}$ in. \times $\frac{1}{2}$ in.		C	..	5

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

Ref. No.	NOMENCLATURE	DETAIL	Army or Navy Ref.	Class of Store	Denom. of Qty.	Carton Unit Qty.
1	2	3	4	5	6	7
15824	SUPPORTS ...	Mycalex, $9\frac{7}{16}$ in. \times 6 in. \times $\frac{1}{2}$ in.		C	each	5
15885	SUPPORTS ...	Mycalex, $17\frac{7}{8}$ in. \times 7 in. \times $\frac{1}{2}$ in.		C	..	1
15886	SUPPORTS ...	Mycalex, 7 in. \times 3 in. \times $\frac{1}{2}$ in.		C	..	1
15896	SUPPORTS ...	Mycalex, 1 ft. $0\frac{1}{8}$ in. \times $7\frac{1}{4}$ in. \times $\frac{3}{4}$ in.		C	..	1
15897	SUPPORTS ...	Mycalex, 1 ft. $0\frac{1}{8}$ in. \times $7\frac{1}{4}$ in. \times $\frac{3}{4}$ in.		C	..	1
15898	SUPPORTS ...	Mycalex, $9\frac{1}{8}$ in. \times 8 in. \times 1 in.		C	..	1
14930	SUPPORTS, BOTTOM.	Mycalex, 1 ft. 0 in. \times $\frac{5}{16}$ in. \times $9\frac{1}{2}$ in.		C	..	1
15237	SUPPORTS, BOTTOM.	Mycalex, 11 in. \times $1\frac{1}{2}$ in. \times $\frac{3}{8}$ in.		C	..	1
15266	SUPPORTS, CAPACITOR, BASE.	Mycalex, 1 ft. $5\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. \times $\frac{5}{8}$ in.		C	..	1
15267	SUPPORTS, CAPACITOR, TOP.	Mycalex, 1 ft. $5\frac{1}{2}$ in. \times $1\frac{1}{2}$ in. \times $\frac{5}{8}$ in.		C	..	1
15806	SUPPORTS, L.H.	Mycalex, 1 ft. $5\frac{3}{4}$ in. \times 3 in. \times $\frac{1}{2}$ in.		C	..	5
15268	SUPPORTS, MAIN	Mycalex, $11\frac{1}{2}$ in. \times 6 in. \times $\frac{3}{8}$ in.		C	..	1
15808	SUPPORTS, MOVING.	Mycalex, shaped, $4\frac{11}{16}$ in. \times $\frac{1}{2}$ in. \times $1\frac{3}{4}$ in. centre.		C	..	5
15807	SUPPORTS, R.H.	Mycalex, 1 ft. $5\frac{3}{4}$ in. \times 3 in. \times $\frac{1}{2}$ in.		C	..	5
14931	SUPPORTS, TOP ...	Mycalex, $1\frac{1}{2}$ in. \times $\frac{3}{8}$ in. \times 1 ft. $4\frac{1}{2}$ in.		C	..	1
15238	SUPPORTS, TOP ...	Mycalex, $17\frac{3}{4}$ in. \times $2\frac{1}{2}$ in. \times 12 in.		C	..	1
	TAG BOARDS:—					
14661	Type 532 ...	15 tags. S.R.B.P. 4.687 in. \times 1 ft. 5 in. \times .093 in.		C	..	1
14662	Type 538 ...	10 tags. S.R.B.P. 3.75 in. \times 2.635 in. \times $\frac{1}{16}$ in.		C	..	1
14665	Type 539 ...	4 tags. S.R.B.P. $1\frac{3}{8}$ in. \times $2\frac{1}{4}$ in. \times $\frac{1}{16}$ in.		C	..	1
2821	TUBES ...	Pyrex, 2 in. dia. \times 20 in., zinc sprayed, 17 in.		C	..	1
2830	TUBES ...	Pyrex, 2 in. dia. \times 20 in., zinc sprayed, 14 in. long.		C	..	1
	VANES:—					
15239	Fixed ...	Aluminium, 11 in. \times $4\frac{3}{4}$ in. \times $\frac{1}{8}$ in.		C	..	5
15240	Moving ...	Aluminium, 11 in. \times 7 in. \times $\frac{1}{8}$ in.		C	..	5
14932	Fixed ...	Brass, 10 in. \times $3\frac{3}{4}$ in. \times $\frac{1}{16}$ in.		C	..	1
14933	Moving ...	Brass, 10 in. \times $6\frac{1}{2}$ in. \times $\frac{1}{16}$ in.		C	..	1
5719	WASHERS ...	Rubber, $1\frac{3}{4}$ in. dia. \times $\frac{1}{16}$ in. \times $\frac{1}{4}$ in. hole.		C	..	1

SECTION 100

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
13	3	469	54	741	17	960	62	2148	10
15	5	477	67	744	42	962	62	2152	128
16	2	482	92	745	21	964	25	2153	128
19	20	496	23	746	68	967	45	2154	128
21	67	497	67	768	89	968	68	2155	19
24	24	499	25	769	68	969	32	2157	44
38	19	520	109	770	68	974	68	2161	59
42	109	531	14	771	127	975	68	2162	58
50	55	532	14	772	127	976	68	2165	60
72	109	533	49	773	127	978	2	2170	54
74	109	534	13	776	127	979	57	2173	41
76	109	535	47	778	127	1805	53	2174	51
77	109	543	67	779	127	2006	39	2175	49
78	109	559	14	780	128	2008	30	2176	51
79	92	560	56	781	128	2009	28	2177	49
80	92	561	52	784	27	2010	29	2179	39
81	109	564	37	785	27	2011	33	2181	40
83	67	565	14	786	27	2012	28	2182	40
84	67	566	58	788	28	2013	39	2184	110
87	19	567	57	789	29	2014	39	2185	93
90	67	568	14	790	29	2017	30	2186	93
94	31	569	58	791	30	2018	68	2187	110
96	19	571	109	793	32	2019	93	2189	53
104	21	572	109	794	34	2020	47	2190	55
214	22	578	92	801	54	2027	1	2191	58
233	67	579	109	826	116	2029	14	2192	50
234	67	580	109	831	128	2030	57	2193	55
245	24	581	109	833	128	2039	18	2194	60
247	67	582	109	834	128	2040	50	2201	128
249	92	583	92	835	128	2043	38	2202	128
251	57	605	109	836	93	2046	61	2207	26
271	20	608	44	837	93	2047	62	2209	8
275	67	609	67	843	68	2048	47	2213	8
276	60	610	10	844	10	2053	61	2220	55
277	60	651	23	846	110	2055	25	2222	57
279	67	652	15	849	92	2061	110	2223	68
288	55	653	15	853	7	2069	68	2224	60
289	11	654	15	857	7	2071	68	2226	110
302	67	655	53	858	7	2073	5	2227	66
308	3	658	109	859	7	2075	6	2232	93
312	67	666	14	861	6	2076	21	2233	93
333	49	667	8	862	6	2078	28	2234	93
336	24	672	6	863	89	2079	7	2235	93
339	67	673	7	866	93	2082	68	2236	93
344	67	674	32	869	8	2083	46	2239	56
369	67	682	18	872	68	2086	68	2240	56
372	67	686	49	873	23	2087	93	2243	40
374	67	695	61	874	6	2090	59	2244	40
380	55	696	61	880	92	2092	110	2245	40
382	10	697	49	883	61	2093	110	2246	40
384	92	706	49	884	46	2098	110	2248	50
386	92	707	47	893	128	2099	128	2252	43
392	67	710	62	894	68	2101	49	2253	43
399	67	712	8	902	93	2102	41	2255	16
409	127	713	6	908	128	2103	68	2257	56
416	127	714	7	912	128	2108	1	2265	16
419	127	715	62	913	128	2111	128	2266	128
420	127	716	14	914	128	2119	53	2268	93
421	127	719	92	915	68	2121	27	2269	93
422	127	728	2	916	68	2123	27	2271	42
443	17	729	1	917	68	2132	47	2273	110
447	92	730	67	938	50	2140	128	2278	26
448	109	731	68	939	50	2142	110	2279	110
449	109	732	8	941	61	2143	110	2280	45
467	56	733	16	954	6	2146	28	2282	68
468	49	735	68	958	22	2147	28	2283	68

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
2289	110	2446	110	2687	53	2844	129	3019	111
2290	50	2447	51	2688	52	2845	129	3023	70
2294	34	2448	53	2690	26	2847	94	3025	3
2296	110	2552	110	2692	110	2849	94	3026	45
2297	110	2554	18	2693	39	2850	94	3028	70
2298	110	2555	110	2696	62	2851	111	3031	70
2299	93	2558	93	2701	93	2855	129	3034	8
2310	37	2560	68	2705	69	2856	129	3035	7
2314	38	2561	7	2706	69	2857	129	3036	5
2317	63	2563	62	2707	2	2858	111	3039	70
2318	68	2564	62	2708	69	2859	94	3042	1
2319	68	2565	45	2710	13	2866	111	3043	3
2320	63	2567	45	2711	43	2870	69	3045	7
2321	63	2570	110	2712	61	2871	46	3046	32
2322	56	2572	68	2714	69	2873	69	3047	70
2323	60	2574	69	2715	41	2874	7	3048	57
2326	59	2575	69	2716	41	2877	3	3049	53
2328	68	2576	110	2717	42	2879	69	3050	56
2329	63	2578	47	2718	7	2881	47	3064	30
2331	60	2579	69	2722	47	2882	69	3066	70
2332	62	2580	110	2724	47	2890	46	3068	22
2334	68	2582	110	2725	69	2891	46	3069	55
2336	53	2585	93	2726	21	2896	69	3070	70
2337	68	2590	41	2727	69	2898	69	3071	17
2339	20	2593	93	2729	16	2908	27	3072	12
2341	47	2594	93	2736	93	2910	129	3075	90
2342	24	2595	110	2737	93	2911	129	3080	29
2346	48	2596	110	2754	129	2912	129	3081	3
2351	51	2598	89	2761	110	2913	129	3084	9
2352	68	2601	110	2762	93	2914	129	3085	70
2353	68	2605	14	2763	110	2915	129	3089	7
2360	93	2606	15	2764	110	2917	129	3092	70
2361	93	2608	128	2765	110	2920	2	3093	23
2364	89	2609	128	2771	129	2922	53	3100	23
2365	89	2610	69	2773	93	2926	20	3101	21
2366	4	2612	17	2775	93	2928	15	3105	25
2367	110	2614	60	2776	129	2930	69	3106	24
2376	110	2615	69	2786	129	2931	69	3111	63
2378	93	2617	69	2789	129	2932	69	3115	23
2379	63	2620	50	2791	42	2933	37	3121	58
2380	62	2622	60	2792	56	2934	38	3122	16
2381	62	2625	44	2794	17	2935	69	3125	70
2382	58	2626	38	2795	63	2936	14	3127	51
2383	62	2630	42	2796	69	2937	58	3129	70
2386	40	2632	128	2798	24	2939	19	3138	11
2387	68	2634	61	2799	69	2942	94	3145	111
2388	23	2635	52	2800	69	2943	125	3146	111
2389	62	2638	69	2801	69	2944	94	3147	111
2390	20	2643	110	2802	69	2951	65	3151	129
2392	89	2644	126	2803	21	2953	94	3156	129
2400	54	2646	156	2806	69	2954	94	3159	129
2401	8	2649	28	2808	3	2958	129	3166	129
2403	2	2651	45	2809	58	2959	129	3167	129
2414	68	2653	10	2810	54	2963	47	3168	129
2416	18	2654	46	2812	41	2965	10	3169	129
2421	22	2656	26	2813	53	2966	70	3173	90
2423	25	2668	4	2816	69	2698	14	3174	90
2426	10	2676	69	2818	57	2969	53	3180	70
2428	29	2677	13	2819	69	2970	55	3183	39
2429	47	2678	47	2821	159	2971	14	3186	70
2434	7	2679	46	2822	127	2973	70	3188	15
2436	50	2680	42	2829	89	2979	5	3191	22
2437	57	2681	46	2830	159	2992	129	3193	38
2438	15	2683	47	2832	89	2994	129	3194	70
2439	47	2684	69	2842	129	3008	94	3196	21
2440	14	2686	47	2843	129	3017	111	3198	32

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
3200	2	3436	3	3606	8	3824	90	3991	36
3207	70	3437	18	3608	58	3825	130	3992	8
3209	63	3439	26	3609	71	3826	130	3994	72
3210	25	3443	32	3610	56	3827	130	3995	72
3211	49	3448	26	3611	1	3829	130	3996	72
3214	8	3451	6	3614	7	3841	71	3998	18
3216	8	3459	55	3615	125	3844	71	3999	72
3219	5	3460	111	3619	130	3845	38	4000	72
3220	94	3462	56	3628	67	3846	71	4010	72
3221	94	3466	71	3638	58	3848	71	4018	5
3224	94	3467	71	3639	11	3850	71	4020	46
3232	129	3474	10	3641	58	3851	72	4021	45
3234	129	3478	152	3642	33	3852	72	4022	11
3235	129	3479	152	3643	29	3853	3	4023	45
3260	5	3485	11	3650	92	3854	3	4024	44
3263	7	3486	65	3653	111	3855	72	4025	72
3265	5	3487	71	3661	71	3856	72	4027	59
3266	6	3490	51	3663	71	3858	72	4028	59
3270	26	3491	58	3666	9	3860	2	4029	55
3271	14	3495	129	3668	9	3861	1	4034	38
3272	14	3496	129	3669	71	3862	48	4036	38
3273	18	3497	129	3670	71	3863	55	4042	38
3275	70	3498	130	3671	1	3864	15	4044	53
3276	44	3499	49	3675	6	3865	72	4045	130
3277	55	3500	71	3676	71	3869	62	4048	130
3290	45	3501	71	3678	20	3870	3	4049	130
3291	45	3509	50	3679	20	3880	157	4054	130
3294	70	3512	56	3682	111	3881	157	4061	90
3298	70	3513	60	3685	111	3882	157	4062	90
3299	70	3516	20	3691	71	3883	157	4064	94
3303	2	3517	71	3693	19	3884	157	4065	94
3304	70	3520	111	3694	71	3895	111	4066	94
3305	70	3522	111	3696	24	3896	111	4067	94
3308	70	3523	111	3698	60	3899	94	4068	94
3313	70	3524	94	3705	71	3900	53	4069	94
3325	70	3530	32	3715	71	3902	47	4070	94
3326	40	3533	29	3717	71	3904	72	4073	111
3330	70	3535	71	3719	62	3905	39	4074	111
3332	70	3541	92	3733	111	3908	72	4075	111
3333	70	3542	130	3736	111	3909	72	4076	111
3336	70	3544	10	3739	111	3912	27	4077	130
3337	6	3545	31	3742	111	3922	28	4078	130
3338	22	3546	71	3743	157	3925	30	4083	111
3341	37	3549	31	3746	156	3927	6	4084	111
3342	65	3550	71	3747	156	3930	57	4086	111
3352	70	3551	71	3765	157	3935	21	4087	111
3354	37	3552	71	3771	111	3938	18	4088	111
3378	90	3560	3	3784	16	3940	72	4091	94
3380	19	3566	6	3786	71	3947	72	4092	94
3383	18	3568	22	3787	11	3948	72	4093	94
3386	40	3572	5	3788	25	3949	3	4094	94
3388	21	3573	7	3790	71	3953	61	4095	10
3389	19	3574	6	3791	71	3954	32	4097	17
3394	70	3575	71	3796	39	3955	30	4100	19
3395	70	3576	71	3798	38	3956	30	4103	26
3397	7	3581	71	3804	93	3957	33	4104	72
3399	46	3586	7	3806	94	3959	72	4106	72
3403	65	3587	21	3807	94	3963	47	4107	72
3414	19	3588	63	3808	94	3967	130	4109	72
3415	22	3589	23	3809	94	3971	111	4112	36
3416	60	3590	94	3815	126	3973	111	4113	36
3425	94	3592	96	3816	130	3974	111	4114	72
3428	111	3593	90	3817	130	3979	94	4115	72
3429	111	3594	30	3818	130	3983	32	4124	130
3434	2	3602	21	3819	130	3989	49	4125	130
3435	2	3603	8	3822	90	3990	37	4126	130

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
4132	95	4380	130	4610	41	4794	6	5016	95
4147	95	4381	130	4611	34	4795	6	5017	95
4150	95	4382	130	4613	32	4797	30	5020	8
4152	95	4383	131	4614	10	4798	29	5021	73
4153	95	4384	131	4615	62	4803	43	5024	73
4175	2	4385	131	4616	62	4805	52	5026	73
4184	29	4397	13	4617	54	4807	73	5027	73
4185	31	4401	17	4618	62	4821	73	5028	73
4187	28	4409	5	4622	5	4823	43	5030	30
4190	40	4415	72	4623	6	4824	57	5034	19
4191	39	4416	18	4624	23	4833	131	5036	8
4197	31	4419	72	4625	22	4835	131	5041	13
4198	31	4424	31	4626	25	4838	131	5042	55
4199	25	4425	72	4630	7	4839	131	5043	73
4201	30	4433	39	4631	11	4845	112	5046	33
4209	33	4450	131	4632	1	4846	112	5047	31
4213	50	4451	131	4634	48	4851	95	5056	28
4214	52	4453	131	4636	48	4858	131	5059	112
4215	39	4454	131	4638	47	4864	73	5060	112
4223	125	4458	131	4640	153	4865	54	5061	112
4227	130	4459	131	4646	2	4868	20	5065	95
4228	130	4461	95	4656	11	4870	73	5066	95
4231	11	4465	111	4683	52	4871	44	5069	95
4237	31	4467	126	4687	18	4872	30	5070	95
4238	30	4470	90	4688	18	4875	73	5077	131
4240	1	4471	90	4695	16	4876	15	5080	112
4249	19	4473	126	4698	19	4884	51	5082	112
4251	6	4474	73	4699	18	4885	20	5084	112
4252	5	4476	27	4703	10	4887	24	5085	112
4253	6	4479	27	4705	73	4889	24	5086	112
4254	5	4486	6	4706	20	4891	24	5087	112
4255	19	4490	25	4710	112	4895	60	5090	95
4263	63	4501	12	4711	112	4896	73	5091	95
4265	72	4506	4	4712	112	4900	59	5094	95
4266	72	4507	73	4713	112	4904	55	5109	131
4267	24	4510	56	4714	112	4905	53	5114	95
4268	20	4512	73	4715	112	4909	43	5122	131
4271	29	4517	95	4728	131	4917	73	5130	112
4274	27	4522	111	4729	131	4920	8	5131	112
4280	111	4523	111	4730	131	4922	27	5132	112
4298	130	4524	112	4731	131	4923	29	5133	113
4301	130	4525	112	4733	131	4932	63	5137	38
4302	130	4526	12	4734	131	4933	15	5142	3
4303	130	4527	59	4738	157	4934	73	5144	31
4304	130	4528	49	4753	1	4938	39	5145	49
4314	130	4530	21	4755	1	4939	28	5147	58
4315	130	4531	53	4760	3	4943	25	5149	42
4316	130	4532	51	4762	3	4947	73	5158	53
4317	130	4533	51	4763	30	4950	10	5162	43
4326	30	4534	49	4765	20	4951	7	5168	2
4334	72	4535	58	4767	22	4959	28	5170	74
4340	72	4536	14	4768	1	4960	30	5176	18
4341	55	4544	44	4772	73	4961	29	5183	54
4342	39	4546	21	4774	41	4965	73	5185	50
4345	38	4555	57	4776	22	4966	73	5191	52
4347	8	4556	18	4777	46	4968	73	5193	38
4349	20	4566	41	4778	11	4969	49	5210	49
4351	15	4568	56	4779	10	4970	23	5215	52
4352	17	4569	73	4780	10	4976	21	5216	51
4357	95	4570	52	4781	10	4977	55	5217	51
4359	95	4571	73	4782	19	4979	73	5218	57
4360	95	4572	53	4785	18	4980	10	5219	57
4362	95	4589	47	4786	49	4995	19	5220	74
4364	130	4592	112	4788	24	4997	54	5221	3
4365	130	4593	112	4791	4	4998	42	5223	37
4366	130	4599	95	4792	73	5002	131	5228	74

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
5230	31	5444	74	5644	15	5801	16	5974	43
5237	74	5455	25	5645	44	5802	30	5976	42
5238	74	5456	31	5647	75	5805	61	5979	33
5239	74	5471	49	5649	2	5806	75	5980	75
5241	74	5475	31	5654	75	5807	41	5983	28
5244	53	5477	30	5655	13	5810	1	5985	75
5245	52	5478	34	5656	21	5818	2	5987	75
5253	23	5479	34	5657	43	5825	15	5989	28
5277	95	5480	53	5661	1	5826	127	5990	28
5285	95	5483	31	5663	7	5828	133	5991	75
5286	113	5484	30	5665	60	5829	133	5993	6
5287	95	5486	113	5666	75	5830	133	5997	75
5288	113	5487	113	5667	75	5833	133	7037	89
5290	113	5492	96	5669	30	5834	133	7039	38
5291	113	5500	132	5670	31	5845	114	7174	35
5292	113	5501	132	5673	43	5847	96	7203	65
5297	57	5520	132	5683	2	5848	126	7204	35
5301	5	5524	53	5686	85	5868	41	7249	65
5302	65	5525	61	5687	24	5871	20	7384	109
5304	74	5528	11	5688	26	5872	8	7386	20
5315	19	5529	19	5689	26	5873	75	7388	22
5317	5	5530	24	5692	54	5875	75	7391	54
5318	5	5531	25	5693	14	5883	11	7469	65
5319	6	5532	40	5697	16	5884	25	7490	92
5320	4	5533	56	5706	75	5887	75	7512	109
5321	5	5534	74	5707	47	5888	75	7593	51
5322	5	5535	74	5710	33	5889	26	7594	65
5323	5	5536	41	5711	50	5890	58	7762	65
5328	54	5537	51	5714	92	5891	50	7763	37
5329	74	5538	13	5715	126	5892	55	7764	38
5333	14	5539	74	5716	126	5893	55	7814	19
5335	14	5543	74	5717	127	5896	75	7847	24
5337	54	5544	74	5718	156	5897	75	7853	65
5338	56	5546	18	5719	159	5898	75	7895	65
5342	74	5548	20	5723	113	5901	32	7901	23
5343	96	5549	22	5724	113	5903	29	7902	19
5349	10	5556	74	5725	113	5905	114	7903	18
5352	25	5559	59	5729	90	5906	114	7904	65
5356	42	5564	25	5730	114	5910	96	7905	65
5362	43	5565	5	5731	114	5911	96	7906	26
5379	113	5566	56	5736	132	5912	96	7912	109
5381	131	5567	58	5737	133	5913	96	8009	21
5382	132	5568	15	5738	133	5914	96	8044	38
5384	132	5576	74	5741	96	5916	114	8048	37
5385	132	5583	29	5743	96	5920	133	8116	65
5386	132	5585	27	5750	90	5923	133	8140	65
5388	132	5586	28	5758	59	5924	133	8162	65
5389	132	5588	74	5759	57	5925	133	8163	38
5394	132	5591	54	5761	7	5936	133	8164	38
5395	113	5592	14	5762	50	5946	12	8166	65
5399	113	5593	74	5763	44	5947	21	8167	65
5402	96	5594	74	5764	50	5948	23	8168	65
5403	96	5595	1	5767	4	5949	50	8169	65
5405	113	5597	53	5769	59	5950	49	8171	65
5406	113	5598	15	5772	75	5951	6	8172	65
5407	113	5606	132	5774	21	5952	24	8206	66
5414	74	5613	96	5782	32	5953	25	8275	54
5415	52	5614	96	5786	33	5954	65	8286	66
5421	89	5615	96	5788	29	5956	3	8378	57
5425	23	5616	96	5790	75	5958	75	8380	66
5426	63	5619	96	5792	31	5960	1	8381	66
5434	14	5623	113	5795	43	5962	5	8383	92
5439	14	5629	90	5796	54	5969	75	8384	92
5440	51	5638	75	5798	33	5970	30	8386	18
5441	21	5639	53	5799	56	5971	31	8387	66
5443	74	5641	43	5800	75	5973	43	8388	20

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
8463	125	9497	109	10655	67	11081	127	11294	28
8464	125	9514	92	10656	67	11082	127	11298	97
8473	89	9606	109	10658	128	11083	127	11300	114
8474	89	9607	109	10699	111	11084	127	11301	114
8483	21	9608	58	10743	67	11098	10	11302	114
8484	66	9611	12	10752	67	11099	31	11303	114
8487	66	9628	109	10753	67	11100	76	11304	114
8488	39	9642	18	10755	14	11107	128	11305	67
8490	66	9675	52	10766	59	11108	133	11313	115
8493	25	9805	57	10775	94	11117	94	11314	97
8496	26	9806	59	10779	94	11131	43	11318	134
8497	37	9807	60	10780	111	11132	46	11322	114
8498	37	9832	92	10790	127	11134	41	11323	114
8499	38	9833	38	10801	51	11136	41	11324	114
8500	39	9907	66	10802	15	11139	41	11325	114
8507	37	10010	39	10803	55	11140	41	11326	97
8561	66	10015	34	10804	128	11141	41	11330	97
8566	66	10047	25	10805	127	11149	96	11331	97
8567	39	10048	53	10821	55	11152	134	11332	115
8634	109	10051	60	10822	55	11153	134	11335	153
8637	66	10082	66	10825	58	11166	134	11336	97
8638	15	10117	92	10826	49	11167	114	11338	115
8639	60	10164	25	10827	60	11169	20	11339	115
8656	24	10167	22	10828	58	11182	3	11340	115
8657	46	10221	38	10829	59	11188	76	11341	92
8658	26	10226	67	10832	60	11189	54	11345	97
8659	18	10227	67	10833	50	11192	34	11346	97
8660	20	10228	29	10883	67	11193	33	11347	134
8669	22	10229	32	10885	56	11196	76	11348	134
8670	25	10230	67	10887	59	11197	39	11349	134
8671	46	10297	50	10911	10	11199	23	11350	134
8672	66	10312	92	10920	54	11203	15	11354	134
8673	21	10317	66	10937	53	11204	14	11355	134
8682	92	10342	51	10938	67	11205	50	11356	134
8716	92	10343	55	10948	2	11206	28	11357	115
8718	92	10344	66	10975	2	11207	76	11364	67
8720	66	10390	66	10986	92	11208	76	11371	63
8800	18	10392	20	11003	15	11210	26	11388	45
8804	66	10393	26	11004	58	11211	76	11393	92
8959	15	10395	2	11005	49	11214	51	11394	50
9011	53	10408	11	11006	76	11215	57	11397	76
9012	52	10460	66	11010	38	11216	58	11399	14
9133	22	10461	66	11011	38	11219	76	11400	14
9145	66	10476	67	11012	38	11221	114	11408	27
9151	66	10504	92	11013	49	11227	96	11409	76
9152	66	10505	92	11025	114	11234	114	11413	76
9178	20	10509	55	11034	19	11242	134	11415	59
9179	22	10511	26	11043	114	11244	134	11417	3
9180	57	10513	66	11045	133	11246	96	11429	115
9181	52	10519	25	11046	133	11255	126	11430	115
9182	66	10534	63	11047	133	11261	76	11432	97
9184	18	10545	89	11048	90	11263	31	11433	97
9186	66	10546	55	11056	28	11264	14	11435	97
9197	66	10552	28	11061	76	11265	15	11438	134
9198	66	10562	26	11062	76	11268	56	11442	115
9206	92	10568	3	11063	17	11269	30	11443	153
9223	61	10569	3	11064	3	11270	33	11444	153
9294	37	10570	27	11065	22	11274	76	11445	115
9297	38	10625	94	11066	76	11277	76	11446	115
9300	66	10626	94	11067	23	11281	62	11447	97
9318	66	10644	67	11068	22	11286	22	11448	97
9341	109	10646	67	11069	76	11287	76	11449	90
9346	66	10647	67	11071	76	11288	76	11450	90
9377	37	10648	67	11072	157	11289	64	11451	153
9382	55	10649	49	11074	1	11290	50	11452	97
9385	58	10651	67	11078	60	11292	49	11455	67

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
11456	134	11603	92	11868	22	11996	12	12128	33
11457	134	11605	92	11871	98	12003	55	12132	45
11458	134	11609	115	11873	115	12006	135	12134	116
11459	62	11610	115	11875	98	12007	57	12137	116
11463	76	11611	115	11876	135	12008	116	12138	78
11471	57	11612	98	11877	135	12009	135	12140	47
11482	10	11615	135	11878	135	12010	135	12141	78
11484	28	11617	98	11879	135	12011	136	12144	42
11485	28	11618	57	11880	135	12018	116	12147	1
11487	27	11621	1	11882	135	12019	116	12153	31
11490	21	11622	77	11883	135	12020	77	12154	116
11491	1	11631	77	11894	77	12021	116	12155	27
11493	56	11637	90	11896	10	12022	116	12157	30
11494	56	11639	98	11899	50	12023	43	12159	32
11495	76	11640	135	11900	51	12024	99	12162	34
11498	57	11656	77	11901	135	12027	99	12163	136
11500	32	11657	1	11904	135	12028	136	12170	136
11502	153	11658	29	11907	12	12029	136	12176	78
11503	134	11693	67	11908	12	12030	136	12178	78
11504	115	11694	24	11909	13	12033	78	12180	78
11505	90	11695	21	11910	77	12040	78	12182	78
11512	31	11697	25	11913	135	12041	127	12185	78
11518	134	11710	135	11916	29	12043	23	12187	4
11519	134	11718	77	11921	77	12045	136	12188	1
11520	134	11722	55	11922	77	12046	23	12190	116
11521	153	11732	24	11924	135	12047	2	12199	136
11522	134	11735	135	11925	135	12051	99	12200	136
11524	116	11738	98	11927	12	12055	78	12202	157
11528	97	11743	9	11929	77	12056	99	12203	157
11529	97	11744	77	11933	77	12061	1	12204	78
11530	97	11746	9	11934	60	12062	2	12205	78
11531	134	11747	44	11935	34	12066	99	12209	136
11532	134	11748	46	11938	27	12067	99	12225	90
11533	134	11752	45	11939	6	12069	29	12226	78
11534	134	11753	44	11941	135	12070	27	12229	78
11535	134	11754	45	11942	33	12071	27	12230	25
11536	126	11756	45	11943	115	12073	27	12232	7
11537	126	11761	38	11944	29	12074	27	12233	6
11540	76	11771	77	11950	26	12075	27	12234	5
11541	76	11779	115	11953	42	12079	29	12246	78
11543	52	11780	77	11954	44	12080	29	12265	78
11544	56	11788	43	11955	43	12081	31	12267	78
11545	47	11793	98	11956	41	12083	32	12280	136
11558	27	11794	98	11958	55	12084	32	12297	136
11560	27	11796	77	11959	42	12086	32	12298	136
11562	30	11797	31	11960	41	12087	32	12299	136
11563	30	11798	90	11961	42	12089	32	12300	136
11564	31	11801	33	11962	98	12092	32	12302	12
11565	77	11804	77	11963	98	12093	33	12308	78
11568	77	11816	77	11964	98	12094	33	12312	19
11569	2	11820	135	11965	153	12095	33	12318	24
11571	90	11821	98	11966	153	12096	33	12320	24
11572	89	11822	98	11967	153	12102	34	12324	21
11573	90	11823	37	11968	98	12104	34	12326	26
11574	90	11826	37	11969	98	12105	34	12328	136
11575	62	11838	46	11970	99	12106	34	12329	136
11576	57	11842	98	11971	115	12107	34	12331	116
11577	62	11844	98	11972	115	12113	3	12332	45
11579	1	11846	115	11973	39	12114	78	12333	19
11584	135	11849	98	11975	49	12115	116	12334	19
11587	89	11853	4	11977	11	12116	99	12347	19
11588	67	11856	11	11978	115	12119	136	12351	22
11592	97	11858	77	11979	15	12121	136	12354	78
11593	97	11859	51	11992	77	12122	136	12356	9
11594	98	11860	2	11993	116	12123	136	12360	136
11601	92	11867	24	11995	12	12127	116	12364	136

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
12365	136	12586	154	12852	17	13106	117	13284	12
12366	137	12592	99	12860	42	13109	100	13287	11
12367	137	12593	99	12863	79	13138	2	13288	10
12369	116	12594	154	12883	44	13147	138	13289	11
12371	24	12604	137	12887	138	13149	80	13290	12
12379	43	12607	14	12889	79	13151	100	13298	46
12383	49	12608	60	12891	79	13152	100	13300	46
12384	78	12619	51	12892	79	13153	126	13306	80
12390	12	12620	79	12894	5	13157	100	13307	57
12391	22	12622	126	12895	5	13158	100	13308	80
12392	78	12633	45	12899	116	13159	100	13312	41
12393	4	12634	54	12916	100	13160	100	13313	91
12394	78	12635	52	12919	117	13161	117	13314	100
12395	127	12636	99	12935	138	13162	100	13315	101
12398	43	12639	137	12937	100	13163	100	13316	50
12400	33	12640	137	12943	32	13165	80	13319	57
12401	34	12648	137	12944	41	13172	22	13323	20
12405	22	12649	79	12946	58	13173	100	13324	80
12409	6	12657	10	12960	42	13179	59	13325	80
12410	6	12659	56	12964	79	13182	117	13326	80
12428	11	12661	116	12965	91	13183	26	13331	80
12430	42	12664	154	12970	79	13185	19	13332	8
12433	12	12680	57	12971	29	13188	45	13338	127
12436	78	12681	55	12973	20	13189	46	13339	39
12439	20	12684	79	12988	43	13190	46	13350	117
12440	19	12690	79	12992	79	13191	13	13351	28
12449	78	12691	116	13005	43	13192	59	13352	29
12450	27	12692	137	13008	48	13193	12	13353	31
12455	99	12693	45	13010	47	13194	11	13354	31
12462	79	12694	45	13013	48	13196	138	13355	32
12469	116	12697	61	13018	46	13198	138	13356	33
12470	79	12698	79	13037	117	13199	138	13357	33
12471	116	12717	137	13038	79	13200	138	13368	158
12472	116	12721	137	13039	79	13201	138	13370	80
12473	116	12722	137	13042	80	13202	138	13374	80
12474	99	12723	137	13044	80	13203	45	13375	12
12476	99	12726	137	13047	54	13204	23	13378	139
12480	79	12727	138	13048	4	13205	153	13379	139
12498	47	12728	138	13049	100	13206	117	13380	139
12505	47	12731	79	13050	62	13208	13	13386	117
12508	48	12732	79	13051	5	13209	44	13387	117
12509	48	12742	4	13054	138	13211	10	13390	117
12510	48	12743	154	13055	138	13212	11	13392	80
12511	48	12745	116	13056	138	13224	117	13394	139
12524	52	12755	99	13060	80	13225	100	13399	101
12526	11	12760	100	13061	80	13226	100	13401	139
12546	137	12761	50	13063	58	13227	100	13403	139
12547	137	12762	116	13068	40	13228	117	13404	139
12554	33	12770	116	13079	100	13238	41	13405	139
12556	2	12772	41	13080	15	13246	138	13406	139
12559	99	12773	42	13083	80	13261	3	13412	153
12560	99	12775	54	13086	11	13262	50	13417	139
12564	90	12776	58	13088	80	13264	59	13418	139
12567	54	12778	28	13089	100	13267	57	13419	139
12571	99	12780	79	13090	138	13270	138	13420	24
12572	59	12781	138	13091	138	13271	60	13422	101
12573	57	12782	138	13092	138	13272	51	13428	139
12574	54	12799	32	13093	59	13273	59	13433	80
12576	137	12809	44	13094	80	13274	54	13434	114
12578	127	12810	45	13095	52	13275	1	13437	154
12579	127	12811	79	13097	100	13276	23	13438	155
12580	137	12818	138	13101	117	13277	117	13439	153
12582	79	12844	116	13102	117	13279	16	13442	101
12583	116	12845	79	13103	117	13280	100	13444	155
12584	116	12847	59	13104	117	13281	10	13456	80
12585	154	12848	60	13105	117	13283	12	13472	26

SECTION 10C—cont.

RADIO CAPACITORS, CHOKES AND INDUCTORS

INDEX TO REFERENCE NUMBERS—cont.

Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page	Ref. No.	Page
13473	117	13664	42	13856	118	14001	23	14196	42
13474	101	13667	126	13857	102	14003	27	14202	57
13482	101	13669	101	13859	81	14005	82	14204	82
13483	101	13670	118	13864	59	14010	141	14205	4
13492	117	13674	11	13873	59	14012	141	14206	142
13493	80	13675	58	13877	118	14013	141	14207	142
13497	41	13676	59	13878	118	14014	118	14211	3
13501	30	13677	63	13879	118	14015	118	14212	119
13502	58	13678	20	13880	118	14016	118	14216	82
13506	81	13680	81	13885	102	14017	102	14221	103
13507	81	13692	118	13896	102	14019	153	14230	82
13508	81	13693	118	13899	82	14024	155	14232	82
13526	139	13704	140	13900	140	14025	155	14234	103
13527	139	13705	118	13901	141	14033	118	14235	103
13528	139	13708	2	13904	118	14041	13	14241	142
13529	81	13714	101	13905	50	14043	28	14243	142
13533	117	13715	140	13906	13	14046	82	14244	142
13534	18	13718	81	13908	27	14047	32	14245	142
13541	139	13719	118	13909	118	14054	141	14246	142
13554	81	13720	118	13910	58	14055	141	14249	59
13560	126	13721	101	13911	102	14060	153	14251	25
13561	101	13724	140	13913	56	14061	91	14263	119
13562	139	13725	140	13914	8	14062	102	14264	155
13563	139	13726	140	13915	59	14063	141	14273	82
13564	139	13727	81	13917	49	14065	102	14274	142
13565	139	13729	118	13919	102	14066	102	14275	142
13570	81	13734	59	13920	141	14070	11	14276	142
13571	117	13736	54	13921	141	14077	102	14285	18
13572	139	13737	118	13922	141	14082	33	14292	119
13573	139	13741	91	13923	141	14090	102	14293	119
13576	51	13742	102	13924	141	14094	141	14294	103
13578	44	13743	102	13925	141	14095	141	14301	82
13580	101	13744	102	13926	141	14099	33	14303	12
13584	101	13745	102	13927	141	14101	103	14312	142
13586	20	13746	102	13928	91	14102	103	14313	142
13589	24	13747	102	13929	82	14103	103	14315	142
13590	81	13748	140	13930	82	14104	103	14316	142
13594	157	13749	81	13931	82	14105	142	14319	103
13596	101	13750	102	13933	118	14106	142	14320	103
13598	140	13755	140	13949	91	14107	142	14321	127
13599	81	13756	140	13950	82	14108	103	14322	127
13600	81	13757	140	13951	82	14109	103	14325	119
13601	81	13758	140	13954	102	14110	103	14326	103
13602	81	13759	140	13955	118	14111	103	14329	51
13618	140	13760	118	13956	141	14112	118	14330	103
13620	117	13761	56	13957	118	14113	154	14332	155
13625	81	13762	52	13958	118	14114	21	14333	155
13629	2	13772	153	13960	56	14118	21	14334	155
13633	52	13773	153	13962	12	14132	118	14335	155
13634	23	13774	102	13966	102	14135	103	14336	155
13635	20	13775	118	13968	127	14141	3	14337	155
13639	140	13776	102	13972	53	14142	82	14338	155
13640	140	13783	118	13973	60	14144	60	14339	142
13641	101	13784	118	13974	61	14154	2	14340	91
13642	101	13789	102	13975	47	14156	103	14341	155
13643	117	13792	81	13979	52	14157	82	14342	155
13645	117	13803	7	13983	54	14159	103	14343	155
13646	12	13809	24	13984	82	14161	118	14345	155
13649	81	13810	23	13990	51	14162	119	14346	44
13650	81	13817	2	13992	61	14164	63	14347	142
13656	101	13820	157	13993	141	14174	11	14349	155
13657	101	13822	140	13994	141	14175	154	14350	155
13659	101	13846	118	13995	141	14177	155	14351	155
13660	101	13847	81	13996	141	14181	53	14354	155
13661	101	13854	118	13998	45	14185	40	14358	142
13662	101	13855	50	13999	12	14194	53		