



PAGE RAM DATA LATCH

NOPMAPROM: When a NOP character is addressed, gives a number (0-F) with bit 5 set (ie. 20-2F). The number is related to the sequence of the characters in the .XMP file and not to any particular code.

CHC7 is set for Packet 26 chars (and other chars in the top half of the ROM). This means that Packet 26 chars must be in the top half of the ROM.

Sets the Alphabet to the default at the start of each line. Then, if TWIST is enabled, toggles the alphabet on each TWIST (ESC) character

Low on Select gives CHARMAPD out

CODEMAPLATCH, clocked on pixel 5

Character Rom Address input latch
Clocked on pixel 7

ADDR	LINE3=0	LINE3=1
ROMA0	LINE0	LINE0
ROMA1	LINE1	CMAF5
ROMA2	LINE2	CMAF6
ROMA3	CMAF0	CMAF0
ROMA4	CMAF1	CMAF1
ROMA5	CMAF2	CMAF2
ROMA6	CMAF3	CMAF3
ROMA7	CMAF4	CMAF4
ROMA8	CMAF5	CMAF7
ROMA9	CMAF6	"1"
ROMA10	CMAF7	"1"
ROMA11	"0"	"1"

File	<Title>	
Size	Document Number	Rev 1
C	<Doc>	
Date	Monday, November 20, 2000	Sheet 1 of 1